
aerospike Documentation

Ronen Botzer

Feb 18, 2021

Contents

1 Content	3
1.1 <code>aerospike</code> — Aerospike Client for Python	3
1.1.1 Methods	3
1.1.2 Operators	14
1.1.3 Policy Options	27
1.1.3.1 Commit Level Policy Options	27
1.1.3.2 AP Read Mode Policy Options	27
1.1.3.3 SC Read Mode Policy Options	27
1.1.3.4 Existence Policy Options	27
1.1.3.5 Generation Policy Options	28
1.1.3.6 Key Policy Options	28
1.1.3.7 Replica Options	28
1.1.3.8 Retry Policy Options	28
1.1.4 Constants	29
1.1.4.1 TTL Constants	29
1.1.4.2 Auth Mode Constants	29
1.1.4.3 Scan Constants	29
1.1.4.4 Job Constants	30
1.1.4.5 Job Statuses	30
1.1.4.6 Serialization Constants	30
1.1.4.7 List Write Flags	30
1.1.4.8 List Return Types	31
1.1.4.9 List Order	31
1.1.4.10 List Sort Flags	31
1.1.4.11 Map Write Flag	31
1.1.4.12 Map Write Mode	32
1.1.4.13 Map Order	32
1.1.4.14 Map Return Types	32
1.1.4.15 Bitwise Write Flags	33
1.1.4.16 Bitwise Resize Flags	33
1.1.4.17 Bitwise Overflow	33
1.1.4.18 HyperLogLog Write Flags	34
1.1.4.19 Bin Types	34
1.1.4.20 Miscellaneous	35
1.1.4.21 Log Level	35
1.1.4.22 Privileges	36

1.1.4.23	Regex Flag Values	36
1.2	Client Class — Client	36
1.2.1	Client	36
1.2.1.1	Connection	37
1.2.1.2	Key Tuple	38
1.2.1.3	Record Tuple	39
1.2.2	Operations	39
1.2.2.1	Record Operations	39
1.2.2.2	Batch Operations	45
1.2.2.3	String Operations	49
1.2.2.4	Numeric Operations	51
1.2.2.5	List Operations	52
1.2.2.6	Map Operations	57
1.2.2.7	Multi-Ops (Operate)	68
1.2.2.8	Scan and Query	72
1.2.2.9	User Defined Functions	73
1.2.2.10	Info Operations	78
1.2.2.11	Index Operations	82
1.2.2.12	Admin Operations	85
1.2.3	Policies	88
1.2.3.1	Write Policies	88
1.2.3.2	Read Policies	90
1.2.3.3	Operate Policies	91
1.2.3.4	Apply Policies	94
1.2.3.5	Remove Policies	95
1.2.3.6	Batch Policies	97
1.2.3.7	Info Policies	99
1.2.3.8	Admin Policies	99
1.2.3.9	List Policies	99
1.2.3.10	Map Policies	100
1.2.3.11	Bit Policies	101
1.2.3.12	HyperLogLog Policies	101
1.2.4	Misc	102
1.2.4.1	Privilege Objects	102
1.2.4.2	Unicode Handling	102
1.3	Scan Class — Scan	102
1.3.1	Scan	102
1.3.1.1	Scan Methods	103
1.3.1.2	Scan Policies	108
1.3.1.3	Scan Options	110
1.4	Query Class — Query	111
1.4.1	Query	111
1.4.1.1	Query Methods	111
1.4.1.2	Query Policies	119
1.4.1.3	Query Options	121
1.5	aerospike.predicates — Query Predicates	121
1.6	aerospike.predexp — Query Predicate Expressions	127
1.7	aerospike.exception — Aerospike Exceptions	138
1.7.1	In Doubt Status	138
1.7.2	Exception Types	138
1.7.3	Exception Hierarchy	142
1.8	aerospike_helpers — Aerospike Helper Package for bin operations (list, map, bit, etc.)	143
1.8.1	Subpackages	143
1.8.1.1	aerospike_helpers.operations package	143

1.8.1.2	aerospike_helpers.expressions package	185
1.8.1.3	aerospike_helpers.cdt_ctx module	256
1.9	GeoJSON Class — GeoJSON	259
1.9.1	GeoJSON	259
1.10	Data_Mapping — Python Data Mappings	261
2	Indices and tables	263
	Python Module Index	265
	Index	267

`aerospike` is a package which provides a Python client for Aerospike database clusters. The Python client is a CPython module, built on the Aerospike C client.

- `aerospike` - the module containing the Client, Query, and Scan Classes.
- *Scan Class* — `Scan` is a class built to handle scan operations of entire sets.
- *Query Class* — `Query` is a class built to handle queries over secondary indexes.
- `aerospike.predicates` is a submodule containing predicate helpers for use with the Query class.
- `aerospike.predexp` is a submodule containing predicate expression helpers for use with the Query class.
- `aerospike.exception` is a submodule containing the exception hierarchy for `AerospikeError` and its subclasses.
- `aerospike_helpers` is a helper package for bin operations (list, map, bitwise, etc.) and aerospike expressions.
- *GeoJSON Class* — `GeoJSON` is a class to handle GeoJSON type data.
- *Data_Mapping* — `Python Data Mappings` How Python types map to Aerospike Server types.

See also:

The [Python Client Manual](#) for a quick guide.

CHAPTER 1

Content

1.1 aerospike — Aerospike Client for Python

The Aerospike client enables you to build an application in Python with an Aerospike cluster as its database. The client manages the connections to the cluster and handles the transactions performed against it.

Data Model

At the top is the `namespace`, a container that has one set of policy rules for all its data, and is similar to the *database* concept in an RDBMS, only distributed across the cluster. A namespace is subdivided into `sets`, similar to *tables*.

Pairs of key-value data called `bins` make up `records`, similar to *columns* of a *row* in a standard RDBMS. Aerospike is schema-less, meaning that you do not need to define your bins in advance.

Records are uniquely identified by their key, and record metadata is contained in an in-memory primary index.

See also:

[Architecture Overview](#) and [Aerospike Data Model](#) for more information about Aerospike.

1.1.1 Methods

`aerospike.client(config)`

Creates a new instance of the `Client` class. This client can `connect()` to the cluster and perform operations against it, such as `put()` and `get()` records.

This is a wrapper function which calls the constructor for the `Client` class. The client may also be constructed by calling the constructor directly.

Parameters `config(dict)` – the client's configuration.

- hosts a required `list` of (`address`, `port`, [`tls-name`]) tuples identifying a node (or multiple nodes) in the cluster.

The client will connect to the first available node in the list, the *seed node*, and will learn about the cluster and partition map from it. If `tls-name` is specified, it must match the `tls-name` specified in the node's server configuration file and match the server's CA certificate.

Note: TLS usage requires Aerospike Enterprise Edition

- **lua** an optional `dict` containing the paths to two types of Lua modules

system_path

The location of the system modules such as `aerospike.lua`

Default: `/usr/local/aerospike/lua`

user_path

The location of the user's record and stream UDFs .

Default: `./`

- **policies** a `dict` of policies

read (dict)

A dictionary containing *Read Policies*.

write (dict)

A dictionary containing *Write Policies*.

apply (dict)

A dictionary containing *Apply Policies*.

operate (dict)

A dictionary containing *Operate Policies*.

remove (dict)

A dictionary containing *Remove Policies*.

query (dict)

A dictionary containing *Query Policies*.

scan (dict)

A dictionary containing *Scan Policies*.

batch (dict)

A dictionary containing *Batch Policies*.

total_timeout default connection timeout in milliseconds

Deprecated: set this individually in the *Policies* dictionaries.

auth_mode

A value of *Auth Mode Constants* defining how the authentication mode with the server, such as `aerospike.AUTH_INTERNAL`.

Default: `aerospike.AUTH_INTERNAL`

login_timeout_ms (int)

Representing the node login timeout in milliseconds.

Default: 5000.

key default key policy

Deprecated: set this individually in the *Policies* dictionaries.

exists default exists policy

Deprecated: set in the *Write Policies* dictionary

max_retries representing the number of times to retry a transaction

Deprecated: set this individually in the *Policies* dictionaries.

replica default replica policy

Deprecated: set this in one or all of the other policies' *Read Policies*, *Write Policies*, *Apply Policies*, *Operate Policies*, *Remove Policies* dictionaries.

commit_level default commit level policy

Deprecated: set this as needed individually in the *Write Policies*, *Apply Policies*, *Operate Policies*, *Remove Policies* dictionaries.

- **shm** a *dict* with optional shared-memory cluster tending parameters

Shared-memory cluster tending is on if the *dict* is provided. If multiple clients are instantiated talking to the same cluster the *shm* cluster-tending should be used.

max_nodes (*int*)

Maximum number of nodes allowed. Pad so new nodes can be added without configuration changes

Default: 16

max_namespaces (*int*)

Similarly pad

Default: 8

takeover_threshold_sec (*int*)

Take over tending if the cluster hasn't been checked for this many seconds

Default: 30

shm_key

Explicitly set the shm key for this client.

If **use_shared_connection** is not set, or set to `False`, the user must provide a value for this field in order for shared memory to work correctly.

If , and only if, **use_shared_connection** is set to `True`, the key will be implicitly evaluated per unique hostname, and can be inspected with `shm_key()` .

It is still possible to specify a key when using **use_shared_connection = True**.

default: `0xA8000000`

- **use_shared_connection (*bool*)**

Indicating whether this instance should share its connection to the Aerospike cluster with other client instances in the same process.

Default: `False`

- **tls** a *dict* of optional TLS configuration parameters.

Note: TLS usage requires Aerospike Enterprise Edition

enable (*bool*)

Indicating whether tls should be enabled or not.

Default: False

cafile (str)

Path to a trusted CA certificate file. By default TLS will use system standard trusted CA certificates

capath (str)

Path to a directory of trusted certificates. See the OpenSSL `SSL_CTX_load_verify_locations` manual page for more information about the format of the directory.

protocols (str)

Specifies enabled protocols. This format is the same as Apache's `SSLPotocol` documented at
https://httpd.apache.org/docs/current/mod/mod_ssl.html#sslprotocol .
If not specified the client will use “-all +TLSv1.2”.

cipher_suite (str)

Specifies enabled cipher suites. The format is the same as OpenSSL's Cipher List Format documented at
<https://www.openssl.org/docs/manmaster/apps/ciphers.html> .
If not specified the OpenSSL default cipher suite described in the ciphers documentation will be used. If you are not sure what cipher suite to select this option is best left unspecified

keyfile (str)

Path to the client's key for mutual authentication. By default mutual authentication is disabled.

keyfile_pw (str)

Decryption password for the client's key for mutual authentication. By default the key is assumed not to be encrypted.

cert_blacklist (str)

Path to a certificate blacklist file. The file should contain one line for each blacklisted certificate. Each line starts with the certificate serial number expressed in hex. Each entry may optionally specify the issuer name of the certificate (serial numbers are only required to be unique per issuer). Example records: 867EC87482B2 /C=US/ST=CA/O=Acme/OU=Engineering/CN=Test Chain CA E2D4B0E570F9EF8E885C065899886461

certfile (str)

Path to the client's certificate chain file for mutual authentication. By default mutual authentication is disabled.

crl_check (bool)

Enable CRL checking for the certificate chain leaf certificate. An error occurs if a suitable CRL cannot be found. By default CRL checking is disabled.

crl_check_all (bool)

Enable CRL checking for the entire certificate chain. An error occurs if a suitable CRL cannot be found. By default CRL checking is disabled.

log_session_info (bool)

Log session information for each connection.

for_login_only (bool)

Log session information for each connection. Use TLS connections only for login authentication. All other communication with the server will be done with non-TLS connections.

Default: `False` (Use TLS connections for all communication with server.)

- **serialization** an optional instance-level `tuple()` of (`serializer`, `deserializer`).

Takes precedence over a class serializer registered with `set_serializer()`.

- **thread_pool_size (int)**

Number of threads in the pool that is used in batch/scan/query commands.

Default: 16

- **max_socket_idle (int)**

Maximum socket idle time in seconds. Connection pools will discard sockets that have been idle longer than the maximum. The value is limited to 24 hours (86400). It's important to set this value to a few seconds less than the server's proto-fd-idle-ms (default 60000 milliseconds, or 1 minute), so the client does not attempt to use a socket that has already been reaped by the server.

Default: 0 seconds (disabled) for non-TLS connections, 55 seconds for TLS connections

- **max_conns_per_node (int)**

Maximum number of pipeline connections allowed for each node

- **tend_interval (int)**

Polling interval in milliseconds for tending the cluster

Default: 1000

- **compression_threshold (int)**

Compress data for transmission if the object size is greater than a given number of bytes

Default: 0, meaning ‘never compress’

Deprecated, set this in the ‘write’ policy dictionary.

- **cluster_name (str)**

Only server nodes matching this name will be used when determining the cluster name.

- **rack_id (int)**

Rack id where this client instance resides.

In order to enable this functionality, the `rack_aware` needs to be set to true, the [Read Policies replica](#) needs to be set to `POLICY_REPLICA_PREFER_RACK`. The server rack configuration must also be configured.

Default: 0

- **rack_aware (bool)**

Track server rack data. This is useful when directing read operations to run on the same rack as the client.

This is useful to lower cloud provider costs when nodes are distributed across different availability zones (represented as racks).

In order to enable this functionality, the `rack_id` needs to be set to local rack, the [read policy replica](#) needs to be set to `POLICY_REPLICA_PREFER_RACK`. The server

rack configuration must also be configured.

Default: False

- **use_services_alternate (bool)**

Flag to signify if “services-alternate” should be used instead of “services”

Default: False

- **connect_timeout (int)**

Initial host connection timeout in milliseconds. The timeout when opening a connection to the server host for the first time.

Default: 1000.

Returns an instance of the `aerospike.Client` class.

See also:

Shared Memory and Per-Transaction Consistency Guarantees.

```
import aerospike

# configure the client to first connect to a cluster node at 127.0.0.1
# the client will learn about the other nodes in the cluster from the
# seed node.
# in this configuration shared-memory cluster tending is turned on,
# which is appropriate for a multi-process context, such as a webserver
config = {
    'hosts': [ ('127.0.0.1', 3000) ],
    'policies': {'read': {total_timeout': 1000}},
    'shm': { } }
client = aerospike.client(config)
```

Changed in version 2.0.0.

```
import aerospike
import sys

# NOTE: Use of TLS Requires Aerospike Enterprise Server Version >= 3.11 and
# Python Client version 2.1.0 or greater
# To view Instructions for server configuration for TLS see https://www.aerospike.
# com/docs/guide/security/tls.html
tls_name = "some-server-tls-name"
tls_ip = "127.0.0.1"
tls_port = 4333

# If tls-name is specified, it must match the tls-name specified in the node's
# server configuration file
# and match the server's CA certificate.
tls_host_tuple = (tls_ip, tls_port, tls_name)
hosts = [tls_host_tuple]

# Example configuration which will use TLS with the specified cafile
tls_config = {
    "cafile": "/path/to/cacert.pem",
    "enable": True
}
```

(continues on next page)

(continued from previous page)

```

client = aerospike.client({
    "hosts": hosts,
    "tls": tls_config
})
try:
    client.connect()
except Exception as e:
    print(e)
    print("Failed to connect")
    sys.exit()

key = ('test', 'demo', 1)
client.put(key, {'aerospike': 'aerospike'})
print(client.get(key))

```

aerospike.null()

A type for distinguishing a server-side null from a Python `None`. Replaces the constant `aerospike.null`.

Returns a type representing the server-side type `as_null`.

New in version 2.0.1.

aerospike.CDTWildcard()

A type representing a wildcard object. This type may only be used as a comparison value in operations. It may not be stored in the database.

Returns a type representing a wildcard value.

```

import aerospike
from aerospike_helpers.operations import list_operations as list_ops

client = aerospike.client({'hosts': [('localhost', 3000)]}).connect()
key = 'test', 'demo', 1

# get all values of the form [1, ...] from a list of lists.
# For example if list is [[1, 2, 3], [2, 3, 4], [1, 'a']], this operation will ↴match
# [1, 2, 3] and [1, 'a']
operations = [list_ops.list_get_by_value('list_bin', [1, aerospike.CDTWildcard()], ↴ aerospike.LIST_RETURN_VALUE)]
_, _, bins = client.operate(key, operations)

```

New in version 3.5.0.

Note: This requires Aerospike Server 4.3.1.3 or greater

aerospike.CDTInfinite()

A type representing an infinite value. This type may only be used as a comparison value in operations. It may not be stored in the database.

Returns a type representing an infinite value.

```

import aerospike
from aerospike_helpers.operations import list_operations as list_ops

client = aerospike.client({'hosts': [('localhost', 3000)]}).connect()

```

(continues on next page)

(continued from previous page)

```
key = 'test', 'demo', 1

# get all values of the form [1, ...] from a list of lists.
# For example if list is [[1, 2, 3], [2, 3, 4], [1, 'a']], this operation will ↴
# [1, 2, 3] and [1, 'a']
operations = [list_ops.list_get_by_value_range('list_bin', aerospike.LIST_RETURN_
    ↴VALUE, [1], [1, aerospike.CDTInfinite()])]
_, _, bins = client.operate(key, operations)
```

New in version 3.5.0.

Note: This requires Aerospike Server 4.3.1.3 or greater

`aerospike.calc_digest(ns, set, key) → bytearray`
Calculate the digest of a particular key. See: [Key Tuple](#).

Parameters

- `ns (str)` – the namespace in the aerospike cluster.
- `set (str)` – the set name.
- `key (str, int or bytearray)` – the primary key identifier of the record within the set.

Returns a RIPEMD-160 digest of the input tuple.

Return type `bytearray`

```
import aerospike
import pprint

digest = aerospike.calc_digest("test", "demo", 1)
pprint(digest)
```

Serialization

Note: By default, the `aerospike.Client` maps the supported types `int`, `str`, `float`, `bytearray`, `list`, `dict` to matching aerospike server types (int, string, double, bytes, list, map). When an unsupported type is encountered, the module uses `cPickle` to serialize and deserialize the data, storing it into `as_bytes` of type ‘Python’ (`AS_BYTES_PYTHON`).

The functions `set_serializer()` and `set_deserializer()` allow for user-defined functions to handle serialization, instead. The serialized data is stored as ‘Generic’ `as_bytes` of type (`AS_BYTES_BLOB`). The `serialization` config param of `aerospike.client()` registers an instance-level pair of functions that handle serialization.

`aerospike.set_serializer(callback)`

Register a user-defined serializer available to all `aerospike.Client` instances.

Parameters `callback (callable)` – the function to invoke for serialization.

See also:

To use this function with `put()` the argument to `serializer` should be `aerospike.SERIALIZER_USER`.

```

import aerospike
import json

def my_serializer(val):
    return json.dumps(val)

aerospike.set_serializer(my_serializer)

```

New in version 1.0.39.

`aerospike.set_deserializer(callback)`

Register a user-defined deserializer available to all `aerospike.Client` instances. Once registered, all read methods (such as `get()`) will run bins containing ‘Generic’ `as_bytes` of type (AS_BYTES_BLOB) through this deserializer.

Parameters `callback(callable)` – the function to invoke for deserialization.

`aerospike.unset_serializers()`

Deregister the user-defined de/serializer available from `aerospike.Client` instances.

New in version 1.0.53.

Note: Serialization Examples

The following example shows the three modes of serialization - built-in, class-level user functions, instance-level user functions:

```

from __future__ import print_function
import aerospike
import marshal
import json

def go_marshal(val):
    return marshal.dumps(val)

def demarshal(val):
    return marshal.loads(val)

def jsonize(val):
    return json.dumps(val)

def dejsonize(val):
    return json.loads(val)

aerospike.set_serializer(go_marshal)
aerospike.set_deserializer(demarshal)
config = {'hosts': [('127.0.0.1', 3000)]}
client = aerospike.client(config).connect()
config['serialization'] = (jsonize, dejsonize)
client2 = aerospike.client(config).connect()

for i in xrange(1, 4):
    try:
        client.remove(('test', 'demo', 'foo' + i))
    except:
        pass

bin_ = {'t': (1, 2, 3)} # tuple is an unsupported type

```

(continues on next page)

(continued from previous page)

```

print("Use the built-in serialization (cPickle)")
client.put(('test','demo','foo1'), bin_)
(key, meta, bins) = client.get(('test','demo','foo1'))
print(bins)

print("Use the class-level user-defined serialization (marshal)")
client.put(('test','demo','foo2'), bin_, serializer=aerospike.SERIALIZER_USER)
(key, meta, bins) = client.get(('test','demo','foo2'))
print(bins)

print("Use the instance-level user-defined serialization (json)")
client2.put(('test','demo','foo3'), bin_, serializer=aerospike.SERIALIZER_USER)
# notice that json-encoding a tuple produces a list
(key, meta, bins) = client2.get(('test','demo','foo3'))
print(bins)
client.close()

```

The expected output is:

```

Use the built-in serialization (cPickle)
{'i': 321, 't': (1, 2, 3)}
Use the class-level user-defined serialization (marshal)
{'i': 321, 't': (1, 2, 3)}
Use the instance-level user-defined serialization (json)
{'i': 321, 't': [1, 2, 3]}

```

While AQL shows the records as having the following structure:

```

aql> select i,t from test.demo where PK='foo1'
+-----+
| i | t |
+-----+
| 321 | 28 49 31 0A 49 32 0A 49 33 0A 74 70 31 0A 2E |
+-----+
1 row in set (0.000 secs)

aql> select i,t from test.demo where PK='foo2'
+-----+
| i | t |
+-----+
| 321 | 28 03 00 00 00 69 01 00 00 00 69 02 00 00 00 69 03 00 00 00 |
+-----+
1 row in set (0.000 secs)

aql> select i,t from test.demo where PK='foo3'
+-----+
| i | t |
+-----+
| 321 | 5B 31 2C 20 32 2C 20 33 5D |
+-----+
1 row in set (0.000 secs)

```

Logging

`aerospike.set_log_handler(callback)`

Set a user-defined function as the log handler for all aerospike objects. The `callback` is invoked whenever a log event passing the logging level threshold is encountered.

Parameters `callback` (`callable`) – the function used as the logging handler.

Note: The callback function must have the five parameters (level, func, path, line, msg)

```
from __future__ import print_function
import aerospike

def as_logger(level, func, path, line, msg):
    def as_logger(level, func, myfile, line, msg):
        print("**", myfile, line, func, ':: ', msg, "**")

    aerospike.set_log_level(aerospike.LOG_LEVEL_DEBUG)
    aerospike.set_log_handler(as_logger)
```

`aerospike.set_log_level(log_level)`

Declare the logging level threshold for the log handler.

Parameters `log_level` (`int`) – one of the `Log Level` constant values.

Geospatial

`aerospike.geodata([geo_data])`

Helper for creating an instance of the `GeoJSON` class. Used to wrap a geospatial object, such as a point, polygon or circle.

Parameters `geo_data` (`dict`) – a `dict` representing the geospatial data.

Returns an instance of the `aerospike.GeoJSON` class.

```
import aerospike

# Create GeoJSON point using WGS84 coordinates.
latitude = 45.920278
longitude = 63.342222
loc = aerospike.geodata({'type': 'Point',
                        'coordinates': [longitude, latitude]})
```

New in version 1.0.54.

`aerospike.geojson([geojson_str])`

Helper for creating an instance of the `GeoJSON` class from a raw GeoJSON `str`.

Parameters `geojson_str` (`dict`) – a `str` of raw GeoJSON.

Returns an instance of the `aerospike.GeoJSON` class.

```
import aerospike

# Create GeoJSON point using WGS84 coordinates.
loc = aerospike.geojson('{"type": "Point", "coordinates": [-80.604333, 28.608389]}')
```

New in version 1.0.54.

1.1.2 Operators

Operators for the multi-ops method `operate()`.

Note: Starting version 3.4.0, it is highly recommended to use the `aerospike_helpers.operations package` to create the arguments for `operate()` and `operate_ordered()`

aerospike.OPERATOR_WRITE

Write a value into a bin

```
{  
    "op" : aerospike.OPERATOR_WRITE,  
    "bin": "name",  
    "val": "Peanut"  
}
```

aerospike.OPERATOR_APPEND

Append to a bin with `str` type data

```
{  
    "op" : aerospike.OPERATOR_APPEND,  
    "bin": "name",  
    "val": "Mr. "  
}
```

aerospike.OPERATOR_PREPEND

Prepend to a bin with `str` type data

```
{  
    "op" : aerospike.OPERATOR_PREPEND,  
    "bin": "name",  
    "val": " Esq."  
}
```

aerospike.OPERATOR_INCR

Increment a bin with `int` or `float` type data

```
{  
    "op" : aerospike.OPERATOR_INCR,  
    "bin": "age",  
    "val": 1  
}
```

aerospike.OPERATOR_READ

Read a specific bin

```
{  
    "op" : aerospike.OPERATOR_READ,  
    "bin": "name"  
}
```

aerospike.OPERATOR_TOUCH

Touch a record, setting its TTL. May be combined with `OPERATOR_READ`

```
{
    "op" : aerospike.OP_LIST_TOUCH
}
```

aerospike.OP_LIST_APPEND

Append an element to a bin with list type data

```
{
    "op" : aerospike.OP_LIST_APPEND,
    "bin": "events",
    "val": 1234,
    "list_policy": {"write_flags": aerospike.LIST_WRITE_ADD_UNIQUE} # Optional,
    ↵new in client 3.4.0
}
```

Changed in version 3.4.0.

aerospike.OP_LIST_APPEND_ITEMS

Extend a bin with list type data with a list of items

```
{
    "op" : aerospike.OP_LIST_APPEND_ITEMS,
    "bin": "events",
    "val": [ 123, 456 ],
    "list_policy": {"write_flags": aerospike.LIST_WRITE_ADD_UNIQUE} # Optional,
    ↵new in client 3.4.0
}
```

Changed in version 3.4.0.

aerospike.OP_LIST_INSERT

Insert an element at a specified index of a bin with list type data

```
{
    "op" : aerospike.OP_LIST_INSERT,
    "bin": "events",
    "index": 2,
    "val": 1234,
    "list_policy": {"write_flags": aerospike.LIST_WRITE_ADD_UNIQUE} # Optional,
    ↵new in client 3.4.0
}
```

Changed in version 3.4.0.

aerospike.OP_LIST_INSERT_ITEMS

Insert the items at a specified index of a bin with list type data

```
{
    "op" : aerospike.OP_LIST_INSERT_ITEMS,
    "bin": "events",
    "index": 2,
    "val": [ 123, 456 ]
    "list_policy": {"write_flags": aerospike.LIST_WRITE_ADD_UNIQUE} # Optional,
    ↵new in client 3.4.0
}
```

Changed in version 3.4.0.

aerospike.OP_LIST_INCREMENT

Increment the value of an item at the given index in a list stored in the specified bin

```
{  
    "op": aerospike.OP_LIST_INCREMENT,  
    "bin": "bin_name",  
    "index": 2,  
    "val": 5,  
    "list_policy": {"write_flags": aerospike.LIST_WRITE_ADD_UNIQUE} # Optional,  
    ↵new in client 3.4.0  
}
```

Changed in version 3.4.0.

aerospike.OP_LIST_POP

Remove and return the element at a specified index of a bin with list type data

```
{  
    "op" : aerospike.OP_LIST_POP, # removes and returns a value  
    "bin": "events",  
    "index": 2  
}
```

aerospike.OP_LIST_POP_RANGE

Remove and return a list of elements at a specified index range of a bin with list type data

```
{  
    "op" : aerospike.OP_LIST_POP_RANGE,  
    "bin": "events",  
    "index": 2,  
    "val": 3 # remove and return 3 elements starting at index 2  
}
```

aerospike.OP_LIST_REMOVE

Remove the element at a specified index of a bin with list type data

```
{  
    "op" : aerospike.OP_LIST_REMOVE, # remove a value  
    "bin": "events",  
    "index": 2  
}
```

aerospike.OP_LIST_REMOVE_RANGE

Remove a list of elements at a specified index range of a bin with list type data

```
{  
    "op" : aerospike.OP_LIST_REMOVE_RANGE,  
    "bin": "events",  
    "index": 2,  
    "val": 3 # remove 3 elements starting at index 2  
}
```

aerospike.OP_LIST_CLEAR

Remove all the elements in a bin with list type data

```
{  
    "op" : aerospike.OP_LIST_CLEAR,
```

(continues on next page)

(continued from previous page)

```
{
    "bin": "events"
}
```

aerospike.OP_LIST_SETSet the element *val* in a specified index of a bin with list type data

```
{
    "op" : aerospike.OP_LIST_SET,
    "bin": "events",
    "index": 2,
    "val": "latest event at index 2" # set this value at index 2,
    "list_policy": {"write_flags": aerospike.LIST_WRITE_ADD_UNIQUE} # Optional,
    ↵new in client 3.4.0
}
```

Changed in version 3.4.0.

aerospike.OP_LIST_GET

Get the element at a specified index of a bin with list type data

```
{
    "op" : aerospike.OP_LIST_GET,
    "bin": "events",
    "index": 2
}
```

aerospike.OP_LIST_GET_RANGE

Get the list of elements starting at a specified index of a bin with list type data

```
{
    "op" : aerospike.OP_LIST_GET_RANGE,
    "bin": "events",
    "index": 2,
    "val": 3 # get 3 elements starting at index 2
}
```

aerospike.OP_LIST_TRIMRemove elements from a bin with list type data which are not within the range starting at a given *index* plus *val*

```
{
    "op" : aerospike.OP_LIST_TRIM,
    "bin": "events",
    "index": 2,
    "val": 3 # remove all elements not in the range between index 2 and index 2 + 3
}
```

aerospike.OP_LIST_SIZE

Count the number of elements in a bin with list type data

```
{
    "op" : aerospike.OP_LIST_SIZE,
    "bin": "events" # gets the size of a list contained in the bin
}
```

aerospike.OP_LIST_GET_BY_INDEX

Get the item at the specified index from a list bin. Server selects list item identified by index and returns selected data specified by `return_type`.

```
{  
    "op" : aerospike.OP_LIST_GET_BY_INDEX,  
    "bin": "events",  
    "index": 2, # Index of the item to fetch  
    "return_type": aerospike.LIST_RETURN_VALUE  
}
```

New in version 3.4.0.

aerospike.OP_LIST_GET_BY_INDEX_RANGE

Server selects count list items starting at specified index and returns selected data specified by `return_type`. If `count` is omitted, the server returns all items from `index` to the end of list.

If `inverted` is set to `True`, return all items outside of the specified range.

```
{  
    "op" : aerospike.OP_LIST_GET_BY_INDEX_RANGE,  
    "bin": "events",  
    "index": 2, # Beginning index of range,  
    "count": 2, # Optional Count.  
    "return_type": aerospike.LIST_RETURN_VALUE,  
    "inverted": False # Optional.  
}
```

New in version 3.4.0.

aerospike.OP_LIST_GET_BY_RANK

Server selects list item identified by `rank` and returns selected data specified by `return_type`.

```
{  
    "op" : aerospike.OP_LIST_GET_BY_RANK,  
    "bin": "events",  
    "rank": 2, # Rank of the item to fetch  
    "return_type": aerospike.LIST_RETURN_VALUE  
}
```

New in version 3.4.0.

aerospike.OP_LIST_GET_BY_RANK_RANGE

Server selects count list items starting at specified rank and returns selected data specified by `return_type`. If `count` is not specified, the server returns items starting at the specified rank to the last ranked item.

If `inverted` is set to `True`, return all items outside of the specified range.

```
{  
    "op" : aerospike.OP_LIST_GET_BY_RANK_RANGE,  
    "bin": "events",  
    "rank": 2, # Rank of the item to fetch  
    "count": 3,  
    "return_type": aerospike.LIST_RETURN_VALUE,  
    "inverted": False # Optional, defaults to False  
}
```

New in version 3.4.0.

aerospike.OP_LIST_GET_BY_VALUE

Server selects list items identified by val and returns selected data specified by return_type.

```
{
    "op" : aerospike.OP_LIST_GET_BY_VALUE,
    "bin": "events",
    "val": 5,
    "return_type": aerospike.LIST_RETURN_COUNT
}
```

New in version 3.4.0.

aerospike.OP_LIST_GET_BY_VALUE_LIST

Server selects list items contained in by value_list and returns selected data specified by return_type.

If inverted is set to True, returns items not included in value_list

```
{
    "op" : aerospike.OP_LIST_GET_BY_VALUE_LIST,
    "bin": "events",
    "value_list": [5, 6, 7],
    "return_type": aerospike.LIST_RETURN_COUNT,
    "inverted": False # Optional, defaults to False
}
```

New in version 3.4.0.

aerospike.OP_LIST_GET_BY_VALUE_RANGE

Create list get by value range operation. Server selects list items identified by value range (begin inclusive, end exclusive). If value_begin is not present the range is less than value_end. If value_end is not specified, the range is greater than or equal to value_begin.

If inverted is set to True, returns items not included in the specified range.

```
{
    "op" : aerospike.OP_LIST_GET_BY_VALUE_RANGE,
    "bin": "events",
    "value_begin": 3, # Optional
    "value_end": 6, Optional
    "return_type": aerospike.LIST_RETURN_VALUE,
    "inverted": False # Optional, defaults to False
}
```

New in version 3.4.0.

aerospike.OP_LIST_REMOVE_BY_INDEX

Remove and return the item at the specified index from a list bin. Server selects list item identified by index and returns selected data specified by return_type.

```
{
    "op" : aerospike.OP_LIST_REMOVE_BY_INDEX,
    "bin": "events",
    "index": 2, # Index of the item to fetch
    "return_type": aerospike.LIST_RETURN_VALUE
}
```

New in version 3.4.0.

aerospike.OP_LIST_REMOVE_BY_INDEX_RANGE

Server remove count list items starting at specified index and returns selected data specified by return_type. if

count is omitted, the server removes and returns all items from index to the end of list.

If inverted is set to True, remove and return all items outside of the specified range.

```
{  
    "op" : aerospike.OP_LIST_REMOVE_BY_INDEX_RANGE,  
    "bin": "events",  
    "index": 2, # Beginning index of range,  
    "count": 2, # Optional Count.  
    "return_type": aerospike.LIST_RETURN_VALUE,  
    "inverted": False # Optional.  
}
```

New in version 3.4.0.

aerospike.OP_LIST_REMOVE_BY_RANK

Server removes and returns list item identified by rank and returns selected data specified by return_type.

```
{  
    "op" : aerospike.OP_LIST_REMOVE_BY_RANK,  
    "bin": "events",  
    "rank": 2, # Rank of the item to fetch  
    "return_type": aerospike.LIST_RETURN_VALUE  
}
```

New in version 3.4.0.

aerospike.OP_LIST_REMOVE_BY_RANK_RANGE

Server removes and returns count list items starting at specified rank and returns selected data specified by return_type. If count is not specified, the server removes and returns items starting at the specified rank to the last ranked item.

If inverted is set to True, removes return all items outside of the specified range.

```
{  
    "op" : aerospike.OP_LIST_REMOVE_BY_RANK_RANGE,  
    "bin": "events",  
    "rank": 2, # Rank of the item to fetch  
    "count": 3,  
    "return_type": aerospike.LIST_RETURN_VALUE,  
    "inverted": False # Optional, defaults to False  
}
```

New in version 3.4.0.

aerospike.OP_LIST_REMOVE_BY_VALUE

Server removes and returns list items identified by val and returns selected data specified by return_type.

If inverted is set to True, removes and returns list items with a value not equal to val.

```
{  
    "op" : aerospike.OP_LIST_REMOVE_BY_VALUE,  
    "bin": "events",  
    "val": 5,  
    "return_type": aerospike.LIST_RETURN_COUNT,  
    "inverted": # Optional, defaults to False  
}
```

New in version 3.4.0.

aerospike.OP_LIST_REMOVE_BY_VALUE_LIST

Server removes and returns list items contained in by `value_list` and returns selected data specified by `return_type`.

If `inverted` is set to `True`, removes and returns items not included in `value_list`

```
{
    "op" : aerospike.OP_LIST_REMOVE_BY_VALUE_LIST,
    "bin": "events",
    "value_list": [5, 6, 7],
    "return_type": aerospike.LIST_RETURN_COUNT,
    "inverted": False # Optional, defaults to False
}
```

New in version 3.4.0.

aerospike.OP_LIST_REMOVE_BY_VALUE_RANGE

Create list remove by value range operation. Server removes and returns list items identified by value range (begin inclusive, end exclusive). If `value_begin` is not present the range is less than `value_end`. If `value_end` is not specified, the range is greater than or equal to `value_begin`.

If `inverted` is set to `True`, removes and returns items not included in the specified range.

```
{
    "op" : aerospike.OP_LIST_REMOVE_BY_VALUE_RANGE,
    "bin": "events",
    "value_begin": 3, # Optional
    "value_end": 6, Optional
    "return_type": aerospike.LIST_RETURN_VALUE,
    "inverted": False # Optional, defaults to False
}
```

New in version 3.4.0.

aerospike.OP_LIST_SET_ORDER

Assign an ordering to the specified list bin. `list_order` should be one of `aerospike.LIST_ORDERED`, `aerospike.LIST_UNORDERED`.

```
{
    "op": aerospike.OP_LIST_SET_ORDER,
    "list_order": aerospike.LIST_ORDERED,
    "bin": "events"
}
```

New in version 3.4.0.

aerospike.OP_LIST_SORT

Perform a sort operation on the bin. `sort_flags`, if provided, can be one of: `aerospike.LIST_SORT_DROP_DUPLICATES` indicating that duplicate elements should be removed from the sorted list.

```
{
    'op': aerospike.OP_LIST_SORT,
    'sort_flags': aerospike.LIST_SORT_DROP_DUPLICATES, # Optional flags or'd_
    ↵together specifying behavior
    'bin': self.test_bin
}
```

New in version 3.4.0.

aerospike.OP_MAP_SET_POLICY

Set the policy for a map bin. The policy controls the write mode and the ordering of the map entries.

```
{  
    "op" : aerospike.OP_MAP_SET_POLICY,  
    "bin": "scores",  
    "map_policy": {"map_write_mode": Aeorspike.MAP_UPDATE, "map_order": Aerospike.  
    ↵MAP_KEY_VALUE_ORDERED}  
}
```

aerospike.OP_MAP_PUT

Put a key/value pair into a map. Operator accepts an optional map_policy dictionary (see OP_MAP_SET_POLICY for an example).

```
{  
    "op" : aerospike.OP_MAP_PUT,  
    "bin": "my_map",  
    "key": "age",  
    "val": 97  
}
```

aerospike.OP_MAP_PUT_ITEM

Put a dictionary of key/value pairs into a map. Operator accepts an optional map_policy dictionary (see OP_MAP_SET_POLICY for an example).

```
{  
    "op" : aerospike.OP_MAP_PUT_ITEMS,  
    "bin": "my_map",  
    "val": {"name": "bubba", "occupation": "dancer"}  
}
```

aerospike.OP_MAP_INCREMENT

Increment the value of map entry by the given “val” argument. Operator accepts an optional map_policy dictionary (see OP_MAP_SET_POLICY for an example).

```
{  
    "op" : aerospike.OP_MAP_INCREMENT,  
    "bin": "my_map",  
    "key": "age",  
    "val": 1  
}
```

aerospike.OP_MAP_DECREMENT

Decrement the value of map entry by the given “val” argument. Operator accepts an optional map_policy dictionary (see OP_MAP_SET_POLICY for an example).

```
{  
    "op" : aerospike.OP_MAP_DECREMENT,  
    "bin": "my_map",  
    "key": "age",  
    "val": 1  
}
```

aerospike.OP_MAP_SIZE

Return the number of entries in the given map bin.

```
{
    "op" : aerospike.OP_MAP_SIZE,
    "bin": "my_map"
}
```

aerospike.OP_MAP_CLEAR

Remove all entries from the given map bin.

```
{
    "op" : aerospike.OP_MAP_CLEAR,
    "bin": "my_map"
}
```

Note that if “return_type” is not specified in the parameters for a map operation, the default is aerospike.MAP_RETURN_NONE

aerospike.OP_MAP_REMOVE_BY_KEY

Remove the first entry from the map bin that matches the given key.

```
{
    "op" : aerospike.OP_MAP_REMOVE_BY_KEY,
    "bin": "my_map",
    "key": "age",
    "return_type": aerospike.MAP_RETURN_VALUE
}
```

aerospike.OP_MAP_REMOVE_BY_KEY_LIST

Remove the entries from the map bin that match the list of given keys. If inverted is set to True, remove all items except those in the list of keys.

```
{
    "op" : aerospike.OP_MAP_REMOVE_BY_KEY_LIST,
    "bin": "my_map",
    "val": ["name", "rank", "serial"],
    "inverted": False #Optional
}
```

aerospike.OP_MAP_REMOVE_BY_KEY_RANGE

Remove the entries from the map bin that have keys which fall between the given “key” (inclusive) and “val” (exclusive). If inverted is set to True, remove all items outside of the specified range.

```
{
    "op" : aerospike.OP_MAP_REMOVE_BY_KEY_RANGE,
    "bin": "my_map",
    "key": "i",
    "val": "j",
    "return_type": aerospike.MAP_RETURN_KEY_VALUE,
    "inverted": False # Optional
}
```

aerospike.OP_MAP_REMOVE_BY_VALUE

Remove the entry or entries from the map bin that have values which match the given “val” parameter. If inverted is set to True, remove all items with a value other than val

```
{
    "op" : aerospike.OP_MAP_REMOVE_BY_VALUE,
    "bin": "my_map",
```

(continues on next page)

(continued from previous page)

```

    "val": 97,
    "return_type": aerospike.MAP_RETURN_KEY
    "inverted": False #optional
}

```

aerospike.OP_MAP_REMOVE_BY_VALUE_LIST

Remove the entries from the map bin that have values which match the list of values given in the “val” parameter. If inverted is set to True, remove all items with values not contained in the list of values.

```

{
    "op" : aerospike.OP_MAP_REMOVE_BY_VALUE_LIST,
    "bin": "my_map",
    "val": [97, 98, 99],
    "return_type": aerospike.MAP_RETURN_KEY,
    "inverted": False # Optional
}

```

aerospike.OP_MAP_REMOVE_BY_VALUE_RANGE

Remove the entries from the map bin that have values starting with the given “val” parameter (inclusive) up to the given “range” parameter (exclusive). If inverted is set to True, remove all items outside of the specified range.

```

{
    "op" : aerospike.OP_MAP_REMOVE_BY_VALUE_RANGE,
    "bin": "my_map",
    "val": 97,
    "range": 100,
    "return_type": aerospike.MAP_RETURN_KEY,
    "inverted": False # Optional
}

```

aerospike.OP_MAP_REMOVE_BY_INDEX

Remove the entry from the map bin at the given “index” location.

```

{
    "op" : aerospike.OP_MAP_REMOVE_BY_INDEX,
    "bin": "my_map",
    "index": 0,
    "return_type": aerospike.MAP_RETURN_KEY_VALUE
}

```

aerospike.OP_MAP_REMOVE_BY_INDEX_RANGE

Remove the entries from the map bin starting at the given “index” location and removing “range” items. If inverted is set to True, remove all items outside of the specified range.

```

{
    "op" : aerospike.OP_MAP_REMOVE_BY_INDEX_RANGE,
    "bin": "my_map",
    "index": 0,
    "val": 2,
    "return_type": aerospike.MAP_RETURN_KEY_VALUE,
    "inverted": False # Optional
}

```

aerospike.OP_MAP_REMOVE_BY_RANK

Remove the first entry from the map bin that has a value with a rank matching the given “index”.

```
{
    "op" : aerospike.OP_MAP_REMOVE_BY_RANK,
    "bin": "my_map",
    "index": 10
}
```

aerospike.OP_MAP_REMOVE_BY_RANK

Remove the entries from the map bin that have values with a rank starting at the given “index” and removing “range” items. If `inverted` is set to True, remove all items outside of the specified range.

```
{
    "op" : aerospike.OP_MAP_REMOVE_BY_RANK_RANGE,
    "bin": "my_map",
    "index": 10,
    "val": 2,
    "return_type": aerospike.MAP_RETURN_KEY_VALUE,
    "inverted": False # Optional
}
```

aerospike.OP_MAP_GET_BY_KEY

Return the entry from the map bin that which has a key that matches the given “key” parameter.

```
{
    "op" : aerospike.OP_MAP_GET_BY_KEY,
    "bin": "my_map",
    "key": "age",
    "return_type": aerospike.MAP_RETURN_KEY_VALUE
}
```

aerospike.OP_MAP_GET_BY_KEY_RANGE

Return the entries from the map bin that have keys which fall between the given “key” (inclusive) and “val” (exclusive). If `inverted` is set to True, return all items outside of the specified range.

```
{
    "op" : aerospike.OP_MAP_GET_BY_KEY_RANGE,
    "bin": "my_map",
    "key": "i",
    "range": "j",
    "return_type": aerospike.MAP_RETURN_KEY_VALUE
    "inverted": False # Optional
}
```

aerospike.OP_MAP_GET_BY_VALUE

Return the entry or entries from the map bin that have values which match the given “val” parameter. If `inverted` is set to True, return all items with a value not equal to the given “val” parameter.

```
{
    "op" : aerospike.OP_MAP_GET_BY_VALUE,
    "bin": "my_map",
    "val": 97,
    "return_type": aerospike.MAP_RETURN_KEY
}
```

aerospike.OP_MAP_GET_BY_VALUE_RANGE

Return the entries from the map bin that have values starting with the given “val” parameter (inclusive) up to the given “range” parameter (exclusive). If `inverted` is set to True, return all items outside of the specified range.

```
{  
    "op" : aerospike.OP_MAP_GET_BY_VALUE_RANGE,  
    "bin": "my_map",  
    "val": 97,  
    "range": 100,  
    "return_type": aerospike.MAP_RETURN_KEY,  
    "inverted": False # Optional  
}
```

aerospike.OP_MAP_GET_BY_INDEX

Return the entry from the map bin at the given “index” location.

```
{  
    "op" : aerospike.OP_MAP_GET_BY_INDEX,  
    "bin": "my_map",  
    "index": 0,  
    "return_type": aerospike.MAP_RETURN_KEY_VALUE  
}
```

aerospike.OP_MAP_GET_BY_INDEX_RANGE

Return the entries from the map bin starting at the given “index” location and returning “range” items. If inverted is set to True, return all items outside of the specified range.

```
{  
    "op" : aerospike.OP_MAP_GET_BY_INDEX_RANGE,  
    "bin": "my_map",  
    "index": 0,  
    "val": 2,  
    "return_type": aerospike.MAP_RETURN_KEY_VALUE,  
    "inverted": False # Optional  
}
```

aerospike.OP_MAP_GET_BY_RANK

Return the first entry from the map bin that has a value with a rank matching the given “index”.

```
{  
    "op" : aerospike.OP_MAP_GET_BY_RANK,  
    "bin": "my_map",  
    "index": 10  
}
```

aerospike.OP_MAP_GET_BY_RANK_RANGE

Return the entries from the map bin that have values with a rank starting at the given “index” and removing “range” items. If inverted is set to True, return all items outside of the specified range.

```
{  
    "op" : aerospike.OP_MAP_GET_BY_RANK_RANGE,  
    "bin": "my_map",  
    "index": 10,  
    "val": 2,  
    "return_type": aerospike.MAP_RETURN_KEY_VALUE,  
    "inverted": False # Optional  
}
```

Changed in version 2.0.4.

1.1.3 Policy Options

1.1.3.1 Commit Level Policy Options

Specifies the number of replicas required to be successfully committed before returning success in a write operation to provide the desired consistency guarantee.

`aerospike.POLICY_COMMIT_LEVEL_ALL`

Return success only after successfully committing all replicas

`aerospike.POLICY_COMMIT_LEVEL_MASTER`

Return success after successfully committing the master replica

1.1.3.2 AP Read Mode Policy Options

Read policy for AP (availability) namespaces.

`aerospike.POLICY_READ_MODE_AP_ONE`

Involve single node in the read operation.

`aerospike.POLICY_READ_MODE_AP_ALL`

Involve all duplicates in the read operation.

New in version 3.7.0.

1.1.3.3 SC Read Mode Policy Options

Read policy for SC (strong consistency) namespaces.

`aerospike.POLICY_READ_MODE_SC_SESSION`

Ensures this client will only see an increasing sequence of record versions. Server only reads from master. This is the default.

`aerospike.POLICY_READ_MODE_SC_LINEARIZE`

Ensures ALL clients will only see an increasing sequence of record versions. Server only reads from master.

`aerospike.POLICY_READ_MODE_SC_ALLOW_REPLICA`

Server may read from master or any full (non-migrating) replica. Increasing sequence of record versions is not guaranteed.

`aerospike.POLICY_READ_MODE_SC_ALLOW_UNAVAILABLE`

Server may read from master or any full (non-migrating) replica or from unavailable partitions. Increasing sequence of record versions is not guaranteed.

New in version 3.7.0.

1.1.3.4 Existence Policy Options

Specifies the behavior for writing the record depending whether or not it exists.

`aerospike.POLICY_EXISTS_CREATE`

Create a record, ONLY if it doesn't exist

`aerospike.POLICY_EXISTS_CREATE_OR_REPLACE`

Completely replace a record if it exists, otherwise create it

`aerospike.POLICY_EXISTS_IGNORE`

Write the record, regardless of existence. (i.e. create or update)

aerospike.POLICY_EXISTS_REPLACE

Completely replace a record, ONLY if it exists

aerospike.POLICY_EXISTS_UPDATE

Update a record, ONLY if it exists

1.1.3.5 Generation Policy Options

Specifies the behavior of record modifications with regard to the generation value.

aerospike.POLICY_GEN_IGNORE

Write a record, regardless of generation

aerospike.POLICY_GEN_EQ

Write a record, ONLY if generations are equal

aerospike.POLICY_GEN_GT

Write a record, ONLY if local generation is greater-than remote generation

1.1.3.6 Key Policy Options

Specifies the behavior for whether keys or digests should be sent to the cluster.

aerospike.POLICY_KEY_DIGEST

Calculate the digest on the client-side and send it to the server

aerospike.POLICY_KEY_SEND

Send the key in addition to the digest. This policy causes a write operation to store the key on the server

1.1.3.7 Replica Options

Specifies which partition replica to read from.

aerospike.POLICY_REPLICA_SEQUENCE

Always try node containing master partition first. If connection fails and *retry_on_timeout* is true, try node containing prole partition. Currently restricted to master and one prole.

aerospike.POLICY_REPLICA_MASTER

Read from the partition master replica node

aerospike.POLICY_REPLICA_ANY

Distribute reads across nodes containing key's master and replicated partition in round-robin fashion. Currently restricted to master and one prole.

aerospike.POLICY_REPLICA_PREFER_RACK

Try node on the same rack as the client first. If there are no nodes on the same rack, use POLICY_REPLICA_SEQUENCE instead.

rack_aware and **rack_id** must be set in the config argument of the client constructor in order to enable this functionality

1.1.3.8 Retry Policy Options

Specifies the behavior of failed operations.

aerospike.POLICY_RETRY_NONE

Only attempt an operation once

aerospike.POLICY_RETRY_ONCE

If an operation fails, attempt the operation one more time

1.1.4 Constants

1.1.4.1 TTL Constants

Specifies the TTL constants.

aerospike.TTL_NAMESPACE_DEFAULT

Use the namespace default TTL.

aerospike.TTL_NEVER_EXPIRE

Set TTL to never expire.

aerospike.TTL_DONT_UPDATE

Do not change the current TTL of the record.

1.1.4.2 Auth Mode Constants

Specifies the type of authentication to be used when communicating with the server.

aerospike.AUTH_INTERNAL

Use internal authentication only. Hashed password is stored on the server. Do not send clear password. This is the default.

aerospike.AUTH_EXTERNAL

Use external authentication (like LDAP). Specific external authentication is configured on server. If TLS defined, send clear password on node login via TLS. Throw exception if TLS is not defined.

aerospike.AUTH_EXTERNAL_INSECURE

Use external authentication (like LDAP). Specific external authentication is configured on server. Send clear password on node login whether or not TLS is defined. This mode should only be used for testing purposes because it is not secure authentication.

1.1.4.3 Scan Constants

aerospike.SCAN_PRIORITY

Deprecated since version 3.10.0: Scan priority has been replaced by the records_per_second policy see [Scan Policies](#).

aerospike.SCAN_STATUS_ABORTED

Deprecated since version 1.0.50: used by [scan_info\(\)](#)

aerospike.SCAN_STATUS_COMPLETED

Deprecated since version 1.0.50: used by [scan_info\(\)](#)

aerospike.SCAN_STATUS_INPROGRESS

Deprecated since version 1.0.50: used by [scan_info\(\)](#)

aerospike.SCAN_STATUS_UNDEF

Deprecated since version 1.0.50: used by [scan_info\(\)](#)

New in version 1.0.39.

1.1.4.4 Job Constants

`aerospike.JOB_SCAN`

Scan job type argument for the module parameter of `job_info()`

`aerospike.JOB_QUERY`

Query job type argument for the module parameter of `job_info()`

1.1.4.5 Job Statuses

`aerospike.JOB_STATUS_UNDEF`

`aerospike.JOB_STATUS_INPROGRESS`

`aerospike.JOB_STATUS_COMPLETED`

New in version 1.0.50.

1.1.4.6 Serialization Constants

`aerospike.SERIALIZER_PYTHON`

Use the cPickle serializer to handle unsupported types (default)

`aerospike.SERIALIZER_USER`

Use a user-defined serializer to handle unsupported types. Must have been registered for the aerospike class or configured for the Client object

`aerospike.SERIALIZER_NONE`

Do not serialize bins whose data type is unsupported

New in version 1.0.47.

1.1.4.7 List Write Flags

Flags used by list write flag.

`aerospike.LIST_WRITE_DEFAULT`

Default. Allow duplicate values and insertions at any index.

`aerospike.LIST_WRITE_ADD_UNIQUE`

Only add unique values.

`aerospike.LIST_WRITE_INSERT_BOUNDED`

Enforce list boundaries when inserting. Do not allow values to be inserted at index outside current list boundaries.

Note: Requires server version >= 4.3.0

`aerospike.LIST_WRITE_NO_FAIL`

Do not raise error if a list item fails due to write flag constraints (always succeed).

Note: Requires server version >= 4.3.0

`aerospike.LIST_WRITE_PARTIAL`

Allow other valid list items to be committed if a list item fails due to write flag constraints.

1.1.4.8 List Return Types

Return types used by various list operations.

`aerospike.LIST_RETURN_NONE`

Do not return any value.

`aerospike.LIST_RETURN_INDEX`

Return key index order.

`aerospike.LIST_RETURN_REVERSE_INDEX`

Return reverse key order.

`aerospike.LIST_RETURN_RANK`

Return value order.

`aerospike.LIST_RETURN_REVERSE_RANK`

Return reverse value order.

`aerospike.LIST_RETURN_COUNT`

Return count of items selected.

`aerospike.LIST_RETURN_VALUE`

Return value for single key read and value list for range read.

1.1.4.9 List Order

Flags used by list order.

`aerospike.LIST_UNORDERED`

List is not ordered. This is the default.

`aerospike.LIST_ORDERED`

Ordered list.

1.1.4.10 List Sort Flags

Flags used by list sort.

`aerospike.LIST_SORT_DEFAULT`

Default. Preserve duplicates when sorting the list.

`aerospike.LIST_SORT_DROP_DUPLICATES`

Drop duplicate values when sorting the list.

1.1.4.11 Map Write Flag

Flags used by map write flag.

Note: Requires server version >= 4.3.0

`aerospike.MAP_WRITE_FLAGS_DEFAULT`

Default. Allow create or update.

`aerospike.MAP_WRITE_FLAGS_CREATE_ONLY`

If the key already exists, the item will be denied. If the key does not exist, a new item will be created.

aerospike.MAP_WRITE_FLAGS_UPDATE_ONLY

If the key already exists, the item will be overwritten. If the key does not exist, the item will be denied.

aerospike.MAP_WRITE_FLAGS_NO_FAIL

Do not raise error if a map item is denied due to write flag constraints (always succeed).

aerospike.MAP_WRITE_FLAGS_PARTIAL

Allow other valid map items to be committed if a map item is denied due to write flag constraints.

1.1.4.12 Map Write Mode

Flags used by map *write mode*.

Note: This should only be used for Server version < 4.3.0

aerospike.MAP_UPDATE

Default. Allow create or update.

aerospike.MAP_CREATE_ONLY

If the key already exists, the item will be denied. If the key does not exist, a new item will be created.

aerospike.MAP_UPDATE_ONLY

If the key already exists, the item will be overwritten. If the key does not exist, the item will be denied.

1.1.4.13 Map Order

Flags used by map order.

aerospike.MAP_UNORDERED

Map is not ordered. This is the default.

aerospike.MAP_KEY_ORDERED

Order map by key.

aerospike.MAP_KEY_VALUE_ORDERED

Order map by key, then value.

1.1.4.14 Map Return Types

Return types used by various map operations.

aerospike.MAP_RETURN_NONE

Do not return any value.

aerospike.MAP_RETURN_INDEX

Return key index order.

aerospike.MAP_RETURN_REVERSE_INDEX

Return reverse key order.

aerospike.MAP_RETURN_RANK

Return value order.

aerospike.MAP_RETURN_REVERSE_RANK

Return reserve value order.

aerospike.MAP_RETURN_COUNT

Return count of items selected.

aerospike.MAP_RETURN_KEY

Return key for single key read and key list for range read.

aerospike.MAP_RETURN_VALUE

Return value for single key read and value list for range read.

aerospike.MAP_RETURN_KEY_VALUE

Return key/value items. Note that key/value pairs will be returned as a list of tuples (i.e. [(key1, value1), (key2, value2)])

1.1.4.15 Bitwise Write Flags

aerospike.BIT_WRITE_DEFAULT

Allow create or update (default).

aerospike.BIT_WRITE_CREATE_ONLY

If bin already exists the operation is denied. Otherwise the bin is created.

aerospike.BIT_WRITE_UPDATE_ONLY

If bin does not exist the operation is denied. Otherwise the bin is updated.

aerospike.BIT_WRITE_NO_FAIL

Do not raise error if operation failed.

aerospike.BIT_WRITE_PARTIAL

Allow other valid operations to be committed if this operation is denied due to flag constraints. i.e. If the number of bytes from the offset to the end of the existing Bytes bin is less than the specified number of bytes, then only apply operations from the offset to the end.

New in version 3.9.0.

1.1.4.16 Bitwise Resize Flags

aerospike.BIT_RESIZE_DEFAULT

Add/remove bytes from the end (default).

aerospike.BIT_RESIZE_FROM_FRONT

Add/remove bytes from the front.

aerospike.BIT_RESIZE_GROW_ONLY

Only allow the bitmap size to increase.

aerospike.BIT_RESIZE_SHRINK_ONLY

Only allow the bitmap size to decrease.

New in version 3.9.0.

1.1.4.17 Bitwise Overflow

aerospike.BIT_OVERFLOW_FAIL

Operation will fail on overflow/underflow.

aerospike.BIT_OVERFLOW_SATURATE

If add or subtract ops overflow/underflow, set to max/min value. Example: MAXINT + 1 = MAXINT.

aerospike.BIT_OVERFLOW_WRAP

If add or subtract ops overflow/underflow, wrap the value. Example: MAXINT + 1 = MININT.

New in version 3.9.0.

1.1.4.18 HyperLogLog Write Flags**aerospike.HLL_WRITE_DEFAULT**

Default. Allow create or update.

aerospike.HLL_WRITE_CREATE_ONLY

If the bin already exists, the operation will be denied. If the bin does not exist, a new bin will be created.

aerospike.HLL_WRITE_UPDATE_ONLY

If the bin already exists, the bin will be overwritten. If the bin does not exist, the operation will be denied.

aerospike.HLL_WRITE_NO_FAIL

Do not raise error if operation is denied.

aerospike.HLL_WRITE_ALLOW_FOLD

Allow the resulting set to be the minimum of provided index bits. For intersect_counts and similarity, allow the usage of less precise HLL algorithms when minhash bits of all participating sets do not match.

New in version 3.11.0.

1.1.4.19 Bin Types**aerospike.AS_BYTES_UNDEF**

(int): 0

aerospike.AS_BYTES_INTEGER

(int): 1

aerospike.AS_BYTES_DOUBLE

(int): 2

aerospike.AS_BYTES_STRING

(int): 3

aerospike.AS_BYTES_BLOB

(int): 4

aerospike.AS_BYTES_JAVA

(int): 7

aerospike.AS_BYTES_CSHARP

(int): 8

aerospike.AS_BYTES_PYTHON

(int): 9

aerospike.AS_BYTES_RUBY

(int): 10

aerospike.AS_BYTES_PHP

(int): 11

aerospike.AS_BYTES_ERLANG

(int): 12

```
aerospike.AS_BYTES_HLL
    (int): 18

aerospike.AS_BYTES_MAP
    (int): 19

aerospike.AS_BYTES_LIST
    (int): 20

aerospike.AS_BYTES_GEOJSON
    (int): 23

aerospike.AS_BYTES_TYPE_MAX
    (int): 24
```

1.1.4.20 Miscellaneous

`aerospike.__version__`

A `str` containing the module's version.

New in version 1.0.54.

`aerospike.null`

A value for distinguishing a server-side null from a Python `None`.

Deprecated since version 2.0.1: use the function `aerospike.null()` instead.

`aerospike.UDF_TYPE_LUA`

UDF type is LUA (which is the only UDF type).

`aerospike.INDEX_STRING`

An index whose values are of the aerospike string data type.

`aerospike.INDEX_NUMERIC`

An index whose values are of the aerospike integer data type.

`aerospike.INDEX_GEO2DSPHERE`

An index whose values are of the aerospike GetJSON data type.

See also:

[Data Types](#).

`aerospike.INDEX_TYPE_LIST`

Index a bin whose contents is an aerospike list.

`aerospike.INDEX_TYPE_MAPKEYS`

Index the keys of a bin whose contents is an aerospike map.

`aerospike.INDEX_TYPE_MAPVALUES`

Index the values of a bin whose contents is an aerospike map.

1.1.4.21 Log Level

`aerospike.LOG_LEVEL_TRACE`

`aerospike.LOG_LEVEL_DEBUG`

`aerospike.LOG_LEVEL_INFO`

`aerospike.LOG_LEVEL_WARN`

`aerospike.LOG_LEVEL_ERROR`

`aerospike.LOG_LEVEL_OFF`

1.1.4.22 Privileges

Permission codes define the type of permission granted for a user's role.

`aerospike.PRIV_READ`

The user is granted read access.

`aerospike.PRIV_WRITE`

The user is granted write access.

`aerospike.PRIV_READ_WRITE`

The user is granted read and write access.

`aerospike.PRIV_READ_WRITE_UDF`

The user is granted read and write access, and the ability to invoke UDFs.

`aerospike.PRIV_SYS_ADMIN`

The user is granted the ability to perform system administration operations. Global scope only.

`aerospike.PRIV_USER_ADMIN`

The user is granted the ability to perform user administration operations. Global scope only.

`aerospike.PRIV_DATA_ADMIN`

User can perform systems administration functions on a database that do not involve user administration. Examples include setting dynamic server configuration. Global scope only.

1.1.4.23 Regex Flag Values

Flags used for the `predexp.string_regex` function.

`aerospike.REGEX_NONE`

Use default behavior.

`aerospike.REGEX_ICASE`

Do not differentiate case.

`aerospike.REGEX_EXTENDED`

Use POSIX Extended Regular Expression syntax when interpreting regex.

`aerospike.REGEX_NOSUB`

Do not report position of matches.

`aerospike.REGEX_NEWLINE`

Match-any-character operators don't match a newline.

1.2 Client Class — Client

1.2.1 Client

The client connects through a seed node (the address of a single node) to an Aerospike database cluster. From the seed node, the client learns of the other nodes and establishes connections to them. It also gets the partition map of the cluster, which is how it knows where every record actually lives.

The client handles the connections, including re-establishing them ahead of executing an operation. It keeps track of changes to the cluster through a cluster-tending thread.

See also:

[Client Architecture and Data Distribution](#).

Example:

```
from __future__ import print_function
# import the module
import aerospike
from aerospike import exception as ex
import sys

# Configure the client
config = {
    'hosts': [ ('127.0.0.1', 3000) ]
}

# Optionally set policies for various method types
write_policies = {'total_timeout': 2000, 'max_retries': 0}
read_policies = {'total_timeout': 1500, 'max_retries': 1}
policies = {'write': write_policies, 'read': read_policies}
config['policies'] = policies

# Create a client and connect it to the cluster
try:
    client = aerospike.client(config).connect()
except ex.ClientError as e:
    print("Error: {} [{!r}]".format(e.msg, e.code))
    sys.exit(1)

# Records are addressable via a tuple of (namespace, set, primary key)
key = ('test', 'demo', 'foo')

try:
    # Write a record
    client.put(key, {
        'name': 'John Doe',
        'age': 32
    })
except ex.RecordError as e:
    print("Error: {} [{!r}]".format(e.msg, e.code))

# Read a record
(key, meta, record) = client.get(key)

# Close the connection to the Aerospike cluster
client.close()

.. index::
    single: Connection

.. _aerospike_connection_operations:
```

1.2.1.1 Connection

```
class aerospike.Client
```

connect ([*username, password*])

Connect to the cluster. The optional *username* and *password* only apply when connecting to the Enterprise Edition of Aerospike.

Parameters

- **username** (*str*) – a defined user with roles in the cluster. See [admin_create_user\(\)](#).
- **password** (*str*) – the password will be hashed by the client using bcrypt.

Raises [ClientError](#), for example when a connection cannot be established to a seed node (any single node in the cluster from which the client learns of the other nodes).

Note: Python client 5.0.0 and up will fail to connect to Aerospike server 4.8.x or older. If you see the error “-10, ‘Failed to connect’”, please make sure you are using server 4.9 or later.

See also:

[Security features article](#).

is_connected()

Tests the connections between the client and the nodes of the cluster. If the result is `False`, the client will require another call to [connect\(\)](#).

Return type `bool`

Changed in version 2.0.0.

close()

Close all connections to the cluster. It is recommended to explicitly call this method when the program is done communicating with the cluster.

1.2.1.2 Key Tuple

key

The key tuple, which is sent and returned by various operations, has the structure

```
(namespace, set, primary key[, the record's RIPEMD-160 digest])
```

- *namespace* the *str* name of the namespace, which must be preconfigured on the cluster.
- *set* the *str* name of the set. Will be created automatically if it does not exist.
- *primary key* the value by which the client-side application identifies the record, which can be of type *str*, *int* or *bytarray*.
- *digest* the first three parts of the tuple get hashed through RIPEMD-160, and the digest used by the clients and cluster nodes to locate the record. A key tuple is also valid if it has the digest part filled and the primary key part set to `None`.

```
>>> client = aerospike.client(config).connect()
>>> client.put('test','demo','oof'), {'id':0, 'a':1})
>>> (key, meta, bins) = client.get('test','demo','oof')
>>> key
('test', 'demo', None, bytearray(b'\t\xcb\xb9\xb6V\xecI
˓→#\xeal\x05\x00H\x98\xe4=')
>>> (key2, meta2, bins2) = client.get(key)
>>> bins2
{'a': 1, 'id': 0}
>>> client.close()
```

See also:

Data Model: Keys and Digests.

1.2.1.3 Record Tuple**record**

The record tuple (key, meta, bins) which is returned by various read operations.

- *key* the *Key Tuple*.
- *meta* a *dict* containing { 'gen' : generation value, 'ttl': ttl value}.
- *bins* a *dict* containing bin-name/bin-value pairs.

See also:

Data Model: Record.

1.2.2 Operations**1.2.2.1 Record Operations****class aerospike.Client****put (key, bins[, meta[, policy[, serializer]]])**

Write a record with a given *key* to the cluster.

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bins** (*dict*) – a *dict* of bin-name / bin-value pairs.
- **meta** (*dict*) – optional record metadata to be set, with field 'ttl' set to *int* number of seconds or one of the *TTL Constants*, and 'gen' set to *int* generation number to compare.
- **policy** (*dict*) – optional *Write Policies*.
- **serializer** – optionally override the serialization mode of the client with one of the *Serialization Constants*. To use a class-level user-defined serialization function registered with `aerospike.set_serializer()` use `aerospike.SERIALIZER_USER`.

Raises a subclass of *AerospikeError*.

```
from __future__ import print_function
import aerospike
from aerospike import exception as ex

config = {
    'hosts': [ ('127.0.0.1', 3000) ],
    'total_timeout': 1500
}
client = aerospike.client(config).connect()
try:
    key = ('test', 'demo', 1)
    bins = {
        '1': [ "qwertyuiop", 1, bytearray("asd;as[d'as;d", "utf-8") ],
        '2': [ "1234567890", 2, bytearray("1234567890", "utf-8") ]
    }
    client.put(key, bins)
except ex.Error as e:
    print("Error", e)
```

(continues on next page)

(continued from previous page)

```

'm': { "key": "asd';q;'1';" },
'i': 1234,
'f': 3.14159265359,
's': '!@#@#$QSDAsd;as'
}
client.put(key, bins,
            policy={'key': aerospike.POLICY_KEY_SEND},
            meta={'ttl':180})
# adding a bin
client.put(key, {'smiley': u"\ud83d\ude04"})
# removing a bin
client.put(key, {'i': aerospike.null()})
except ex.AerospikeError as e:
    print("Error: {} [{}].format(e.msg, e.code)")
    sys.exit(1)
finally:
    client.close()

```

Note: Version >= 3.10.0 Supports predicate expressions for record operations see [predexp](#). Requires server version >= 4.7.0.

```

from __future__ import print_function
import aerospike
from aerospike import predexp
from aerospike import exception as ex
import sys

config = {"hosts": [("127.0.0.1", 3000)]}
client = aerospike.client(config).connect()

try:
    keys = [("test", "demo", 1), ("test", "demo", 2), ("test", "demo", 3)]
    records = [{"number": 1}, {"number": 2}, {"number": 3}]
    for i in range(3):
        client.put(keys[i], records[i])

    preds = [  # check that the record has a value < 2 bin 'name'
        predexp.integer_bin("number"),
        predexp.integer_value(2),
        predexp.integer_less(),
    ]
    records = []

    for i in range(3):
        try:
            records.append(client.get(keys[i], policy={"predexp": preds}))
        except ex.FilteredOut as e:
            print("Error: {} [{}].format(e.msg, e.code)")

        print(records)
except ex.AerospikeError as e:
    print("Error: {} [{}].format(e.msg, e.code)")
    sys.exit(1)
finally:
    client.close()

```

(continues on next page)

(continued from previous page)

```
# the get only returns records that match the preds
# otherwise, an error is returned
# EXPECTED OUTPUT:
# Error: 127.0.0.1:3000 AEROSPIKE_FILTERED_OUT [27]
# Error: 127.0.0.1:3000 AEROSPIKE_FILTERED_OUT [27]
# [((('test', 'demo', 1, bytarray(b'\xb7\xf4\xb8\x89\xe2\xdag\xdeh>
# \xd1\xf6\x91\x9a\x1e\xac\xc4F\xc8')), {'gen': 8, 'ttl': 2592000}, {'charges':
# ': [10, 20, 14], 'name': 'John', 'number': 1})]
```

Note: Using Generation Policy

The generation policy allows a record to be written only when the generation is a specific value. In the following example, we only want to write the record if no change has occurred since `exists()` was called.

```
from __future__ import print_function
import aerospike
from aerospike import exception as ex
import sys

config = { 'hosts': [ ('127.0.0.1',3000)]}
client = aerospike.client(config).connect()

try:
    (key, meta) = client.exists(('test','test','key1'))
    print(meta)
    print('=====')
    client.put(('test','test','key1'), {'id':1,'a':2},
               meta={'gen': 33},
               policy={'gen':aerospike.POLICY_GEN_EQ})
    print('Record written.')
except ex.RecordGenerationError:
    print("put() failed due to generation policy mismatch")
except ex.AerospikeError as e:
    print("Error: {} [{}]".format(e.msg, e.code))
client.close()
```

`exists(key[, policy]) -> (key, meta)`

Check if a record with a given `key` exists in the cluster and return the record as a `tuple()` consisting of `key` and `meta`. If the record does not exist the `meta` data will be `None`.

Parameters

- **key** (`tuple`) – a *Key Tuple* associated with the record.
- **policy** (`dict`) – optional *Read Policies*.

Return type `tuple()` (key, meta)

Raises a subclass of `AerospikeError`.

```
from __future__ import print_function
import aerospike
from aerospike import exception as ex
import sys
```

(continues on next page)

(continued from previous page)

```

config = { 'hosts': [('127.0.0.1', 3000)] }
client = aerospike.client(config).connect()

try:
    # assuming a record with such a key exists in the cluster
    key = ('test', 'demo', 1)
    (key, meta) = client.exists(key)
    print(key)
    print('-----')
    print(meta)
except ex.RecordNotFound:
    print("Record not found:", key)
except ex.AerospikeError as e:
    print("Error: {} [{}].format(e.msg, e.code)")
    sys.exit(1)
finally:
    client.close()

```

Changed in version 2.0.3.

get (*key[, policy]*) -> (*key, meta, bins*)

Read a record with a given *key*, and return the record as a `tuple()` consisting of *key, meta* and *bins*.

Parameters

- **key** (`tuple`) – a *Key Tuple* associated with the record.
- **policy** (`dict`) – optional *Read Policies*.

Returns a *Record Tuple*. See [Unicode Handling](#).

Raises `RecordNotFound`.

```

from __future__ import print_function
import aerospike
from aerospike import exception as ex
import sys

config = {'hosts': [('127.0.0.1', 3000)]}
client = aerospike.client(config).connect()

try:
    # assuming a record with such a key exists in the cluster
    key = ('test', 'demo', 1)
    (key, meta, bins) = client.get(key)
    print(key)
    print('-----')
    print(meta)
    print('-----')
    print(bins)
except ex.RecordNotFound:
    print("Record not found:", key)
except ex.AerospikeError as e:
    print("Error: {} [{}].format(e.msg, e.code)")
    sys.exit(1)
finally:
    client.close()

```

Warning: The client has been changed to raise a `RecordNotFound` exception when `get()` does not find the record. Code that used to check for `meta != None` should be modified.

Changed in version 2.0.0.

`select(key, bins[, policy]) -> (key, meta, bins)`

Read a record with a given `key`, and return the record as a `tuple()` consisting of `key`, `meta` and `bins`, with the specified bins projected. Prior to Aerospike server 3.6.0, if a selected bin does not exist its value will be `None`. Starting with 3.6.0, if a bin does not exist it will not be present in the returned `Record Tuple`.

Parameters

- `key` (`tuple`) – a `Key Tuple` associated with the record.
- `bins` (`list`) – a list of bin names to select from the record.
- `policy` (`dict`) – optional `Read Policies`.

Returns a `Record Tuple`. See [Unicode Handling](#).

Raises `RecordNotFound`.

```
from __future__ import print_function
import aerospike
from aerospike import exception as ex
import sys

config = { 'hosts': [('127.0.0.1', 3000)] }
client = aerospike.client(config).connect()

try:
    # assuming a record with such a key exists in the cluster
    key = ('test', 'demo', 1)
    (key, meta, bins) = client.select(key, ['name'])
    print("name: ", bins.get('name'))
except ex.RecordNotFound:
    print("Record not found:", key)
except ex.AerospikeError as e:
    print("Error: {} [{}]".format(e.msg, e.code))
    sys.exit(1)
finally:
    client.close()
```

Warning: The client has been changed to raise a `RecordNotFound` exception when `select()` does not find the record. Code that used to check for `meta != None` should be modified.

Changed in version 2.0.0.

`touch(key[, val=0[, meta[, policy]]])`

Touch the given record, setting its `time-to-live` and incrementing its generation.

Parameters

- `key` (`tuple`) – a `Key Tuple` tuple associated with the record.
- `val` (`int`) – the optional ttl in seconds, with 0 resolving to the default value in the server config.
- `meta` (`dict`) – optional record metadata to be set.

- **policy** (*dict*) – optional *Operate Policies*.

Raises a subclass of *AerospikeError*.

See also:

Record TTL and Evictions and FAQ.

```
import aerospike

config = { 'hosts': [('127.0.0.1', 3000)] }
client = aerospike.client(config).connect()

key = ('test', 'demo', 1)
client.touch(key, 120, policy={'total_timeout': 100})
client.close()
```

remove (*key[meta, policy]*)

Remove a record matching the *key* from the cluster.

Parameters

- **key** (*tuple*) – a *Key Tuple* associated with the record.
- **meta** (*dict*) – Optional dictionary allowing a user to specify the expected generation of the record.
- **policy** (*dict*) – optional *Remove Policies*. May be passed as a keyword argument.

Raises a subclass of *AerospikeError*.

```
import aerospike

config = { 'hosts': [('127.0.0.1', 3000)] }
client = aerospike.client(config).connect()

key = ('test', 'demo', 1)
client.remove(key, meta={'gen': 5}, policy={'gen': aerospike.POLICY_GEN_EQ})
client.close()
```

get_key_digest (*ns, set, key*) → *bytarray*

Calculate the digest of a particular key. See: *Key Tuple*.

Parameters

- **ns** (*str*) – the namespace in the aerospike cluster.
- **set** (*str*) – the set name.
- **key** (*str or int*) – the primary key identifier of the record within the set.

Returns a RIPEMD-160 digest of the input tuple.

Return type *bytarray*

```
import aerospike
import pprint

pp = pprint.PrettyPrinter(indent=2)
config = { 'hosts': [('127.0.0.1', 3000)] }
client = aerospike.client(config).connect()

digest = client.get_key_digest("test", "demo", 1)
```

(continues on next page)

(continued from previous page)

```
pp.pprint(digest)
key = ('test', 'demo', None, digest)
(key, meta, bins) = client.get(key)
pp.pprint(bins)
client.close()
```

Deprecated since version 2.0.1: use the function `aerospike.calc_digest()` instead.

Removing a Bin

remove_bin(*key*, *list*[, *meta*[, *policy*]])

Remove a list of bins from a record with a given *key*. Equivalent to setting those bins to `aerospike.null()` with a `put()`.

Parameters

- **key** (*tuple*) – a *Key Tuple* associated with the record.
- **list** (*list*) – the bins names to be removed from the record.
- **meta** (*dict*) – optional record metadata to be set, with field 'ttl' set to *int* number of seconds or one of the *TTL Constants*, and 'gen' set to *int* generation number to compare.
- **policy** (*dict*) – optional *Write Policies*.

Raises a subclass of `AerospikeError`.

```
import aerospike

config = { 'hosts': [('127.0.0.1', 3000)] }
client = aerospike.client(config).connect()

key = ('test', 'demo', 1)
meta = { 'ttl': 3600 }
client.remove_bin(key, ['name', 'age'], meta, {'retry': aerospike.POLICY_
    ↴RETRY_ONCE})
client.close()
```

1.2.2.2 Batch Operations

class aerospike.Client

get_many(*keys*[, *policy*]) → [(*key*, *meta*, *bins*)]

Batch-read multiple records, and return them as a *list*. Any record that does not exist will have a `None` value for metadata and bins in the record tuple.

Parameters

- **keys** (*list*) – a list of *Key Tuple*.
- **policy** (*dict*) – optional *Batch Policies*.

Returns a list of *Record Tuple*.

Raises a `ClientError` if the batch is too big.

See also:

More information about the [Batch Index](#) interface new to Aerospike server >= 3.6.0.

```
from __future__ import print_function
import aerospike
from aerospike import exception as ex
import sys

config = { 'hosts': [('127.0.0.1', 3000)] }
client = aerospike.client(config).connect()

try:
    # assume the fourth key has no matching record
    keys = [
        ('test', 'demo', '1'),
        ('test', 'demo', '2'),
        ('test', 'demo', '3'),
        ('test', 'demo', '4')
    ]
    records = client.get_many(keys)
    print(records)
except ex.AerospikeError as e:
    print("Error: {} [{}].format(e.msg, e.code))")
    sys.exit(1)
finally:
    client.close()
```

Note: We expect to see something like:

```
[((('test', 'demo', '1', bytearray(b'ev\xb4\x88\x8c\xcf\x92\x9c\x0b\xbd\x90\xd0\x9d\xf3\xf6\xd1\x0c\xf3')), {'gen': 1, 'ttl': 2592000}, {'age': 1, 'name': u'Name1'}), ((('test', 'demo', '2', bytearray(b'\n\xcd7p\x88\xdcF\xe1\xd6\x0e\x05\xfb\xcbs\x a68I\xf0T\xfd')), {'gen': 1, 'ttl': 2592000}, {'age': 2, 'name': u'Name2'}), ((('test', 'demo', '3', bytearray(b'\x9f\xf2\xe3\xf3\xc0\xc1\xc3q\xb5\xn\xf8\xccV\x a9\xed\xd91a\x86')), {'gen': 1, 'ttl': 2592000}, {'age': 3, 'name': u'Name3'}), ((('test', 'demo', '4', bytearray(b'\x8eu\x19\xbe\xe0(\xda ^\xfa\x8ca\x93s\xe8\xb3%\xa8]\x8b')), None, None)])]
```

Note: Version >= 3.10.0 Supports predicate expressions for batch operations see [predexp](#). Requires server version >= 4.7.0

```
from __future__ import print_function
import aerospike
from aerospike import predexp
from aerospike import exception as ex
import sys

config = {"hosts": ["127.0.0.1", 3000]}
client = aerospike.client(config).connect()
```

(continues on next page)

(continued from previous page)

```

try:
    keys = [ ("test", "demo", 1), ("test", "demo", 2), ("test", "demo", 3) ]
    records = [{"number": 1}, {"number": 2}, {"number": 3}]
    for i in range(3):
        client.put(keys[i], records[i])

    preds = [ # check that the record has a value less than 2 in bin 'name'
        predexp.integer_bin("number"),
        predexp.integer_value(2),
        predexp.integer_less(),
    ]
    records = client.get_many(keys, policy={"predexp": preds})
    print(records)
except ex.AerospikeError as e:
    print("Error: {} [{}].format(e.msg, e.code)")
    sys.exit(1)
finally:
    client.close()
# the get_many only returns the records that matched the preds
# EXPECTED OUTPUT:
# [
#     ('test', 'demo', 1, bytearray(b'\xb7\xf4\xb8\x89\xe2\xdag\xdeh>
# \xd1\xf6\x91\x9a\x1e\xac\xc4F\xc8')), {'gen': 8, 'ttl': 2592000}, {'charges':
# ': [10, 20, 14], 'name': 'John', 'number': 1}),
#     ('test', 'demo', 2, bytearray(b'\xaejQ_
# \x7\xdeJ\xda\xccD\x96\xe2\xda\x1f\xea\x84\x8c:\x92p')), None, None),
#     ('test', 'demo', 3, bytearray(b
# \xb1\xa5`g\xf6\xd4\x8\x4D9\xd3\xafb\xbf\xf8ha\x01\x94\xcd')), None, None)
# ]

```

Warning: The return type changed to `list` starting with version 1.0.50.

`exists_many(keys[, policy])` → [(key, meta)]

Batch-read metadata for multiple keys, and return it as a list. Any record that does not exist will have a `None` value for metadata in the result tuple.

Parameters

- **keys** (`list`) – a list of `Key Tuple`.
- **policy** (`dict`) – optional `Batch Policies`.

Returns a list of (key, metadata) `tuple()`.

See also:

More information about the `Batch Index` interface new to Aerospike server >= 3.6.0.

```

from __future__ import print_function
import aerospike
from aerospike import exception as ex
import sys

```

(continues on next page)

(continued from previous page)

```

config = { 'hosts': [ ('127.0.0.1', 3000) ] }
client = aerospike.client(config).connect()

try:
    # assume the fourth key has no matching record
    keys = [
        ('test', 'demo', '1'),
        ('test', 'demo', '2'),
        ('test', 'demo', '3'),
        ('test', 'demo', '4')
    ]
    records = client.exists_many(keys)
    print(records)
except ex.AerospikeError as e:
    print("Error: {} [{}].format(e.msg, e.code)")
    sys.exit(1)
finally:
    client.close()

```

Note: We expect to see something like:

```

[
    (('test', 'demo', '1', bytearray(b'ev\xb4\x88\x8c\xcf\x92\x9c\x0b\xbd\x90\xd0\x9d\xf3\xf6\xd1\x0c\xf3')), {'gen': 2, 'ttl': 2592000}),
    (('test', 'demo', '2', bytearray(b'n\xcd7p\x88\xdc\xe1\xd6\x0e\x05\xfb\xcbs\x a68I\xf0T\xfd')), {'gen': 7, 'ttl': 1337}),
    (('test', 'demo', '3', bytearray(b'\x9f\xf2\xe3\xf3\xc0\xc1\xc3q\xb5\xf8\xcc\x9\xed\xd9\x86')), {'gen': 9, 'ttl': 543}),
    (('test', 'demo', '4', bytearray(b'\x8eu\x19\xbe\xe0(\xda^\xfa\x8ca\x93s\xe8\xb3%\xa8]\x8b')), None)
]

```

Warning: The return type changed to `list` starting with version 1.0.50.

select_many (`keys, bins[, policy]`) → `[(key, meta, bins), ...]`

Batch-read multiple records, and return them as a `list`. Any record that does not exist will have a `None` value for metadata and bins in the record tuple. The `bins` will be filtered as specified.

Parameters

- **keys** (`list`) – a list of *Key Tuple*.
- **bins** (`list`) – the bin names to select from the matching records.
- **policy** (`dict`) – optional *Batch Policies*.

Returns a list of *Record Tuple*.

See also:

More information about the `Batch Index` interface new to Aerospike server >= 3.6.0.

```

from __future__ import print_function
import aerospike
from aerospike import exception as ex
import sys

config = { 'hosts': [ ('127.0.0.1', 3000)] }
client = aerospike.client(config).connect()

try:
    # assume the fourth key has no matching record
    keys = [
        ('test', 'demo', None, bytearray(b'\x0b\xbd\x90\xd0\x9d\xf3\xf6\xd1\x0c\xf3')),
        ('test', 'demo', None, bytearray(b'\n\xcd7p\x88\xdc\xe1\xd6\x0e\x05\xfb\xcbs\x\x68I\x\x0T\xfd')),
        ('test', 'demo', None, bytearray(b'\x9f\xf2\xe3\xf3\xc0\xc1\xc3q\xb5\x\x88\xcc\x\x9\x\xed\x\x91a\x\x86')),
        ('test', 'demo', None, bytearray(b'\x8eu\x19\xbe\xe0(\x\xda ^\x\xfa\x\xca\x\x93s\x\x8\x\xb3%\x\x8a]\x\x8b'))
    ]
    records = client.select_many(keys, [u'name'])
    print(records)
except ex.AerospikeError as e:
    print("Error: {} [{}].format(e.msg, e.code))")
    sys.exit(1)
finally:
    client.close()

```

Note: We expect to see something like:

```
[
    ({'test', 'demo', None, bytearray(b'\x0b\xbd\x90\xd0\x9d\xf3\xf6\xd1\x0c\xf3')}, {'gen': 1, 'ttl': 2592000}, {
    'name': u'Name1'}),
    ({'test', 'demo', None, bytearray(b'\n\xcd7p\x88\xdc\xe1\xd6\x0e\x05\xfb\xcbs\x\x68I\x\x0T\xfd')}, {'gen': 1,
    'ttl': 2592000}, {'name': u'Name2'}),
    ({'test', 'demo', None, bytearray(b'\x9f\xf2\xe3\xf3\xc0\xc1\xc3q\xb5\x\x88\xcc\x\x9\x\xed\x\x91a\x\x86')}, {'gen': 1, 'ttl': 2592000}, {'name': u'Name3'}),
    ({'test', 'demo', None, bytearray(b'\x8eu\x19\xbe\xe0(\x\xda ^\x\xfa\x\xca\x\x93s\x\x8\x\xb3%\x\x8a]\x\x8b')}, None, None)
]
```

Warning: The return type changed to list starting with version 1.0.50.

1.2.2.3 String Operations

```
class aerospike.Client
```

Note: Please see `aerospike_helpers.operations.operations` for the new way to use string operations.

append(*key, bin, val[, meta[, policy]]*)

Append the string *val* to the string value in *bin*.

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **val** (*str*) – the string to append to the value of *bin*.
- **meta** (*dict*) – optional record metadata to be set, with field 'ttl' set to *int* number of seconds or one of the *TTL Constants*, and 'gen' set to *int* generation number to compare.
- **policy** (*dict*) – optional *Operate Policies*.

Raises a subclass of *AerospikeError*.

```
from __future__ import print_function
import aerospike
from aerospike import exception as ex
import sys

config = { 'hosts': [('127.0.0.1', 3000)] }
client = aerospike.client(config).connect()

try:
    key = ('test', 'demo', 1)
    client.append(key, 'name', ' jr.', policy={'total_timeout': 1200})
except ex.AerospikeError as e:
    print("Error: {} [{}].format(e.msg, e.code)")
    sys.exit(1)
finally:
    client.close()
```

prepend(*key, bin, val[, meta[, policy]]*)

Prepend the string value in *bin* with the string *val*.

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **val** (*str*) – the string to prepend to the value of *bin*.
- **meta** (*dict*) – optional record metadata to be set, with field 'ttl' set to *int* number of seconds or one of the *TTL Constants*, and 'gen' set to *int* generation number to compare.
- **policy** (*dict*) – optional *Operate Policies*.

Raises a subclass of *AerospikeError*.

```
from __future__ import print_function
import aerospike
from aerospike import exception as ex
```

(continues on next page)

(continued from previous page)

```

import sys

config = { 'hosts': [('127.0.0.1', 3000)] }
client = aerospike.client(config).connect()

try:
    key = ('test', 'demo', 1)
    client.prepend(key, 'name', 'Dr. ', policy={'total_timeout': 1200})
except ex.AerospikeError as e:
    print("Error: {} [{}].format(e.msg, e.code)")
    sys.exit(1)
finally:
    client.close()

```

1.2.2.4 Numeric Operations

```
class aerospike.Client
```

Note: Please see `aerospike_helpers.operations.operations` for the new way to use numeric operations using the operate command.

increment (*key, bin, offset[, meta[, policy]]*)

Increment the integer value in *bin* by the integer *val*.

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **offset** (*int* or *float*) – the value by which to increment the value in *bin*.
- **meta** (*dict*) – optional record metadata to be set, with field 'ttl' set to *int* number of seconds or one of the *TTL Constants*, and 'gen' set to *int* generation number to compare.
- **policy** (*dict*) – optional *Operate Policies*. Note: the exists policy option may not be: `aerospike.POLICY_EXISTS_CREATE_OR_REPLACE` nor `aerospike.POLICY_EXISTS_REPLACE`

Raises a subclass of `AerospikeError`.

```

from __future__ import print_function
import aerospike
from aerospike import exception as ex
import sys

config = { 'hosts': [('127.0.0.1', 3000)] }
client = aerospike.client(config).connect()

try:
    client.put(('test', 'cats', 'mr. peppy'), {'breed':'persian'}, policy={
        'exists': aerospike.POLICY_EXISTS_CREATE_OR_REPLACE})
    (key, meta, bins) = client.get(('test', 'cats', 'mr. peppy'))

```

(continues on next page)

(continued from previous page)

```

print("Before:", bins, "\n")
client.increment(key, 'lives', -1)
(key, meta, bins) = client.get(key)
print("After:", bins, "\n")
client.increment(key, 'lives', -1)
(key, meta, bins) = client.get(key)
print("Poor Kitty:", bins, "\n")
print(bins)
except ex.AerospikeError as e:
    print("Error: {} [{}].format(e.msg, e.code))")
    sys.exit(1)
finally:
    client.close()

```

1.2.2.5 List Operations

`class aerospike.Client`

Note: Please see `aerospike_helpers.operations.list_operations` for the new way to use list operations.

Note: List operations require server version >= 3.7.0

List operations support negative indexing. If the index is negative, the resolved index starts backwards from end of list.

Index examples:

- 0: first element in the list
- 4: fifth element in the list
- -1: last element in the list

Index range examples:

- 1, count 2: second and third elements in the list
- -3, count 3: last three elements in the list

If an index is out of bounds, a parameter error will be returned. If a range is partially out of bounds, the valid part of the range will be returned.

Comparisons:

- A wildcard function is available `aerospike.CDTWildcard()`.
- An infinite function is available `aerospike.CDTInfinite()`.

Those values are for comparison only and will not be saved in the database.

See also:

[Lists \(Data Types\)](#).

list_append(*key*, *bin*, *val*[, *meta*[, *policy*]])
Append a single element to a list value in *bin*.

Parameters

- **key** (`tuple`) – a *Key Tuple* tuple associated with the record.
- **bin** (`str`) – the name of the bin.
- **val** – `int`, `str`, `float`, `bytearray`, `list`, `dict`. An unsupported type will be serialized.
- **meta** (`dict`) – optional record metadata to be set, with field 'ttl' set to `int` number of seconds or one of the *TTL Constants*, and 'gen' set to `int` generation number to compare.
- **policy** (`dict`) – optional *Operate Policies*.

Raises a subclass of `AerospikeError`.

list_extend (`key, bin, items[, meta[, policy]]`)

Extend the list value in *bin* with the given *items*.

Parameters

- **key** (`tuple`) – a *Key Tuple* tuple associated with the record.
- **bin** (`str`) – the name of the bin.
- **items** (`list`) – the items to append the list in *bin*.
- **meta** (`dict`) – optional record metadata to be set, with field 'ttl' set to `int` number of seconds or one of the *TTL Constants*, and 'gen' set to `int` generation number to compare.
- **policy** (`dict`) – optional *Operate Policies*.

Raises a subclass of `AerospikeError`.

list_insert (`key, bin, index, val[, meta[, policy]]`)

Insert an element at the specified *index* of a list value in *bin*.

Parameters

- **key** (`tuple`) – a *Key Tuple* tuple associated with the record.
- **bin** (`str`) – the name of the bin.
- **index** (`int`) – the position in the index where the value should be inserted.
- **val** – `int`, `str`, `float`, `bytearray`, `list`, `dict`. An unsupported type will be serialized.
- **meta** (`dict`) – optional record metadata to be set, with field 'ttl' set to `int` number of seconds or one of the *TTL Constants*, and 'gen' set to `int` generation number to compare.
- **policy** (`dict`) – optional *Operate Policies*.

Raises a subclass of `AerospikeError`.

list_insert_items (`key, bin, index, items[, meta[, policy]]`)

Insert the *items* at the specified *index* of a list value in *bin*.

Parameters

- **key** (`tuple`) – a *Key Tuple* tuple associated with the record.
- **bin** (`str`) – the name of the bin.
- **index** (`int`) – the position in the index where the items should be inserted.

- **items** (*list*) – the items to insert into the list in *bin*.
- **meta** (*dict*) – optional record metadata to be set, with field 'ttl' set to *int* number of seconds or one of the *TTL Constants*, and 'gen' set to *int* generation number to compare.
- **policy** (*dict*) – optional *Operate Policies*.

Raises a subclass of *AerospikeError*.

list_pop (*key, bin, index[, meta[, policy]]*) → val

Remove and get back a list element at a given *index* of a list value in *bin*.

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **index** (*int*) – the index position in the list element which should be removed and returned.
- **meta** (*dict*) – optional record metadata to be set, with field 'ttl' set to *int* number of seconds or one of the *TTL Constants*, and 'gen' set to *int* generation number to compare.
- **policy** (*dict*) – optional *Operate Policies*.

Returns a single list element.

Raises a subclass of *AerospikeError*.

list_pop_range (*key, bin, index, count[, meta[, policy]]*) → val

Remove and get back list elements at a given *index* of a list value in *bin*.

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **index** (*int*) – the index of first element in a range which should be removed and returned.
- **count** (*int*) – the number of elements in the range.
- **meta** (*dict*) – optional record metadata to be set, with field 'ttl' set to *int* number of seconds or one of the *TTL Constants*, and 'gen' set to *int* generation number to compare.
- **policy** (*dict*) – optional *Operate Policies*.

Returns a list of elements.

Raises a subclass of *AerospikeError*.

list_remove (*key, bin, index[, meta[, policy]]*)

Remove a list element at a given *index* of a list value in *bin*.

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **index** (*int*) – the index position in the list element which should be removed.

- **meta** (`dict`) – optional record metadata to be set, with field 'ttl' set to `int` number of seconds or one of the *TTL Constants*, and 'gen' set to `int` generation number to compare.
- **policy** (`dict`) – optional *Operate Policies*.

Raises a subclass of `AerospikeError`.

list_remove_range (`key, bin, index, count[, meta[, policy]]`)

Remove list elements at a given `index` of a list value in `bin`.

Parameters

- **key** (`tuple`) – a *Key Tuple* tuple associated with the record.
- **bin** (`str`) – the name of the bin.
- **index** (`int`) – the index of first element in a range which should be removed.
- **count** (`int`) – the number of elements in the range.
- **meta** (`dict`) – optional record metadata to be set, with field 'ttl' set to `int` number of seconds or one of the *TTL Constants*, and 'gen' set to `int` generation number to compare.
- **policy** (`dict`) – optional *Operate Policies*.

Raises a subclass of `AerospikeError`.

list_clear (`key, bin[, meta[, policy]]`)

Remove all the elements from a list value in `bin`.

Parameters

- **key** (`tuple`) – a *Key Tuple* tuple associated with the record.
- **bin** (`str`) – the name of the bin.
- **meta** (`dict`) – optional record metadata to be set, with field 'ttl' set to `int` number of seconds or one of the *TTL Constants*, and 'gen' set to `int` generation number to compare.
- **policy** (`dict`) – optional *Operate Policies*.

Raises a subclass of `AerospikeError`.

list_set (`key, bin, index, val[, meta[, policy]]`)

Set list element `val` at the specified `index` of a list value in `bin`.

Parameters

- **key** (`tuple`) – a *Key Tuple* tuple associated with the record.
- **bin** (`str`) – the name of the bin.
- **index** (`int`) – the position in the index where the value should be set.
- **val** – `int, str, float, bytearray, list, dict`. An unsupported type will be serialized.
- **meta** (`dict`) – optional record metadata to be set, with field 'ttl' set to `int` number of seconds or one of the *TTL Constants*, and 'gen' set to `int` generation number to compare.
- **policy** (`dict`) – optional *Operate Policies*.

Raises a subclass of `AerospikeError`.

list_get (*key, bin, index*[, *meta*[, *policy*]]) → val
Get the list element at the specified *index* of a list value in *bin*.

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **index** (*int*) – the position in the index where the value should be set.
- **meta** (*dict*) – unused for this operation
- **policy** (*dict*) – optional *Operate Policies*.

Raises a subclass of *AerospikeError*.

Returns the list elements at the given index.

list_get_range (*key, bin, index, count*[, *meta*[, *policy*]]) → val
Get the list of *count* elements starting at a specified *index* of a list value in *bin*.

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **index** (*int*) – the position in the index where the value should be set.
- **meta** (*dict*) – unused for this operation
- **policy** (*dict*) – optional *Operate Policies*.

Raises a subclass of *AerospikeError*.

Returns a list of elements.

list_trim (*key, bin, index, count*[, *meta*[, *policy*]]) → val
Remove elements from the list which are not within the range starting at the given *index* plus *count*.

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **index** (*int*) – the position in the index marking the start of the range.
- **index** – the index position of the first element in a range which should not be removed.
- **count** (*int*) – the number of elements in the range.
- **meta** (*dict*) – optional record metadata to be set, with field 'ttl' set to *int* number of seconds or one of the *TTL Constants*, and 'gen' set to *int* generation number to compare.
- **policy** (*dict*) – optional *Operate Policies*.

Raises a subclass of *AerospikeError*.

Returns a list of elements.

list_size (*key, bin*[, *meta*[, *policy*]]) → count
Count the number of elements in the list value in *bin*.

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **meta** (*dict*) – unused for this operation
- **policy** (*dict*) – optional *Operate Policies*.

Raises a subclass of *AerospikeError*.

Returns a *int*.

1.2.2.6 Map Operations

```
class aerospike.Client
```

Note: Please see *aerospike_helpers.operations.map_operations* for the new way to use map operations.

Note: Map operations require server version >= 3.8.4

All maps maintain an index and a rank. Map supports negative indexing for index and rank.

An index in the context of the map API is the order of a particular key in a map. The key with the lowest key value has index 0.

A rank is the order of a particular value in a map. If multiple copies of a value exist, the ranks of those copies are based on their key ordering.

Index examples:

- 0: lowest key in the map
- 4: fifth key in the map
- -1: highest key in the map

Index range examples:

- 1, count 2: second and third keys in the map
- -3, count 3: highest three keys in the map

Rank examples:

- 0: element with the lowest value rank in the map
- -1: element with the highest ranked value in the map

Rank range examples:

- 1, count 2: second and third lowest ranked elements in the map
- -3, count 3: top three ranked elements in the map.

The default map order is *aerospike.MAP_UNORDERED*.

Comparisons:

- A wildcard function is available *aerospike.CDTWildcard()*.
- An infinite function is available *aerospike.CDTInfinite()*.

Those values are for comparison only and will not be saved in the database.

```
from __future__ import print_function
import aerospike
from aerospike import exception as e

config = {'hosts': [('127.0.0.1', 3000)]}
try:
    client = aerospike.client(config).connect()
except e.ClientError as e:
    print("Error: {} [{}]".format(e.msg, e.code))
    sys.exit(2)

key = ('test', 'demo', 'map-example')
abc = {}
for i in xrange(1, 10, 1):
    abc[chr(64 + i)] = i
for i in xrange(11, 26, 1):
    abc[chr(64 + i)] = i

try:
    if client.exists(key):
        client.remove(key)
    map_policy = {
        'map_write_mode': aerospike.MAP_UPDATE,
        'map_order': aerospike.MAP_KEY_VALUE_ORDERED
    }
    client.map_put_items(key, 'abc', abc, map_policy)
    client.map_put(key, 'abc', 'J', 10, map_policy)
    print(client.map_get_by_key_range(key, 'abc', 'A', 'D', aerospike.MAP_RETURN_
KEY_VALUE))
    client.map_put(key, 'abc', 'Z', 26, map_policy)
    print(client.map_get_by_index_range(key, 'abc', -3, 3, aerospike.MAP_RETURN_
VALUE))
    print(client.map_get_by_rank_range(key, 'abc', 0, 10, aerospike.MAP_RETURN_
KEY))
    print("\nRound 2")
    more = {'AA': 100, 'BB': 200, 'ZZ': 2600}
    client.map_put_items(key, 'abc', more, map_policy)
    print(client.map_get_by_key_range(key, 'abc', 'A', 'D', aerospike.MAP_RETURN_
KEY_VALUE))
    print(client.map_get_by_index_range(key, 'abc', -3, 3, aerospike.MAP_RETURN_
VALUE))
    print(client.map_get_by_rank_range(key, 'abc', 0, 10, aerospike.MAP_RETURN_
KEY))
except e.AerospikeError as e:
    print("Error: {} [{}]".format(e.msg, e.code))

client.close()
```

Note: We expect to see

```
[('A', 1), ('B', 2), ('C', 3)]
[24, 25, 26]
['A', 'B', 'C', 'D', 'E', 'F', 'G', 'H', 'I', 'J']
```

(continues on next page)

(continued from previous page)

```
Round 2
[('A', 1), ('AA', 100), ('B', 2), ('BB', 200), ('C', 3)]
[25, 26, 2600]
['A', 'B', 'C', 'D', 'E', 'F', 'G', 'H', 'I', 'J']
```

See also:[Maps \(Data Types\).](#)**map_set_policy**(*key, bin, map_policy*)Set the map policy for the given *bin*.**Parameters**

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **map_policy** (*dict*) – *Map Policies*.

Raises a subclass of [AerospikeError](#).**map_put**(*key, bin, map_key, val[, map_policy[, meta[, policy]]]*)Add the given *map_key*/*val* pair to the map at *key* and *bin*.**Parameters**

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **map_key** – *int, str, float, bytearray*. An unsupported type will be serialized.
- **val** – *int, str, float, bytearray, list, dict*. An unsupported type will be serialized.
- **map_policy** (*dict*) – optional *Map Policies*.
- **meta** (*dict*) – optional record metadata to be set, with field 'ttl' set to *int* number of seconds or one of the *TTL Constants*, and 'gen' set to *int* generation number to compare.
- **policy** (*dict*) – optional *Operate Policies*.

Raises a subclass of [AerospikeError](#).**map_put_items**(*key, bin, items[, map_policy[, meta[, policy]]]*)Add the given *items* dict of key/value pairs to the map at *key* and *bin*.**Parameters**

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **items** (*dict*) – key/value pairs.
- **map_policy** (*dict*) – optional *Map Policies*.
- **meta** (*dict*) – optional record metadata to be set, with field 'ttl' set to *int* number of seconds or one of the *TTL Constants*, and 'gen' set to *int* generation number to compare.

- **policy** (`dict`) – optional *Operate Policies*.

Raises a subclass of `AerospikeError`.

map_increment (`key, bin, map_key, incr[, map_policy[, meta[, policy]]]`)

Increment the value of a numeric map element by `incr`. Element is specified by `key`, `bin` and `map_key`.

Parameters

- **key** (`tuple`) – a *Key Tuple* tuple associated with the record.
- **bin** (`str`) – the name of the bin.
- **map_key** – `int`, `str`, `float`, `bytearray`. An unsupported type will be serialized.
- **incr** – `int` or `float`
- **map_policy** (`dict`) – optional *Map Policies*.
- **meta** (`dict`) – optional record metadata to be set, with field 'ttl' set to `int` number of seconds or one of the *TTL Constants*, and 'gen' set to `int` generation number to compare.
- **policy** (`dict`) – optional *Operate Policies*.

Raises a subclass of `AerospikeError`.

map_decrement (`key, bin, map_key, decr[, map_policy[, meta[, policy]]]`)

Decrement the value of a numeric map element by `decr`. Element is specified by `key`, `bin` and `map_key`.

Parameters

- **key** (`tuple`) – a *Key Tuple* tuple associated with the record.
- **bin** (`str`) – the name of the bin.
- **map_key** – `int`, `str`, `float`, `bytearray`. An unsupported type will be serialized.
- **decr** – `int` or `float`
- **map_policy** (`dict`) – optional *Map Policies*.
- **meta** (`dict`) – optional record metadata to be set, with field 'ttl' set to `int` number of seconds or one of the *TTL Constants*, and 'gen' set to `int` generation number to compare.
- **policy** (`dict`) – optional *Operate Policies*.

Raises a subclass of `AerospikeError`.

map_size (`key, bin[, meta[, policy]]`) → count

Return the size of the map at `key` and `bin`.

Parameters

- **key** (`tuple`) – a *Key Tuple* tuple associated with the record.
- **bin** (`str`) – the name of the bin.
- **meta** (`dict`) – unused for this operation
- **policy** (`dict`) – optional *Operate Policies*.

Raises a subclass of `AerospikeError`.

Returns a `int`.

map_clear(*key, bin[, meta[, policy]]*)
Remove all elements from the map at *key* and *bin*.

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **meta** (*dict*) – optional record metadata to be set, with field 'ttl' set to *int* number of seconds or one of the *TTL Constants*, and 'gen' set to *int* generation number to compare.
- **policy** (*dict*) – optional *Operate Policies*.

Raises a subclass of *AerospikeError*.

map_remove_by_key(*key, bin, map_key, return_type[, meta[, policy]]*)
Remove and return a map element specified by *key*, *bin* and *map_key*.

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **map_key** – *int, str, float, bytearray*. An unsupported type will be serialized.
- **return_type** – *int Map Return Types*
- **meta** (*dict*) – optional record metadata to be set, with field 'ttl' set to *int* number of seconds or one of the *TTL Constants*, and 'gen' set to *int* generation number to compare.
- **policy** (*dict*) – optional *Operate Policies*.

Raises a subclass of *AerospikeError*.**Returns** depends on *return_type* parameter

map_remove_by_key_list(*key, bin, list, return_type[, meta[, policy]][], meta[, policy][][]*)
Remove and return map elements specified by *key*, *bin* and *list* of keys.

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **list** – list the list of keys to match
- **return_type** – *int Map Return Types*
- **meta** (*dict*) – optional record metadata to be set, with field 'ttl' set to *int* number of seconds or one of the *TTL Constants*, and 'gen' set to *int* generation number to compare.
- **policy** (*dict*) – optional *Operate Policies*.

Raises a subclass of *AerospikeError*.**Returns** depends on *return_type* parameter

map_remove_by_key_range(*key, bin, map_key, range, return_type[, meta[, policy]]*)
Remove and return map elements specified by *key*, *bin* and identified by a key range [*map_key* inclusive, *range* exclusive).

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **map_key** – *int, str, float, bytearray*. An unsupported type will be serialized.
- **range** – *int, str, float, bytearray*. An unsupported type will be serialized.
- **return_type** – *int Map Return Types*
- **meta** (*dict*) – optional record metadata to be set, with field 'ttl' set to *int* number of seconds or one of the *TTL Constants*, and 'gen' set to *int* generation number to compare.
- **policy** (*dict*) – optional *Operate Policies*.

Raises a subclass of *AerospikeError*.

Returns depends on return_type parameter

map_remove_by_value (*key, bin, val, return_type[, meta[, policy]]*)

Remove and return map elements specified by *key, bin* and *val*.

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **val** – *int, str, float, bytearray*. An unsupported type will be serialized.
- **return_type** – *int Map Return Types*
- **meta** (*dict*) – optional record metadata to be set, with field 'ttl' set to *int* number of seconds or one of the *TTL Constants*, and 'gen' set to *int* generation number to compare.
- **policy** (*dict*) – optional *Operate Policies*.

Raises a subclass of *AerospikeError*.

Returns depends on return_type parameter

map_remove_by_value_list (*key, bin, list, return_type[, meta[, policy]]*)

Remove and return map elements specified by *key, bin* and *list* of values.

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **list** – list the list of values to match
- **return_type** – *int Map Return Types*
- **meta** (*dict*) – optional record metadata to be set, with field 'ttl' set to *int* number of seconds or one of the *TTL Constants*, and 'gen' set to *int* generation number to compare.
- **policy** (*dict*) – optional *Operate Policies*.

Raises a subclass of *AerospikeError*.

Returns depends on return_type parameter

`map_remove_by_value_range`(*key, bin, val, range, return_type*[, *meta*[, *policy*]])

Remove and return map elements specified by *key*, *bin* and value range [*val* inclusive, *range* exclusive).

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **val** – *int, str, float, bytearray*. An unsupported type will be serialized.
- **range** – *int, str, float, bytearray*. An unsupported type will be serialized.
- **return_type** – *int Map Return Types*
- **meta** (*dict*) – optional record metadata to be set, with field 'ttl' set to *int* number of seconds or one of the *TTL Constants*, and 'gen' set to *int* generation number to compare.
- **policy** (*dict*) – optional *Operate Policies*.

Raises a subclass of *AerospikeError*.

Returns depends on return_type parameter

`map_remove_by_index`(*key, bin, index, return_type*[, *meta*[, *policy*]])

Remove and return map elements specified by *key*, *bin* and *index*.

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **index** – *int* the index position of the map element
- **return_type** – *int Map Return Types*
- **meta** (*dict*) – optional record metadata to be set, with field 'ttl' set to *int* number of seconds or one of the *TTL Constants*, and 'gen' set to *int* generation number to compare.
- **policy** (*dict*) – optional *Operate Policies*.

Raises a subclass of *AerospikeError*.

Returns depends on return_type parameter

`map_remove_by_index_range`(*key, bin, index, range, return_type*[, *meta*[, *policy*]])

Remove and return map elements specified by *key*, *bin* starting at *index* position and removing *range* number of elements.

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **index** – *int* the index position of the first map element to remove
- **range** – *int* the number of items to remove from the map
- **return_type** – *int Map Return Types*
- **meta** (*dict*) – optional record metadata to be set, with field 'ttl' set to *int* number of seconds or one of the *TTL Constants*, and 'gen' set to *int* generation number to compare.

- **policy** (`dict`) – optional *Operate Policies*.

Raises a subclass of `AerospikeError`.

Returns depends on return_type parameter

`map_remove_by_rank` (`key, bin, rank, return_type[, meta[, policy]]`)

Remove and return map elements specified by `key`, `bin` and `rank`.

Parameters

- **key** (`tuple`) – a *Key Tuple* tuple associated with the record.
- **bin** (`str`) – the name of the bin.
- **rank** – `int` the rank of the value of the element in the map
- **return_type** – `int` *Map Return Types*
- **meta** (`dict`) – optional record metadata to be set, with field 'ttl' set to `int` number of seconds or one of the *TTL Constants*, and 'gen' set to `int` generation number to compare.
- **policy** (`dict`) – optional *Operate Policies*.

Raises a subclass of `AerospikeError`.

Returns depends on return_type parameter

`map_remove_by_rank_range` (`key, bin, rank, range, return_type[, meta[, policy]]`)

Remove and return map elements specified by `key`, `bin` with starting `rank` and removing `range` number of elements.

Parameters

- **key** (`tuple`) – a *Key Tuple* tuple associated with the record.
- **bin** (`str`) – the name of the bin.
- **rank** – `int` the rank of the value of the first map element to remove
- **range** – `int` the number of items to remove from the map
- **return_type** – `int` *Map Return Types*
- **meta** (`dict`) – optional record metadata to be set, with field 'ttl' set to `int` number of seconds or one of the *TTL Constants*, and 'gen' set to `int` generation number to compare.
- **policy** (`dict`) – optional *Operate Policies*.

Raises a subclass of `AerospikeError`.

Returns depends on return_type parameter

`map_get_by_key` (`key, bin, map_key, return_type[, meta[, policy]]`)

Return map element specified by `key`, `bin` and `map_key`.

Parameters

- **key** (`tuple`) – a *Key Tuple* tuple associated with the record.
- **bin** (`str`) – the name of the bin.
- **map_key** – `int`, `str`, `float`, `bytearray`. An unsupported type will be serialized.
- **return_type** – `int` *Map Return Types*

- **meta** (*dict*) – unused for this operation
- **policy** (*dict*) – optional *Operate Policies*.

Raises a subclass of *AerospikeError*.

Returns depends on return_type parameter

map_get_by_key_range (*key, bin, map_key, range, return_type*[, *meta*[, *policy*]])

Return map elements specified by *key, bin* and key range [*map_key* inclusive, *range* exclusive).

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **map_key** – *int, str, float, bytearray*. An unsupported type will be serialized.
- **range** – *int, str, float, bytearray*. An unsupported type will be serialized.
- **return_type** – *int Map Return Types*
- **meta** (*dict*) – unused for this operation
- **policy** (*dict*) – optional *Operate Policies*.

Raises a subclass of *AerospikeError*.

Returns depends on return_type parameter

map_get_by_key_list (*key, bin, key_list, return_type*[, *meta*[, *policy*]])

Return map elements specified by *key, bin* and *key_list*.

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **key_list** – list A list of map keys to fetch entries for
- **return_type** – *int Map Return Types*
- **meta** (*dict*) – unused for this operation
- **policy** (*dict*) – optional *Operate Policies*.

Raises a subclass of *AerospikeError*.

Returns depends on return_type parameter

Note: Requires server version >= 3.16.0.1

New in version 3.2.0.

map_get_by_value (*key, bin, val, return_type*[, *meta*[, *policy*]])

Return map elements specified by *key, bin* and *val*.

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **val** – *int, str, float, bytearray*. An unsupported type will be serialized.

- **return_type** – int *Map Return Types*
- **meta** (*dict*) – unused for this operation
- **policy** (*dict*) – optional *Operate Policies*.

Raises a subclass of *AerospikeError*.

Returns depends on return_type parameter

map_get_by_value_range (*key, bin, val, range, return_type[, meta[, policy]]*)

Return map elements specified by *key, bin* and value range [*val* inclusive, *range* exclusive).

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **val** – *int, str, float, bytearray*. An unsupported type will be serialized.
- **range** – *int, str, float, bytearray*. An unsupported type will be serialized.
- **return_type** – int *Map Return Types*
- **meta** (*dict*) – unused for this operation
- **policy** (*dict*) – optional *Operate Policies*.

Raises a subclass of *AerospikeError*.

Returns depends on return_type parameter

map_get_by_value_list (*key, bin, value_list, return_type[, meta[, policy]]*)

Return map elements specified by *key, bin* and *value_list*.

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **value_list** – list A list of map values specifying the entries to be retrieved.
- **return_type** – int *Map Return Types*
- **meta** (*dict*) – unused for this operation
- **policy** (*dict*) – optional *Operate Policies*.

Raises a subclass of *AerospikeError*.

Returns depends on return_type parameter

Note: Requires server version >= 3.16.0.1

New in version 3.2.0.

map_get_by_index (*key, bin, index, return_type[, meta[, policy]]*)

Return the map element specified by *key, bin* and *index* position.

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **index** – *int* the index position of the map element

- **return_type** – int *Map Return Types*
- **meta** (*dict*) – unused for this operation
- **policy** (*dict*) – optional *Operate Policies*.

Raises a subclass of *AerospikeError*.

Returns depends on return_type parameter

map_get_by_index_range (*key, bin, index, range, return_type[, meta[, policy]]*)

Return a *range* number of elements from the map at *key* and *bin*, starting at the given *index*.

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **index** – *int* the starting index for the range
- **range** – *int* number of elements in the range
- **return_type** – int *Map Return Types*
- **meta** (*dict*) – unused for this operation
- **policy** (*dict*) – optional *Operate Policies*.

Raises a subclass of *AerospikeError*.

Returns depends on return_type parameter

map_get_by_rank (*key, bin, rank, return_type[, meta[, policy]]*)

Return the map element specified by *key, bin* and *rank*.

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **rank** – *int* the rank of the value of the element in the map
- **return_type** – int *Map Return Types*
- **meta** (*dict*) – unused for this operation
- **policy** (*dict*) – optional *Operate Policies*.

Raises a subclass of *AerospikeError*.

Returns depends on return_type parameter

map_get_by_rank_range (*key, bin, rank, range, return_type[, meta[, policy]]*)

Return map elements specified by *key, bin* with starting *rank* and *range* number of elements.

Parameters

- **key** (*tuple*) – a *Key Tuple* tuple associated with the record.
- **bin** (*str*) – the name of the bin.
- **rank** – *int* the rank of the value of the first map element to remove
- **range** – *int* the number of items to remove from the map
- **return_type** – int *Map Return Types*
- **meta** (*dict*) – unused for this operation

- **policy** (*dict*) – optional *Operate Policies*.

Raises a subclass of *AerospikeError*.

Returns depends on return_type parameter

1.2.2.7 Multi-Ops (Operate)

class aerospike.Client

operate (*key*, *list*[, *meta*[, *policy*]]) -> (*key*, *meta*, *bins*)

Perform multiple bin operations on a record with a given *key*. In Aerospike server versions prior to 3.6.0, non-existent bins being read will have a *None* value. Starting with 3.6.0 non-existent bins will not be present in the returned *Record Tuple*. The returned record tuple will only contain one element per bin, even if multiple operations were performed on the bin.

Parameters

- **key** (*tuple*) – a *Key Tuple* associated with the record.
- **list** (*list*) – a list of one or more bin operations, each structured as the *dict* {‘bin’: bin name, ‘op’: aerospike.OPERATOR_* [, ‘val’: value]}. See *aerospike_helpers.operations package*.
- **meta** (*dict*) – optional record metadata to be set, with field ‘ttl’ set to *int* number of seconds or one of the *TTL Constants*, and ‘gen’ set to *int* generation number to compare.
- **policy** (*dict*) – optional *Operate Policies*.

Returns a *Record Tuple*. See *Unicode Handling*.

Raises a subclass of *AerospikeError*.

Note: Version >= 3.10.0 Supports predicate expressions for Multi-Ops see *predexp*. Requires server version >= 4.7.0.

```
from __future__ import print_function
import aerospike
from aerospike import predexp
from aerospike_helpers.operations import list_operations, operations
from aerospike import exception as ex
import sys

config = {"hosts": [("127.0.0.1", 3000)]}
client = aerospike.client(config).connect()

try:
    unique_id = 1
    key = ("test", "demo", unique_id)
    client.put(key, {"name": "John", "charges": [10, 20, 14]})

    ops = [list_operations.list_append("charges", 25)]

    preds = [ # check that the record has value 'Kim' in bin 'name'
        predexp.string_bin("name"),
        predexp.string_value("Kim"),
        predexp.string_equal(),
```

(continues on next page)

(continued from previous page)

```

]

# Because the record's name bin is 'John' and not 'Kim',
# client.operate() will fail with AEROSPIKE_FILTERED_OUT and the
# operations will not be applied.
try:
    client.operate(key, ops, policy={"predexp": preds})
except ex.FilteredOut as e:
    print("Error: {} [{}].format(e.msg, e.code)")

record = client.get(key)
print(record)

# This client.operate() will succeed because the name bin is 'John'.
preds = [ # check that the record has value 'John' in bin 'name'
    predexp.string_bin("name"),
    predexp.string_value("John"),
    predexp.string_equal(),
]
client.operate(key, ops, policy={"predexp": preds})

record = client.get(key)
print(record)

except ex.AerospikeError as e:
    print("Error: {} [{}].format(e.msg, e.code)")
    sys.exit(1)
finally:
    client.close()
# Error: 127.0.0.1:3000 AEROSPIKE_FILTERED_OUT [27]
# (('test', 'demo', None, bytarray(b'\xb7\xf4\xb8\x89\xe2\xdag\xdeh>
# \xd\xf6\x91\x9a\x1e\xac\xc4F\xc8')), {'ttl': 2592000, 'gen': 23}, {'number
# ': 1, 'name': 'John', 'charges': [10, 20, 14]})
# (('test', 'demo', None, bytarray(b'\xb7\xf4\xb8\x89\xe2\xdag\xdeh>
# \xd\xf6\x91\x9a\x1e\xac\xc4F\xc8')), {'ttl': 2592000, 'gen': 24}, {'number
# ': 1, 'name': 'John', 'charges': [10, 20, 14, 25]})
```

Note: In version 2.1.3 the return format of certain bin entries for this method, **only in cases when a map operation specifying a ‘return_type’ is used**, has changed. Bin entries for map operations using “return_type” of aerospike.MAP_RETURN_KEY_VALUE will now return a bin value of a list of keys and corresponding values, rather than a list of key/value tuples. See the following code block for details.

```
# pre 2.1.3 formatting of key/value bin value
[('key1', 'val1'), ('key2', 'val2'), ('key3', 'val3')]

# >= 2.1.3 formatting
['key1', 'val1', 'key2', 'val2', 'key3', 'val3']
```

Note: `operate()` can now have multiple write operations on a single bin.

```

from __future__ import print_function
import aerospike
from aerospike_helpers.operations import operations as op_helpers
from aerospike import exception as ex
import sys

config = { 'hosts': [ ('127.0.0.1', 3000)] }
client = aerospike.client(config).connect()

try:
    key = ('test', 'demo', 1)
    client.put(key, {'age': 25, 'career': 'delivery boy'})
    ops = [
        op_helpers.increment("age", 1000),
        op_helpers.write("name", "J."),
        op_helpers.prepend("name", "Phillip "),
        op_helpers.append("name", " Fry"),
        op_helpers.read("name"),
        op_helpers.read("career"),
        op_helpers.read("age")
    ]
    (key, meta, bins) = client.operate(key, ops, {'ttl':360}, {'total_timeout':500})

    print(key)
    print('-----')
    print(meta)
    print('-----')
    print(bins) # will display all bins selected by OPERATOR_READ operations
except ex.AerospikeError as e:
    print("Error: {} [{}].format(e.msg, e.code))")
    sys.exit(1)
finally:
    client.close()

```

Note: `OPERATOR_TOUCH` should only ever combine with `OPERATOR_READ`, for example to implement LRU expiry on the records of a set.

Warning: Having `val` associated with `OPERATOR_TOUCH` is deprecated. Use the meta `ttl` field instead.

```

from __future__ import print_function
import aerospike
from aerospike import exception as ex
import sys

config = { 'hosts': [ ('127.0.0.1', 3000)] }
client = aerospike.client(config).connect()

try:
    key = ('test', 'demo', 1)
    ops = [
        {

```

(continues on next page)

(continued from previous page)

```

        "op" : aerospike.OPERATOR_TOUCH,
    },
{
    "op" : aerospike.OPERATOR_READ,
    "bin": "name"
}
]
(key, meta, bins) = client.operate(key, ops, {'ttl':1800})
print("Touched the record for {0}, extending its ttl by 30m".
→format(bins))
except ex.AerospikeError as e:
    print("Error: {0} [{1}]".format(e.msg, e.code))
    sys.exit(1)
finally:
    client.close()

```

Changed in version 2.1.3.

operate_ordered(*key*, *list*[, *meta*[, *policy*]]) -> (*key*, *meta*, *bins*)

Perform multiple bin operations on a record with the results being returned as a list of (bin-name, result) tuples. The order of the elements in the list will correspond to the order of the operations from the input parameters.

Parameters

- **key** (*tuple*) – a *Key Tuple* associated with the record.
- **list** (*list*) – a list of one or more bin operations, each structured as the *dict* {‘bin’: bin name, ‘op’: aerospike.OPERATOR_* [, ‘val’: value]}. See [aerospike_helpers.operations package](#).
- **meta** (*dict*) – optional record metadata to be set, with field ‘ttl’ set to *int* number of seconds or one of the *TTL Constants*, and ‘gen’ set to *int* generation number to compare.
- **policy** (*dict*) – optional *Operate Policies*.

Returns a *Record Tuple*. See [Unicode Handling](#).

Raises a subclass of [AerospikeError](#).

Note: In version 2.1.3 the return format of bin entries for this method, **only in cases when a map operation specifying a ‘return_type’ is used**, has changed. Map operations using “return_type” of aerospike.MAP_RETURN_KEY_VALUE will now return a bin value of a list of keys and corresponding values, rather than a list of key/value tuples. See the following code block for details. In addition, some operations which did not return a value in versions <= 2.1.2 will now return a response.

```

# pre 2.1.3 formatting of key/value bin value
[('key1', 'val1'), ('key2', 'val2'), ('key3', 'val3')]

# >= 2.1.3 formatting
['key1', 'val1', 'key2', 'val2', 'key3', 'val3']

```

```

from __future__ import print_function
import aerospike
from aerospike import exception as ex

```

(continues on next page)

(continued from previous page)

```

from aerospike_helpers.operations import operations as op_helpers
import sys

config = { 'hosts': [('127.0.0.1', 3000)] }
client = aerospike.client(config).connect()

try:
    key = ('test', 'demo', 1)
    policy = {
        'total_timeout': 1000,
        'key': aerospike.POLICY_KEY_SEND,
        'commit_level': aerospike.POLICY_COMMIT_LEVEL_MASTER
    }

    llist = [
        op_helpers.append("name", "aa"),
        op_helpers.read("name"),
        op_helpers.increment("age", 3),
        op_helpers.read("age")
    ]

    client.operate_ordered(key, llist, {}, policy)
except ex.AerospikeError as e:
    print("Error: {} [{}].format(e.msg, e.code))")
    sys.exit(1)
finally:
    client.close()

```

Changed in version 2.1.3.

1.2.2.8 Scan and Query

`class aerospike.Client`

`scan(namespace[, set]) → Scan`

Return a `aerospike.Scan` object to be used for executing scans over a specified `set` (which can be omitted or `None`) in a `namespace`. A scan with a `None` set returns all the records in the namespace.

Parameters

- `namespace (str)` – the namespace in the aerospike cluster.
- `set (str)` – optional specified set name, otherwise the entire `namespace` will be scanned.

`Returns` an `aerospike.Scan` class.

`query(namespace[, set]) → Query`

Return a `aerospike.Query` object to be used for executing queries over a specified `set` (which can be omitted or `None`) in a `namespace`. A query with a `None` set returns records which are **not in any named set**. This is different than the meaning of a `None` set in a scan.

Parameters

- `namespace (str)` – the namespace in the aerospike cluster.
- `set (str)` – optional specified set name, otherwise the records which are not part of any `set` will be queried (**Note:** this is different from not providing the `set` in `scan()`).

Returns an `aerospike.Query` class.

1.2.2.9 User Defined Functions

`class aerospike.Client`

`udf_put(filename[, udf_type=aerospike.UDF_TYPE_LUA[, policy]])`

Register a UDF module with the cluster.

Parameters

- `filename (str)` – the path to the UDF module to be registered with the cluster.
- `udf_type (int)` – `aerospike.UDF_TYPE_LUA`.
- `policy (dict)` – currently `timeout` in milliseconds is the available policy.

Raises a subclass of `AerospikeError`.

Note: Register the UDF module and copy it to the Lua ‘user_path’, a directory that should contain a copy of the modules registered with the cluster.

```
config = {
    'hosts': [ ('127.0.0.1', 3000)],
    'lua': { 'user_path': '/path/to/lua/user_path' }}
client = aerospike.client(config).connect()
client.udf_put('/path/to/my_module.lua')
client.close()
```

`udf_remove(module[, policy])`

Remove a previously registered UDF module from the cluster.

Parameters

- `module (str)` – the UDF module to be deregistered from the cluster.
- `policy (dict)` – currently `timeout` in milliseconds is the available policy.

Raises a subclass of `AerospikeError`.

```
client.udf_remove('my_module.lua')
```

`udf_list([policy]) → []`

Return the list of UDF modules registered with the cluster.

Parameters `policy (dict)` – currently `timeout` in milliseconds is the available policy.

Return type list

Raises a subclass of `AerospikeError`.

```
from __future__ import print_function
import aerospike

config = {'hosts': [('127.0.0.1', 3000)] }
client = aerospike.client(config).connect()
print(client.udf_list())
client.close()
```

Note: We expect to see something like:

```
[{'content': bytearray(b''),
 'hash': bytearray(b'195e39ceb51c110950bd'),
 'name': 'my_udf1.lua',
 'type': 0},
 {'content': bytearray(b''),
 'hash': bytearray(b'8a2528e8475271877b3b'),
 'name': 'stream_udf.lua',
 'type': 0},
 {'content': bytearray(b''),
 'hash': bytearray(b'362ea79c8b64857701c2'),
 'name': 'aggregate_udf.lua',
 'type': 0},
 {'content': bytearray(b''),
 'hash': bytearray(b'635f47081431379baa4b'),
 'name': 'module.lua',
 'type': 0}]
```

udf_get (*module*[, *language=aerospike.UDF_TYPE_LUA*[, *policy*]]) → str
Return the content of a UDF module which is registered with the cluster.

Parameters

- **module** (*str*) – the UDF module to read from the cluster.
- **udf_type** (*int*) – *aerospike.UDF_TYPE_LUA*
- **policy** (*dict*) – currently **timeout** in milliseconds is the available policy.

Return type *str*

Raises a subclass of *AerospikeError*.

apply (*key*, *module*, *function*, *args*[, *policy*])
Apply a registered (see *udf_put ()*) record UDF to a particular record.

Parameters

- **key** (*tuple*) – a *Key Tuple* associated with the record.
- **module** (*str*) – the name of the UDF module.
- **function** (*str*) – the name of the UDF to apply to the record identified by *key*.
- **args** (*list*) – the arguments to the UDF.
- **policy** (*dict*) – optional *Apply Policies*.

Returns the value optionally returned by the UDF, one of *str*, *int*, *float*, *bytearray*, *list*, *dict*.

Raises a subclass of *AerospikeError*.

See also:

Record UDF and Developing Record UDFs.

Note: Version >= 3.10.0 Supports predicate expressions for apply, scan_apply, and query_apply see *predexp*. Requires server version 4.7.0.

```

from __future__ import print_function
import aerospike
from aerospike import predexp
from aerospike import exception as ex
import sys

config = {"hosts": [("127.0.0.1", 3000)]}
client = aerospike.client(config).connect()

# register udf
try:
    client.udf_put("/path/to/my_udf.lua")
except ex.FilteredOut as e:
    print("Error: {} [{1}].format(e.msg, e.code))")
    client.close()
    sys.exit(1)

# put records and apply udf
try:
    keys = [("test", "demo", 1), ("test", "demo", 2), ("test", "demo", 3)]
    records = [{"number": 1}, {"number": 2}, {"number": 3}]
    for i in range(3):
        client.put(keys[i], records[i])

    preds = [ # check that the record has value < 2 or == 3 in bin 'name'
        predexp.integer_bin("number"),
        predexp.integer_value(2),
        predexp.integer_less(),
        predexp.integer_bin("number"),
        predexp.integer_value(3),
        predexp.integer_equal(),
        predexp.predexp_or(2),
    ]

```

policy = {"predexp": preds}

```

    client.scan_apply("test", None, "my_udf", "my_udf", ["number", 10], policy)
    records = client.get_many(keys)

    print(records)
except ex.AerospikeError as e:
    print("Error: {} [{1}].format(e.msg, e.code))")
    sys.exit(1)
finally:
    client.close()
# the udf has only modified the records that matched the preds
# EXPECTED OUTPUT:
# [
#     (('test', 'demo', 1, bytearray(b'\xb7\xf4\xb8\x89\xe2\xdag\xdeh>
# \xd1\xf6\x91\x9a\x1e\xac\xc4F\xc8')), {'gen': 2, 'ttl': 2591999, 'number': 11}),
#     (('test', 'demo', 2, bytearray(b'\xaejQ_
# \xdeJ\xda\xccD\x96\xe2\xda\x1f\xea\x84\x8c:\x92p')), {'gen': 12, 'ttl': 2591999, 'number': 2}),
#     (('test', 'demo', 3, bytearray(b'\xb1\x95`g\xf6\xd4\x9a\x4D9\xd3\xaf\xbf\xf8ha\x01\x94\xcd')), {'gen': 13, 'ttl': 2591999, 'number': 13})
]

```

(continues on next page)

(continued from previous page)

]

```
# contents of my_udf.lua
function my_udf(rec, bin, offset)
    info("my transform: %s", tostring(record.digest(rec)))
    rec[bin] = rec[bin] + offset
    aerospike:update(rec)
end
```

scan_apply(*ns*, *set*, *module*, *function*[, *args*[, *policy*[, *options*]]]) → int

Initiate a scan and apply a record UDF to each record matched by the scan. This method blocks until the scan is complete.

Parameters

- **ns** (*str*) – the namespace in the aerospike cluster.
- **set** (*str*) – the set name. Should be `None` if the entire namespace is to be scanned.
- **module** (*str*) – the name of the UDF module.
- **function** (*str*) – the name of the UDF to apply to the records matched by the scan.
- **args** (*list*) – the arguments to the UDF.
- **policy** (*dict*) – optional *Scan Policies*.
- **options** (*dict*) – the *Scan Options* that will apply to the scan.

Return type `int`

Returns a job ID that can be used with `job_info()` to check the status of the `aerospike.JOB_SCAN`.

Raises a subclass of `AerospikeError`.

See also:

[Record UDF and Developing Record UDFs](#).

query_apply(*ns*, *set*, *predicate*, *module*, *function*[, *args*[, *policy*]]) → int

Initiate a query and apply a record UDF to each record matched by the query. This method blocks until the query is completed.

Parameters

- **ns** (*str*) – the namespace in the aerospike cluster.
- **set** (*str*) – the set name. Should be `None` if you want to query records in the *ns* which are in no set.
- **predicate** (*tuple*) – the `tuple()` produced by one of the `aerospike.predicates` methods.
- **module** (*str*) – the name of the UDF module.
- **function** (*str*) – the name of the UDF to apply to the records matched by the query.
- **args** (*list*) – the arguments to the UDF.
- **policy** (*dict*) – optional *Write Policies*.

Return type `int`

Returns a job ID that can be used with `job_info()` to check the status of the `aerospike.JOB_QUERY`.

Raises a subclass of `AerospikeError`.

See also:

Record UDF and Developing Record UDFs.

`job_info(job_id, module[, policy]) → dict`

Return the status of a job running in the background.

Parameters

- `job_id(int)` – the job ID returned by `scan_apply()` and `query_apply()`.
- `module` – one of *Job Constants*.

Returns a `dict` with keys `status`, `records_read`, and `progress_pct`. The value of `status` is one of *Job Statuses*.

Raises a subclass of `AerospikeError`.

```
from __future__ import print_function
import aerospike
from aerospike import exception as ex
import time

config = {'hosts': [ ('127.0.0.1', 3000)]}
client = aerospike.client(config).connect()

try:
    # run the UDF 'add_val' in Lua module 'simple' on the records of test.
    ↪demo
    job_id = client.scan_apply('test', 'demo', 'simple', 'add_val', ['age', ↪
    ↪1])
    while True:
        time.sleep(0.25)
        response = client.job_info(job_id, aerospike.JOB_SCAN)
        if response['status'] == aerospike.JOB_STATUS_COMPLETED:
            break
        print("Job ", str(job_id), " completed")
        print("Progress percentage : ", response['progress_pct'])
        print("Number of scanned records : ", response['records_read'])
except ex.AerospikeError as e:
    print("Error: {} [{}].format(e.msg, e.code)")
client.close()
```

`scan_info(scan_id) → dict`

Return the status of a scan running in the background.

Parameters `scan_id(int)` – the scan ID returned by `scan_apply()`.

Returns a `dict` with keys `status`, `records_scanned`, and `progress_pct`. The value of `status` is one of *Job Statuses*.

Raises a subclass of `AerospikeError`.

Deprecated since version 1.0.50: Use `job_info()` instead.

```

from __future__ import print_function
import aerospike
from aerospike import exception as ex

config = {'hosts': [ ('127.0.0.1', 3000)]}
client = aerospike.client(config).connect()
try:
    scan_id = client.scan_apply('test', 'demo', 'simple', 'add_val', ['age', ↴
→1])
    while True:
        response = client.scan_info(scan_id)
        if response['status'] == aerospike.SCAN_STATUS_COMPLETED or \
           response['status'] == aerospike.SCAN_STATUS_ABORTED:
            break
        if response['status'] == aerospike.SCAN_STATUS_COMPLETED:
            print("Background scan successful")
            print("Progress percentage : ", response['progress_pct'])
            print("Number of scanned records : ", response['records_scanned'])
            print("Background scan status : ", "SCAN_STATUS_COMPLETED")
        else:
            print("Scan_apply failed")
except ex.AerospikeError as e:
    print("Error: {0} [{1}]".format(e.msg, e.code))
client.close()

```

1.2.2.10 Info Operations

class aerospike.Client

get_nodes() → []
 Return the list of hosts present in a connected cluster.

Returns a list of node address tuples.

Raises a subclass of *AerospikeError*.

```

import aerospike

config = {'hosts': [('127.0.0.1', 3000)] }
client = aerospike.client(config).connect()

nodes = client.get_nodes()
print(nodes)
client.close()

```

Note: We expect to see something like:

```
[('127.0.0.1', 3000), ('127.0.0.1', 3010)]
```

Changed in version 3.0.0.

Warning: In versions < 3.0.0 get_nodes will not work when using TLS

info (*command*[, *hosts*[, *policy*]]) → {}

Deprecated since version 3.0.0: Use [info_node\(\)](#) to send a request to a single node, or [info_all\(\)](#) to send a request to the entire cluster. Sending requests to specific nodes can be better handled with a simple Python function such as:

```
def info_to_host_list(client, request, hosts, policy=None):
    output = {}
    for host in hosts:
        try:
            response = client.info_node(request, host, policy)
            output[host] = response
        except Exception as e:
            # Handle the error gracefully here
            output[host] = e
    return output
```

Send an info *command* to all nodes in the cluster and filter responses to only include nodes specified in a *hosts* list.

Parameters

- **command** (*str*) – the info command.
- **hosts** (*list*) – a list containing an *address, port* tuple(). Example: [('127.0.0.1', 3000)]
- **policy** (*dict*) – optional [Info Policies](#).

Return type *dict*

Raises a subclass of [AerospikeError](#).

See also:

[Info Command Reference](#).

```
import aerospike

config = {'hosts': [('127.0.0.1', 3000)] }
client = aerospike.client(config).connect()

response = client.info(command)
client.close()
```

Note: We expect to see something like:

```
{'BB9581F41290C00': (None, '127.0.0.1:3000\n'), 'BC3581F41290C00': (None,
→'127.0.0.1:3010\n')}
```

Changed in version 3.0.0.

info_all (*command*[, *policy*]) → {}

Send an info *command* to all nodes in the cluster to which the client is connected. If any of the individual requests fail, this will raise an exception.

Parameters

- **command** (*str*) – the info command.
- **policy** (*dict*) – optional [Info Policies](#).

Return type `dict`

Raises a subclass of `AerospikeError`.

See also:

Info Command Reference.

```
import aerospike

config = {'hosts': [('127.0.0.1', 3000)] }
client = aerospike.client(config).connect()

response = client.info_all(command)
client.close()
```

Note: We expect to see something like:

```
{'BB9581F41290C00': (None, '127.0.0.1:3000\n'), 'BC3581F41290C00': (None,
˓→'127.0.0.1:3010\n')}
```

New in version 3.0.0.

info_node (*command*, *host*[, *policy*]) → str

Send an info *command* to a single node specified by *host*.

Parameters

- **command** (`str`) – the info command.
- **host** (`tuple`) – a `tuple()` containing an *address*, *port* , optional *tls-name* . Example: ('127.0.0.1', 3000) or when using TLS ('127.0.0.1', 4333, 'server-tls-name'). In order to send an info request when TLS is enabled, the *tls-name* must be present.
- **policy** (`dict`) – optional *Info Policies*.

Return type `str`

Raises a subclass of `AerospikeError`.

See also:

Info Command Reference.

Changed in version 3.0.0.

```
Warning: for client versions < 3.0.0 info_node will not work when using TLS
```

set_xdr_filter (*data_center*, *namespace*, *expression_filter*[, *policy*]) → str

Set the cluster's xdr filter using an Aerospike expression. The cluster's current filter can be removed by setting *expression_filter* to None.

Parameters

- **data_center** (`str`) – The data center to apply the filter to.
- **namespace** (`str`) – The namespace to apply the filter to.

- **expression_filter** (*expression*) – The filter to set. See expressions at [aerospike_helpers](#).
- **policy** (*dict*) – optional *Info Policies*.

Raises a subclass of [AerospikeError](#).

See also:

[xdr-set-filter Info Command Reference](#).

Changed in version 5.0.0.

Warning: for client versions < 3.0.0 `set_xdr_filter` will not work when using TLS.

shm_key() → int

Expose the value of the `shm_key` for this client if shared-memory cluster tending is enabled,

Return type int or None

truncate (*namespace, set, nanos[, policy]*)

Remove records in specified namespace/set efficiently. This method is many orders of magnitude faster than deleting records one at a time. See [Truncate command reference](#).

Note: Requires Aerospike Server versions >= 3.12

This asynchronous server call may return before the truncation is complete. The user can still write new records after the server returns because new records will have last update times greater than the truncate cutoff (set at the time of truncate call)

Parameters

- **namespace** (*str*) – The namespace on which the truncation operation should be performed.
- **set** (*str*) – The set to truncate. Pass in `None` to indicate that all records in the namespace should be truncated.
- **nanos** (*long*) – A cutoff threshold indicating that records last updated before the threshold will be removed. Units are in nanoseconds since unix epoch (1970-01-01). A value of 0 indicates that all records in the set should be truncated regardless of update time. The value must not be in the future.

- **policy** (*dict*) – Optional *Info Policies*

Return type Status indicating the success of the operation.

Raises a subclass of [AerospikeError](#).

```
import aerospike
import time

client = aerospike.client({'hosts': [('localhost', 3000)]}).connect()

# Store 10 items in the database
for i in range(10):
    key = ('test', 'truncate', i)
    record = {'item': i}
    client.put(key, record)
```

(continues on next page)

(continued from previous page)

```

time.sleep(2)
current_time = time.time()
# Convert the current time to nanoseconds since epoch
threshold_ns = int(current_time * 10 ** 9)

time.sleep(2) # Make sure some time passes before next round of additions

# Store another 10 items into the database
for i in range(10, 20):
    key = ('test', 'truncate', i)
    record = {'item': i}
    client.put(key, record)

# Store a record in the 'test' namespace without a set
key = ('test', None, 'no set')
record = ({'item': 'no set'})
client.put(key, record)

# Remove all items created before the threshold time
# The first 10 records we added will be removed by this call.
# The second 10 will remain.
client.truncate('test', 'truncate', threshold_ns)

# Remove all records from test/truncate.
# After this the record with key ('test', None, 'no set') still exists
client.truncate('test', 'truncate', 0)

# Remove all records from the test namespace
client.truncate('test', None, 0)

client.close()

```

1.2.2.11 Index Operations

class aerospike.Client

index_string_create(ns, set, bin, index_name[, policy])

Create a string index with *index_name* on the *bin* in the specified *ns, set*.

Parameters

- **ns** (*str*) – the namespace in the aerospike cluster.
- **set** (*str*) – the set name.
- **bin** (*str*) – the name of bin the secondary index is built on.
- **index_name** (*str*) – the name of the index.
- **policy** (*dict*) – optional *Info Policies*.

Raises a subclass of *AerospikeError*.

index_integer_create(ns, set, bin, index_name[, policy])

Create an integer index with *index_name* on the *bin* in the specified *ns, set*.

Parameters

- **ns** (*str*) – the namespace in the aerospike cluster.
- **set** (*str*) – the set name.
- **bin** (*str*) – the name of bin the secondary index is built on.
- **index_name** (*str*) – the name of the index.
- **policy** (*dict*) – optional *Info Policies*.

Raises a subclass of *AerospikeError*.

index_list_create (*ns, set, bin, index_datatype, index_name[, policy]*)

Create an index named *index_name* for numeric, string or GeoJSON values (as defined by *index_datatype*) on records of the specified *ns, set* whose *bin* is a list.

Parameters

- **ns** (*str*) – the namespace in the aerospike cluster.
- **set** (*str*) – the set name.
- **bin** (*str*) – the name of bin the secondary index is built on.
- **index_datatype** – Possible values are `aerospike.INDEX_STRING`, `aerospike.INDEX_NUMERIC` and `aerospike.INDEX_GEO2DSPHERE`.
- **index_name** (*str*) – the name of the index.
- **policy** (*dict*) – optional *Info Policies*.

Raises a subclass of *AerospikeError*.

Note: Requires server version >= 3.8.0

index_map_keys_create (*ns, set, bin, index_datatype, index_name[, policy]*)

Create an index named *index_name* for numeric, string or GeoJSON values (as defined by *index_datatype*) on records of the specified *ns, set* whose *bin* is a map. The index will include the keys of the map.

Parameters

- **ns** (*str*) – the namespace in the aerospike cluster.
- **set** (*str*) – the set name.
- **bin** (*str*) – the name of bin the secondary index is built on.
- **index_datatype** – Possible values are `aerospike.INDEX_STRING`, `aerospike.INDEX_NUMERIC` and `aerospike.INDEX_GEO2DSPHERE`.
- **index_name** (*str*) – the name of the index.
- **policy** (*dict*) – optional *Info Policies*.

Raises a subclass of *AerospikeError*.

Note: Requires server version >= 3.8.0

index_map_values_create (*ns, set, bin, index_datatype, index_name[, policy]*)

Create an index named *index_name* for numeric, string or GeoJSON values (as defined by *index_datatype*) on records of the specified *ns, set* whose *bin* is a map. The index will include the values of the map.

Parameters

- **ns** (*str*) – the namespace in the aerospike cluster.
- **set** (*str*) – the set name.
- **bin** (*str*) – the name of bin the secondary index is built on.
- **index_datatype** – Possible values are aerospike.INDEX_STRING, aerospike.INDEX_NUMERIC and aerospike.INDEX_GEO2DSPHERE.
- **index_name** (*str*) – the name of the index.
- **policy** (*dict*) – optional *Info Policies*.

Raises a subclass of *AerospikeError*.

Note: Requires server version >= 3.8.0

```
import aerospike

client = aerospike.client({ 'hosts': [ ('127.0.0.1', 3000)] }).connect()

# assume the bin fav_movies in the set test.demo bin should contain
# a dict { (str) _title_ : (int) _times_viewed_ }
# create a secondary index for string values of test.demo records whose 'fav_
# →movies' bin is a map
client.index_map_keys_create('test', 'demo', 'fav_movies', aerospike.INDEX_
# →STRING, 'demo_fav_movies_titles_idx')
# create a secondary index for integer values of test.demo records whose
# →'fav_movies' bin is a map
client.index_map_values_create('test', 'demo', 'fav_movies', aerospike.INDEX_
# →NUMERIC, 'demo_fav_movies_views_idx')
client.close()
```

index_geo2dsphere_create (*ns, set, bin, index_name[, policy]*)

Create a geospatial 2D spherical index with *index_name* on the *bin* in the specified *ns, set*.

Parameters

- **ns** (*str*) – the namespace in the aerospike cluster.
- **set** (*str*) – the set name.
- **bin** (*str*) – the name of bin the secondary index is built on.
- **index_name** (*str*) – the name of the index.
- **policy** (*dict*) – optional *Info Policies*.

Raises a subclass of *AerospikeError*.

See also:

aerospike.GeoJSON, aerospike.predicates

Note: Requires server version >= 3.7.0

```
import aerospike

client = aerospike.client({ 'hosts': [ ('127.0.0.1', 3000)] }).connect()
client.index_geo2dsphere_create('test', 'pads', 'loc', 'pads_loc_geo')
client.close()
```

index_remove(ns, index_name[, policy])

Remove the index with *index_name* from the namespace.

Parameters

- **ns** (*str*) – the namespace in the aerospike cluster.
- **index_name** (*str*) – the name of the index.
- **policy** (*dict*) – optional *Info Policies*.

Raises a subclass of *AerospikeError*.

1.2.2.12 Admin Operations**class aerospike.Client**

Note: The admin methods implement the security features of the Enterprise Edition of Aerospike. These methods will raise a *SecurityNotSupported* when the client is connected to a Community Edition cluster (see *aerospike.exception*).

A user is validated by the client against the server whenever a connection is established through the use of a username and password (passwords hashed using bcrypt). When security is enabled, each operation is validated against the user's roles. Users are assigned roles, which are collections of *Privilege Objects*.

```
import aerospike
from aerospike import exception as ex
import time

config = {'hosts': [('127.0.0.1', 3000)] }
client = aerospike.client(config).connect('ipji', 'life is good')

try:
    dev_privileges = [{ 'code': aerospike.PRIV_READ}, { 'code': aerospike.PRIV_READ_WRITE}]
    client.admin_create_role('dev_role', dev_privileges)
    client.admin_grant_privileges('dev_role', [{ 'code': aerospike.PRIV_READ_WRITE_UDF}])
    client.admin_create_user('dev', 'you young whatchacallit... idiot', ['dev_role'])
    time.sleep(1)
    print(client.admin_query_user('dev'))
    print(admin_query_users())
except ex.AdminError as e:
    print("Error [{0}]: {1}".format(e.code, e.msg))
client.close()
```

See also:

[Security features article](#).

admin_create_role(*role*, *privileges*[, *policy*])
Create a custom, named *role* containing a *list* of *privileges*.

Parameters

- **role** (*str*) – the name of the role.
- **privileges** (*list*) – a list of *Privilege Objects*.
- **policy** (*dict*) – optional *Admin Policies*.

Raises one of the *AdminError* subclasses.

admin_drop_role(*role*[, *policy*])
Drop a custom *role*.

Parameters

- **role** (*str*) – the name of the role.
- **policy** (*dict*) – optional *Admin Policies*.

Raises one of the *AdminError* subclasses.

admin_grant_privileges(*role*, *privileges*[, *policy*])
Add *privileges* to a *role*.

Parameters

- **role** (*str*) – the name of the role.
- **privileges** (*list*) – a list of *Privilege Objects*.
- **policy** (*dict*) – optional *Admin Policies*.

Raises one of the *AdminError* subclasses.

admin_revoke_privileges(*role*, *privileges*[, *policy*])
Remove *privileges* from a *role*.

Parameters

- **role** (*str*) – the name of the role.
- **privileges** (*list*) – a list of *Privilege Objects*.
- **policy** (*dict*) – optional *Admin Policies*.

Raises one of the *AdminError* subclasses.

admin_query_role(*role*[, *policy*]) → []
Get the list of privileges associated with a *role*.

Parameters

- **role** (*str*) – the name of the role.
- **policy** (*dict*) – optional *Admin Policies*.

Returns a list of *Privilege Objects*.

Raises one of the *AdminError* subclasses.

admin_query_roles([*policy*]) → {}
Get all named roles and their privileges.

Parameters *policy* (*dict*) – optional *Admin Policies*.

Returns a *dict* of *Privilege Objects* keyed by role name.

Raises one of the `AdminError` subclasses.

admin_create_user (`username`, `password`, `roles`[, `policy`])
Create a user with a specified `username` and grant it `roles`.

Parameters

- **username** (`str`) – the username to be added to the aerospike cluster.
- **password** (`str`) – the password associated with the given username.
- **roles** (`list`) – the list of role names assigned to the user.
- **policy** (`dict`) – optional `Admin Policies`.

Raises one of the `AdminError` subclasses.

admin_drop_user (`username`[, `policy`])
Drop the user with a specified `username` from the cluster.

Parameters

- **username** (`str`) – the username to be dropped from the aerospike cluster.
- **policy** (`dict`) – optional `Admin Policies`.

Raises one of the `AdminError` subclasses.

admin_change_password (`username`, `password`[, `policy`])
Change the `password` of the user `username`. This operation can only be performed by that same user.

Parameters

- **username** (`str`) – the username.
- **password** (`str`) – the password associated with the given username.
- **policy** (`dict`) – optional `Admin Policies`.

Raises one of the `AdminError` subclasses.

admin_set_password (`username`, `password`[, `policy`])
Set the `password` of the user `username` by a user administrator.

Parameters

- **username** (`str`) – the username to be added to the aerospike cluster.
- **password** (`str`) – the password associated with the given username.
- **policy** (`dict`) – optional `Admin Policies`.

Raises one of the `AdminError` subclasses.

admin_grant_roles (`username`, `roles`[, `policy`])
Add `roles` to the user `username`.

Parameters

- **username** (`str`) – the username to be granted the roles.
- **roles** (`list`) – a list of role names.
- **policy** (`dict`) – optional `Admin Policies`.

Raises one of the `AdminError` subclasses.

admin_revoke_roles (`username`, `roles`[, `policy`])
Remove `roles` from the user `username`.

Parameters

- **username** (*str*) – the username to have the roles revoked.
- **roles** (*list*) – a list of role names.
- **policy** (*dict*) – optional *Admin Policies*.

Raises one of the *AdminError* subclasses.

admin_query_user (*username*[, *policy*]) → []

Return the list of roles granted to the specified user *username*.

Parameters

- **username** (*str*) – the username to query for.
- **policy** (*dict*) – optional *Admin Policies*.

Returns a list of role names.

Raises one of the *AdminError* subclasses.

admin_query_users ([*policy*]) → {}

Return the *dict* of users, with their roles keyed by username.

Parameters *policy* (*dict*) – optional *Admin Policies*.

Returns a *dict* of roles keyed by username.

Raises one of the *AdminError* subclasses.

1.2.3 Policies

1.2.3.1 Write Policies

policy

A *dict* of optional write policies, which are applicable to *put()*, *query_apply()*, *remove_bin()*.

- **max_retries** (*int*)

Maximum number of retries before aborting the current transaction. The initial attempt is not counted as a retry.

If *max_retries* is exceeded, the transaction will return error AEROSPIKE_ERR_TIMEOUT.

Default: 0

Warning: Database writes that are not idempotent (such as “add”) should not be retried because the write operation may be performed multiple times if the client timed out previous transaction attempts. It’s important to use a distinct write policy for non-idempotent writes, which sets *max_retries* = 0;

- **sleep_between_retries** (*int*)

Milliseconds to sleep between retries. Enter 0 to skip sleep.

Default: 0

- **socket_timeout** (*int*)

Socket idle timeout in milliseconds when processing a database command.

If socket_timeout is not 0 and the socket has been idle for at least socket_timeout, both max_retries and total_timeout are checked. If max_retries and total_timeout are not exceeded, the transaction is retried.

If both socket_timeout and total_timeout are non-zero and socket_timeout > total_timeout, then socket_timeout will be set to total_timeout. If socket_timeout is 0, there will be no socket idle limit.

Default: 0

- **total_timeout** ([int](#))

Total transaction timeout in milliseconds.

The total_timeout is tracked on the client and sent to the server along with the transaction in the wire protocol. The client will most likely timeout first, but the server also has the capability to timeout the transaction.

If total_timeout is not 0 and total_timeout is reached before the transaction completes, the transaction will return error `AEROSPIKE_ERR_TIMEOUT`. If total_timeout is 0, there will be no total time limit.

Default: 1000

- **compress** ([bool](#))

Compress client requests and server responses.

Use zlib compression on write or batch read commands when the command buffer size is greater than 128 bytes. In addition, tell the server to compress its response on read commands. The server response compression threshold is also 128 bytes.

This option will increase cpu and memory usage (for extra compressed buffers), but decrease the size of data sent over the network.

Default: False

- **key**

One of the *Key Policy Options* values such as `aerospike.POLICY_KEY_DIGEST`

Default: `aerospike.POLICY_KEY_DIGEST`

- **exists**

One of the *Existence Policy Options* values such as `aerospike.POLICY_EXISTS_CREATE`

Default: `aerospike.POLICY_EXISTS_IGNORE`

- **gen**

One of the *Generation Policy Options* values such as `aerospike.POLICY_GEN_IGNORE`

Default: `aerospike.POLICY_GEN_IGNORE`

- **commit_level**

One of the *Commit Level Policy Options* values such as
`aerospike.POLICY_COMMIT_LEVEL_ALL`

Default: `aerospike.POLICY_COMMIT_LEVEL_ALL`

- **durable_delete** ([bool](#))

Perform durable delete

Default: False

Note: Requires Enterprise server version >= 5.0

- **expressions list**

Compiled aerospike expressions `aerospike_helpers` used for filtering records within a transaction.

Default: None

1.2.3.2 Read Policies

`policy`

A `dict` of optional read policies, which are applicable to `get()`, `exists()`, `select()`.

- **max_retries (int)**

Maximum number of retries before aborting the current transaction. The initial attempt is not counted as a retry.

If max_retries is exceeded, the transaction will return error AEROSPIKE_ERR_TIMEOUT.

Default: 2

- **sleep_between_retries (int)**

Milliseconds to sleep between retries. Enter 0 to skip sleep.

Default: 0

- **socket_timeout (int)**

Socket idle timeout in milliseconds when processing a database command.

If socket_timeout is not 0 and the socket has been idle for at least socket_timeout, both max_retries and total_timeout are checked. If max_retries and total_timeout are not exceeded, the transaction is retried.

If both socket_timeout and total_timeout are non-zero and `socket_timeout > total_timeout`, then socket_timeout will be set to total_timeout. If socket_timeout is 0, there will be no socket idle limit.

Default: 0

- **total_timeout (int)**

Total transaction timeout in milliseconds.

The total_timeout is tracked on the client and sent to the server along with the transaction in the wire protocol. The client will most likely timeout first, but the server also has the capability to timeout the transaction.

If total_timeout is not 0 and total_timeout is reached before the transaction completes, the transaction will return error AEROSPIKE_ERR_TIMEOUT. If total_timeout is 0, there will be no total time limit.

Default: 1000

- **compress (bool)**
Compress client requests and server responses.

Use zlib compression on write or batch read commands when the command buffer size is greater than 128 bytes. In addition, tell the server to compress its response on read commands. The server response compression threshold is also 128 bytes.

This option will increase cpu and memory usage (for extra compressed buffers), but decrease the size of data sent over the network.

Default: False

- **deserialize (bool)**
Should raw bytes representing a list or map be deserialized to a list or dictionary.
Set to *False* for backup programs that just need access to raw bytes.

Default: True

- **key**
One of the *Key Policy Options* values such as `aerospike.POLICY_KEY_DIGEST`

Default: `aerospike.POLICY_KEY_DIGEST`

- **read_mode_ap**
One of the *AP Read Mode Policy Options* values such as
`aerospike.AS_POLICY_READ_MODE_AP_ONE`

Default: `aerospike.AS_POLICY_READ_MODE_AP_ONE`

New in version 3.7.0.

- **read_mode_sc**
One of the *SC Read Mode Policy Options* values such as
`aerospike.POLICY_READ_MODE_SC_SESSION`

Default: `aerospike.POLICY_READ_MODE_SC_SESSION`

New in version 3.7.0.

- **replica**
One of the *Replica Options* values such as `aerospike.POLICY_REPLICA_MASTER`

Default: `aerospike.POLICY_REPLICA_SEQUENCE`

Note: Requires Enterprise server version >= 5.0

- **expressions list**
Compiled aerospike expressions `aerospike_helpers` used for filtering records within a transaction.

Default: None

1.2.3.3 Operate Policies

policy

A `dict` of optional operate policies, which are applicable to `append()`, `prepend()`, `increment()`, `operate()`, and atomic list and map operations.

- **max_retries (int)**

Maximum number of retries before aborting the current transaction. The initial attempt is not counted as a retry.

If max_retries is exceeded, the transaction will return error AEROSPIKE_ERR_TIMEOUT.

Default: 0

Warning: Database writes that are not idempotent (such as “add”) should not be retried because the write operation may be performed multiple times if the client timed out previous transaction attempts. It’s important to use a distinct write policy for non-idempotent writes, which sets max_retries = 0;

- **sleep_between_retries (int)**

Milliseconds to sleep between retries. Enter 0 to skip sleep.

Default: 0

- **socket_timeout (int)**

Socket idle timeout in milliseconds when processing a database command.

If socket_timeout is not 0 and the socket has been idle for at least socket_timeout, both max_retries and total_timeout are checked. If max_retries and total_timeout are not exceeded, the transaction is retried.

If both socket_timeout and total_timeout are non-zero and socket_timeout > total_timeout, then socket_timeout will be set to total_timeout. If socket_timeout is 0, there will be no socket idle limit.

Default: 0

- **total_timeout (int)**

Total transaction timeout in milliseconds.

The total_timeout is tracked on the client and sent to the server along with the transaction in the wire protocol. The client will most likely timeout first, but the server also has the capability to timeout the transaction.

If total_timeout is not 0 and total_timeout is reached before the transaction completes, the transaction will return error AEROSPIKE_ERR_TIMEOUT. If total_timeout is 0, there will be no total time limit.

Default: 1000

- **compress (bool)**

Compress client requests and server responses.

Use zlib compression on write or batch read commands when the command buffer size is greater than 128 bytes. In addition, tell the server to compress its response on read commands. The server response compression threshold is also 128 bytes.

This option will increase cpu and memory usage (for extra compressed buffers), but decrease the size of data sent over the network.

- Default: False
 - **key**
One of the *Key Policy Options* values such as `aerospike.POLICY_KEY_DIGEST`
 - Default: `aerospike.POLICY_KEY_DIGEST`
 - **gen**
One of the *Generation Policy Options* values such as `aerospike.POLICY_GEN_IGNORE`
 - Default: `aerospike.POLICY_GEN_IGNORE`
 - **replica**
One of the *Replica Options* values such as `aerospike.POLICY_REPLICA_MASTER`
 - Default: `aerospike.POLICY_REPLICA_SEQUENCE`
 - **commit_level**
One of the *Commit Level Policy Options* values such as
`aerospike.POLICY_COMMIT_LEVEL_ALL`
 - Default: `aerospike.POLICY_COMMIT_LEVEL_ALL`
 - **read_mode_ap**
One of the *AP Read Mode Policy Options* values such as
`aerospike.AS_POLICY_READ_MODE_AP_ONE`
 - Default: `aerospike.AS_POLICY_READ_MODE_AP_ONE`
New in version 3.7.0.
 - **read_mode_sc**
One of the *SC Read Mode Policy Options* values such as
`aerospike.POLICY_READ_MODE_SC_SESSION`
 - Default: `aerospike.POLICY_READ_MODE_SC_SESSION`
New in version 3.7.0.
 - **exists**
One of the *Existence Policy Options* values such as `aerospike.POLICY_EXISTS_CREATE`
 - Default: `aerospike.POLICY_EXISTS_IGNORE`
 - **durable_delete (bool)**
Perform durable delete
 - Default: False
-
- Note:** Requires Enterprise server version >= 5.0
-
- **expressions list**
Compiled aerospike expressions `aerospike_helpers` used for filtering records within a transaction.
- Default: None

1.2.3.4 Apply Policies

policy

A `dict` of optional apply policies, which are applicable to `apply()`.

- **max_retries (int)**

Maximum number of retries before aborting the current transaction. The initial attempt is not counted as a retry.

If `max_retries` is exceeded, the transaction will return error `AEROSPIKE_ERR_TIMEOUT`.

Default: 0

Warning: Database writes that are not idempotent (such as “add”) should not be retried because the write operation may be performed multiple times if the client timed out previous transaction attempts. It’s important to use a distinct write policy for non-idempotent writes, which sets `max_retries = 0`;

- **sleep_between_retries (int)**

Milliseconds to sleep between retries. Enter 0 to skip sleep.

Default: 0

- **socket_timeout (int)**

Socket idle timeout in milliseconds when processing a database command.

If `socket_timeout` is not 0 and the socket has been idle for at least `socket_timeout`, both `max_retries` and `total_timeout` are checked. If `max_retries` and `total_timeout` are not exceeded, the transaction is retried.

If both `socket_timeout` and `total_timeout` are non-zero and `socket_timeout > total_timeout`, then `socket_timeout` will be set to `total_timeout`. If `socket_timeout` is 0, there will be no socket idle limit.

Default: 0

- **total_timeout (int)**

Total transaction timeout in milliseconds.

The `total_timeout` is tracked on the client and sent to the server along with the transaction in the wire protocol. The client will most likely timeout first, but the server also has the capability to timeout the transaction.

If `total_timeout` is not 0 and `total_timeout` is reached before the transaction completes, the transaction will return error `AEROSPIKE_ERR_TIMEOUT`. If `total_timeout` is 0, there will be no total time limit.

Default: 1000

- **compress (bool)**

Compress client requests and server responses.

Use zlib compression on write or batch read commands when the command buffer size is greater than 128 bytes. In addition, tell the server to compress its response on read commands. The server

response compression threshold is also 128 bytes.

This option will increase cpu and memory usage (for extra compressed buffers), but decrease the size of data sent over the network.

Default: False

- **key**

One of the *Key Policy Options* values such as `aerospike.POLICY_KEY_DIGEST`

Default: `aerospike.POLICY_KEY_DIGEST`

- **replica**

One of the *Replica Options* values such as `aerospike.POLICY_REPLICA_MASTER`

Default: `aerospike.POLICY_REPLICA_SEQUENCE`

- **gen**

One of the *Generation Policy Options* values such as `aerospike.POLICY_GEN_IGNORE`

Default: `aerospike.POLICY_GEN_IGNORE`

- **commit_level**

One of the *Commit Level Policy Options* values such as
`aerospike.POLICY_COMMIT_LEVEL_ALL`

Default: `aerospike.POLICY_COMMIT_LEVEL_ALL`

- **durable_delete (bool)**

Perform durable delete

Default: False

Note: Requires Enterprise server version >= 5.0

- **expressions list**

Compiled aerospike expressions `aerospike_helpers` used for filtering records within a transaction.

Default: None

1.2.3.5 Remove Policies

policy

A `dict` of optional remove policies, which are applicable to `remove()`.

- **max_retries (int)**

Maximum number of retries before aborting the current transaction. The initial attempt is not counted as a retry.

If `max_retries` is exceeded, the transaction will return error `AEROSPIKE_ERR_TIMEOUT`.

Default: 0

Warning: Database writes that are not idempotent (such as “add”) should not be retried because the write operation may be performed multiple times if the client timed out previous transaction attempts. It’s important to use a distinct write policy for non-idempotent writes, which sets `max_retries = 0`;

- **`sleep_between_retries` (`int`)**

Milliseconds to sleep between retries. Enter 0 to skip sleep.

Default: 0

- **`socket_timeout` (`int`)**

Socket idle timeout in milliseconds when processing a database command.

If `socket_timeout` is not 0 and the socket has been idle for at least `socket_timeout`, both `max_retries` and `total_timeout` are checked. If `max_retries` and `total_timeout` are not exceeded, the transaction is retried.

If both `socket_timeout` and `total_timeout` are non-zero and `socket_timeout > total_timeout`, then `socket_timeout` will be set to `total_timeout`. If `socket_timeout` is 0, there will be no socket idle limit.

Default: 0

- **`total_timeout` (`int`)**

Total transaction timeout in milliseconds.

The `total_timeout` is tracked on the client and sent to the server along with the transaction in the wire protocol. The client will most likely timeout first, but the server also has the capability to timeout the transaction.

If `total_timeout` is not 0 and `total_timeout` is reached before the transaction completes, the transaction will return error `AEROSPIKE_ERR_TIMEOUT`. If `total_timeout` is 0, there will be no total time limit.

Default: 1000

- **`compress` (`bool`)**

Compress client requests and server responses.

Use zlib compression on write or batch read commands when the command buffer size is greater than 128 bytes. In addition, tell the server to compress its response on read commands. The server response compression threshold is also 128 bytes.

This option will increase cpu and memory usage (for extra compressed buffers), but decrease the size of data sent over the network.

Default: False

- **`key`**

One of the *Key Policy Options* values such as `aerospike.POLICY_KEY_DIGEST`

Default: `aerospike.POLICY_KEY_DIGEST`

- **`commit_level`**

One of the *Commit Level Policy Options* values such as
`aerospike.POLICY_COMMIT_LEVEL_ALL`

- **gen**
Default: `aerospike.POLICY_COMMIT_LEVEL_ALL`
One of the *Generation Policy Options* values such as `aerospike.POLICY_GEN_IGNORE`

- **durable_delete (bool)**
Default: `aerospike.POLICY_GEN_IGNORE`
Perform durable delete

Default: False

Note: Requires Enterprise server version >= 3.10

- **replica**
One of the *Replica Options* values such as `aerospike.POLICY_REPLICA_MASTER`

Default: `aerospike.POLICY_REPLICA_SEQUENCE`

Note: Requires Enterprise server version >= 5.0

- **expressions list**
Compiled aerospike expressions `aerospike_helpers` used for filtering records within a transaction.

Default: None

1.2.3.6 Batch Policies

policy

A `dict` of optional batch policies, which are applicable to `get_many()`, `exists_many()` and `select_many()`.

- **max_retries (int)**
Maximum number of retries before aborting the current transaction. The initial attempt is not counted as a retry.

If `max_retries` is exceeded, the transaction will return error `AEROSPIKE_ERR_TIMEOUT`.

Default: 2

- **sleep_between_retries (int)**
Milliseconds to sleep between retries. Enter 0 to skip sleep.

Default: 0

- **socket_timeout (int)**
Socket idle timeout in milliseconds when processing a database command.

If `socket_timeout` is not 0 and the socket has been idle for at least `socket_timeout`, both `max_retries` and `total_timeout` are checked. If `max_retries` and `total_timeout` are not exceeded, the transaction is retried.

If both `socket_timeout` and `total_timeout` are non-zero and `socket_timeout >`

`total_timeout`, then `socket_timeout` will be set to `total_timeout`. If `socket_timeout` is 0, there will be no socket idle limit.

Default: 0

- **total_timeout** (`int`)

Total transaction timeout in milliseconds.

The `total_timeout` is tracked on the client and sent to the server along with the transaction in the wire protocol. The client will most likely timeout first, but the server also has the capability to timeout the transaction.

If `total_timeout` is not 0 and `total_timeout` is reached before the transaction completes, the transaction will return error `AEROSPIKE_ERR_TIMEOUT`. If `total_timeout` is 0, there will be no total time limit.

Default: 1000

- **compress** (`bool`)

Compress client requests and server responses.

Use zlib compression on write or batch read commands when the command buffer size is greater than 128 bytes. In addition, tell the server to compress its response on read commands. The server response compression threshold is also 128 bytes.

This option will increase cpu and memory usage (for extra compressed buffers), but decrease the size of data sent over the network.

Default: False

- **read_mode_ap**

One of the *AP Read Mode Policy Options* values such as `aerospike.AS_POLICY_READ_MODE_AP_ONE`

Default: `aerospike.AS_POLICY_READ_MODE_AP_ONE`
New in version 3.7.0.

- **read_mode_sc**

One of the *SC Read Mode Policy Options* values such as `aerospike.POLICY_READ_MODE_SC_SESSION`

Default: `aerospike.POLICY_READ_MODE_SC_SESSION`
New in version 3.7.0.

- **replica**

One of the *Replica Options* values such as `aerospike.POLICY_REPLICA_MASTER`

Default: `aerospike.POLICY_REPLICA_SEQUENCE`

- **concurrent** (`bool`)

Determine if batch commands to each server are run in parallel threads.

Default False

- **allow_inline** (`bool`)

Allow batch to be processed immediately in the server's receiving thread when the server deems it to be appropriate. If *False*, the batch will always be processed in separate transaction threads. This field is only relevant for the new batch index protocol.

- Default True
- **send_set_name (bool)**
Send set name field to server for every key in the batch for batch index protocol. This is only necessary when authentication is enabled and security roles are defined on a per set basis.

- Default: False
- **deserialize (bool)**
Should raw bytes be deserialized to as_list or as_map. Set to *False* for backup programs that just need access to raw bytes.

- Default: True
- **predexp list**
A list of *aerospike.predexp* used as a predicate filter for record, bin, batch, and record UDF operations.

- Default: None

1.2.3.7 Info Policies

policy

A `dict` of optional info policies, which are applicable to `info()`, `info_node()` and index operations.

- **timeout (int)**
Read timeout in milliseconds

1.2.3.8 Admin Policies

policy

A `dict` of optional admin policies, which are applicable to admin (security) operations.

- **timeout (int)**
Admin operation timeout in milliseconds

1.2.3.9 List Policies

policy

A `dict` of optional list policies, which are applicable to list operations.

- **write_flags**
Write flags for the operation.
One of the *List Write Flags* values such as `aerospike.LIST_WRITE_DEFAULT`

Default: `aerospike.LIST_WRITE_DEFAULT`

Values should be or'd together:

```
aerospike.LIST_WRITE_ADD_UNIQUE |  
aerospike.LIST_WRITE_INSERT_BOUNDED
```

- **list_order**
Ordering to maintain for the list.
One of *List Order*, such as `aerospike.LIST_ORDERED`

Default: `aerospike.LIST_UNORDERED`

Example:

```
list_policy = {
    "write_flags": aerospike.LIST_WRITE_ADD_UNIQUE | aerospike.LIST_
    ↪WRITE_INSERT_BOUNDED,
    "list_order": aerospike.LIST_ORDERED
}
```

1.2.3.10 Map Policies

policy

A `dict` of optional map policies, which are applicable to map operations. Only one of `map_write_mode` or `map_write_flags` should be provided. `map_write_mode` should be used for Aerospike Server versions < 4.3.0 and `map_write_flags` should be used for Aerospike server versions greater than or equal to 4.3.0.

- **map_write_mode**

Write mode for the map operation.

One of the *Map Write Mode* values such as `aerospike.MAP_UPDATE`

Default: `aerospike.MAP_UPDATE`

Note: This should only be used for Server version < 4.3.0.

- **map_write_flags**

Write flags for the map operation.

One of the *Map Write Flag* values such as `aerospike.MAP_WRITE_FLAGS_DEFAULT`

Default: `aerospike.MAP_WRITE_FLAGS_DEFAULT`

Values should be or'd together:

`aerospike.LIST_WRITE_ADD_UNIQUE |`
`aerospike.LIST_WRITE_INSERT_BOUNDED`

Note: This is only valid for Aerospike Server versions >= 4.3.0.

- **map_order**

Ordering to maintain for the map entries.

One of *Map Order*, such as `aerospike.MAP_KEY_ORDERED`

Default: `aerospike.MAP_UNORDERED`

Example:

```
# Server >= 4.3.0
map_policy = {
    'map_order': aerospike.MAP_UNORDERED,
    'map_write_flags': aerospike.MAP_WRITE_FLAGS_CREATE_ONLY
}

# Server < 4.3.0
```

(continues on next page)

(continued from previous page)

```
map_policy = {
    'map_order': aerospike.MAP_UNORDERED,
    'map_write_mode': aerospike.MAP_CREATE_ONLY
}
```

1.2.3.11 Bit Policies

policy

A `dict` of optional bit policies, which are applicable to bit operations.

Note: Requires server version >= 4.6.0

- **bit_write_flags**

Write flags for the bit operation.

One of the *Bitwise Write Flags* values such as `aerospike.BIT_WRITE_DEFAULT`

Default: `aerospike.BIT_WRITE_DEFAULT`

Example:

```
bit_policy = {
    'bit_write_flags': aerospike.BIT_WRITE_UPDATE_ONLY
}
```

1.2.3.12 HyperLogLog Policies

policy

A `dict` of optional HyperLogLog policies, which are applicable to bit operations.

Note: Requires server version >= 4.9.0

- **flags**

Write flags for the HLL operation.

One of the *HyperLogLog Write Flags* values such as `aerospike.HLL_WRITE_DEFAULT`

Default: `aerospike.HLL_WRITE_DEFAULT`

Example:

```
HLL_policy = {
    'flags': aerospike.HLL_WRITE_UPDATE_ONLY
}
```

1.2.4 Misc

1.2.4.1 Privilege Objects

privilege

A `dict` describing a privilege associated with a specific role.

- **code** one of the `Privileges` values such as `aerospike.PRIV_READ`
- **ns** optional namespace, to which the privilege applies, otherwise the privilege applies globally.
- **set** optional set within the `ns`, to which the privilege applies, otherwise to the entire namespace.

Example:

```
{'code': aerospike.PRIV_READ, 'ns': 'test', 'set': 'demo'}
```

1.2.4.2 Unicode Handling

Both `str` and `unicode()` values are converted by the client into UTF-8 encoded strings for storage on the aerospike server. Read methods such as `get()`, `query()`, `scan()` and `operate()` will return that data as UTF-8 encoded `str` values. To get a `unicode()` you will need to manually decode.

Warning: Prior to release 1.0.43 read operations always returned strings as `unicode()`.

```
>>> client.put(key, { 'name': 'Dr. Zeta Alphabet'a, 'age': 47})
>>> (key, meta, record) = client.get(key)
>>> type(record['name'])
<type 'str'>
>>> record['name']
'Dr. Zeta Alphabet'a
>>> client.put(key, { 'name': unichr(0x2603), 'age': 21})
>>> (key, meta, record) = client.get(key)
>>> type(record['name'])
<type 'str'>
>>> record['name']
'\xe2\x98\x83'
>>> print(record['name'])

>>> name = record['name'].decode('utf-8')
>>> type(name)
<type 'unicode'>
>>> name
u'\u2603'
>>> print(name)
```

1.3 Scan Class — Scan

1.3.1 Scan

The Scan object is used to return all the records in a specified set (which can be omitted or `None`). A Scan with a `None` set returns all the records in the namespace.

The scan is invoked using `foreach()`, `results()`, or `execute_background()`. The bins returned can be filtered using `select()`.

See also:

[Scans and Managing Scans](#).

1.3.1.1 Scan Methods

class aerospike.Scan

select (bin1[, bin2[, bin3..]])

Set a filter on the record bins resulting from `results()` or `foreach()`. If a selected bin does not exist in a record it will not appear in the `bins` portion of that record tuple.

apply (module, function[, arguments])

Apply a record UDF to each record found by the scan UDF.

Parameters

- **module (str)** – the name of the Lua module.
- **function (str)** – the name of the Lua function within the *module*.
- **arguments (list)** – optional arguments to pass to the *function*. NOTE: these arguments must be types supported by Aerospike See: [supported data types](#). If you need to use an unsupported type, (e.g. set or tuple) you can use a serializer such as pickle first.

Returns one of the supported types, `int`, `str`, `float (double)`, `list`, `dict (map)`, `bytearray (bytes)`.

See also:

[Developing Record UDFs](#)

add_ops (ops)

Add a list of write ops to the scan. When used with `Scan.execute_background()` the scan will perform the write ops on any records found. If no predicate is attached to the scan it will apply ops to all the records in the specified set. See [aerospike_helpers](#) for available ops.

Parameters ops – list A list of write operations generated by the `aerospike_helpers` e.g. `list_operations`, `map_operations`, etc.

Note: Requires server version >= 4.7.0.

```
import aerospike
from aerospike_helpers.operations import list_operations
from aerospike_helpers.operations import operations
scan = client.scan('test', 'demo')

ops = [
    operations.append(test_bin, 'val_to_append'),
    list_operations.list_remove_by_index(test_bin, list_index_to_remove, ↴
                                          aerospike.LIST_RETURN_NONE)
]
scan.add_ops(ops)
```

(continues on next page)

(continued from previous page)

```
id = scan.execute_background()
client.close()
```

For a more comprehensive example, see using a list of write ops with `Query.execute_background()`.

results ([*policy*[, *nodename*]]) -> list of (*key*, *meta*, *bins*)

Buffer the records resulting from the scan, and return them as a list of records.

Parameters

- **policy** (*dict*) – optional *Scan Policies*.
- **nodename** (*str*) – optional Node ID of node used to limit the scan to a single node.

Returns a list of *Record Tuple*.

```
import aerospike
import pprint

pp = pprint.PrettyPrinter(indent=2)
config = { 'hosts': [ ('127.0.0.1', 3000)] }
client = aerospike.client(config).connect()

client.put(('test','test','key1'), {'id':1,'a':1},
           policy={'key':aerospike.POLICY_KEY_SEND})
client.put(('test','test','key2'), {'id':2,'b':2},
           policy={'key':aerospike.POLICY_KEY_SEND})

scan = client.scan('test', 'test')
scan.select('id','a','zzz')
res = scan.results()
pp.pprint(res)
client.close()
```

Note: We expect to see:

```
[ ( ( 'test',
      'test',
      u'key2',
      bytearray(b
→ '\xb2\x18\xd4\xce\xd8\xba:\x96\xf5\x9ba\xf1j\xat\xee\x01')),
    { 'gen': 52, 'ttl': 2592000},
    { 'id': 2}),
  ( ( 'test',
      'test',
      u'key1',
      bytearray(b'\x1cJ\xce\xa7\xd4Vj\xef+\xdf@W\xa5\xd8o\x8d:\xc9\xf4\xde
→ ')),
    { 'gen': 52, 'ttl': 2592000},
    { 'a': 1, 'id': 1})]
```

Note: Python client versions >= 3.10.0 Supports predicate expressions for results, foreach, and execute_background see `predexp`. Requires server version >= 4.7.0.

```

from __future__ import print_function
import aerospike
from aerospike import predexp
from aerospike import exception as ex
import sys
import time

config = { 'hosts': [ ('127.0.0.1', 3000)] }
client = aerospike.client(config).connect()

# register udf
try:
    client.udf_put('/path/to/my_udf.lua')
except ex.AerospikeError as e:
    print("Error: {} [{}].format(e.msg, e.code))")
    client.close()
    sys.exit(1)

# put records and run scan
try:
    keys = [('test', 'demo', 1), ('test', 'demo', 2), ('test', 'demo', 3)]
    records = [{ 'number': 1}, { 'number': 2}, { 'number': 3}]
    for i in range(3):
        client.put(keys[i], records[i])

    scan = client.scan('test', 'demo')

    preds = [ # check that the record has value < 2 or value == 3 in bin
    ↪ 'name'
        predexp.integer_bin('number'),
        predexp.integer_value(2),
        predexp.integer_less(),
        predexp.integer_bin('number'),
        predexp.integer_value(3),
        predexp.integer_equal(),
        predexp.predexp_or(2)
    ]

    policy = {
        'predexp': preds
    }

    records = scan.results(policy)
    print(records)
except ex.AerospikeError as e:
    print("Error: {} [{}].format(e.msg, e.code))")
    sys.exit(1)
finally:
    client.close()
# the scan only returns records that match the predexp
# EXPECTED OUTPUT:
# [
#     ('test', 'demo', 1, bytearray(b'\xb7\xf4\xb8\x89\xe2\xdag\xdeh>
# ↪ \x1d\xf6\x91\x9a\x1e\xac\xc4F\xc8')), {'gen': 2, 'ttl': 2591999}, {'number
# ↪ ': 1}),
#     ('test', 'demo', 3, bytearray(b
# ↪ '\xb1\x95\xf6\xd4\x8a\x4D9\xd3\xafb\xbf\xf8ha\x01\x94\xcd')), {'gen': 13,
# ↪ 'ttl': 2591999}, {'number': 3})

```

(continues on next page)

(continued from previous page)

]

```
# contents of my_udf.lua
function my_udf(rec, bin, offset)
    info("my transform: %s", tostring(record.digest(rec)))
    rec[bin] = rec[bin] + offset
    aerospike:update(rec)
end
```

foreach(*callback*[, *policy*[, *options*[, *nodename*]]])Invoke the *callback* function for each of the records streaming back from the scan.**Parameters**

- ***callback*** (*callable*) – the function to invoke for each record.
- ***policy*** (*dict*) – optional *Scan Policies*.
- ***options*** (*dict*) – the *Scan Options* that will apply to the scan.
- ***nodename*** (*str*) – optional Node ID of node used to limit the scan to a single node.

Note: A *Record Tuple* is passed as the argument to the callback function.

```
import aerospike
import pprint

pp = pprint.PrettyPrinter(indent=2)
config = { 'hosts': [ ('127.0.0.1', 3000)] }
client = aerospike.client(config).connect()

client.put(('test', 'test', 'key1'), {'id':1,'a':1},
           policy={'key':aerospike.POLICY_KEY_SEND})
client.put(('test', 'test', 'key2'), {'id':2,'b':2},
           policy={'key':aerospike.POLICY_KEY_SEND})

def show_key(record):
    key, meta, bins = record
    print(key)

scan = client.scan('test', 'test')
scan_opts = {
    'concurrent': True,
    'nobins': True,
    'priority': aerospike.SCAN_PRIORITY_MEDIUM
}
scan.foreach(show_key, options=scan_opts)
client.close()
```

Note: We expect to see:

```
('test', 'test', u'key2', bytarray(b
→'\xb2\x18\n\xd4\xce\xd8\xba:\x96s\xf5\x9ba\xf1j\x a7t\xee\x01'))
('test', 'test', u'key1', bytarray(b
→'\x1c\xce\x a7\xd4V\xef\xdf@W\x a5\xd8\x8d.\xc9\xf4\xde'))
```

(continues on next page)

(continued from previous page)

Note: To stop the stream return False from the callback function.

```
from __future__ import print_function
import aerospike

config = { 'hosts': [ ('127.0.0.1', 3000)]}
client = aerospike.client(config).connect()

def limit(lim, result):
    c = [0] # integers are immutable so a list (mutable) is used for the
    ↪ counter
    def key_add(record):
        key, metadata, bins = record
        if c[0] < lim:
            result.append(key)
            c[0] = c[0] + 1
        else:
            return False
    return key_add

scan = client.scan('test', 'user')
keys = []
scan.foreach(limit(100, keys))
print(len(keys)) # this will be 100 if the number of matching records > 100
client.close()
```

execute_background([policy])

Execute a record UDF on records found by the scan in the background. This method returns before the scan has completed. A UDF can be added to the scan with [Scan.apply\(\)](#).

Parameters `policy` (`dict`) – optional *Write Policies*.

Returns a job ID that can be used with `aerospike.Client.job_info()` to track the status of the `aerospike.JOB_SCAN`, as it runs in the background.

Note: Python client version 3.10.0 implemented scan execute_background.

```
from __future__ import print_function
import aerospike
from aerospike import exception as ex
import sys
import time

config = {"hosts": [("127.0.0.1", 3000)]}
client = aerospike.client(config).connect()

# register udf
try:
    client.udf_put("/path/to/my_udf.lua")
except ex.AerospikeError as e:
    print("Error: {} [{}].format(e.msg, e.code))
```

(continues on next page)

(continued from previous page)

```

client.close()
sys.exit(1)

# put records and apply udf
try:
    keys = [("test", "demo", 1), ("test", "demo", 2), ("test", "demo", 3)]
    records = [{"number": 1}, {"number": 2}, {"number": 3}]
    for i in range(3):
        client.put(keys[i], records[i])

    scan = client.scan("test", "demo")
    scan.apply("my_udf", "my_udf", ["number", 10])
    job_id = scan.execute_background()

# wait for job to finish
while True:
    response = client.job_info(job_id, aerospike.JOB_SCAN)
    if response["status"] != aerospike.JOB_STATUS_INPROGRESS:
        break
    time.sleep(0.25)

    records = client.get_many(keys)
    print(records)
except ex.AerospikeError as e:
    print("Error: {} [{}].format(e.msg, e.code))")
    sys.exit(1)
finally:
    client.close()
# EXPECTED OUTPUT:
[
    (('test', 'demo', 1, bytearray(b'\xb7\xf4\xb8\x89\xe2\xdag\xdeh>
→\x1d\xf6\x91\x9a\x1e\xac\xc4F\xc8')), {'gen': 2, 'ttl': 2591999}, {'number
→': 11}),
    (('test', 'demo', 2, bytearray(b'\xaejQ
→7\xdeJ\xda\xccD\x96\xe2\xda\x1f\xea\x84\x8c:\x92p')), {'gen': 12, 'ttl':
→2591999}, {'number': 12}),
    (('test', 'demo', 3, bytearray(b
→'\xb1\xa5\xf6\xd4\x8a\x4D9\xd3\xaf\xbf\xf8ha\x01\x94\xcd')), {'gen':
→13, 'ttl': 2591999}, {'number': 13})
[ ]

```

```

# contents of my_udf.lua
function my_udf(rec, bin, offset)
    info("my transform: %s", tostring(record.digest(rec)))
    rec[bin] = rec[bin] + offset
    aerospike:update(rec)
end

```

1.3.1.2 Scan Policies

policy

A dict of optional scan policies which are applicable to `Scan.results()` and `Scan.foreach()`. See [Policy Options](#).

- `max_retries int`

Maximum number of retries before aborting the current transaction. The initial attempt is not counted as a retry.

If max_retries is exceeded, the transaction will return error AEROSPIKE_ERR_TIMEOUT.

Default: 0

Warning: Database writes that are not idempotent (such as “add”) should not be retried because the write operation may be performed multiple times if the client timed out previous transaction attempts. It’s important to use a distinct write policy for non-idempotent writes which sets max_retries = 0;

- **sleep_between_retries int**

Milliseconds to sleep between retries. Enter 0 to skip sleep.

Default: 0

- **socket_timeout int**

Socket idle timeout in milliseconds when processing a database command.

If socket_timeout is not 0 and the socket has been idle for at least socket_timeout, both max_retries and total_timeout are checked. If max_retries and total_timeout are not exceeded, the transaction is retried.

If both socket_timeout and total_timeout are non-zero and socket_timeout > total_timeout, then socket_timeout will be set to total_timeout. If socket_timeout is 0, there will be no socket idle limit.

Default: 30000.

- **total_timeout int**

Total transaction timeout in milliseconds.

The total_timeout is tracked on the client and sent to the server along with the transaction in the wire protocol. The client will most likely timeout first, but the server also has the capability to timeout the transaction.

If total_timeout is not 0 and total_timeout is reached before the transaction completes, the transaction will return error AEROSPIKE_ERR_TIMEOUT. If total_timeout is 0, there will be no total time limit.

Default: 0

- **compress (bool)**

Compress client requests and server responses.

Use zlib compression on write or batch read commands when the command buffer size is greater than 128 bytes. In addition, tell the server to compress its response on read commands. The server response compression threshold is also 128 bytes.

This option will increase cpu and memory usage (for extra compressed buffers), but decrease the size of data sent over the network.

Default: False

- **fail_on_cluster_change bool**

Abort the scan if the cluster is not in a stable state. Only used for server versions < 4.9.

Default: False

- **durable_delete bool**

Perform durable delete (requires Enterprise server version >= 3.10)

If the transaction results in a record deletion, leave a tombstone for the record.

Default: False

- **records_per_second int**

Limit the scan to process records at records_per_second.

Requires server version >= 4.7.0.

Default: 0 (no limit).

Note: Requires Enterprise server version >= 5.0

- **expressions list**

Compiled aerospike expressions *aerospike_helpers* used for filtering records within a transaction.

Default: None

1.3.1.3 Scan Options

options

A `dict` of optional scan options which are applicable to `Scan.foreach()`.

- **priority**

Scan priority has been replaced by the records_per_second policy see *Scan Policies*.

- **nobins bool**

Whether to return the *bins* portion of the *Record Tuple*.

Default False.

- **concurrent bool**

Whether to run the scan concurrently on all nodes of the cluster.

Default False.

- **percent int**

Percentage of records to return from the scan.

Default 100.

New in version 1.0.39.

1.4 Query Class — Query

1.4.1 Query

The query object created by calling `aerospike.Client.query()` is used for executing queries over a secondary index of a specified set (which can be omitted or `None`). For queries, the `None` set contains those records which are not part of any named set.

The query can (optionally) be assigned one of the following

- One of the `predicates(between())` or `equals()` using `where()`.
- A list of `predexp` using `predexp()`

A query without a predicate will match all the records in the given set, similar to a `Scan`.

The query is invoked using `foreach()`, `results()`, or `execute_background()`. The bins returned can be filtered by using `select()`.

If a list of write operations is added to the query with `add_ops()`, they will be applied to each record processed by the query. See available write operations at See `aerospike_helpers`

Finally, a stream UDF may be applied with `apply()`. It will aggregate results out of the records streaming back from the query.

See also:

[Queries and Managing Queries](#).

1.4.1.1 Query Methods

`class aerospike.Query`

select (`bin1[, bin2[, bin3..]]`)

Set a filter on the record bins resulting from `results()` or `foreach()`. If a selected bin does not exist in a record it will not appear in the `bins` portion of that record tuple.

where (`predicate`)

Set a where `predicate` for the query, without which the query will behave similar to `aerospike.Scan`. The predicate is produced by one of the `aerospike.predicates` methods `equals()` and `between()`.

Parameters `predicate` (`tuple`) – the `tuple()` produced by one of the `aerospike.predicates` methods.

Note: Currently, you can assign at most one predicate to the query.

results (`[,policy [, options]]`) -> `list of (key, meta, bins)`

Buffer the records resulting from the query, and return them as a list of records.

Parameters

- `policy` (`dict`) – optional `Query Policies`.
- `options` (`dict`) – optional `Query Options`.

Returns a list of `Record Tuple`.

```

import aerospike
from aerospike import predicates as p
import pprint

config = { 'hosts': [ ('127.0.0.1', 3000)]}
client = aerospike.client(config).connect()

pp = pprint.PrettyPrinter(indent=2)
query = client.query('test', 'demo')
query.select('name', 'age') # matched records return with the values of
#these bins
# assuming there is a secondary index on the 'age' bin of test.demo
query.where(p.equals('age', 40))
records = query.results( {'total_timeout':2000})
pp.pprint(records)
client.close()

```

Note: Queries require a secondary index to exist on the *bin* being queried.

Note: Python client version >= 3.10.0 Supports predicate expressions for results, foreach, and execute_background see [predexp](#). Requires server versions >= 4.7.0.

```

from __future__ import print_function
import aerospike
from aerospike import predexp
from aerospike import exception as ex
import sys
import time

config = {"hosts": [("127.0.0.1", 3000)]}
client = aerospike.client(config).connect()

# register udf
try:
    client.udf_put(
        "/path/to/my_udf.lua"
    )
except ex.AerospikeError as e:
    print("Error: {} [{}]".format(e.msg, e.code))
    client.close()
    sys.exit(1)

# put records and apply udf
try:
    keys = [("test", "demo", 1), ("test", "demo", 2), ("test", "demo", 3)]
    records = [{"number": 1}, {"number": 2}, {"number": 3}]
    for i in range(3):
        client.put(keys[i], records[i])

    try:
        client.index_integer_create("test", "demo", "number", "test_demo_number_"
#idx")
    except ex.IndexFoundError:
        pass

```

(continues on next page)

(continued from previous page)

```

query = client.query("test", "demo")
query.apply("my_udf", "my_udf", ["number", 10])
job_id = query.execute_background()

# wait for job to finish
while True:
    response = client.job_info(job_id, aerospike.JOB_SCAN)
    print(response)
    if response["status"] != aerospike.JOB_STATUS_INPROGRESS:
        break
    time.sleep(0.25)

    records = client.get_many(keys)
    print(records)
except ex.AerospikeError as e:
    print("Error: {} [{}].format(e.msg, e.code)")
    sys.exit(1)
finally:
    client.close()
# EXPECTED OUTPUT:
# [
#     (('test', 'demo', 1, bytearray(b'\xb7\xf4\xb8\x89\xe2\xdag\xdeh\x1d\xf6\x91\x9a\x1e\xac\xc4F\xc8')), {'gen': 2, 'ttl': 2591999}, {'number': 11}),
#     (('test', 'demo', 2, bytearray(b'\xaejQ\x7\xdeJ\xda\xccD\x96\xe2\xda\x1f\xea\x84\x8c:\x92p')), {'gen': 12, 'ttl': 2591999}, {'number': 12}),
#     (('test', 'demo', 3, bytearray(b'\xb1\xa5`g\xf6\xd4\xa8\x4D9\xd3\xafb\xbf\xf8ha\x01\x94\xcd')), {'gen': 13, 'ttl': 2591999}, {'number': 13})
# ]

```

```

# contents of my_udf.lua
function my_udf(rec, bin, offset)
    info("my transform: %s", tostring(record.digest(rec)))
    rec[bin] = rec[bin] + offset
    aerospike:update(rec)
end

```

Note: For a similar example using `.results()` see `aerospike.Scan.results()`.

`foreach(callback[, policy[, options]])`

Invoke the `callback` function for each of the records streaming back from the query.

Parameters

- **callback** (`callable`) – the function to invoke for each record.
- **policy** (`dict`) – optional *Query Policies*.
- **options** (`dict`) – optional *Query Options*.

Note: A *Record Tuple* is passed as the argument to the callback function.

```

import aerospike
from aerospike import predicates as p
import pprint

config = { 'hosts': [ ('127.0.0.1', 3000)]}
client = aerospike.client(config).connect()

pp = pprint.PrettyPrinter(indent=2)
query = client.query('test', 'demo')
query.select('name', 'age') # matched records return with the values of
# assuming there is a secondary index on the 'age' bin of test.demo
query.where(p.between('age', 20, 30))
names = []
def matched_names(record):
    key, metadata, bins = record
    pp.pprint(bins)
    names.append(bins['name'])

query.foreach(matched_names, {'total_timeout':2000})
pp.pprint(names)
client.close()

```

Note: To stop the stream return False from the callback function.

```

from __future__ import print_function
import aerospike
from aerospike import predicates as p

config = { 'hosts': [ ('127.0.0.1',3000)]}
client = aerospike.client(config).connect()

def limit(lim, result):
    c = [0] # integers are immutable so a list (mutable) is used for the
# counter
    def key_add(record):
        key, metadata, bins = record
        if c[0] < lim:
            result.append(key)
            c[0] = c[0] + 1
        else:
            return False
    return key_add

query = client.query('test','user')
query.where(p.between('age', 20, 30))
keys = []
query.foreach(limit(100, keys))
print(len(keys)) # this will be 100 if the number of matching records > 100
client.close()

```

apply(*module, function[, arguments]*)

Aggregate the *results()* using a stream UDF. If no predicate is attached to the *Query* the stream UDF will aggregate over all the records in the specified set.

Parameters

- **module** (*str*) – the name of the Lua module.
- **function** (*str*) – the name of the Lua function within the *module*.
- **arguments** (*list*) – optional arguments to pass to the *function*. NOTE: these arguments must be types supported by Aerospike See: [supported data types](#). If you need to use an unsupported type, (e.g. set or tuple) you can use a serializer like pickle first.

Returns one of the supported types, `int`, `str`, `float` (double), `list`, `dict` (map), `bytearray` (bytes).

See also:

[Developing Stream UDFs](#)

Note: Assume we registered the following Lua module with the cluster as `stream_udf.lua` using `aerospike.Client.udf_put()`.

```

local function having_ge_threshold(bin_having, ge_threshold)
    return function(rec)
        debug("group_count::thresh_filter: %s > %s ?", tostring(rec[bin_
→having]), tostring(ge_threshold))
        if rec[bin_having] < ge_threshold then
            return false
        end
        return true
    end
end

local function count(group_by_bin)
    return function(group, rec)
        if rec[group_by_bin] then
            local bin_name = rec[group_by_bin]
            group[bin_name] = (group[bin_name] or 0) + 1
            debug("group_count::count: bin %s has value %s which has the count of
→%s", tostring(bin_name), tostring(group[bin_name]))
        end
        return group
    end
end

local function add_values(val1, val2)
    return val1 + val2
end

local function reduce_groups(a, b)
    return map.merge(a, b, add_values)
end

function group_count(stream, group_by_bin, bin_having, ge_threshold)
    if bin_having and ge_threshold then
        local myfilter = having_ge_threshold(bin_having, ge_threshold)
        return stream : filter(myfilter) : aggregate(map{}, count(group_by_bin))_
→: reduce(reduce_groups)
    else
        return stream : aggregate(map{}, count(group_by_bin)) : reduce(reduce_-
→groups)
    end
end

```

(continues on next page)

(continued from previous page)

`end`

Find the first name distribution of users in their twenties using a query aggregation:

```
import aerospike
from aerospike import predicates as p
import pprint

config = {'hosts': [('127.0.0.1', 3000)],
          'lua': {'system_path': '/usr/local/aerospike/lua/',
                  'user_path': '/usr/local/aerospike/usr-lua/'}}
client = aerospike.client(config).connect()

pp = pprint.PrettyPrinter(indent=2)
query = client.query('test', 'users')
query.where(p.between('age', 20, 29))
query.apply('stream_udf', 'group_count', [ 'first_name' ])
names = query.results()
# we expect a dict (map) whose keys are names, each with a count value
pp.pprint(names)
client.close()
```

With stream UDFs, the final reduce steps (which ties the results from the reducers of the cluster nodes) executes on the client-side. Explicitly setting the Lua `user_path` in the config helps the client find the local copy of the module containing the stream UDF. The `system_path` is constructed when the Python package is installed, and contains system modules such as `aerospike.lua`, `as.lua`, and `stream_ops.lua`. The default value for the Lua `system_path` is `/usr/local/aerospike/lua`.

`add_ops(ops)`

Add a list of write ops to the query. When used with `Query.execute_background()` the query will perform the write ops on any records found. If no predicate is attached to the Query it will apply ops to all the records in the specified set.

Parameters `ops` – *list* A list of write operations generated by the `aerospike_helpers` e.g. `list_operations`, `map_operations`, etc.

Note: Requires server version >= 4.7.0.

```
import aerospike
from aerospike_helpers.operations import list_operations
from aerospike_helpers.operations import operations
query = client.query('test', 'demo')

ops = [
    operations.append(test_bin, 'val_to_append'),
    list_operations.list_remove_by_index(test_bin, list_index_to_remove, ↴
                                          aerospike.LIST_RETURN_NONE)
]
query.add_ops(ops)

id = query.execute_background()
client.close()
```

For a more comprehensive example, see using a list of write ops with *Query.execute_background()*.

predexp (predicates)

Set the predicate expression filters to be used by this query.

Parameters predicates – list A list of predicates generated by the *aerospike.predexp — Query Predicate Expressions* functions

```
import aerospike
from aerospike import predexp as predexp
query = client.query('test', 'demo')

predexps = [
    predexp.rec_device_size(),
    predexp.integer_value(65 * 1024),
    predexp.integer_greater()
]
query.predexp(predexps)

big_records = query.results()
client.close()
```

execute_background ([policy])

Execute a record UDF or write operations on records found by the query in the background. This method returns before the query has completed. A UDF or a list of write operations must have been added to the query with *Query.apply()* or *Query.add_ops()* respectively.

Parameters policy (dict) – optional *Write Policies*.

Returns a job ID that can be used with *aerospike.Client.job_info()* to track the status of the *aerospike.JOB_QUERY*, as it runs in the background.

```
# Using a record UDF
import aerospike
query = client.query('test', 'demo')
query.apply('myudfs', 'myfunction', ['a', 1])
query_id = query.execute_background()
# This id can be used to monitor the progress of the background query
```

```
# Using a list of write ops.
from __future__ import print_function
import aerospike
from aerospike import predicates
from aerospike import exception as ex
from aerospike_helpers.operations import list_operations
import sys
import time

# Configure the client.
config = {"hosts": [("127.0.0.1", 3000)]}

# Create a client and connect it to the cluster.
try:
    client = aerospike.client(config).connect()
except ex.ClientError as e:
    print("Error: {} [{}].format(e.msg, e.code)")
    sys.exit(1)
```

(continues on next page)

(continued from previous page)

```

TEST_NS = "test"
TEST_SET = "demo"
nested_list = [{"name": "John", "id": 100}, {"name": "Bill", "id": 200}]
# Write the records.
try:
    keys = [(TEST_NS, TEST_SET, i) for i in range(5)]
    for i, key in enumerate(keys):
        client.put(key, {"account_number": i, "members": nested_list})
except ex.RecordError as e:
    print("Error: {} [{}].format(e.msg, e.code)")

# EXAMPLE 1: Append a new account member to all accounts.
try:
    new_member = {"name": "Cindy", "id": 300}

    ops = [list_operations.list_append("members", new_member)]

    query = client.query(TEST_NS, TEST_SET)
    query.add_ops(ops)
    id = query.execute_background()
    # allow for query to complete
    time.sleep(3)
    print("EXAMPLE 1")

    for i, key in enumerate(keys):
        _, _, bins = client.get(key)
        print(bins)
except ex.ClientError as e:
    print("Error: {} [{}].format(e.msg, e.code)")
    sys.exit(1)

# EXAMPLE 2: Remove a member from a specific account using predicates.
try:
    # Add index to the records for use with predex.
    client.index_integer_create(
        TEST_NS, TEST_SET, "account_number", "test_demo_account_number_idx"
    )

    ops = [
        list_operations.list_remove_by_index("members", 0, aerospike.LIST_
        ↪RETURN_NONE)
    ]

    query = client.query(TEST_NS, TEST_SET)
    number_predicate = predicates.equals("account_number", 3)
    query.where(number_predicate)
    query.add_ops(ops)
    id = query.execute_background()
    # allow for query to complete
    time.sleep(3)
    print("EXAMPLE 2")

    for i, key in enumerate(keys):
        _, _, bins = client.get(key)
        print(bins)
except ex.ClientError as e:

```

(continues on next page)

(continued from previous page)

```

print("Error: {0} [{1}].format(e.msg, e.code))
sys.exit(1)

# Cleanup and close the connection to the Aerospike cluster.
for i, key in enumerate(keys):
    client.remove(key)
client.index_remove(TEST_NS, "test_demo_account_number_idx")
client.close()

"""

EXPECTED OUTPUT:
EXAMPLE 1
{'account_number': 0, 'members': [{'name': 'John', 'id': 100}, {'name': 'Bill
→', 'id': 200}, {'name': 'Cindy', 'id': 300}]}
{'account_number': 1, 'members': [{'name': 'John', 'id': 100}, {'name': 'Bill
→', 'id': 200}, {'name': 'Cindy', 'id': 300}]}
{'account_number': 2, 'members': [{'name': 'John', 'id': 100}, {'name': 'Bill
→', 'id': 200}, {'name': 'Cindy', 'id': 300}]}
{'account_number': 3, 'members': [{'name': 'John', 'id': 100}, {'name': 'Bill
→', 'id': 200}, {'name': 'Cindy', 'id': 300}]}
{'account_number': 4, 'members': [{'name': 'John', 'id': 100}, {'name': 'Bill
→', 'id': 200}, {'name': 'Cindy', 'id': 300}]}
EXAMPLE 2
{'account_number': 0, 'members': [{'name': 'John', 'id': 100}, {'name': 'Bill
→', 'id': 200}, {'name': 'Cindy', 'id': 300}]}
{'account_number': 1, 'members': [{'name': 'John', 'id': 100}, {'name': 'Bill
→', 'id': 200}, {'name': 'Cindy', 'id': 300}]}
{'account_number': 2, 'members': [{'name': 'John', 'id': 100}, {'name': 'Bill
→', 'id': 200}, {'name': 'Cindy', 'id': 300}]}
{'account_number': 3, 'members': [{'name': 'Bill', 'id': 200}, {'name':
→'Cindy', 'id': 300}]}
{'account_number': 4, 'members': [{'name': 'John', 'id': 100}, {'name': 'Bill
→', 'id': 200}, {'name': 'Cindy', 'id': 300}]}
"""

```

1.4.1.2 Query Policies

policy

A dict of optional query policies which are applicable to `Query.results()` and `Query.foreach()`. See [Policy Options](#).

- **max_retries int**

Maximum number of retries before aborting the current transaction. The initial attempt is not counted as a retry.

If `max_retries` is exceeded, the transaction will return error `AEROSPIKE_ERR_TIMEOUT`.

Default: 0

Warning: : Database writes that are not idempotent (such as “add”) should not be retried because the write operation may be performed multiple times if the client timed out previous transaction attempts. It’s important to use a distinct write policy for non-idempotent writes which sets `max_retries = 0`;

- **sleep_between_retries int**

Milliseconds to sleep between retries. Enter 0 to skip sleep.

Default: 0

- **socket_timeout int**

Socket idle timeout in milliseconds when processing a database command.

If socket_timeout is not 0 and the socket has been idle for at least socket_timeout, both max_retries and total_timeout are checked. If max_retries and total_timeout are not exceeded, the transaction is retried.

If both socket_timeout and total_timeout are non-zero and socket_timeout > total_timeout, then socket_timeout will be set to total_timeout. If socket_timeout is 0, there will be no socket idle limit.

Default: 30000.

- **total_timeout int**

Total transaction timeout in milliseconds.

The total_timeout is tracked on the client and sent to the server along with the transaction in the wire protocol. The client will most likely timeout first, but the server also has the capability to timeout the transaction.

If total_timeout is not 0 total_timeout is reached before the transaction completes, the transaction will return error AEROSPIKE_ERR_TIMEOUT. If total_timeout is 0, there will be no total time limit.

Default: 0

- **compress (bool)**

Compress client requests and server responses.

Use zlib compression on write or batch read commands when the command buffer size is greater than 128 bytes. In addition, tell the server to compress its response on read commands. The server response compression threshold is also 128 bytes.

This option will increase cpu and memory usage (for extra compressed buffers), but decrease the size of data sent over the network.

Default: False

- **deserialize bool**

Should raw bytes representing a list or map be deserialized to a list or dictionary.

Set to *False* for backup programs that just need access to raw bytes.

Default: True

- **fail_on_cluster_change bool**

Terminate query if cluster is in migration state.

Default False

Note: Requires Enterprise server version >= 5.0

- **expressions list**

Compiled aerospike expressions `aerospike_helpers` used for filtering records within a transaction.

Default: None

1.4.1.3 Query Options

options

A `dict` of optional query options which are applicable to `Query.foreach()` and `Query.results()`.

- **nobins bool**

Whether to return the `bins` portion of the `Record Tuple`.

Default `False`.

New in version 3.0.0.

1.5 `aerospike.predicates` — Query Predicates

`aerospike.predicates.between(bin, min, max)`

Represent a `bin BETWEEN min AND max` predicate.

Parameters

- **bin (str)** – the bin name.
- **min (int)** – the minimum value to be matched with the between operator.
- **max (int)** – the maximum value to be matched with the between operator.

Returns `tuple()` to be used in `aerospike.Query.where()`.

```
from __future__ import print_function
import aerospike
from aerospike import predicates as p

config = { 'hosts': [ ('127.0.0.1', 3000)] }
client = aerospike.client(config).connect()
query = client.query('test', 'demo')
query.where(p.between('age', 20, 30))
res = query.results()
print(res)
client.close()
```

`aerospike.predicates.equals(bin, val)`

Represent a `bin = val` predicate.

Parameters

- **bin (str)** – the bin name.
- **val (str or int)** – the value to be matched with an equals operator.

Returns `tuple()` to be used in `aerospike.Query.where()`.

```

from __future__ import print_function
import aerospike
from aerospike import predicates as p

config = { 'hosts': [ ('127.0.0.1', 3000)]}
client = aerospike.client(config).connect()
query = client.query('test', 'demo')
query.where(p.equals('name', 'that guy'))
res = query.results()
print(res)
client.close()

```

`aerospike.predicates.geo_within_geojson_region(bin, shape[, index_type])`

Predicate for finding any point in bin which is within the given shape. Requires a geo2dsphere index (`index_geo2dsphere_create()`) over a `bin` containing `GeoJSON` point data.

Parameters

- `bin` (`str`) – the bin name.
- `shape` (`str`) – the shape formatted as a GeoJSON string.
- `index_type` – Optional. Possible `aerospike.INDEX_TYPE_*` values are detailed in *Miscellaneous*.

Returns `tuple()` to be used in `aerospike.Query.where()`.

Note: Requires server version `>= 3.7.0`

```

from __future__ import print_function
import aerospike
from aerospike import GeoJSON
from aerospike import predicates as p

config = { 'hosts': [ ('127.0.0.1', 3000)]}
client = aerospike.client(config).connect()

client.index_geo2dsphere_create('test', 'pads', 'loc', 'pads_loc_geo')
bins = {'pad_id': 1,
        'loc': aerospike.geojson('{"type": "Point", "coordinates": [-80.604333, 28.
        ↵608389]})}
client.put(('test', 'pads', 'launchpad1'), bins)

# Create a search rectangle which matches screen boundaries:
# (from the bottom left corner counter-clockwise)
scrn = GeoJSON({ 'type': "Polygon",
                 'coordinates': [
                     [[-80.590000, 28.60000],
                      [-80.590000, 28.61800],
                      [-80.620000, 28.61800],
                      [-80.620000, 28.60000],
                      [-80.590000, 28.60000]]]})

# Find all points contained in the rectangle.
query = client.query('test', 'pads')
query.select('pad_id', 'loc')
query.where(p.geo_within_geojson_region('loc', scrn.dumps()))

```

(continues on next page)

(continued from previous page)

```
records = query.results()
print(records)
client.close()
```

New in version 1.0.58.

`aerospike.predicates.geo_within_radius(bin, long, lat, radius_meters[, index_type])`

Predicate helper builds an AeroCircle GeoJSON shape, and returns a ‘within GeoJSON region’ predicate. Requires a geo2dsphere index (`index_geo2dsphere_create()`) over a `bin` containing `GeoJSON` point data.

Parameters

- `bin (str)` – the bin name.
- `long (float)` – the longitude of the center point of the AeroCircle.
- `lat (float)` – the latitude of the center point of the AeroCircle.
- `radius_meters (float)` – the radius length in meters of the AeroCircle.
- `index_type` – Optional. Possible `aerospike.INDEX_TYPE_*` values are detailed in [Miscellaneous](#).

Returns `tuple()` to be used in `aerospike.Query.where()`.

Note: Requires server version >= 3.8.1

```
from __future__ import print_function
import aerospike
from aerospike import GeoJSON
from aerospike import predicates as p

config = { 'hosts': [ ('127.0.0.1', 3000)]}
client = aerospike.client(config).connect()

client.index_geo2dsphere_create('test', 'pads', 'loc', 'pads_loc_geo')
bins = {'pad_id': 1,
        'loc': aerospike.geojson({'type': "Point", "coordinates": [-80.604333, 28.608389]})}
client.put(('test', 'pads', 'launchpad1'), bins)

query = client.query('test', 'pads')
query.select('pad_id', 'loc')
query.where(p.geo_within_radius('loc', -80.605000, 28.60900, 400.0))
records = query.results()
print(records)
client.close()
```

New in version 1.0.58.

`aerospike.predicates.geo_contains_geojson_point(bin, point[, index_type])`

Predicate for finding any regions in the bin which contain the given point. Requires a geo2dsphere index (`index_geo2dsphere_create()`) over a `bin` containing `GeoJSON` point data.

Parameters

- `bin (str)` – the bin name.

- **point** (*str*) – the point formatted as a GeoJSON string.
- **index_type** – Optional. Possible aerospike.INDEX_TYPE_* values are detailed in *Miscellaneous*.

Returns tuple() to be used in `aerospike.Query.where()`.

Note: Requires server version >= 3.7.0

```
from __future__ import print_function
import aerospike
from aerospike import GeoJSON
from aerospike import predicates as p

config = { 'hosts': [ ('127.0.0.1', 3000)]}
client = aerospike.client(config).connect()

client.index_geo2dsphere_create('test', 'launch_centers', 'area', 'launch_area_geo'
˓→')
rect = GeoJSON({ 'type': "Polygon",
                 'coordinates': [
                     [-80.590000, 28.60000],
                     [-80.590000, 28.61800],
                     [-80.620000, 28.61800],
                     [-80.620000, 28.60000],
                     [-80.590000, 28.60000]]})
bins = {'area': rect}
client.put(('test', 'launch_centers', 'kennedy space center'), bins)

# Find all geo regions containing a point
point = GeoJSON({'type': "Point",
                  'coordinates': [-80.604333, 28.608389]})
query = client.query('test', 'launch_centers')
query.where(p.geo_contains_geojson_point('area', point.dumps()))
records = query.results()
print(records)
client.close()
```

New in version 1.0.58.

`aerospike.predicates.geo_contains_point(bin, long, lat[, index_type])`

Predicate helper builds a GeoJSON point, and returns a ‘contains GeoJSON point’ predicate. Requires a geo2dsphere index (`index_geo2dsphere_create()`) over a *bin* containing *GeoJSON* point data.

Parameters

- **bin** (*str*) – the bin name.
- **long** (*float*) – the longitude of the point.
- **lat** (*float*) – the latitude of the point.
- **index_type** – Optional. Possible aerospike.INDEX_TYPE_* values are detailed in *Miscellaneous*.

Returns tuple() to be used in `aerospike.Query.where()`.

Note: Requires server version >= 3.7.0

```

from __future__ import print_function
import aerospike
from aerospike import GeoJSON
from aerospike import predicates as p

config = { 'hosts': [ ('127.0.0.1', 3000)]}
client = aerospike.client(config).connect()

client.index_geo2dsphere_create('test', 'launch_centers', 'area', 'launch_area_geo'
˓→')
rect = GeoJSON({ 'type': "Polygon",
                 'coordinates': [
                     [[-80.590000, 28.60000],
                      [-80.590000, 28.61800],
                      [-80.620000, 28.61800],
                      [-80.620000, 28.60000],
                      [-80.590000, 28.60000]]]})
bins = {'area': rect}
client.put(('test', 'launch_centers', 'kennedy space center'), bins)

# Find all geo regions containing a point
query = client.query('test', 'launch_centers')
query.where(p.geo_contains_point('area', -80.604333, 28.608389))
records = query.results()
print(records)
client.close()

```

New in version 1.0.58.

`aerospike.predicates.contains(bin, index_type, val)`

Represent the predicate `bin CONTAINS val` for a bin with a complex (list or map) type.

Parameters

- `bin (str)` – the bin name.
- `index_type` – Possible `aerospike.INDEX_TYPE_*` values are detailed in [Miscellaneous](#).
- `val (str or int)` – match records whose `bin` is an `index_type` (ex: list) containing `val`.

Returns `tuple()` to be used in `aerospike.Query.where()`.

Note: Requires server version >= 3.8.1

```

from __future__ import print_function
import aerospike
from aerospike import predicates as p

config = { 'hosts': [ ('127.0.0.1', 3000)]}
client = aerospike.client(config).connect()

# assume the bin fav_movies in the set test.demo bin should contain
# a dict { (str) _title_ : (int) _times_viewed_ }
# create a secondary index for string values of test.demo records whose 'fav_
˓→movies' bin is a map
client.index_map_keys_create('test', 'demo', 'fav_movies', aerospike.INDEX_STRING,
˓→ 'demo_fav_movies_titles_idx')

```

(continues on next page)

(continued from previous page)

```
# create a secondary index for integer values of test.demo records whose 'fav_movies' bin is a map
client.index_map_values_create('test', 'demo', 'fav_movies', aerospike.INDEX_TYPE_NUMERIC, 'demo_fav_movies_views_idx')

client.put([('test', 'demo', 'Dr. Doom'), {'age':43, 'fav_movies': {'12 Monkeys': 1, 'Brasil': 2}})
client.put([('test', 'demo', 'The Hulk'), {'age':38, 'fav_movies': {'Blindness': 1, 'Eternal Sunshine': 2}})

query = client.query('test', 'demo')
query.where(p.contains('fav_movies', aerospike.INDEX_TYPE_MAPKEYS, '12 Monkeys'))
res = query.results()
print(res)
client.close()
```

aerospike.predicates.range(*bin, index_type, min, max*)

Represent the predicate *bin* CONTAINS values BETWEEN *min* AND *max* for a bin with a complex (list or map) type.

Parameters

- **bin** (*str*) – the bin name.
- **index_type** – Possible aerospike.INDEX_TYPE_* values are detailed in [Miscellaneous](#).
- **min** (*int*) – the minimum value to be used for matching with the range operator.
- **max** (*int*) – the maximum value to be used for matching with the range operator.

Returns tuple() to be used in `aerospike.Query.where()`.

Note: Requires server version >= 3.8.1

```
from __future__ import print_function
import aerospike
from aerospike import predicates as p

config = { 'hosts': [ ('127.0.0.1', 3000)]}
client = aerospike.client(config).connect()

# create a secondary index for numeric values of test.demo records whose 'age' bin is a list
client.index_list_create('test', 'demo', 'age', aerospike.INDEX_TYPE_NUMERIC, 'demo_age_nidx')

# query for records whose 'age' bin has a list with numeric values between 20 and 30
query = client.query('test', 'demo')
query.where(p.range('age', aerospike.INDEX_TYPE_LIST, 20, 30))
res = query.results()
print(res)
client.close()
```

1.6 aerospike.predexp — Query Predicate Expressions

The following methods allow a user to define a predicate expression filter. Predicate expression filters are applied on the query results on the server. Predicate expression filters may occur on any bin in the record.

`aerospike.predexp.predexp_and(nexpr)`

Create an AND logical predicate expression.

Parameters `nexpr` – `int` Number of expressions to combine with “and”. The value of `nexpr` must be between 1 and 65535.

Returns `tuple()` to be used in `aerospike.Query.predexp()`.

For example, the following sequence of predicate expressions selects records where the value of bin “c” is between 11 and 20 inclusive:

```
from aerospike import predexp as predexp
predexprs = [
    predexp.integer_bin("c"),
    predexp.integer_value(11),
    predexp.integer_greatereq(),
    predexp.integer_bin("c"),
    predexp.integer_value(20),
    predexp.integer_lesseq(),
    predexp.predexp_and(2)
]
```

`aerospike.predexp.predexp_or(nexpr)`

Create an Or logical predicate expression.

Parameters `nexpr` – `int` Number of expressions to combine with “or”. The value of `nexpr` must be between 1 and 65535.

Returns `tuple()` to be used in `aerospike.Query.predexp()`.

For example, the following sequence of predicate expressions selects records where the value of bin “pet” is “dog” or “cat”

```
from aerospike import predexp as predexp
predexprs = [
    predexp.string_bin("pet"),
    predexp.string_value("cat"),
    predexp.string_equal(),
    predexp.string_bin("pet"),
    predexp.string_value("dog"),
    predexp.string_equal(),
    predexp.predexp_or(2)
]
```

`aerospike.predexp.predexp_not()`

Create a not logical predicate expression which negates the previous predicate expression on the stack.

Returns `tuple()` to be used in `aerospike.Query.predexp()`.

For example, the following sequence of predicate expressions selects records where the value of bin “pet” is not “cat”

```
from aerospike import predexp as predexp
predexprs = [
```

(continues on next page)

(continued from previous page)

```

predexp.string_bin("pet"),
predexp.string_value("cat"),
predexp.string_equal(),
predexp.predexp_not()
]

```

`aerospike.predexp.integer_bin(bin_name)`

Create an integer bin value predicate expression.

Parameters `bin_name` – `str` The name of the bin containing an integer.

Returns `tuple()` to be used in `aerospike.Query.predexp()`.

For example, the following sequence of predicate expressions selects records where the value of bin “age” is 42

```

from aerospike import predexp as predexp
predexps = [
    predexp.integer_bin("age"),
    predexp.integer_value(42),
    predexp.integer_equal()
]

```

`aerospike.predexp.string_bin(bin_name)`

Create a string bin value predicate expression.

Parameters `bin_name` – `str` The name of the bin containing a string.

Returns `tuple()` to be used in `aerospike.Query.predexp()`.

For example, the following sequence of predicate expressions selects records where the value of bin “name” is “Bob”.

```

from aerospike import predexp as predexp
predexps = [
    predexp.string_bin("name"),
    predexp.string_value("Bob"),
    predexp.string_equal()
]

```

`aerospike.predexp.geojson_bin(bin_name)`

Create a GeoJSON bin value predicate expression.

Parameters `bin_name` – `str` The name of the bin containing a GeoJSON value.

Returns `tuple()` to be used in `aerospike.Query.predexp()`.

For example, the following sequence of predicate expressions selects records where the value of bin “location” is within a specified region.

```

from aerospike import predexp as predexp
geo_region = aerospike.GeoJSON(
    {"type": "AeroCircle", "coordinates": [[-122.0, 37.5], 1000]}).dumps()
predexps = [
    predexp.geojson_bin("location"),
    predexp.geojson_value(geo_region),
    predexp.geojson_within()
]

```

`aerospike.predexp.list_bin(bin_name)`

Create a list bin value predicate expression.

Parameters `bin_name` – `str` The name of the bin containing a list.

Returns `tuple()` to be used in `aerospike.Query.predexp()`.

For example, the following sequence of predicate expressions selects records where the list in bin “names” contains an entry equal to “Alice”

```
from aerospike import predexp as predexp
predexps = [
    predexp.string_var("list_entry"),
    predexp.string_value("Alice"),
    predexp.string_equal(),
    predexp.list_bin("names"),
    predexp.list_iterate_or("list_entry")
]
```

`aerospike.predexp.map_bin(bin_name)`

Create a map bin value predicate expression.

Parameters `bin_name` – `str` The name of the bin containing a map value.

Returns `tuple()` to be used in `aerospike.Query.predexp()`.

For example, the following sequence of predicate expressions selects records where the map in bin “pet_count” has an entry with a key equal to “Cat”

```
from aerospike import predexp as predexp
predexps = [
    predexp.string_var("map_key"),
    predexp.string_value("Cat"),
    predexp.string_equal(),
    predexp.map_bin("pet_count"),
    predexp.mapkey_iterate_or("map_key")
]
```

`aerospike.predexp.geojson_value(geo_value)`

Create a GeoJSON value predicate expression.

Parameters `bin_name` – `str` The geojson string.

Returns `tuple()` to be used in `aerospike.Query.predexp()`.

For example, the following sequence of predicate expressions selects records where the value of bin “location” is within a specified region.

```
from aerospike import predexp as predexp
geo_region = aerospike.GeoJSON(
    {"type": "AeroCircle", "coordinates": [[-122.0, 37.5], 1000]}).dumps()
predexps = [
    predexp.geojson_bin("location"),
    predexp.geojson_value(geo_region),
    predexp.geojson_within()
]
```

`aerospike.predexp.integer_value(int_value)`

Create an integer value predicate expression.

Parameters `bin_name` – `int` The integer value

Returns `tuple()` to be used in `aerospike.Query.predexp()`.

For example, the following sequence of predicate expressions selects records where the value of bin “age” is 42

```
from aerospike import predexp as predexp
predexps = [
    predexp.integer_bin("age"),
    predexp.integer_value(42),
    predexp.integer_equal()
]
```

`aerospike.predexp.string_value(string_value)`

Create a string value predicate expression.

Parameters `bin_name` – `str` The string value.

Returns `tuple()` to be used in `aerospike.Query.predexp()`.

For example, the following sequence of predicate expressions selects records where the value of bin “name” is “Bob”.

```
from aerospike import predexp as predexp
predexps = [
    predexp.string_bin("name"),
    predexp.string_value("Bob"),
    predexp.string_equal()
]
```

`aerospike.predexp.integer_var(var_name)`

Create an integer iteration variable predicate expression.

Parameters `var_name` – `str` The name of the variable. This should match a value used when specifying the iteration.

Returns `tuple()` to be used in `aerospike.Query.predexp()`.

For example the following selects a record where the list in bin “numbers” contains an entry equal to 42

```
from aerospike import predexp as predexp
predexps = [
    predexp.integer_var("item"),
    predexp.integer_value(42),
    predexp.integer_equal(),
    predexp.list_bin("numbers"),
    predexp.list_iterate_or("item")
]
```

`aerospike.predexp.string_var(var_name)`

Create an string iteration variable predicate expression.

Parameters `var_name` – `str` The name of the variable. This should match a value used when specifying the iteration.

Returns `tuple()` to be used in `aerospike.Query.predexp()`.

For example the following selects a record where the list in bin “languages” contains an entry equal to “Python”

```
from aerospike import predexp as predexp
predexps = [
    predexp.string_var("item"),
    predexp.string_value("Python"),
    predexp.string_equal(),
    predexp.list_bin("languages"),
```

(continues on next page)

(continued from previous page)

```

predexp.list_iterate_or("item")
]

```

`aerospike.predexp.geojson_var(var_name)`

Create an GeoJSON iteration variable predicate expression.

Parameters `var_name` – `str` The name of the variable. This should match a value used when specifying the iteration.

Returns `tuple()` to be used in `aerospike.Query.predexp()`.

`aerospike.predexp.list_iterate_or(var_name)`

Create an list iteration OR logical predicate expression.

Parameters `bin_name` – `str` The name of the iteration variable

Returns `tuple()` to be used in `aerospike.Query.predexp()`.

The list iteration expression pops two children off the expression stack. The left child (pushed earlier) must contain a logical subexpression containing one or more matching iteration variable expressions. The right child (pushed later) must specify a list bin. The list iteration traverses the list and repeatedly evaluates the subexpression substituting each list element’s value into the matching iteration variable. The result of the iteration expression is a logical OR of all of the individual element evaluations.

If the list bin contains zero elements `list_iterate_or()` will evaluate to false.

For example, the following sequence of predicate expressions selects records where the list in bin “names” contains an entry equal to “Alice”

```

from aerospike import predexp as predexp
predexps = [
    predexp.string_var("list_entry"),
    predexp.string_value("Alice"),
    predexp.string_equal(),
    predexp.list_bin("names"),
    predexp.list_iterate_or("list_entry")
]

```

`aerospike.predexp.list_iterate_and(var_name)`

Create an list iteration And logical predicate expression.

Parameters `var_name` – `str` The name of the iteration variable

Returns `tuple()` to be used in `aerospike.Query.predexp()`.

The list iteration expression pops two children off the expression stack. The left child (pushed earlier) must contain a logical subexpression containing one or more matching iteration variable expressions. The right child (pushed later) must specify a list bin. The list iteration traverses the list and repeatedly evaluates the subexpression substituting each list element’s value into the matching iteration variable. The result of the iteration expression is a logical AND of all of the individual element evaluations.

If the list bin contains zero elements `list_iterate_and()` will evaluate to true. This is useful when testing for exclusion (see example).

For example, the following sequence of predicate expressions selects records where the list in bin “names” contains no entries equal to “Bob”.

```

from aerospike import predexp as predexp
predexps = [
    predexp.string_var("list_entry"),

```

(continues on next page)

(continued from previous page)

```

predexp.string_value("Bob"),
predexp.string_equal(),
predexp.predexp_not(),
predexp.list_bin("names"),
predexp.list_iterate_and("list_entry")
]

```

`aerospike.predexp.mapkey_iterate_or(var_name)`

Create an map key iteration Or logical predicate expression.

Parameters `var_name` – `str` The name of the iteration variable

Returns `tuple()` to be used in `aerospike.Query.predexp()`.

The mapkey iteration expression pops two children off the expression stack. The left child (pushed earlier) must contain a logical subexpression containing one or more matching iteration variable expressions. The right child (pushed later) must specify a map bin. The mapkey iteration traverses the map and repeatedly evaluates the subexpression substituting each map key value into The matching iteration variable. The result of the iteration expression is a logical OR of all of the individual element evaluations.

If the map bin contains zero elements `mapkey_iterate_or()` will return false. For example, the following sequence of predicate expressions selects records where the map in bin “pet_count” has an entry with a key equal to “Cat”

```

from aerospike import predexp as predexp
predexps = [
    predexp.string_var("map_key"),
    predexp.string_value("Cat"),
    predexp.string_equal(),
    predexp.map_bin("pet_count"),
    predexp.mapkey_iterate_or("map_key")
]

```

`aerospike.predexp.mapkey_iterate_and(var_name)`

Create an map key iteration AND logical predicate expression.

Parameters `var_name` – `str` The name of the iteration variable

Returns `tuple()` to be used in `aerospike.Query.predexp()`.

The mapkey iteration expression pops two children off the expression stack. The left child (pushed earlier) must contain a logical subexpression containing one or more matching iteration variable expressions. The right child (pushed later) must specify a map bin. The mapkey iteration traverses the map and repeatedly evaluates the subexpression substituting each map key value into The matching iteration variable. The result of the iteration expression is a logical AND of all of the individual element evaluations.

If the map bin contains zero elements `mapkey_iterate_and()` will return true. This is useful when testing for exclusion (see example).

For example, the following sequence of predicate expressions selects records where the map in bin “pet_count” does not contain an entry with a key equal to “Cat”.

```

from aerospike import predexp as predexp
predexps = [
    predexp.string_var("map_key"),
    predexp.string_value("Cat"),
    predexp.string_equal(),
    predexp.predexp_not(),
]

```

(continues on next page)

(continued from previous page)

```

predexp.map_bin("pet_count"),
predexp.mapkey_iterate_and("map_key")
]

```

`aerospike.predexp.mapval_iterate_or(var_name)`

Create an map value iteration Or logical predicate expression.

Parameters `var_name` – `str` The name of the iteration variable

Returns `tuple()` to be used in `aerospike.Query.predexp()`.

The mapval iteration expression pops two children off the expression stack. The left child (pushed earlier) must contain a logical subexpression containing one or more matching iteration variable expressions. The right child (pushed later) must specify a map bin. The mapval iteration traverses the map and repeatedly evaluates the subexpression substituting each map value into the matching iteration variable. The result of the iteration expression is a logical OR of all of the individual element evaluations.

If the map bin contains zero elements `mapval_iterate_or()` will return false.

For example, the following sequence of predicate expressions selects records where at least one of the values in the map in bin “pet_count” is 0

```

from aerospike import predexp as predexp
predexprs = [
    predexp.string_var("map_key"),
    predexp.integer_value(0),
    predexp.integer_equal(),
    predexp.map_bin("pet_count"),
    predexp.mapval_iterate_or("map_key")
]

```

`aerospike.predexp.mapval_iterate_and(var_name)`

Create an map value iteration AND logical predicate expression.

Parameters `var_name` – `str` The name of the iteration variable

Returns `tuple()` to be used in `aerospike.Query.predexp()`.

The mapval iteration expression pops two children off the expression stack. The left child (pushed earlier) must contain a logical subexpression containing one or more matching iteration variable expressions. The right child (pushed later) must specify a map bin. The mapval iteration traverses the map and repeatedly evaluates the subexpression substituting each map value into the matching iteration variable. The result of the iteration expression is a logical AND of all of the individual element evaluations.

If the map bin contains zero elements `mapval_iterate_and()` will return true. This is useful when testing for exclusion (see example).

For example, the following sequence of predicate expressions selects records where none of the values in the map in bin “pet_count” is 0

```

from aerospike import predexp as predexp
predexprs = [
    predexp.string_var("map_key"),
    predexp.integer_value(0),
    predexp.integer_equal(),
    predexp.predexp_not(),
    predexp.map_bin("pet_count"),
    predexp.mapval_iterate_and("map_key")
]

```

aerospike.predexp.rec_digest_modulo(mod)

Create a digest modulo record metadata value predicate expression.

Parameters `mod` – `int` The value of this expression assumes the value of 4 bytes of the digest modulo this argument.

Returns `tuple()` to be used in `aerospike.Query.predexp()`.

For example, the following sequence of predicate expressions selects records that have `digest(key) % 3 == 1`:

```
from aerospike import predexp as predexp
predexprs = [
    predexp.rec_digest_modulo(3),
    predexp.integer_value(1),
    predexp.integer_equal()
]
```

aerospike.predexp.rec_last_update()

Create a last update record metadata value predicate expression. The record last update expression assumes the value of the number of nanoseconds since the unix epoch that the record was last updated.

Returns `tuple()` to be used in `aerospike.Query.predexp()`.

For example, the following sequence of predicate expressions selects records that have been updated after a timestamp:

```
from aerospike import predexp as predexp
predexprs = [
    predexp.rec_last_update(),
    predexp.integer_value(timestamp_ns),
    predexp.integer_greater()
]
```

aerospike.predexp.rec_void_time()

Create a void time record metadata value predicate expression. The record void time expression assumes the value of the number of nanoseconds since the unix epoch when the record will expire. The special value of 0 means the record will not expire.

Returns `tuple()` to be used in `aerospike.Query.predexp()`.

For example, the following sequence of predicate expressions selects records that have void time set to 0 (no expiration):

```
from aerospike import predexp as predexp
predexprs = [
    predexp.rec_void_time(),
    predexp.integer_value(0),
    predexp.integer_equal()
]
```

aerospike.predexp.rec_device_size()

Create a record device size metadata value predicate expression. The record device size expression assumes the value of the size in bytes that the record occupies on device storage. For non-persisted records, this value is 0.

Returns `tuple()` to be used in `aerospike.Query.predexp()`.

For example, the following sequence of predicate expressions selects records whose device storage size is larger than 65K:

```
from aerospike import predexp as predexp
predexprs = [
    predexp.rec_device_size(),
    predexp.integer_value(65 * 1024),
    predexp.integer_greater()
]
```

aerospike.predexp.integer_equal()

Create an integer comparison logical predicate expression. If the value of either of the child expressions is unknown because a specified bin does not exist or contains a value of the wrong type the result of the comparison is false. If a true outcome is desirable in this situation use the complimentary comparison and enclose in a logical NOT.

Returns tuple() to be used in `aerospike.Query.predexp()`.

For example, the following sequence of predicate expressions selects records that have bin “foo” equal to 42:

```
from aerospike import predexp as predexp
predexprs = [
    predexp.integer_bin("foo"),
    predexp.integer_value(42),
    predexp.integer_equal()
]
```

aerospike.predexp.integer_greater()

Create an integer comparison logical predicate expression.

Returns tuple() to be used in `aerospike.Query.predexp()`.

For example, the following sequence of predicate expressions selects records that have bin “foo” greater than 42:

```
from aerospike import predexp as predexp
predexprs = [
    predexp.integer_bin("foo"),
    predexp.integer_value(42),
    predexp.integer_greater()
]
```

aerospike.predexp.integer_greatereq()

Create an integer comparison logical predicate expression.

Returns tuple() to be used in `aerospike.Query.predexp()`.

For example, the following sequence of predicate expressions selects records that have bin “foo” greater than or equal to 42:

```
from aerospike import predexp as predexp
predexprs = [
    predexp.integer_bin("foo"),
    predexp.integer_value(42),
    predexp.integer_greatereq()
]
```

aerospike.predexp.integer_less()

Create an integer comparison logical predicate expression.

Returns tuple() to be used in `aerospike.Query.predexp()`.

For example, the following sequence of predicate expressions selects records that have bin “foo” less than 42:

```
from aerospike import predexp as predexp
predexprs = [
    predexp.integer_bin("foo"),
    predexp.integer_value(42),
    predexp.integer_less()
]
```

aerospike.predexp.integer_lesseq()

Create an integer comparison logical predicate expression.

Returns tuple() to be used in `aerospike.Query.predexp()`.

For example, the following sequence of predicate expressions selects records that have bin “foo” less than or equal to 42:

```
from aerospike import predexp as predexp
predexprs = [
    predexp.integer_bin("foo"),
    predexp.integer_value(42),
    predexp.integer_lesseq()
]
```

aerospike.predexp.integer_unequal()

Create an integer comparison logical predicate expression.

Returns tuple() to be used in `aerospike.Query.predexp()`.

This expression will evaluate to true if, and only if, both children of the expression exist, and are of type integer, and are not equal to each other. If this is not desired, utilize `aerospike.predexp.integer_equal()` in conjunction with `aerospike.predexp.predexp_not()`.

For example, the following sequence of predicate expressions selects records that have bin “foo” not equal to 42:

```
from aerospike import predexp as predexp
predexprs = [
    predexp.integer_bin("foo"),
    predexp.integer_value(42),
    predexp.integer_unequal()
]
```

aerospike.predexp.string_equal()

Create an integer comparison logical predicate expression. If the value of either of the child expressions is unknown because a specified bin does not exist or contains a value of the wrong type the result of the comparison is false. If a true outcome is desirable in this situation use the complimentary comparison and enclose in a logical NOT.

Returns tuple() to be used in `aerospike.Query.predexp()`.

For example, the following sequence of predicate expressions selects records that have bin “foo” equal to “bar”:

```
from aerospike import predexp as predexp
predexprs = [
    predexp.string_bin("foo"),
    predexp.string_value("bar"),
    predexp.string_equal()
]
```

aerospike.predexp.string_unequal()

Create an integer comparison logical predicate expression.

Returns tuple() to be used in `aerospike.Query.predexp()`.

This expression will evaluate to true if, and only if, both children of the expression exist, and are of type string, and are not equal to each other. If this is not desired, utilize `aerospike.predexp.string_equal()` in conjunction with `aerospike.predexp.predexp_not()`.

For example, the following sequence of predicate expressions selects records that have bin “foo” not equal to “bar”:

```
from aerospike import predexp as predexp
predexprs = [
    predexp.string_bin("foo"),
    predexp.string_value("bar"),
    predexp.string_unequal()
]
```

`aerospike.predexp.geojson_within()`

Create a Geojson within predicate expression.

Returns tuple() to be used in `aerospike.Query.predexp()`.

```
from aerospike import predexp as predexp
predexprs = [
    predexp.geojson_bin("location"),
    predexp.geojson_value(my_geo_region),
    predexp.geojson_within()
]
```

`aerospike.predexp.geojson_contains()`

Create a Geojson contains predicate expression.

Returns tuple() to be used in `aerospike.Query.predexp()`.

```
from aerospike import predexp as predexp
predexprs = [
    predexp.geojson_bin("region"),
    predexp.geojson_value(my_geo_point),
    predexp.geojson_contains()
]
```

`aerospike.predexp.string_regex(*flags)`

Create a string regex predicate. May be called without any arguments to specify default behavior.

Parameters `flags` – int *Regex Flag Values* Any, or none of the aerospike REGEX constants

Returns tuple() to be used in `aerospike.Query.predexp()`.

For example, the following sequence of predicate expressions selects records that have bin “hex” value ending in ‘1’ or ‘2’:

```
from aerospike import predexp as predexp
predexprs = [
    predexp.string_bin('hex'),
    predexp.string_value('0x00.[12]'),
    predexp.string_regex(aerospike.REGEX_ICASE)
]
```

1.7 aerospike.exception — Aerospike Exceptions

```
from __future__ import print_function

import aerospike
from aerospike import exception as ex

try:
    config = { 'hosts': [ ('127.0.0.1', 3000)], 'policies': { 'total_timeout': 1200}}
    client = aerospike.client(config).connect()
    client.close()
except ex.AerospikeError as e:
    print("Error: {} [{!}]".format(e.msg, e.code))
```

New in version 1.0.44.

1.7.1 In Doubt Status

The in doubt status of a caught exception can be checked by looking at the 5th element of its *args* tuple

```
key = 'test', 'demo', 1
record = {'some': 'thing'}
try:
    client.put(key, record)
except AerospikeError as exc:
    print("The in doubt nature of the operation is: {}".format(exc.args[4]))
```

New in version 3.0.1.

1.7.2 Exception Types

`exception aerospike.exception.AerospikeError`

The parent class of all exceptions raised by the Aerospike client, inherits from `exceptions.Exception`. These attributes should be checked by executing `'exc.args[i]` where i is the index of the attribute. For example to check `in_doubt`, run `exc.args[4]`

`code`

The associated status code.

`msg`

The human-readable error message.

`file`

`line`

`in_doubt`

True if it is possible that the operation succeeded.

`exception aerospike.exception.ClientError`

Exception class for client-side errors, often due to mis-configuration or misuse of the API methods. Subclass of `AerospikeError`.

`exception aerospike.exception.InvalidHostError`

Subclass of `ClientError`.

```
exception aerospike.exception.ParamError
    The operation was not performed because of invalid parameters.

exception aerospike.exception.ServerError
    The parent class for all errors returned from the cluster.

exception aerospike.exception.InvalidRequest
    Protocol-level error. Subclass of ServerError.

exception aerospike.exception.OpNotApplicable
    The operation cannot be applied to the current bin value on the server. Subclass of ServerError.

exception aerospike.exception.FilteredOut
    The transaction was not performed because the preexp was false.

exception aerospike.exception.ServerFull
    The server node is running out of memory and/or storage device space reserved for the specified namespace.
    Subclass of ServerError.

exception aerospike.exception.AlwaysForbidden
    Operation not allowed in current configuration. Subclass of ServerError.

exception aerospike.exception.UnsupportedFeature
    Encountered an unimplemented server feature. Subclass of ServerError.

exception aerospike.exception.DeviceOverload
    The server node's storage device(s) can't keep up with the write load. Subclass of ServerError.

exception aerospike.exception.NamespaceNotFound
    Namespace in request not found on server. Subclass of ServerError.

exception aerospike.exception.ForbiddenError
    Operation not allowed at this time. Subclass of ServerError.

exception aerospike.exception.ElementExistsError
    Raised when trying to alter a map key which already exists, when using a create_only policy.
    Subclass of ServerError.

exception aerospike.exception.ElementNotFoundError
    Raised when trying to alter a map key which does not exist, when using an update_only policy.
    Subclass of ServerError.

exception aerospike.exception.RecordError
    The parent class for record and bin exceptions associated with read and write operations. Subclass of ServerError.
```

key
The key identifying the record.

bin
Optionally the bin associated with the error.

```
exception aerospike.exception.RecordKeyMismatch
    Record key sent with transaction did not match key stored on server. Subclass of RecordError.

exception aerospike.exception.RecordNotFoundError
    Record does not exist in database. May be returned by read, or write with policy aerospike.POLICY\_EXISTS\_UPDATE. Subclass of RecordError.

exception aerospike.exception.RecordGenerationError
    Generation of record in database does not satisfy write policy. Subclass of RecordError.
```

exception aerospike.exception.RecordExistsError

Record already exists. May be returned by write with policy `aerospike.POLICY_EXISTS_CREATE`. Subclass of `RecordError`.

exception aerospike.exception.RecordBusy

Too many concurrent requests for one record - a “hot-key” situation. Subclass of `RecordError`.

exception aerospike.exception.RecordTooBig

Record being (re-)written can't fit in a storage write block. Subclass of `RecordError`.

exception aerospike.exception.BinNameError

Length of bin name exceeds the limit of 14 characters. Subclass of `RecordError`.

exception aerospike.exception.BinIncompatibleType

Bin modification operation can't be done on an existing bin due to its value type (for example appending to an integer). Subclass of `RecordError`.

exception aerospike.exception.IndexError

The parent class for indexing exceptions. Subclass of `ServerError`.

index_name

The name of the index associated with the error.

exception aerospike.exception.IndexNotFound

Subclass of `IndexError`.

exception aerospike.exception.IndexFoundError

Subclass of `IndexError`.

exception aerospike.exception.IndexOOM

The index is out of memory. Subclass of `IndexError`.

exception aerospike.exception.IndexNotReadable

Subclass of `IndexError`.

exception aerospike.exception.IndexNameMaxLen

Subclass of `IndexError`.

exception aerospike.exception.IndexNameMaxCount

Reached the maximum allowed number of indexes. Subclass of `IndexError`.

exception aerospike.exception.QueryError

Exception class for query errors. Subclass of `AerospikeError`.

exception aerospike.exception.QueryQueueFull

Subclass of `QueryError`.

exception aerospike.exception.QueryTimeout

Subclass of `QueryError`.

exception aerospike.exception.ClusterError

Cluster discovery and connection errors. Subclass of `AerospikeError`.

exception aerospike.exception.ClusterChangeError

A cluster state change occurred during the request. This may also be returned by scan operations with the fail-on-cluster-change flag set. Subclass of `ClusterError`.

exception aerospike.exception.AdminError

The parent class for exceptions of the security API.

exception aerospike.exception.ExpiredPassword

Subclass of `AdminError`.

```
exception aerospike.exception.ForbiddenPassword
    Subclass of AdminError.
```

```
exception aerospike.exception.IllegalState
    Subclass of AdminError.
```

```
exception aerospike.exception.InvalidCommand
    Subclass of AdminError.
```

```
exception aerospike.exception.InvalidCredential
    Subclass of AdminError.
```

```
exception aerospike.exception.InvalidField
    Subclass of AdminError.
```

```
exception aerospike.exception.InvalidPassword
    Subclass of AdminError.
```

```
exception aerospike.exception.InvalidPrivilege
    Subclass of AdminError.
```

```
exception aerospike.exception.InvalidRole
    Subclass of AdminError.
```

```
exception aerospike.exception.InvalidUser
    Subclass of AdminError.
```

```
exception aerospike.exception.NotAuthenticated
    Subclass of AdminError.
```

```
exception aerospike.exception.RoleExistsError
    Subclass of AdminError.
```

```
exception aerospike.exception.RoleViolation
    Subclass of AdminError.
```

```
exception aerospike.exception.SecurityNotEnabled
    Subclass of AdminError.
```

```
exception aerospike.exception.SecurityNotSupported
    Subclass of AdminError.
```

```
exception aerospike.exception.SecuritySchemeNotSupported
    Subclass of AdminError.
```

```
exception aerospike.exception.UserExistsError
    Subclass of AdminError.
```

```
exception aerospike.exception.UDFError
    The parent class for UDF exceptions exceptions. Subclass of ServerError.
```

```
module
    The UDF module associated with the error.
```

```
func
    Optionally the name of the UDF function.
```

```
exception aerospike.exception.UDFNotFound
    Subclass of UDFError.
```

```
exception aerospike.exception.LuaFileNotFoundException
    Subclass of UDFError.
```

1.7.3 Exception Hierarchy

```
AerospikeError (*)
  +-- TimeoutError (9)
  +-- ClientError (-1)
    |    +-- InvalidHost (-4)
    |    +-- ParamError (-2)
  +-- ServerError (1)
    +-- InvalidRequest (4)
    +-- ServerFull (8)
    +-- AlwaysForbidden (10)
    +-- UnsupportedFeature (16)
    +-- DeviceOverload (18)
    +-- NamespaceNotFound (20)
    +-- ForbiddenError (22)
    +-- ElementNotFoundError (23)
    +-- ElementExistsError (24)
    +-- RecordError (*)
      |    +-- RecordKeyMismatch (19)
      |    +-- RecordNotFound (2)
      |    +-- RecordGenerationError (3)
      |    +-- RecordExistsError (5)
      |    +-- RecordTooBig (13)
      |    +-- RecordBusy (14)
      |    +-- BinNameError (21)
      |    +-- BinIncompatibleType (12)
  +-- IndexError (204)
    |    +-- IndexNotFound (201)
    |    +-- IndexFoundError (200)
    |    +-- IndexOOM (202)
    |    +-- IndexNotReadable (203)
    |    +-- IndexNameMaxLen (205)
    |    +-- IndexNameMaxCount (206)
  +-- QueryError (213)
    |    +-- QueryQueueFull (211)
    |    +-- QueryTimeout (212)
  +-- ClusterError (11)
    |    +-- ClusterChangeError (7)
  +-- AdminError (*)
    |    +-- SecurityNotSupported (51)
    |    +-- SecurityNotEnabled (52)
    |    +-- SecuritySchemeNotSupported (53)
    |    +-- InvalidCommand (54)
    |    +-- InvalidField (55)
    |    +-- IllegalState (56)
    |    +-- InvalidUser (60)
    |    +-- UserExistsError (61)
    |    +-- InvalidPassword (62)
    |    +-- ExpiredPassword (63)
    |    +-- ForbiddenPassword (64)
    |    +-- InvalidCredential (65)
    |    +-- InvalidRole (70)
    |    +-- RoleExistsError (71)
    |    +-- RoleViolation (81)
    |    +-- InvalidPrivilege (72)
    |    +-- NotAuthenticated (80)
  +-- UDFError (*)
```

(continues on next page)

(continued from previous page)

```
+-- UDFNotFound (1301)
+-- LuaFileNotFound (1302)
```

1.8 aerospike_helpers — Aerospike Helper Package for bin operations (list, map, bit, etc.)

This package contains helpers to be used by the operate and operate_ordered methods for bin operations. (list, map, bitwise, etc.)

1.8.1 Subpackages

1.8.1.1 aerospike_helpers.operations package

aerospike_helpers.operations.operations module

Module with helper functions to create dictionaries consumed by the `aerospike.Client.operate` and `aerospike.Client.operate_ordered` methods for the `aerospike.client` class.

`aerospike_helpers.operations.operations.append(bin_name, append_item)`
Create an append operation dictionary.

The append operation appends `append_item` to the value in `bin_name`.

Parameters

- **bin** (*string*) – The name of the bin to be used.
- **append_item** – The value which will be appended to the item contained in the specified bin.

Returns A dictionary to be passed to operate or operate_ordered.

`aerospike_helpers.operations.operations.delete()`
Create a delete operation dictionary.

The delete operation deletes a record and all associated bins. Requires server version >= 4.7.0.8.

Returns A dictionary to be passed to operate or operate_ordered.

`aerospike_helpers.operations.operations.increment(bin_name, amount)`
Create an increment operation dictionary.

The increment operation increases a value in `bin_name` by the specified amount, or creates a bin with the value of amount.

Parameters

- **bin** (*string*) – The name of the bin to be incremented.
- **amount** – The amount by which to increment the item in the specified bin.

Returns A dictionary to be passed to operate or operate_ordered.

`aerospike_helpers.operations.operations.prepend(bin_name, prepend_item)`
Create a prepend operation dictionary.

The prepend operation prepends `prepend_item` to the value in `bin_name`.

Parameters

- **bin** (*string*) – The name of the bin to be used.
- **prepend_item** – The value which will be prepended to the item contained in the specified bin.

Returns A dictionary to be passed to operate or operate_ordered.

`aerospike_helpers.operations.operations.read(bin_name)`

Create a read operation dictionary.

The read operation reads and returns the value in *bin_name*.

Parameters **bin** – String the name of the bin from which to read.

Returns A dictionary to be passed to operate or operate_ordered.

`aerospike_helpers.operations.operations.touch(ttl=None)`

Create a touch operation dictionary.

Using ttl here is deprecated. It should be set in the record metadata for the operate method.

Parameters **ttl** (*int*) – Deprecated. The ttl that should be set for the record. This should be set in the metadata passed to the operate or operate_ordered methods.

Returns A dictionary to be passed to operate or operate_ordered.

`aerospike_helpers.operations.operations.write(bin_name, write_item)`

Create a write operation dictionary.

The write operation writes *write_item* into the bin specified by *bin_name*.

Parameters

- **bin** (*string*) – The name of the bin into which *write_item* will be stored.
- **write_item** – The value which will be written into the bin.

Returns A dictionary to be passed to operate or operate_ordered.

[aerospike_helpers.operations.list_operations module](#)

This module provides helper functions to produce dictionaries to be used with the `aerospike.Client.operate` and `aerospike.Client.operate_ordered` methods of the aerospike module.

List operations support nested CDTs through an optional ctx context argument. The *ctx* argument is a list of *cdt_ctx* objects. See `aerospike_helpers.cdt_ctx`.

Note: Nested CDT (ctx) requires server version >= 4.6.0

`aerospike_helpers.operations.list_operations.list_append(bin_name, value, policy=None, ctx=None)`

Creates a list append operation to be used with operate, or operate_ordered

The list append operation instructs the aerospike server to append an item to the end of a list bin.

Parameters

- **bin_name** (*str*) – The name of the bin to be operated on.
- **value** – The value to be appended to the end of the list.
- **policy** (*dict*) – An optional dictionary of *list write options*.

- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_append_items(bin_name,
                                                               values,      pol-
                                                               icy=None,
                                                               ctx=None)
```

Creates a list append items operation to be used with operate, or operate_ordered

The list append items operation instructs the aerospike server to append multiple items to the end of a list bin.

Parameters

- **bin_name** (*str*) – The name of the bin to be operated on.
- **values** – (*list*): A sequence of items to be appended to the end of the list.
- **policy** (*dict*) – An optional dictionary of *list write options*.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_clear(bin_name, ctx=None)
```

Create list clear operation.

The list clear operation removes all items from the list specified by *bin_name*

Parameters

- **bin_name** (*str*) – The name of the bin containing the list to be cleared
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_get(bin_name, index, ctx=None)
```

Create a list get operation.

The list get operation gets the value of the item at *index* and returns the value

Parameters

- **bin_name** (*str*) – The name of the bin containing the list to fetch items from.
- **index** (*int*) – The index of the item to be returned.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_get_by_index(bin_name,
                                                               index,      re-
                                                               turn_type,
                                                               ctx=None)
```

Create a list get index operation.

The list get operation gets the item at *index* and returns a value specified by *return_type*

Parameters

- **bin_name** (*str*) – The name of the bin containing the list to fetch items from.
- **index** (*int*) – The index of the item to be returned.
- **return_type** (*int*) – Value specifying what should be returned from the operation.
This should be one of the [List Return Types](#) values
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_get_by_index_range(bin_name,  
                     index,  
                     re-  
                     turn_type,  
                     count=None,  
                     in-  
                     verted=False,  
                     ctx=None)
```

Create a list get index range operation.

The list get by index range operation gets *count* items starting at *index* and returns a value specified by *return_type*

Parameters

- **bin_name** (*str*) – The name of the bin containing the list to fetch items from.
- **index** (*int*) – The index of the first item to be returned.
- **count** (*int*) – The number of list items to be selected.
- **return_type** (*int*) – Value specifying what should be returned from the operation.
This should be one of the [List Return Types](#) values.
- **inverted** (*bool*) – Optional bool specifying whether to invert the return type. If set to *True*, all items outside of the specified range will be returned. Default: *False*
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_get_by_rank(bin_name, rank,  
                                         return_type,  
                                         ctx=None)
```

Create a list get by rank operation.

Server selects list item identified by *rank* and returns selected data specified by *return_type*.

Parameters

- **bin_name** (*str*) – The name of the bin containing the list to fetch a value from.
- **rank** (*int*) – The rank of the item to be fetched.
- **return_type** (*int*) – Value specifying what should be returned from the operation.
This should be one of the [List Return Types](#) values

- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_get_by_rank_range(bin_name,
                                                               rank, re-
                                                               turn_type,
                                                               count=None,
                                                               in-
                                                               verted=False,
                                                               ctx=None)
```

Create a list get by rank range operation.

Server selects *count* items starting at the specified *rank* and returns selected data specified by *return_type*.

Parameters

- **bin_name** (*str*) – The name of the bin containing the list to fetch items from.
- **rank** (*int*) – The rank of the first items to be returned.
- **count** (*int*) – A positive number indicating number of items to be returned.
- **return_type** (*int*) – Value specifying what should be returned from the operation.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs. This should be one of the [List Return Types](#) values
- **inverted** (*bool*) – Optional bool specifying whether to invert the return type. If set to *True*, all items outside of the specified rank range will be returned. Default: *False*

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_get_by_value(bin_name,
                                                               value,           re-
                                                               turn_type,
                                                               inverted=False,
                                                               ctx=None)
```

Create a list get by value operation.

Server selects list items with a value equal to *value* and returns selected data specified by *return_type*.

Parameters

- **bin_name** (*str*) – The name of the bin containing the list to fetch items from.
- **value** – The server returns all items matching this value
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [List Return Types](#) values
- **inverted** (*bool*) – Optional bool specifying whether to invert the return type. If set to *True*, all items not equal to *value* will be selected. Default: *False*
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_get_by_value_list(bin_name,  
                    value_list,  
                    re-  
                    turn_type,  
                    in-  
                    verted=False,  
                    ctx=None)
```

Create a list get by value list operation.

Server selects list items with a value contained in *value_list* and returns selected data specified by *return_type*.

Parameters

- **bin_name** (*str*) – The name of the bin containing the list to fetch items from.
- **value_list** (*list*) – Return items from the list matching an item in this list.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the *List Return Types* values
- **inverted** (*bool*) – Optional bool specifying whether to invert the return type. If set to *True*, all items not matching an entry in *value_list* will be selected. Default: *False*
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_get_by_value_range(bin_name,  
                    re-  
                    turn_type,  
                    value_begin,  
                    value_end,  
                    in-  
                    verted=False,  
                    ctx=None)
```

Create a list get by value list operation.

Server selects list items with a value greater than or equal to *value_begin* and less than *value_end*. If *value_begin* is *None*, range is greater than or equal to the first element of the list. If *value_end* is *None* range extends to the end of the list. Server returns selected data specified by *return_type*.

Parameters

- **bin_name** (*str*) – The name of the bin containing the list to fetch items from.
- **value_begin** – The start of the value range.
- **value_end** – The end of the value range.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the *List Return Types* values
- **inverted** (*bool*) – Optional bool specifying whether to invert the return type. If set to *True*, all items not included in the specified range will be returned. Default: *False*
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_get_by_value_rank_range_relative(bin_name,
value,
off-
set,
re-
turn_type,
count=None,
in-
verted=False,
ctx=None)
```

Create a list get by value rank range relative operation

Create list get by value relative to rank range operation. Server selects list items nearest to value and greater by relative rank. Server returns selected data specified by return_type.

Note: This operation requires server version 4.3.0 or greater.

Examples

These examples show what would be returned for specific arguments when dealing with an ordered list: [0, 4, 5, 9, 11, 15]

```
(value, offset, count) = [selected items]
(5, 0, None) = [5, 9, 11, 15]
(5, 0, 2) = [5, 9]
(5, -1, None) = [4, 5, 9, 11, 15]
(5, -1, 3) = [4, 5, 9]
(3, 3, None) = [11, 15]
(3, -3, None) = [0, 4, 5, 9, 11, 15]
(3, 0, None) = [4, 5, 9, 11, 15]
```

Parameters

- **bin_name** (*str*) – The name of the bin containing the list.
- **value** (*str*) – The value of the item in the list for which to search
- **offset** (*int*) – Begin returning items with rank == rank(found_item) + offset
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [List Return Types](#) values
- **count** (*int*) – If specified, the number of items to return. If None, all items until end of list are returned.
- **inverted** (*bool*) – If True, the operation is inverted, and items outside of the specified range are returned.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_get_range(bin_name,      index,
count, ctx=None)
```

Create a list get range operation.

The list get range operation gets *count* items starting *index* and returns the values.

Parameters

- **bin_name** (*str*) – The name of the bin containing the list to fetch items from.
- **index** (*int*) – The index of the item to be returned.
- **count** (*int*) – A positive number of items to be returned.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_increment(bin_name, index,  
value, policy=None,  
ctx=None)
```

Creates a list increment operation to be used with operate, or operate_ordered

The list insert operation inserts an item at index: *index* into the list contained in the specified bin.

Parameters

- **bin_name** (*str*) – The name of the bin to be operated on.
- **index** (*int*) – The index of the list item to increment.
- **value** (*int*, *float*) – The value to be added to the list item.
- **policy** (*dict*) – An optional dictionary of *list write options*.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_insert(bin_name, index, value,  
policy=None, ctx=None)
```

Creates a list insert operation to be used with operate, or operate_ordered

The list insert operation inserts an item at index: *index* into the list contained in the specified bin.

Parameters

- **bin_name** (*str*) – The name of the bin to be operated on.
- **index** (*int*) – The index at which to insert an item. The value may be positive to use zero based indexing or negative to index from the end of the list.
- **value** – The value to be inserted into the list.
- **policy** (*dict*) – An optional dictionary of *list write options*.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_insert_items(bin_name, index,  
values, policy=None,  
ctx=None)
```

Creates a list insert items operation to be used with operate, or operate_ordered

The list insert items operation inserts items at index: *index* into the list contained in the specified bin.

Parameters

- **bin_name** (*str*) – The name of the bin to be operated on.
- **index** (*int*) – The index at which to insert the items. The value may be positive to use zero based indexing or negative to index from the end of the list.
- **values** (*list*) – The values to be inserted into the list.
- **policy** (*dict*) – An optional dictionary of *list write options*.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_pop(bin_name, index, ctx=None)
Creates a list pop operation to be used with operate, or operate_ordered
```

The list pop operation removes and returns an item index: *index* from list contained in the specified bin.

Parameters

- **bin_name** (*str*) – The name of the bin to be operated on.
- **index** (*int*) – The index of the item to be removed.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_pop_range(bin_name, index,
count, ctx=None)
Creates a list pop range operation to be used with operate, or operate_ordered
```

The list insert range operation removes and returns *count* items starting from index: *index* from the list contained in the specified bin.

Parameters

- **bin_name** (*str*) – The name of the bin to be operated on.
- **index** (*int*) – The index of the first item to be removed.
- **count** (*int*) – A positive number indicating how many items, including the first,
- **be removed and returned** (*to*) –
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_remove(bin_name, index,
ctx=None)
Create list remove operation.
```

The list remove operation removes an item located at *index* in the list specified by *bin_name*

Parameters

- **bin_name** (*str*) – The name of the bin containing the item to be removed.

- **index** (`int`) – The index at which to remove the item.
- **ctx** (`list`) – An optional list of nested CDT context operations (`cdt_cdx` object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_remove_by_index(bin_name,
                                                               index,
                                                               return_type,
                                                               ctx=None)
```

Create a list remove by index operation.

The `list_remove_by_index` operation removes the value of the item at `index` and returns a value specified by `return_type`

Parameters

- **bin_name** (`str`) – The name of the bin containing the list to remove an item from.
- **index** (`int`) – The index of the item to be removed.
- **return_type** (`int`) – Value specifying what should be returned from the operation. This should be one of the [List Return Types](#) values
- **ctx** (`list`) – An optional list of nested CDT context operations (`cdt_cdx` object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_remove_by_index_range(bin_name,
                                                                       index,
                                                                       return_type,
                                                                       count=None,
                                                                       inverted=False,
                                                                       ctx=None)
```

Create a list remove by index range operation.

The list remove by index range operation removes `count` starting at `index` and returns a value specified by `return_type`.

Parameters

- **bin_name** (`str`) – The name of the bin containing the list to remove items from.
- **index** (`int`) – The index of the first item to be removed.
- **count** (`int`) – The number of items to be removed
- **return_type** (`int`) – Value specifying what should be returned from the operation. This should be one of the [List Return Types](#) values.
- **inverted** (`bool`) – Optional bool specifying whether to invert the operation. If set to `True`, all items outside of the specified range will be removed. Default: `False`
- **ctx** (`list`) – An optional list of nested CDT context operations (`cdt_cdx` object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_remove_by_rank(bin_name,
                                                               rank,
                                                               re-
                                                               turn_type,
                                                               ctx=None)
```

Create a list remove by rank operation.

Server removes a list item identified by *rank* and returns selected data specified by *return_type*.

Parameters

- **bin_name** (*str*) – The name of the bin containing the list to fetch a value from.
- **rank** (*int*) – The rank of the item to be removed.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [List Return Types](#) values
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_remove_by_rank_range(bin_name,
                                                                     rank,
                                                                     re-
                                                                     turn_type,
                                                                     count=None,
                                                                     in-
                                                                     verted=False,
                                                                     ctx=None)
```

Create a list remove by rank range operation.

Server removes *count* items starting at the specified *rank* and returns selected data specified by *return_type*.

Parameters

- **bin_name** (*str*) – The name of the bin containing the list to fetch items from.
- **rank** (*int*) – The rank of the first item to removed.
- **count** (*int*) – A positive number indicating number of items to be removed.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [List Return Types](#) values
- **inverted** (*bool*) – Optional bool specifying whether to invert the operation. If set to *True*, all items outside of the specified rank range will be removed. Default: *False*
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_remove_by_value(bin_name,
                                                                value,
                                                                re-
                                                                turn_type,
                                                                in-
                                                                verted=False,
                                                                ctx=None)
```

Create a list remove by value operation.

Server removes list items with a value equal to *value* and returns selected data specified by *return_type*.

Parameters

- **bin_name** (*str*) – The name of the bin containing the list to remove items from.
- **value** – The server removes all list items matching this value.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [List Return Types](#) values
- **inverted** (*bool*) – Optional bool specifying whether to invert the operation. If set to *True*, all items not equal to *value* will be removed. Default: *False*
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_remove_by_value_list(bin_name,  
                      value_list,  
                      re-  
                      turn_type,  
                      in-  
                      verted=False,  
                      ctx=None)
```

Create a list remove by value list operation.

Server removes list items with a value matching one contained in *value_list* and returns selected data specified by *return_type*.

Parameters

- **bin_name** (*str*) – The name of the bin containing the list to remove items from.
- **value_list** (*list*) – The server removes all list items matching one of these values.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [List Return Types](#) values
- **inverted** (*bool*) – Optional bool specifying whether to invert the operation. If set to *True*, all items not equal to a value contained in *value_list* will be removed. Default: *False*
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_remove_by_value_range(bin_name,  
                      re-  
                      turn_type,  
                      value_begin=None,  
                      value_end=None,  
                      in-  
                      verted=False,  
                      ctx=None)
```

Create a list remove by value range operation.

Server removes list items with a value greater than or equal to `value_begin` and less than `value_end`. If `value_begin` is `None`, range is greater than or equal to the first element of the list. If `value_end` is `None` range extends to the end of the list. Server returns selected data specified by `return_type`.

Parameters

- `bin_name (str)` – The name of the bin containing the list to fetch items from.
- `value_begin` – The start of the value range.
- `value_end` – The end of the value range.
- `return_type (int)` – Value specifying what should be returned from the operation. This should be one of the [List Return Types](#) values
- `inverted (bool)` – Optional bool specifying whether to invert the operation. If set to `True`, all items not included in the specified range will be removed. Default: `False`
- `ctx (list)` – An optional list of nested CDT context operations (`cdt_cdx` object) for use on nested CDTs.

Returns A dictionary usable in `operate` or `operate_ordered`. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_remove_by_value_rank_range_relative(bin_na
value,
off-
set,
re-
turn_t
count=
in-
verted
ctx=N
```

Create a list get by value rank range relative operation

Create list remove by value relative to rank range operation. Server removes and returns list items nearest to value and greater by relative rank. Server returns selected data specified by `return_type`.

Note: This operation requires server version 4.3.0 or greater.

These examples show what would be removed and returned for specific arguments when dealing with an ordered list: `[0, 4, 5, 9, 11, 15]`

```
(value, offset, count) = [selected items]
(5, 0, None) = [5, 9, 11, 15]
(5, 0, 2) = [5, 9]
(5, -1, None) = [4, 5, 9, 11, 15]
(5, -1, 3) = [4, 5, 9]
(3, 3, None) = [11, 15]
(3, -3, None) = [0, 4, 5, 9, 11, 15]
(3, 0, None) = [4, 5, 9, 11, 15]
```

Parameters

- `bin_name (str)` – The name of the bin containing the list.
- `value (str)` – The value of the item in the list for which to search

- **offset** (`int`) – Begin removing and returning items with rank == rank(found_item) + offset
- **count** (`int`) – If specified, the number of items to remove and return. If None, all items until end of list are returned.
- **inverted** (`bool`) – If True, the operation is inverted, and items outside of the specified range are removed and returned.
- **ctx** (`list`) – An optional list of nested CDT context operations (`cdt_cdx` object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_remove_range(bin_name,  
                                                               index,      count,  
                                                               ctx=None)
```

Create list remove range operation.

The list remove range operation removes `count` items starting at `index` in the list specified by `bin_name`

Parameters

- **bin_name** (`str`) – The name of the bin containing the items to be removed.
- **index** (`int`) – The index of the first item to remove.
- **count** (`int`) – A positive number representing the number of items to be removed.
- **ctx** (`list`) – An optional list of nested CDT context operations (`cdt_cdx` object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_set(bin_name, index, value, pol-  
                                                icy=None, ctx=None)
```

Create a list set operation.

The list set operations sets the value of the item at `index` to `value`

Parameters

- **bin_name** (`str`) – The name of the bin containing the list to be operated on.
- **index** (`int`) – The index of the item to be set.
- **value** – The value to be assigned to the list item.
- **policy** (`dict`) – An optional dictionary of *list write options*.
- **ctx** (`list`) – An optional list of nested CDT context operations (`cdt_cdx` object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_set_order(bin_name,  
                                                               list_order,  
                                                               ctx=None)
```

Create a list set order operation.

The list_set_order operation sets an order on a specified list bin.

Parameters

- **bin_name** (*str*) – The name of the list bin.
- **list_order** – The ordering to apply to the list. Should be aerospike.LIST_ORDERED or aerospike.LIST_UNORDERED .
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_size(bin_name, ctx=None)
Create a list size operation.
```

Server returns the size of the list in the specified bin.

Parameters

- **bin_name** (*str*) – The name of the bin containing the list.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_sort(bin_name,
sort_flags=<MagicMock
id='140171719258384'>,
ctx=None)
```

Create a list sort operation

The list sort operation will sort the specified list bin.

Parameters

- **bin_name** (*str*) – The name of the bin to sort.
- **sort_flags** – Optional flags modifying the behavior of list_sort. This should be constructed by bitwise or'ing together values from [List Sort Flags](#).
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.list_operations.list_trim(bin_name, index, count,
ctx=None)
```

Create a list trim operation.

Server removes items in list bin that do not fall into range specified by index and count range.

Parameters

- **bin_name** (*str*) – The name of the bin containing the list to be trimmed.
- **index** (*int*) – The index of the items to be kept.
- **count** (*int*) – A positive number of items to be kept.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

aerospike_helpers.operations.map_operations module

Helper functions to create map operation dictionaries arguments for. the `aerospike.Client.operate` and `aerospike.Client.operate_ordered` methods of the aerospike client.

Map operations support nested CDTs through an optional ctx context argument. The ctx argument is a list of `cdt_ctx` objects. See `aerospike_helpers.cdt_ctx`.

Note: Nested CDT (ctx) requires server version >= 4.6.0

`aerospike_helpers.operations.map_operations.map_clear(bin_name, ctx=None)`

Creates a map_clear operation to be used with operate or operate_ordered

The operation removes all items from the map stored in the specified bin.

Parameters

- `bin_name (str)` – The name of the bin containing the map.
- `ctx (list)` – An optional list of nested CDT context operations (`cdt_cdx` object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

`aerospike_helpers.operations.map_operations.map_decrement(bin_name, key, amount, map_policy=None, ctx=None)`

Creates a map_decrement operation to be used with operate or operate_ordered

The operation allows a user to decrement the value of a value stored in the map on the server.

Parameters

- `bin_name (str)` – The name of the bin containing the map.
- `key` – The key for the value to be decremented.
- `amount` – The amount by which to decrement the value stored in map[key]
- `map_policy (list, optional)` – Optional `map_policy dictionary` dictates the type of map to create when it does not exist. The map policy also specifies the mode used when writing items to the map. Defaults to `None`.
- `ctx (list)` – An optional list of nested CDT context operations (`cdt_cdx` object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

`aerospike_helpers.operations.map_operations.map_get_by_index(bin_name, index, return_type, ctx=None)`

Creates a map_get_by_index operation to be used with operate or operate_ordered

The operation returns the entry at index from the map.

Parameters

- `bin_name (str)` – The name of the bin containing the map.
- `index (int)` – The index of the entry to return.

- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [Map Return Types](#) values.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.map_operations.map_get_by_index_range(bin_name,
    in-
    dex_start,
    get_amt,
    re-
    turn_type,
    in-
    verted=False,
    ctx=None)
```

Creates a map_get_by_index_range operation to be used with operate or operate_ordered

The operation returns get_amt entries starting at index_start from the map.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **index_start** (*int*) – The index of the first entry to return.
- **get_amt** (*int*) – The number of entries to return from the map.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [Map Return Types](#) values.
- **inverted** (*bool*) – If true, entries in the specified index range should be ignored, and all other entries returned. Default: False
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.map_operations.map_get_by_key(bin_name, key, re-
    turn_type, ctx=None)
```

Creates a map_get_by_key operation to be used with operate or operate_ordered

The operation returns an item, specified by the key from the map stored in the specified bin.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **key** – The key of the item to be returned from the map
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [Map Return Types](#) values.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.map_operations.map_get_by_key_index_range_relative(bin_name,
value,
off-
set,
re-
turn_type,
count=None,
in-
verted=False,
ctx=None)
```

Create a map get by value rank range relative operation

Create map get by key relative to index range operation. Server removes and returns map items with key nearest to value and greater by relative index. Server returns selected data specified by return_type.

Note: This operation requires server version 4.3.0 or greater.

Examples

Examples for a key ordered map {0: 6, 6: 12, 10: 18, 15: 24} and return type of aerospike.MAP_RETURN_KEY

```
(value, offset, count) = [returned keys]
(5, 0, None) = [6, 10, 15]
(5, 0, 2) = [6, 10]
(5,-1, None) = [0, 6, 10, 15]
(5, -1, 3) = [0, 6, 10]
(3, 2, None) = [15]
(3, 5, None) = []
```

Parameters

- **bin_name** (*str*) – The name of the bin containing the list.
- **value** (*str*) – The value of the item in the list for which to search
- **offset** (*int*) – Begin removing and returning items with rank == rank(fount_item) + offset
- **count** (*int*) – If specified, the number of items to remove and return. If None, all items until end of list are returned.
- **inverted** (*bool*) – If True, the operation is inverted and items outside of the specified range are returned.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.map_operations.map_get_by_key_list(bin_name,
key_list,    re-
turn_type,   in-
verted=False,
ctx=None)
```

Creates a map_get_by_key_list operation to be used with operate or operate_ordered

The operation returns items, specified by the keys in key_list from the map stored in the specified bin.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **key_list** (*list*) – A list of keys to be returned from the map.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [Map Return Types](#) values.
- **inverted** (*bool*) – If true, keys with values not specified in the key_list will be returned, and those keys specified in the key_list will be ignored. Default: False
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.map_operations.map_get_by_key_range(bin_name,
                                                               key_range_start,
                                                               key_range_end,
                                                               return_type,
                                                               inverted=False,
                                                               ctx=None)
```

Creates a map_get_by_key_range operation to be used with operate or operate_ordered

The operation returns items with keys between key_range_start(inclusive) and key_range_end(exclusive) from the map

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **key_range_start** – The start of the range of keys to be returned. (Inclusive)
- **key_range_end** – The end of the range of keys to be returned. (Exclusive)
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [Map Return Types](#) values.
- **inverted** (*bool*) – If True, values outside of the specified range will be returned, and values inside of the range will be ignored. Default: False
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.map_operations.map_get_by_rank(bin_name,      rank,
                                                               return_type,
                                                               ctx=None)
```

Creates a map_get_by_rank operation to be used with operate or operate_ordered

The operation returns the item with the specified rank from the map.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **rank** (*int*) – The rank of the entry to return.

- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [Map Return Types](#) values.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.map_operations.map_get_by_rank_range(bin_name,
                                                               rank_start,
                                                               get_amt, re-
                                                               turn_type,
                                                               in-
                                                               verted=False,
                                                               ctx=None)
```

Creates a map_get_by_rank_range operation to be used with operate or operate_ordered

The operation returns item within the specified rank range from the map.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **rank_start** (*int*) – The start of the rank of the entries to return.
- **get_amt** (*int*) – The number of entries to return.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [Map Return Types](#) values.
- **inverted** (*bool*) – If True, items with ranks inside the specified range should be ignored, and all other entries returned. Default: False.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.map_operations.map_get_by_value(bin_name,   value,
                                                               return_type,   in-
                                                               verted=False,
                                                               ctx=None)
```

Creates a map_get_by_value operation to be used with operate or operate_ordered

The operation returns entries whose value matches the specified value.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **value** – Entries with a value matching this argument will be returned from the map.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [Map Return Types](#) values.
- **inverted** (*bool*) – If True, entries with a value different than the specified value will be returned. Default: False
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.map_operations.map_get_by_value_list(bin_name,
key_list, re-
turn_type,
in-
verted=False,
ctx=None)
```

Creates a map_get_by_value_list operation to be used with operate or operate_ordered

The operation returns entries whose values are specified in the value_list.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **value_list** (*list*) – Entries with a value contained in this list will be returned from the map.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [Map Return Types](#) values.
- **inverted** (*bool*) – If True, entries with a value contained in value_list will be ignored, and all others will be returned.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.map_operations.map_get_by_value_range(bin_name,
value_start,
value_end,
re-
turn_type,
in-
verted=False,
ctx=None)
```

Creates a map_get_by_value_range operation to be used with operate or operate_ordered

The operation returns items, with values between value_start(inclusive) and value_end(exclusive) from the map

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **value_start** – The start of the range of values to be returned. (Inclusive)
- **value_end** – The end of the range of values to be returned. (Exclusive)
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [Map Return Types](#) values.
- **inverted** (*bool*) – If True, values outside of the specified range will be returned, and values inside of the range will be ignored. Default: False
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.map_operations.map_get_by_value_rank_range_relative(bin_name,
value,
off-
set,
re-
turn_type,
count=None,
in-
verted=False,
ctx=None)
```

Create a map remove by value rank range relative operation

Create list map get by value relative to rank range operation. Server returns map items with value nearest to value and greater by relative rank. Server returns selected data specified by return_type.

Note: This operation requires server version 4.3.0 or greater.

Examples

Examples for map {0: 6, 10: 18, 6: 12, 15: 24} and return type of aerospike.
MAP_RETURN_KEY

```
(value, offset, count) = [returned keys]
(6, 0, None) = [0, 6, 10, 15]
(5, 0, 2) = [0, 6]
(7, -1, 1) = [0]
(7, -1, 3) = [0, 6, 10]
```

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **value** (*str*) – The value of the item in the list for which to search
- **offset** (*int*) – Begin removing and returning items with rank == rank(fount_item) + offset
- **count** (*int*) – If specified, the number of items to remove and return. If None, all items until end of list are returned.
- **inverted** (*bool*) – If True, the operation is inverted and items outside of the specified range are returned.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.map_operations.map_increment(bin_name, key, amount,
map_policy=None,
ctx=None)
```

Creates a map_increment operation to be used with operate or operate_ordered

The operation allows a user to increment the value of a value stored in the map on the server.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **key** – The key for the value to be incremented.
- **amount** – The amount by which to increment the value stored in map[key]
- **map_policy** (*list, optional*) – Optional *map_policy dictionary* dictates the type of map to create when it does not exist. The map policy also specifies the mode used when writing items to the map. Defaults to *None*.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.map_operations.map_put(bin_name,      key,      value,
                                                    map_policy=None, ctx=None)
```

Creates a map_put operation to be used with operate or operate_ordered

The operation allows a user to set the value of an item in the map stored on the server.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **key** – The key for the map.
- **value** – The item to store in the map with the corresponding key.
- **map_policy** (*list, optional*) – Optional *map_policy dictionary* dictates the type of map to create when it does not exist. The map policy also specifies the mode used when writing items to the map. Defaults to *None*.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.map_operations.map_put_items(bin_name,    item_dict,
                                                       map_policy=None,
                                                       ctx=None)
```

Creates a map_put_items operation to be used with operate or operate_ordered

The operation allows a user to add or update items in the map stored on the server.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **item_dict** (*dict*) – A dictionary of key value pairs to be added to the map on the server.
- **map_policy** (*list, optional*) – Optional *map_policy dictionary* dictates the type of map to create when it does not exist. The map policy also specifies the mode used when writing items to the map. Defaults to *None*.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.map_operations.map_remove_by_index(bin_name,
                                                               index,      re-
                                                               turn_type,
                                                               ctx=None)
```

Creates a map_remove_by_index operation to be used with operate or operate_ordered

The operation removes the entry at index from the map.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **index** (*int*) – The index of the entry to remove.
- **return_type** (*int*) – Value specifying what should be returned from the operation.
This should be one of the [Map Return Types](#) values.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.map_operations.map_remove_by_index_range(bin_name,
                                                                     index_start,
                                                                     remove_amt,
                                                                     return_type,
                                                                     inverted=False,
                                                                     ctx=None)
```

Creates a map_remove_by_index_range operation to be used with operate or operate_ordered

The operation removes remove_amt entries starting at index_start from the map.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **index_start** (*int*) – The index of the first entry to remove.
- **remove_amt** (*int*) – The number of entries to remove from the map.
- **return_type** (*int*) – Value specifying what should be returned from the operation.
This should be one of the [Map Return Types](#) values.
- **inverted** (*bool*) – If true, entries in the specified index range should be kept, and all other entries removed. Default: False
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.map_operations.map_remove_by_key(bin_name,   key,
                                                               return_type,
                                                               ctx=None)
```

Creates a map_remove_by_key operation to be used with operate or operate_ordered

The operation removes an item, specified by the key from the map stored in the specified bin.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **key** – The key to be removed from the map
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [Map Return Types](#) values.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.map_operations.map_remove_by_key_index_range_relative(bin_name,
key,
offset,
re-
turn_type,
count=None,
in-
verted=False,
ctx=None)
```

Create a map get by value rank range relative operation

Create map remove by key relative to index range operation. Server removes and returns map items with key nearest to value and greater by relative index. Server returns selected data specified by return_type.

Note: This operation requires server version 4.3.0 or greater.

Examples

Examples for a key ordered map {0: 6, 6: 12, 10: 18, 15: 24} and return type of aerospike.MAP_RETURN_KEY

```
(value, offset, count) = [removed keys]
(5, 0, None) = [6, 10, 15]
(5, 0, 2) = [6, 10]
(5, -1, None) = [0, 6, 10, 15]
(5, -1, 3) = [0, 6, 10]
(3, 2, None) = [15]
(3, 5, None) = []
```

Parameters

- **bin_name** (*str*) – The name of the bin containing the list.
- **key** (*str*) – The key of the item in the list for which to search
- **offset** (*int*) – Begin removing and returning items with rank == rank(fount_item) + offset
- **count** (*int*) – If specified, the number of items to remove and return. If None, all items until end of list are returned.
- **inverted** (*bool*) – If True, the operation is inverted and items outside of the specified range are returned.

- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.map_operations.map_remove_by_key_list(bin_name,  
key_list,  
re-  
turn_type,  
in-  
verted=False,  
ctx=None)
```

Creates a map_remove_by_key operation to be used with operate or operate_ordered

The operation removes items, specified by the keys in key_list from the map stored in the specified bin.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **key_list** (*list*) – A list of keys to be removed from the map.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [Map Return Types](#) values.
- **inverted** (*bool*) – If true, keys with values not specified in the key_list will be removed, and those keys specified in the key_list will be kept. Default: False
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.map_operations.map_remove_by_key_range(bin_name,  
key_range_start,  
key_range_end,  
re-  
turn_type,  
in-  
verted=False,  
ctx=None)
```

Creates a map_remove_by_key_range operation to be used with operate or operate_ordered

The operation removes items, with keys between key_range_start(inclusive) and key_range_end(exclusive) from the map.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **key_range_start** – The start of the range of keys to be removed. (Inclusive)
- **key_range_end** – The end of the range of keys to be removed. (Exclusive)
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [Map Return Types](#) values.
- **inverted** (*bool*) – If True, values outside of the specified range will be removed, and values inside of the range will be kept. Default: False

- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.map_operations.map_remove_by_rank(bin_name, rank,
                                                               return_type,
                                                               ctx=None)
```

Creates a map_remove_by_rank operation to be used with operate or operate_ordered

The operation removes the item with the specified rank from the map.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **rank** (*int*) – The rank of the entry to remove.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the *Map Return Types* values.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.map_operations.map_remove_by_rank_range(bin_name,
                                                                     rank_start,
                                                                     re-
                                                                     move_amt,
                                                                     re-
                                                                     turn_type,
                                                                     in-
                                                                     verted=False,
                                                                     ctx=None)
```

Creates a map_remove_by_rank_range operation to be used with operate or operate_ordered

The operation removes *remove_amt* items beginning with the item with the specified rank from the map.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **rank_start** (*int*) – The rank of the entry to remove.
- **remove_amt** (*int*) – The number of entries to remove.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the *Map Return Types* values.
- **inverted** (*bool*) – If True, items with ranks inside the specified range should be kept, and all other entries removed. Default: False.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.map_operations.map_remove_by_value(bin_name,  
value,      re-  
turn_type, in-  
verted=False,  
ctx=None)
```

Creates a map_remove_by_value operation to be used with operate or operate_ordered

The operation removes key value pairs whose value matches the specified value.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **value** – Entries with a value matching this argument will be removed from the map.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [Map Return Types](#) values.
- **inverted** (*bool*) – If True, entries with a value different than the specified value will be removed. Default: False
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.map_operations.map_remove_by_value_list(bin_name,  
value_list,      re-  
turn_type, in-  
verted=False,  
ctx=None)
```

Creates a map_remove_by_value_list operation to be used with operate or operate_ordered

The operation removes key value pairs whose values are specified in the value_list.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **value_list** (*list*) – Entries with a value contained in this list will be removed from the map.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [Map Return Types](#) values.
- **inverted** (*bool*) – If True, entries with a value contained in value_list will be kept, and all others will be removed and returned.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.map_operations.map_remove_by_value_range(bin_name,
    value_start,
    value_end,
    re-
    turn_type,
    in-
    verted=False,
    ctx=None)
```

Creates a map_remove_by_value_range operation to be used with operate or operate_ordered

The operation removes items, with values between value_start(inclusive) and value_end(exclusive) from the map

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **value_start** – The start of the range of values to be removed. (Inclusive)
- **value_end** – The end of the range of values to be removed. (Exclusive)
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [Map Return Types](#) values.
- **inverted** (*bool*) – If True, values outside of the specified range will be removed, and values inside of the range will be kept. Default: False
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.map_operations.map_remove_by_value_rank_range_relative(bin_name,
    value,
    off-
    set,
    re-
    turn_type,
    count=None,
    in-
    verted=False,
    ctx=None)
```

Create a map remove by value rank range relative operation

Create map remove by value relative to rank range operation. Server removes and returns map items nearest to value and greater by relative rank. Server returns selected data specified by return_type.

Note: This operation requires server version 4.3.0 or greater.

Examples

Examples for map {0: 6, 10: 18, 6: 12, 15: 24} and return type of aerospike.
MAP_RETURN_KEY

(value, offset, count) = [removed keys]
(6, 0, None) = [0, 6, 10, 15]

(continues on next page)

(continued from previous page)

```
(5, 0, 2) = [0, 6]
(7, -1, 1) = [0]
(7, -1, 3) = [0, 6, 10]
```

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **value** – The value of the entry in the map for which to search
- **offset** (*int*) – Begin removing and returning items with rank == rank(found_item) + offset
- **count** (*int*) – If specified, the number of items to remove and return. If None, all items with rank greater than found_item are returned.
- **return_type** – Specifies what to return from the operation.
- **inverted** (*bool*) – If True, the operation is inverted and items outside of the specified range are returned.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.map_operations.map_set_policy(bin_name, policy,
                                                               ctx=None)
```

Creates a map_set_policy_operation to be used with operate or operate_ordered

The operation allows a user to set the policy for the map.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **policy** (*dict*) – The *map_policy dictionary*.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.map_operations.map_size(bin_name, ctx=None)
```

Creates a map_size_operation to be used with operate or operate_ordered

The operation returns the size of the map stored in the specified bin.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **ctx** (*list*) – An optional list of nested CDT context operations (*cdt_cdx* object) for use on nested CDTs.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

aerospike_helpers.operations.bit_operations module

Helper functions to create bit operation dictionary arguments for the `aerospike.Client.operate` and `aerospike.Client.operate_ordered` methods of the aerospike client.

Note: Bitwise operations require server version >= 4.6.0

Bit offsets are oriented left to right. Negative offsets are supported and start backwards from the end of the target bitmap.

Offset examples:

- 0: leftmost bit in the map
- 4: fifth bit in the map
- -1: rightmost bit in the map
- -4: 3 bits from rightmost

Example:

```
from __future__ import print_function
import aerospike
from aerospike import exception as ex
from aerospike_helpers.operations import bitwise_operations
import sys

# Configure the client.
config = {"hosts": [("127.0.0.1", 3000)]}

# Create a client and connect it to the cluster.
try:
    client = aerospike.client(config).connect()
except ex.ClientError as e:
    print("Error: {} [{}]".format(e.msg, e.code))
    sys.exit(1)

key = ("test", "demo", "foo")
five_ones_bin_name = "bitwisel"
five_one_blob = bytearray([1] * 5)

# Write the record.
try:
    client.put(key, {five_ones_bin_name: five_one_blob})
except ex.RecordError as e:
    print("Error: {} [{}]".format(e.msg, e.code))

# EXAMPLE 1: resize the five_ones bin to a bytesize of 10.
try:
    ops = [bitwise_operations.bit_resize(five_ones_bin_name, 10)]

    _, _, bins = client.get(key)
    _, _, newbins = client.operate(key, ops)
    print("EXAMPLE 1: before resize: ", bins)
    print("EXAMPLE 1: is now: ", newbins)
except ex.ClientError as e:
```

(continues on next page)

(continued from previous page)

Example:

```
from __future__ import print_function
import aerospike
from aerospike import exception as e
from aerospike_helpers.operations import bitwise_operations

config = {'hosts': [('127.0.0.1', 3000)]}
try:
    client = aerospike.client(config).connect()
except e.ClientError as e:
    print("Error: {} [{}]".format(e.msg, e.code))
    sys.exit(2)

key = ('test', 'demo', 'bit_example')
five_one_blob = bytearray([1] * 5)
five_one_bin = 'bitwisel'

try:
    if client.exists(key):
        client.remove(key)
    bit_policy = {
        'map_write_mode': aerospike.BIT_WRITE_DEFAULT,
```

(continues on next page)

(continued from previous page)

```

        }
        client.put(
            key,
            {
                five_one_bin: five_one_blob
            }
        )

        # Example 1: read bits
        ops = [
            bitwise_operations.bit_get(five_one_bin, 0, 40)
        ]
        print('=====EXAMPLE1=====')
        _, _, results = client.operate(key, ops)
        print(results)

        # Example 2: modify bits using the 'or' op, then read bits
        ops = [
            bitwise_operations.bit_or(five_one_bin, 0, 8, 1, bytearray([255]), bit_
policy),
            bitwise_operations.bit_get(five_one_bin, 0, 40)
        ]
        print('=====EXAMPLE2=====')
        _, _, results = client.operate(key, ops)
        print(results)

        # Example 3: modify bits using the 'remove' op, then read bits'
        ops = [
            bitwise_operations.bit_remove(five_one_bin, 0, 2, bit_policy),
            bitwise_operations.bit_get(five_one_bin, 0, 24)
        ]
        print('=====EXAMPLE3=====')
        _, _, results = client.operate(key, ops)
        print(results)

    except e.AerospikeError as e:
        print("Error: {} [{}].format(e.msg, e.code)")

    client.close()

"""

EXPECTED OUTPUT:
=====
EXAMPLE1=====
{'bitwise1': bytearray(b'\x01\x01\x01\x01\x01\x01')}

=====
EXAMPLE2=====
{'bitwise1': bytearray(b'\xff\x01\x01\x01\x01')}

=====
EXAMPLE3=====
{'bitwise1': bytearray(b'\x01\x01\x01')}

"""

```

See also:[Bits \(Data Types\)](#).

`aerospike_helpers.operations.bitwise_operations.bit_add(bin_name, bit_offset, bit_size, value, sign, action, policy=None)`

Creates a bit_add_operation to be used with operate or operate_ordered.

Creates a bit add operation. Server adds value to the bin at bit_offset for bit_size. bit_size must <= 64. If Sign is true value will be treated as a signed number. If an underflow or overflow occurs, as_bit_overflow_action is used. Server returns nothing.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **bit_offset** (*int*) – The offset where the bits will be added.
- **bit_size** (*int*) – How many bits of value to add.
- **value** (*int*) – The value to be added.
- **sign** (*bool*) – True: treat value as signed, False: treat value as unsigned.
- **action** (*aerospike.constant*) – Action taken if an overflow/underflow occurs.
- **policy** (*dict*, *optional*) – The *bit_policy* policy dictionary. default: None.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.bitwise_operations.bit_and(bin_name, bit_offset, bit_size, value_byte_size, value, policy=None)
```

Creates a bit_and_operation to be used with operate or operate_ordered.

Creates a bit and operation. Server performs an and op with value and bitmap in bin at bit_offset for bit_size. Server returns nothing.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **bit_offset** (*int*) – The offset where the bits will be modified.
- **bit_size** (*int*) – How many bits of value to and.
- **value_byte_size** (*int*) – Length of value in bytes.
- **value** (*bytes/byte array*) – Bytes to be used in and operation.
- **policy** (*dict*, *optional*) – The *bit_policy* policy dictionary. default: None.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.bitwise_operations.bit_count(bin_name, bit_offset, bit_size)
```

Creates a bit_count_operation to be used with operate or operate_ordered.

Server returns an integer count of all set bits starting at bit_offset for bit_size bits.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **bit_offset** (*int*) – The offset where the set bits will begin being counted.
- **bit_size** (*int*) – How many bits will be considered for counting.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.bitwise_operations.bit_get(bin_name, bit_offset, bit_size)
```

Creates a bit_get_operation to be used with operate or operate_ordered.

Server returns bits from bitmap starting at bit_offset for bit_size.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **bit_offset** (*int*) – The offset where the bits will start being read.
- **bit_size** (*int*) – How many bits to get.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.bitwise_operations.bit_get_int(bin_name, bit_offset,  
                                          bit_size, sign)
```

Creates a bit_get_int_operation to be used with operate or operate_ordered.

Server returns an integer formed from the bits read from bitmap starting at bit_offset for bit_size.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **bit_offset** (*int*) – The offset where the bits will start being read.
- **bit_size** (*int*) – How many bits to get.
- **sign** (*bool*) – True: Treat read value as signed. False: treat read value as unsigned.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.bitwise_operations.bit_insert(bin_name, byte_offset,  
                                          value_byte_size,  
                                          value, policy=None)
```

Creates a bit_insert_operation to be used with operate or operate_ordered.

Server inserts the bytes from value into the bitmap at byte_offset. No value is returned.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **byte_offset** (*int*) – The offset where the bytes will be inserted.
- **value_byte_size** (*int*) – Size of value in bytes.
- **value** (*bytes/byte array*) –
- **policy** (*dict, optional*) – The *bit_policy policy* dictionary. default: None.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.bitwise_operations.bit_lscan(bin_name,    bit_offset,  
                                          bit_size, value)
```

Creates a bit_lscan_operation to be used with operate or operate_ordered.

Server returns an integer representing the bit offset of the first occurrence of the specified value bit. Starts scanning at bit_offset for bit_size. Returns -1 if value not found.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **bit_offset** (*int*) – The offset where the bits will start being scanned.
- **bit_size** (*int*) – How many bits to scan.

- **value** (`bool`) – True: look for 1, False: look for 0.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.bitwise_operations.bit_lshift(bin_name, bit_offset,  
bit_size, shift, policy=None)
```

Creates a bit_lshift_operation to be used with operate or operate_ordered.

Server left shifts bitmap starting at bit_offset for bit_size by shift bits. No value is returned.

Parameters

- **bin_name** (`str`) – The name of the bin containing the map.
- **bit_offset** (`int`) – The offset where the bits will start being shifted.
- **bit_size** (`int`) – The number of bits that will be shifted by shift places.
- **shift** (`int`) – How many bits to shift by.
- **policy** (`dict, optional`) – The `bit_policy` policy dictionary. default: None.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.bitwise_operations.bit_not(bin_name, bit_offset,  
bit_size, policy=None)
```

Creates a bit_not_operation to be used with operate or operate_ordered.

Server negates bitmap starting at bit_offset for bit_size. No value is returned.

Parameters

- **bin_name** (`str`) – The name of the bin containing the map.
- **bit_offset** (`int`) – The offset where the bits will start being scanned.
- **bit_size** (`int`) – How many bits to scan.
- **policy** (`dict, optional`) – The `bit_policy` policy dictionary. default: None.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.bitwise_operations.bit_or(bin_name, bit_offset,  
bit_size, value_byte_size,  
value, policy=None)
```

Creates a bit_or_operation to be used with operate or operate_ordered.

Creates a bit or operation. Server performs bitwise or with value and bitmap in bin at bit_offset for bit_size. Server returns nothing.

Parameters

- **bin_name** (`str`) – The name of the bin containing the map.
- **bit_offset** (`int`) – The offset where the bits will start being compared.
- **bit_size** (`int`) – How many bits of value to or.
- **value_byte_size** (`int`) – Length of value in bytes.
- **value** (`bytes/byte array`) – Value to be used in or operation.
- **policy** (`dict, optional`) – The `bit_policy` policy dictionary. default: None.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.bitwise_operations.bit_remove(bin_name, byte_offset,
                                                       byte_size,          policy=None)
```

Creates a bit_remove_operation to be used with operate or operate_ordered.

Remove bytes from bitmap at byte_offset for byte_size.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **byte_offset** (*int*) – Position of bytes to be removed.
- **byte_size** (*int*) – How many bytes to remove.
- **policy** (*dict, optional*) – The *bit_policy policy* dictionary. default: None.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.bitwise_operations.bit_resize(bin_name, byte_size,
                                                       policy=None,          re-
                                                       size_flags=<MagicMock
                                                       id='140171703805328'>)
```

Creates a bit_resize_operation to be used with operate or operate_ordered.

Change the size of a bytes bin stored in a record on the Aerospike Server.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **byte_size** (*int*) – The new size of the bytes.
- **policy** (*dict, optional*) – The *bit_policy policy* dictionary. default: None.
- **resize_flags** (*int, optional*) – Flags modifying the behavior of the resize. This should be constructed by bitwise or'ing together any of the values: *Bitwise Resize Flags* . e.g. *aerospike.BIT_RESIZE_GROW_ONLY* | *aerospike.BIT_RESIZE_FROM_FRONT* default: *aerospike.BIT_RESIZE_DEFAULT*

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.bitwise_operations.bit_rscan(bin_name, bit_offset,
                                                       bit_size, value)
```

Creates a bit_rscan_operation to be used with operate or operate_ordered.

Server returns an integer representing the bit offset of the last occurrence of the specified value bit. Starts scanning at bit_offset for bit_size. Returns -1 if value not found.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **bit_offset** (*int*) – The offset where the bits will start being scanned.
- **bit_size** (*int*) – How many bits to scan.
- **value** (*bool*) – True: Look for 1, False: look for 0.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.bitwise_operations.bit_rshift (bin_name, bit_offset,  
bit_size, shift, policy=None)
```

Creates a bit_rshift_operation to be used with operate or operate_ordered.

Server right shifts bitmap starting at bit_offset for bit_size by shift bits. No value is returned.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **bit_offset** (*int*) – The offset where the bits will start being shifted.
- **bit_size** (*int*) – The number of bits that will be shifted by shift places.
- **shift** (*int*) – How many bits to shift by.
- **policy** (*dict, optional*) – The *bit_policy policy* dictionary. default: None.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.bitwise_operations.bit_set (bin_name, bit_offset,  
bit_size, value_byte_size,  
value, policy=None)
```

Creates a bit_set_operation to be used with operate or operate_ordered.

Set the value on a bitmap at bit_offset for bit_size in a record on the Aerospike Server.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **bit_offset** (*int*) – The offset where the bits will be set.
- **bit_size** (*int*) – How many bits of value to write.
- **value_byte_size** (*int*) – Size of value in bytes.
- **value** (*bytes/byte array*) – The value to be set.
- **policy** (*dict, optional*) – The *bit_policy policy* dictionary. default: None.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.bitwise_operations.bit_subtract (bin_name,  
bit_offset, bit_size,  
value, sign, action,  
policy=None)
```

Creates a bit_subtract_operation to be used with operate or operate_ordered.

Creates a bit add operation. Server subtracts value from the bits at bit_offset for bit_size. bit_size must <= 64. If sign is true value will be treated as a signed number. If an underflow or overflow occurs, as_bit_overflow_action is used. Server returns nothing.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **bit_offset** (*int*) – The offset where the bits will be subtracted.
- **bit_size** (*int*) – How many bits of value to subtract.
- **value** (*int*) – The value to be subtracted.
- **sign** (*bool*) – True: treat value as signed, False: treat value as unsigned.

- **action** (*aerospike.constant*) – Action taken if an overflow/underflow occurs.
- **policy** (*dict, optional*) – The *bit_policy policy* dictionary. default: None.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

```
aerospike_helpers.operations.bitwise_operations.bit_xor(bin_name, bit_offset,
                                                       bit_size, value_byte_size,
                                                       value, policy=None)
```

Creates a bit_xor_operation to be used with operate or operate_ordered.

Creates a bit and operation. Server performs bitwise xor with value and bitmap in bin at bit_offset for bit_size. Server returns nothing.

Parameters

- **bin_name** (*str*) – The name of the bin containing the map.
- **bit_offset** (*int*) – The offset where the bits will start being compared.
- **bit_size** (*int*) – How many bits of value to xor.
- **value_byte_size** (*int*) – Length of value in bytes.
- **value** (*bytes/byte array*) – Value to be used in xor operation.
- **policy** (*dict, optional*) – The *bit_policy policy* dictionary. default: None.

Returns A dictionary usable in operate or operate_ordered. The format of the dictionary should be considered an internal detail, and subject to change.

aerospike_helpers.operations.hll_operations module

Helper functions to create HyperLogLog operation dictionary arguments for the *aerospike.Client.operate* and *aerospike.Client.operate_ordered* methods of the aerospike client. HyperLogLog bins and operations allow for your application to form fast, reasonable approximations of members in the union or intersection between multiple HyperLogLog bins. HyperLogLog's estimates are a balance between complete accuracy and efficient savings in space and speed in dealing with extremely large datasets.

Note: HyperLogLog operations require server version >= 4.9.0

See also:

[HyperLogLog \(Data Type\) more info..](#)

Example:

```
from __future__ import print_function
import sys

import aerospike
from aerospike import exception as ex
from aerospike_helpers.operations import hll_operations as hll_ops
from aerospike_helpers.operations import operations

TEST_NS = "test"
TEST_SET = "demo"
```

(continues on next page)

(continued from previous page)

```

NUM_INDEX_BITS = 12
NUM_MH_BITS = 24

# Configure the client.
config = {"hosts": [("127.0.0.1", 3000)]}

# Create a client and connect it to the cluster.
try:
    client = aerospike.client(config).connect()
except ex.ClientError as e:
    print("Error: {} [{}].format(e.msg, e.code)")
    sys.exit(1)

# Add HLL bins.
customers = ["Amy", "Farnsworth", "Scruffy"]
customer_record_keys = [
    (TEST_NS, TEST_SET, "Amy"),
    (TEST_NS, TEST_SET, "Farnsworth"),
    (TEST_NS, TEST_SET, "Scruffy"),
]
items_viewed = [
    ("item%${}" % str(i) for i in range(0, 500)),
    ("item%${}" % str(i) for i in range(0, 750)),
    ("item%${}" % str(i) for i in range(250, 1000)),
]

for customer, key, items in zip(customers, customer_record_keys, items_viewed):
    ops = [
        operations.write("name", customer),
        hll_ops.hll_add("viewed", list(items), NUM_INDEX_BITS, NUM_MH_BITS),
    ]

    try:
        client.operate(key, ops)
    except ex.ClientError as e:
        print("Error: {} [{}].format(e.msg, e.code)")
        sys.exit(1)

# Find out how many items viewed Amy, Farnsworth, and Scruffy have in common.
Farnsworth_viewed = client.get(customer_record_keys[1])[2]["viewed"]
Scruffy_viewed = client.get(customer_record_keys[2])[2]["viewed"]
viewed = [Farnsworth_viewed, Scruffy_viewed]
ops = [hll_ops.hll_get_intersect_count("viewed", viewed)]

try:
    _, _, res = client.operate(customer_record_keys[0], ops)
except ex.ClientError as e:
    print("Error: {} [{}].format(e.msg, e.code)")
    sys.exit(1)

print(
    "Estimated items viewed intersection: %d."
    % res["viewed"]
)
print("Actual intersection: 250.\n")

# Find out how many unique products Amy, Farnsworth, and Scruffy have viewed.

```

(continues on next page)

(continued from previous page)

```

Farnsworth_viewed = client.get(customer_record_keys[1])[2]["viewed"]
Scruffy_viewed = client.get(customer_record_keys[2])[2]["viewed"]
viewed = [Farnsworth_viewed, Scruffy_viewed]
ops = [hll_ops.hll_get_union_count("viewed", viewed)]

try:
    _, _, res = client.operate(customer_record_keys[0], ops)
except ex.ClientError as e:
    print("Error: {0} [{1}]".format(e.msg, e.code))
    sys.exit(1)

print(
    "Estimated items viewed union: %d."
    % res["viewed"]
)
print("Actual union: 1000.\n")

# Find the similarity of Amy, Farnsworth, and Scruffy's product views.
Farnsworth_viewed = client.get(customer_record_keys[1])[2]["viewed"]
Scruffy_viewed = client.get(customer_record_keys[2])[2]["viewed"]
viewed = [Farnsworth_viewed, Scruffy_viewed]
ops = [hll_ops.hll_get_similarity("viewed", viewed)]

try:
    _, _, res = client.operate(customer_record_keys[0], ops)
except ex.ClientError as e:
    print("Error: {0} [{1}]".format(e.msg, e.code))
    sys.exit(1)

print(
    "Estimated items viewed similarity: %f%%."
    % (res["viewed"] * 100)
)
print("Actual similarity: 25%.")

"""
Expected output:
Estimated items viewed intersection: 235.
Actual intersection: 250.

Estimated items viewed union: 922.
Actual union: 1000.

Estimated items viewed similarity: 25.488069%.
Actual similarity: 25%.
"""

```

```
aerospike_helpers.operations.hll_operations.hll_add(bin_name,      values,      in-
                                                dex_bit_count=None,
                                                mh_bit_count=None,      pol-
                                                icy=None)
```

Creates a hll_add operation to be used with operate, or operate_ordered.

Server will add the values to the hll bin. If the HLL bin does not exist, it will be created with index_bit_count and/or mh_bit_count if they have been supplied.

Parameters

- **bin_name** (*str*) – The name of the bin to be operated on.
- **values** – The values to be added to the HLL set.
- **index_bit_count** – An optional number of index bits. Must be between 4 and 16 inclusive.
- **mh_bit_count** – An optional number of min hash bits. Must be between 4 and 58 inclusive.
- **policy** (*dict*) – An optional dictionary of *hll policy options*.

`aerospike_helpers.operations.hll_operations.hll_describe(bin_name)`

Creates a hll_describe operation to be used with operate, or operate_ordered.

Server returns index and minhash bit counts used to create HLL bin in a list of integers. The list size is 2.

Parameters **bin_name** (*str*) – The name of the bin to be operated on.

`aerospike_helpers.operations.hll_operations.hll_fold(bin_name, index_bit_count)`

Creates a hll_fold operation to be used with operate, or operate_ordered.

Servers folds index_bit_count to the specified value. This can only be applied when minhash bit count on the HLL bin is 0. Server does not return a value.

Parameters

- **bin_name** (*str*) – The name of the bin to be operated on.
- **index_bit_count** – number of index bits. Must be between 4 and 16 inclusive.

`aerospike_helpers.operations.hll_operations.hll_get_count(bin_name)`

Creates a hll_get_count operation to be used with operate, or operate_ordered.

Server returns estimated count of elements in the HLL bin.

Parameters **bin_name** (*str*) – The name of the bin to be operated on.

`aerospike_helpers.operations.hll_operations.hll_get_intersect_count(bin_name, hll_list)`

Creates a hll_get_intersect_count operation to be used with operate, or operate_ordered.

Server returns estimate of elements that would be contained by the intersection of these HLL objects.

Parameters

- **bin_name** (*str*) – The name of the bin to be operated on.
- **hll_list** (*list*) – The HLLs to be intersected.

`aerospike_helpers.operations.hll_operations.hll_get_similarity(bin_name, hll_list)`

Creates a hll_get_similarity operation to be used with operate, or operate_ordered.

Server returns estimated similarity of the HLL objects. Server returns a float.

Parameters

- **bin_name** (*str*) – The name of the bin to be operated on.
- **hll_list** (*list*) – The HLLs used for similarity estimation.

`aerospike_helpers.operations.hll_operations.hll_get_union(bin_name, hll_list)`

Creates a hll_get_union operation to be used with operate, or operate_ordered.

Server returns an HLL object that is the union of all specified HLL objects in hll_list with the HLL bin.

Parameters

- **bin_name** (*str*) – The name of the bin to be operated on.
- **hll_list** (*list*) – The HLLs to be unioned.

```
aerospike_helpers.operations.hll_operations.hll_get_union_count(bin_name,
                                                               hll_list)
```

Creates a hll_get_union_count operation to be used with operate, or operate_ordered.

Server returns the estimated count of elements that would be contained by the union of all specified HLL objects in the list with the HLL bin.

Parameters

- **bin_name** (*str*) – The name of the bin to be operated on.
- **hll_list** (*list*) – The HLLs to be unioned.

```
aerospike_helpers.operations.hll_operations.hll_init(bin_name,           in-
                                                       index_bit_count=None,      dex_bit_count=None,
                                                       mh_bit_count=None,         mh_bit_count=None,
                                                       policy=None)               policy=None)
```

Creates a hll_init operation to be used with operate, or operate_ordered.

Server creates a new HLL or resets an existing HLL. If index_bit_count and mh_bit_count are None, an existing HLL bin will be reset but retain its configuration. If 1 of index_bit_count or mh_bit_count are set, an existing HLL bin will set that config and retain its current value for the unset config. If the HLL bin does not exist, index_bit_count is required to create it, mh_bit_count is optional. Server does not return a value.

Parameters

- **bin_name** (*str*) – The name of the bin to be operated on.
- **index_bit_count** – An optional number of index bits. Must be between 4 and 16 inclusive.
- **mh_bit_count** – An optional number of min hash bits. Must be between 4 and 58 inclusive.
- **policy** (*dict*) – An optional dictionary of *hll policy options*.

```
aerospike_helpers.operations.hll_operations.hll_refresh_count(bin_name)
```

Creates a hll_refresh_count operation to be used with operate, or operate_ordered.

Server updates the cached count if it is stale. Server returns the count.

Parameters **bin_name** (*str*) – The name of the bin to be operated on.

```
aerospike_helpers.operations.hll_operations.hll_set_union(bin_name, hll_list, pol-
                                                               icy=None)
```

Creates a hll_set_union operation to be used with operate, or operate_ordered.

Server sets the union of all specified HLL objects with the HLL bin. Server returns nothing.

Parameters

- **bin_name** (*str*) – The name of the bin to be operated on.
- **hll_list** (*list*) – The HLLs whose union will be set.
- **policy** (*dict*) – An optional dictionary of *hll policy options*.

1.8.1.2 aerospike_helpers.expressions package

Classes for the creation and use of aerospike expressions. See:: [Aerospike Expressions](#).

Aerospike Expressions are a small domain specific language that allow for filtering records in transactions by manipulating and comparing bins and record metadata. Expressions can be used everywhere that predicate expressions have been used and allow for expanded functionality and customizability.

In the Python client, Aerospike expressions are built using a series of classes that represent comparison and logical operators, bins, metadata operations, and bin operations. Expressions are constructed using a Lisp like syntax by instantiating an expression that yields a boolean, such as Eq() or And(), while passing them other expressions and constants as arguments, and finally calling the compile() method. See the example below.

Example:

```
# See if integer bin "bin_name" contains a value equal to 10.
from aerospike_helpers import expressions as exp
expr = exp.Eq(exp.IntBin("bin_name"), 10).compile()
```

By passing these compiled expressions to transactions via the “expressions” policy field, the expressions will filter the results. See the example below.

Example:

```
from __future__ import print_function
import aerospike
from aerospike_helpers import expressions as exp
from aerospike import exception as ex
import sys

TEST_NS = "test"
TEST_SET = "demo"
FIRST_RECORD_INDEX = 0
SECOND_RECORD_INDEX = 1
BIN_INDEX = 2

# Configure the client.
config = {"hosts": [("127.0.0.1", 3000)]}

# Create a client and connect it to the cluster.
try:
    client = aerospike.client(config).connect()
except ex.ClientError as e:
    print("Error: {} [{}].format(e.msg, e.code))")
    sys.exit(1)

# Write records
keys = [(TEST_NS, TEST_SET, i) for i in range(1, 5)]
records = [
    {'user': "Chief", 'team': "blue", 'scores': [6, 12, 4, 21], 'kd': 1.0, 'status': "MasterPlatinum"}, 
    {'user': "Arbiter", 'team': "blue", 'scores': [5, 10, 5, 8], 'kd': 1.0, 'status': "MasterGold"}, 
    {'user': "Johnson", 'team': "blue", 'scores': [8, 17, 20, 5], 'kd': 0.99, 'status': "SergeantGold"}, 
    {'user': "Regret", 'team': "red", 'scores': [4, 2, 3, 5], 'kd': 0.33, 'status': "ProphetSilver"}]

try:
    for key, record in zip(keys, records):
        client.put(key, record)
except ex.RecordError as e:
```

(continues on next page)

(continued from previous page)

```

print("Error: {0} [{1}]".format(e.msg, e.code))

# EXAMPLE 1: Get records for users who's top scores are above 20 using a scan.
try:
    expr = exp.GT(exp.ListGetByRank(None, aerospike.LIST_RETURN_VALUE, exp.ResultType.
→INTEGER, -1, exp.ListBin("scores")), # rank -1 == largest value
                  20).compile()

    scan = client.scan(TEST_NS, TEST_SET)
    policy = {
        'expressions': expr
    }

    records = scan.results(policy)
    # This scan will only return the record for "Chief" since it is the only account
    →with a score over 20 using batch get.
    print(records[FIRST_RECORD_INDEX][BIN_INDEX])
except ex.AerospikeError as e:
    print("Error: {0} [{1}]".format(e.msg, e.code))
    sys.exit(1)

# EXPECTED OUTPUT:
# {'user': 'Chief', 'team': 'blue', 'scores': [6, 12, 4, 21], 'kd': 1.0, 'status':
→'MasterPlatinum'}

# EXAMPLE 2: Get player's records with a kd >= 1.0 with a status including "Gold".
try:
    expr = exp.And(
        exp.CmpRegex(aerospike.REGEX_ICASE, '.*Gold', exp.StrBin('status')),
        exp.GE(exp.FloatBin("kd"), 1.0)).compile()

    policy = {
        'expressions': expr
    }

    records = client.get_many(keys, policy)
    # This get_many will only return the record for "Arbiter" since it is the only
    →account with a kd >= 1.0 and Gold status.
    print(records[SECOND_RECORD_INDEX][BIN_INDEX])
except ex.AerospikeError as e:
    print("Error: {0} [{1}]".format(e.msg, e.code))
    sys.exit(1)
finally:
    client.close()

# EXPECTED OUTPUT:
# {'user': 'Arbiter', 'team': 'blue', 'scores': [5, 10, 5, 8], 'kd': 1.0, 'status':
→'MasterGold'}

```

By nesting expressions, complicated filters can be created. See the example below.

Example:

```

from aerospike_helpers import expressions as exp
expr = Eq(

```

(continues on next page)

(continued from previous page)

```

exp.ListGetByIndexRangeToEnd(ctx, aerospike.LIST_RETURN_VALUE, 0,
    exp.ListSort(ctx, aerospike.LIST_SORT_DEFAULT,
        exp.ListAppend(ctx, policy, value_x,
            exp.ListAppendItems(ctx, policy, value_y,
                exp.ListInsert(ctx, policy, 1, value_z, bin_name)))),
    expected_answer
),

```

Note:

Aerospike expressions are evaluated server side, and do not return any values to the client themselves.

When the following documentation says an expression returns a "list expression", it means that the expression returns a list during evalution on the server side. When these docs say that a parameter requires an "integer or integer expression" It means it will accept a literal integer, or an expression that will return an integer during evaluation. When the docs say an expression returns a "expression" this means that the data type returned may vary, usually depending on the `return_type` parameter.

Current Limitations:

Currently, Aerospike expressions for the python client do not support comparing as python_bytes blobs. Comparrisions between constant map values and map expressions are also unsupported.

The expressions module uses typehints, here are a table of custom typehints mapped to standard types.

Table 1: Title

Type Name	Type Description
TypeResultType	Optional[int]
TypeFixedEle	Union[int, float, str, bytes, dict]
TypeFixed	Optional[Dict[str, TypeFixedEle]]
TypeCompiledOp	Tuple[int, TypeResultType, TypeFixed, int]
TypeExpression	List[TypeCompiledOp]
TypeChild	Union[int, float, str, bytes, _AtomExpr]
TypeChildren	Tuple[TypeChild, ...]
TypeBinName	Union[_BaseExpr, str]
TypeListValue	Union[_BaseExpr, List[Any]]
TypeIndex	Union[_BaseExpr, int, aerospike.CDTInfinite]
TypeCDT	Union[None, List[cdt_ctx._cdt_ctx]]
TypeRank	Union[_BaseExpr, int, aerospike.CDTInfinite]
TypeCount	Union[_BaseExpr, int, aerospike.CDTInfinite]
TypeValue	Union[_BaseExpr, Any]
TypePolicy	Union[Dict[str, Any], None]
TypeComparisonArg	Union[_BaseExpr, int, str, list, dict, aerospike.CDTInfinite]
TypeGeo	Union[_BaseExpr, aerospike.GeoJSON]
TypeKey	Union[_BaseExpr, Any]
TypeKeyList	Union[_BaseExpr, List[Any]]
TypeBitValue	Union[bytes, bytearray]

Note: Requires server version >= 5.2.0

aerospike_helpers.expressions.basemodule

Base expressions include operators, bin, and meta data related expressions.

Example:

```
import aerospike_helpers.expressions.base as exp
# See if integer bin "bin_name" contains a value equal to 10.
expr = exp.Eq(exp.IntBin("bin_name"), 10).compile()
```

class aerospike_helpers.expressions.base.And(*exprs)

Create an “and” operator that applies to a variable amount of expressions.

__init__(*exprs)

Create an “and” operator that applies to a variable amount of expressions.

Parameters *exprs (_BaseExpr) – Variable amount of expressions to be ANDed together.

Returns (boolean value)

Example:

```
# (a > 5 || a == 0) && b < 3
expr = And(
    Or(
        GT(IntBin("a"), 5),
        Eq(IntBin("a"), 0)),
        LT(IntBin("b"), 3)).compile()
```

class aerospike_helpers.expressions.base.BinExists(bin: str)

Create an expression that returns True if bin exists.

__init__(bin: str)

Create an expression that returns True if bin exists.

Parameters bin (str) – bin name.

Return (boolean value) True if bin exists, False otherwise.

Example:

```
#Bin "a" exists in record.
expr = BinExists("a").compile()
```

class aerospike_helpers.expressions.base.BinType(bin: str)

Create an expression that returns the type of a bin as one of the aerospike *bin types*

__init__(bin: str)

Create an expression that returns the type of a bin as one of the aerospike *bin types*.

Parameters bin (str) – bin name.

Return (integer value) returns the bin type.

Example:

```
# bin "a" == type string.
expr = Eq(BinType("a"), aerospike.AS_BYTES_STRING).compile()
```

class aerospike_helpers.expressions.base.**BlobBin**(*bin: str*)

Create an expression that returns a bin as a blob. Returns ‘unknown’ if the bin is not a blob.

__init__(*bin: str*)

Create an expression that returns a bin as a blob. Returns ‘unknown’ if the bin is not a blob.

Parameters **bin** (*str*) – Bin name.

:return (blob bin)

Example:

```
#. Blob bin "a" == bytearray([0x65, 0x65])
expr = Eq(BlobBin("a"), bytearray([0x65, 0x65])).compile()
```

class aerospike_helpers.expressions.base.**CmpGeo**(*expr0: Union[aerospike_helpers.expressions.resources._BaseExpr, <MagicMock id='140171716724048'>], expr1: Union[aerospike_helpers.expressions.resources._BaseExpr, <MagicMock id='140171716724048'>]*)

Create a point within region or region contains point expression.

__init__(*expr0: Union[aerospike_helpers.expressions.resources._BaseExpr, <MagicMock id='140171716724048'>], expr1: Union[aerospike_helpers.expressions.resources._BaseExpr, <MagicMock id='140171716724048'>]*)

Create a point within region or region contains point expression.

Parameters

- **expr0** (*TypeGeo*) – Left expression in comparrison.
- **expr1** (*TypeGeo*) – Right expression in comparrison.

Returns (boolean value)

Example:

```
# Geo bin "point" is within geo bin "region".
expr = CmpGeo(GeoBin("point"), GeoBin("region")).compile()
```

class aerospike_helpers.expressions.base.**CmpRegex**(*options: int, regex_str: str, cmp_str: Union[aerospike_helpers.expressions.resources._BaseExpr, str]*)

Create an expression that performs a regex match on a string bin or value expression.

__init__(*options: int, regex_str: str, cmp_str: Union[aerospike_helpers.expressions.resources._BaseExpr, str]*)

Create an expression that performs a regex match on a string bin or value expression.

Parameters

- **options** (*int*) – One of the aerospike regex constants, *Regex Flag Values*.
- **regex_str** (*str*) – POSIX regex string.
- **cmp_str** (*Union[_BaseExpr, str]*) – String expression to compare against.

Returns (boolean value)

Example:

```
# Select string bin "a" that starts with "prefix" and ends with "suffix".
# Ignore case and do not match newline.
expr = CmpRegex(aerospike.REGEX_ICASE | aerospike.REGEX_NEWLINE, "prefix.
→*suffix", BinStr("a")).compile()
```

class aerospike_helpers.expressions.base.**DeviceSize**

Create an expression that returns record size on disk. If server storage-engine is memory, then zero is returned. This expression usually evaluates quickly because record meta data is cached in memory.

__init__()

Create an expression that returns record size on disk. If server storage-engine is memory, then zero is returned. This expression usually evaluates quickly because record meta data is cached in memory.

Return (integer value) Uncompressed storage size of the record.

Example:

```
# Record device size >= 100 KB.
expr = GE(DeviceSize(), 100 * 1024).compile()
```

class aerospike_helpers.expressions.base.**DigestMod**(mod: int)

Create an expression that returns record digest modulo as integer.

__init__(mod: int)

Create an expression that returns record digest modulo as integer.

Parameters **mod** (*int*) – Divisor used to divide the digest to get a remainder.

Return (integer value) Value in range 0 and mod (exclusive).

Example:

```
# Records that have digest(key) % 3 == 1.
expr = Eq(DigestMod(3), 1).compile()
```

class aerospike_helpers.expressions.base.**Eq**(expr0: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], expr1: Union[aerospike_helpers.expressions.resources._BaseExpr, Any])

Create an equals, (==) expression.

__init__(expr0: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], expr1: Union[aerospike_helpers.expressions.resources._BaseExpr, Any])

Create an equals, (==) expression.

Parameters

- **expr0** (*TypeComparisonArg*) – Left argument to ==.
- **expr1** (*TypeComparisonArg*) – Right argument to ==.

Returns (boolean value)

Example:

```
# Integer bin "a" == 11
expr = Eq(IntBin("a"), 11).compile()
```

class aerospike_helpers.expressions.base.**FloatBin**(bin: str)

Create an expression that returns a bin as a float. Returns ‘unknown’ if the bin is not a float.

`__init__(bin: str)`

Create an expression that returns a bin as a float. Returns ‘unknown’ if the bin is not a float.

Parameters `bin (str)` – Bin name.

Returns (float bin)

Example:

```
# Float bin "a" > 2.71.  
expr = GT(FloatBin("a"), 2.71).compile()
```

class aerospike_helpers.expressions.base.**GE** (`expr0: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], expr1: Union[aerospike_helpers.expressions.resources._BaseExpr, Any]`)

Create a greater than or equal to (\geq) expression.

`__init__(expr0: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], expr1: Union[aerospike_helpers.expressions.resources._BaseExpr, Any])`

Create a greater than or equal to (\geq) expression.

Parameters

- `expr0 (TypeComparisonArg)` – Left argument to \geq .
- `expr1 (TypeComparisonArg)` – Right argument to \geq .

Returns (boolean value)

Example:

```
# Integer bin "a" >= 88.  
expr = GE(IntBin("a"), 88).compile()
```

class aerospike_helpers.expressions.base.**GT** (`expr0: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], expr1: Union[aerospike_helpers.expressions.resources._BaseExpr, Any]`)

Create a greater than ($>$) expression.

`__init__(expr0: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], expr1: Union[aerospike_helpers.expressions.resources._BaseExpr, Any])`

Create a greater than ($>$) expression.

Parameters

- `expr0 (TypeComparisonArg)` – Left argument to $>$.
- `expr1 (TypeComparisonArg)` – Right argument to $>$.

Returns (boolean value)

Example:

```
# Integer bin "a" > 8.  
expr = GT(IntBin("a"), 8).compile()
```

class aerospike_helpers.expressions.base.**GeoBin** (`bin: str`)

Create an expression that returns a bin as a geojson. Returns ‘unknown’ if the bin is not a geojson.

`__init__(bin: str)`

Create an expression that returns a bin as a geojson. Returns ‘unknown’ if the bin is not a geojson.

Parameters `bin (str)` – Bin name.

:return (geojson bin)

Example:

```
#GeoJSON bin "a" contained by GeoJSON bin "b".
expr = CmpGeo(GeoBin("a"), GeoBin("b")).compile()
```

class aerospike_helpers.expressions.base.**HLLBin**(`bin: str`)

Create an expression that returns a bin as a HyperLogLog. Returns ‘unknown’ if the bin is not a HyperLogLog.

__init__(`bin: str`)

Create an expression that returns a bin as a HyperLogLog. Returns ‘unknown’ if the bin is not a HyperLogLog.

Parameters `bin (str)` – Bin name.

:return (HyperLogLog bin)

Example:

```
# Does HLL bin "a" have a hll_count > 1000000.
expr = GT(HllGetCount(HllBin("a")), 1000000).compile()
```

class aerospike_helpers.expressions.base.**IntBin**(`bin: str`)

Create an expression that returns a bin as an integer. Returns ‘unknown’ if the bin is not an integer.

__init__(`bin: str`)

Create an expression that returns a bin as an integer. Returns ‘unknown’ if the bin is not an integer.

Parameters `bin (str)` – Bin name.

Returns (integer bin)

Example:

```
# Integer bin "a" == 200.
expr = Eq(IntBin("a"), 200).compile()
```

class aerospike_helpers.expressions.base.**IsTombstone**

Create an expression that returns if record has been deleted and is still in tombstone state. This expression usually evaluates quickly because record meta data is cached in memory. NOTE: this is only applicable for XDR filter expressions.

__init__()

Create an expression that returns if record has been deleted and is still in tombstone state. This expression usually evaluates quickly because record meta data is cached in memory. NOTE: this is only applicable for XDR filter expressions.

Return (boolean value) True if the record is a tombstone, false otherwise.

Example:

```
# Detect deleted records that are in tombstone state.
expr = IsTombstone().compile()
```

class aerospike_helpers.expressions.base.**KeyBlob**

Create an expression that returns the key as a blob. Returns ‘unknown’ if the key is not a blob.

__init__()

Create an expression that returns the key as a blob. Returns ‘unknown’ if the key is not a blob.

Return (blob value) Blob value of the key if the key is a blob.

Example:

```
# blob record key <= bytearray([0x65, 0x65]).  
expr = GE(KeyBlob(), bytearray([0x65, 0x65])).compile()
```

class aerospike_helpers.expressions.base.KeyExists

Create an expression that returns if the primary key is stored in the record storage data as a boolean expression. This would occur on record write, when write policies set the *key* field to aerospike.POLICY_KEY_SEND.

__init__()

Create an expression that returns if the primary key is stored in the record storage data as a boolean expression. This would occur on record write, when write policies set the *key* field to aerospike.POLICY_KEY_SEND.

Return (boolean value) True if the record has a stored key, false otherwise.

Example:

```
# Key exists in record meta data.  
expr = KeyExists().compile()
```

class aerospike_helpers.expressions.base.KeyInt

Create an expression that returns the key as an integer. Returns ‘unknown’ if the key is not an integer.

__init__()

Create an expression that returns the key as an integer. Returns ‘unknown’ if the key is not an integer.

Return (integer value) Integer value of the key if the key is an integer.

Example:

```
# Integer record key >= 10000.  
expr = GE(KeyInt(), 10000).compile()
```

class aerospike_helpers.expressions.base.KeyStr

Create an expression that returns the key as a string. Returns ‘unknown’ if the key is not a string.

__init__()

Create an expression that returns the key as a string. Returns ‘unknown’ if the key is not a string.

Return (string value) string value of the key if the key is an string.

Example:

```
# string record key == "aaa".  
expr = Eq(KeyStr(), "aaa").compile()
```

**class aerospike_helpers.expressions.base.LE(expr0: Union[aerospike_helpers.expressions.resources._BaseExpr,
Any], expr1: Union[aerospike_helpers.expressions.resources._BaseExpr, Any])**

Create a less than or equal to (\leq) expression.

__init__(expr0: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], expr1: Union[aerospike_helpers.expressions.resources._BaseExpr, Any])

Create a less than or equal to (\leq) expression.

Parameters

- **expr0** (*TypeComparisonArg*) – Left argument to \leq .

- **expr1** (*TypeComparisonArg*) – Right argument to <=.

Returns (boolean value)

Example:

```
# Integer bin "a" <= 1.
expr = LE(IntBin("a"), 1).compile()
```

```
class aerospike_helpers.expressions.base.LT(expr0: Union[aerospike_helpers.expressions.resources._BaseExpr,
                                                       Any],                                              expr1:
                                                       Union[aerospike_helpers.expressions.resources._BaseExpr,
                                                       Any])
```

Create a less than (<) expression.

```
__init__(expr0: Union[aerospike_helpers.expressions.resources._BaseExpr, Any],      expr1:
        Union[aerospike_helpers.expressions.resources._BaseExpr, Any])
```

Create a less than (<) expression.

Parameters

- **expr0** (*TypeComparisonArg*) – Left argument to <.
- **expr1** (*TypeComparisonArg*) – Right argument to <.

Returns (boolean value)

Example:

```
# Integer bin "a" < 1000.
expr = LT(IntBin("a"), 1000).compile()
```

```
class aerospike_helpers.expressions.base.LastUpdateTime
```

Create an expression that returns record last update time expressed as 64 bit integer nanoseconds since 1970-01-01 epoch.

```
__init__()
```

Create an expression that returns record last update time expressed as 64 bit integer nanoseconds since 1970-01-01 epoch.

Return (integer value) When the record was last updated.

Example:

```
# Record last update time >= 2020-01-15.
expr = GE(LastUpdateTime(), 1577836800).compile()
```

```
class aerospike_helpers.expressions.base.ListBin(bin: str)
```

Create an expression that returns a bin as a list. Returns ‘unknown’ if the bin is not a list.

```
__init__(bin: str)
```

Create an expression that returns a bin as a list. Returns ‘unknown’ if the bin is not a list.

Parameters **bin** (*str*) – Bin name.

:return (list bin)

Example:

```
# List bin "a" contains at least one item with value "abc".
expr = GT(ListGetByValue(None, aerospike.LIST_RETURN_COUNT,
                         ResultType.INTEGER, "abc", ListBin("a")),
          0).compile()
```

class aerospike_helpers.expressions.base.**MapBin**(*bin: str*)

Create an expression that returns a bin as a map. Returns ‘unknown’ if the bin is not a map.

__init__(*bin: str*)

Create an expression that returns a bin as a map. Returns ‘unknown’ if the bin is not a map.

Parameters **bin** (*str*) – Bin name.

:return (map bin)

Example:

```
# Map bin "a" size > 7.
expr = GT(MapSize(None, MapBin("a")), 7).compile()
```

class aerospike_helpers.expressions.base.**NE**(*expr0: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], expr1: Union[aerospike_helpers.expressions.resources._BaseExpr, Any]*)

Create a not equals (not ==) expressions.

__init__(*expr0: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], expr1: Union[aerospike_helpers.expressions.resources._BaseExpr, Any]*)

Create a not equals (not ==) expressions.

Parameters

- **expr0** (*TypeComparisonArg*) – Left argument to *not ==*.
- **expr1** (*TypeComparisonArg*) – Right argument to *not ==*.

Returns (boolean value)

Example:

```
# Integer bin "a" not == 13.
expr = NE(IntBin("a"), 13).compile()
```

class aerospike_helpers.expressions.base.**Not**(**exprs*)

Create a “not” (not) operator expression.

__init__(**exprs*)

Create a “not” (not) operator expression.

Parameters ***exprs** (*_BaseExpr*) – Variable amount of expressions to be negated.**Returns** (boolean value)

Example:

```
# not (a == 0 or a == 10)
expr = Not(Or(
    Eq(IntBin("a"), 0),
    Eq(IntBin("a"), 10))).compile()
```

class aerospike_helpers.expressions.base.**Or**(**exprs*)

Create an “or” operator that applies to a variable amount of expressions.

__init__(**exprs*)

Create an “or” operator that applies to a variable amount of expressions.

Parameters ***exprs** (*_BaseExpr*) – Variable amount of expressions to be ORed together.**Returns** (boolean value)

Example:

```
# (a == 0 || b == 0)
expr = Or(
    Eq(IntBin("a"), 0),
    Eq(IntBin("b"), 0)).compile()
```

class aerospike_helpers.expressions.base.SetName

Create an expression that returns record set name string. This expression usually evaluates quickly because record meta data is cached in memory.

__init__()

Create an expression that returns record set name string. This expression usually evaluates quickly because record meta data is cached in memory.

Return (string value) Name of the set this record belongs to.

Example:

```
# Record set name == "myset".
expr = Eq(SetName(), "myset").compile()
```

class aerospike_helpers.expressions.base.SinceUpdateTime

Create an expression that returns milliseconds since the record was last updated. This expression usually evaluates quickly because record meta data is cached in memory.

__init__()

Create an expression that returns milliseconds since the record was last updated. This expression usually evaluates quickly because record meta data is cached in memory.

Return (integer value) Number of milliseconds since last updated.

Example:

```
# Record last updated more than 2 hours ago.
expr = GT(SinceUpdateTime(), 2 * 60 * 1000).compile()
```

class aerospike_helpers.expressions.base.StrBin(bin: str)

Create an expression that returns a bin as a string. Returns ‘unknown’ if the bin is not a string.

__init__(bin: str)

Create an expression that returns a bin as a string. Returns ‘unknown’ if the bin is not a string.

Parameters **bin (str)** – Bin name.

Returns (string bin)

Example:

```
# String bin "a" == "xyz".
expr = Eq(StrBin("a"), "xyz").compile()
```

class aerospike_helpers.expressions.base.TTL

Create an expression that returns record expiration time (time to live) in integer seconds.

__init__()

Create an expression that returns record expiration time (time to live) in integer seconds.

Return (integer value) Number of seconds till the record will expire, returns -1 if the record never expires.

Example:

```
# Record expires in less than 1 hour.  
expr = LT(TTL(), 60 * 60).compile()
```

class aerospike_helpers.expressions.base.VoidTime

Create an expression that returns record expiration time expressed as 64 bit integer nanoseconds since 1970-01-01 epoch.

__init__()

Create an expression that returns record expiration time expressed as 64 bit integer nanoseconds since 1970-01-01 epoch.

Return (integer value) Expiration time in nanoseconds since 1970-01-01.

Example:

```
# Record expires on 2021-01-01.  
expr = And(  
    GE(VoidTime(), 1609459200),  
    LT(VoidTime(), 1609545600)).compile()
```

aerospike_helpers.expressions.list module

List expressions contain list read and modify expressions.

Example:

```
import aerospike_helpers.expressions as exp  
#Take the size of list bin "a".  
expr = exp.ListSize(None, exp.ListBin("a")).compile()
```

```
class aerospike_helpers.expressions.list.ListAppend(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], policy: Optional[Dict[str, Any]], value: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that appends value to end of list.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], policy: Optional[Dict[str, Any]], value: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that appends value to end of list.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **policy** (*TypePolicy*) – Optional dictionary of list write options *list write options*.
- **value** (*TypeValue*) – Value or value expression to append to list.
- **bin** (*TypeBinName*) – List bin or list expression.

Returns List expression.

Example:

```
# Check if length of list bin "a" is > 5 after appending 1 item.
expr = GT(
    ListSize(None, ListAppend(None, None, 3, ListBin("a"))),
    5).compile()
```

```
class aerospike_helpers.expressions.list.ListAppendItems(ctx: Union[None,
    List[aerospike_helpers.cdt_ctx._cdt_ctx]], policy: Optional[Dict[str,
    Any]], value: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], bin:
    Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that appends a list of items to the end of a list.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], policy: Optional[Dict[str,
    Any]], value: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], bin:
    Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that appends a list of items to the end of a list.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **policy** (*TypePolicy*) – Optional dictionary of list write options *list write options*.
- **value** (*TypeValue*) – List or list expression of items to be appended.
- **bin** (*TypeBinName*) – Bin name or list expression.

Returns

List expression.

Example:

```
# Check if length of list bin "a" is > 5 after appending multiple items.
expr = GT(
    ListSize(None, ListAppendItems(None, None, [3, 2], ListBin("a"))),
    5).compile()
```

```
class aerospike_helpers.expressions.list.ListClear(ctx: Union[None,
    List[aerospike_helpers.cdt_ctx._cdt_ctx]], bin:
    Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that removes all items in a list.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], bin:
    Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that removes all items in a list.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **bin** (*TypeBinName*) – List bin or list expression to clear.

Returns

List expression.

Example:

```
# Clear list value of list nested in list bin "a" index 1.
from aerospike_helpers import cdt_ctx
expr = ListClear([cdt_ctx.cdt_ctx_list_index(1)], "a").compile()
```

```
class aerospike_helpers.expressions.list.ListGetByIndex(ctx: Union[None,
    List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int,
    value_type: int, index: Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
    id='140171717163152'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
    str])
```

Create an expression that selects list item identified by index and returns selected data specified by return_type.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int, value_type:
    int, index: Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
    id='140171717163152'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
    str])
```

Create an expression that selects list item identified by index and returns selected data specified by return_type.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [List Return Types](#) values
- **value_type** (*int*) – The value type that will be returned by this expression (ResultType).
- **index** (*TypeIndex*) – Integer or integer expression of index to get element at.
- **bin** (*TypeBinName*) – List bin name or list expression.

Returns

Expression.

Example:

```
# Get the value at index 0 in list bin "a". (assume this value is an integer)
expr = ListGetByIndex(None, aerospike.LIST_RETURN_VALUE, ResultType.INTEGER, _  
→0, ListBin("a")).compile()
```

```
class aerospike_helpers.expressions.list.ListGetByIndexRange(ctx: Union[None,
    List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int,
    value_type: int, index: Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
    id='140171717163152'>], count: Union[aerospike_helpers.expressions.resources._BaseExpr,
    int, <MagicMock id='140171717171792'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
    str])
```

Create an expression that selects “count” list items starting at specified index and returns selected data specified by return_type.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int, index: Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock id='140171717163152'>], count: Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock id='140171717171792'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that selects “count” list items starting at specified index and returns selected data specified by return_type.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [List Return Types](#) values One of the aerospike list return types.
- **index** (*TypeIndex*) – Integer or integer expression of index to start getting elements at.
- **count** (*TypeCount*) – Integer or integer expression for count of elements to get.
- **bin** (*TypeBinName*) – List bin name or list expression.

Returns Expression.

Example:

```
# Get elements at indexes 3, 4, 5, 6 in list bin "a".
expr = ListGetByIndexRange(None, aerospike.LIST_RETURN_VALUE, 3, 4, ListBin("a")).compile()
```

```
class aerospike_helpers.expressions.list.ListGetByIndexRangeToEnd(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int, index: Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock id='140171717163152'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that selects list items starting at specified index to the end of list and returns selected data specified by return_type.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int, index: Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock id='140171717163152'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that selects list items starting at specified index to the end of list and returns selected data specified by return_type.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.

- **return_type** (`int`) – Value specifying what should be returned from the operation. This should be one of the [List Return Types](#) values One of the aerospike list return types.
- **index** (`TypeIndex`) – Integer or integer expression of index to start getting elements at.
- **bin** (`TypeBinName`) – List bin name or list expression.

Returns Expression.

Example:

```
# Get element 5 to end from list bin "a".
expr = ListGetByIndexRangeToEnd(None, aerospike.LIST_RETURN_VALUE, 5,
→ListBin("a")).compile()
```

```
class aerospike_helpers.expressions.list.ListGetByRank(ctx: Union[None,
                                                               List[aerospike_helpers.cdt_ctx._cdt_ctx]],
                                                       return_type: int,
                                                       value_type: int, rank:
                                                       Union[aerospike_helpers.expressions.resources._BaseExpr,
                                                             int, <MagicMock
                                                             id='140171717161232'>],
                                                       bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
                                                                 str])
```

Create an expression that selects list item identified by rank and returns selected data specified by return_type.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int, value_type:
        int, rank: Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
        id='140171717161232'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
                                              str])
```

Create an expression that selects list item identified by rank and returns selected data specified by return_type.

Parameters

- **ctx** (`TypeCDT`) – Optional context path for nested CDT.
- **return_type** (`int`) – Value specifying what should be returned from the operation. This should be one of the [List Return Types](#) values One of the aerospike list return types.
- **value_type** (`int`) – The value type that will be returned by this expression (ResultType).
- **rank** (`TypeRank`) – Rank integer or integer expression of element to get.
- **bin** (`TypeBinName`) – List bin name or list expression.

Returns Expression.

Example:

```
# Get the smallest element in list bin "a".
expr = ListGetByRank(None, aerospike.LIST_RETURN_VALUE, aerospike.ResultType.
→INTEGER, 0, ListBin("a")).compile()
```

```
class aerospike_helpers.expressions.list.ListGetByRankRange (ctx: Union[None,
    List[aerospike_helpers.cdt_ctx._cdt_ctx]],
    return_type:
        int, rank:
        Union[aerospike_helpers.expressions.resources._BaseExpr,
            int, <MagicMock
                id='140171717161232'>],
    count:
        Union[aerospike_helpers.expressions.resources._BaseExpr,
            int, <MagicMock
                id='140171717171792'>],
    bin:
        Union[aerospike_helpers.expressions.resources._BaseExpr,
            str])
```

Create an expression that selects “count” list items starting at specified rank and returns selected data specified by return_type.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int,
        rank: Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
            id='140171717161232'>], count: Union[aerospike_helpers.expressions.resources._BaseExpr,
            int, <MagicMock id='140171717171792'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
            str])
```

Create an expression that selects “count” list items starting at specified rank and returns selected data specified by return_type.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [List Return Types](#) values One of the aerospike list return types.
- **rank** (*TypeRank*) – Rank integer or integer expression of first element to get.
- **count** (*TypeCount*) – Count integer or integer expression for how many elements to get.
- **bin** (*TypeBinName*) – List bin name or list expression.

Returns

Expression.

Example:

```
# Get the 3 smallest elements in list bin "a".
expr = ListGetByRankRange(None, aerospike.LIST_RETURN_VALUE, 0, 3, ListBin("a
    ↴")) .compile()
```

```
class aerospike_helpers.expressions.list.ListGetByRankRangeToEnd (ctx:
    Union[None,
        List[aerospike_helpers.cdt_ctx._cdt_ctx]],
    return_type:
        int, rank:
        Union[aerospike_helpers.expressions.resources._BaseExpr,
            int, <MagicMock
                id='140171717161232'>],
    bin:
        Union[aerospike_helpers.expressions.resources._BaseExpr,
            str])
```

Create an expression that selects list items starting at specified rank to the last ranked item and returns selected data specified by return_type.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int,
        rank: Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
                    id='140171717161232'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
                    str])
```

Create an expression that selects list items starting at specified rank to the last ranked item and returns selected data specified by return_type.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [List Return Types](#) values One of the aerospike list return types.
- **rank** (*TypeRank*) – Rank integer or integer expression of first element to get.
- **bin** (*TypeBinName*) – List bin name or list expression.

Returns

Expression.

Example:

```
# Get the three largest elements in list bin "a".
expr = ListGetByRankRangeToEnd(None, aerospike.LIST_RETURN_VALUE, -3, ↴
    ListBin("a")).compile()
```

```
class aerospike_helpers.expressions.list.ListGetByValue(ctx: Union[None,
                                                                List[aerospike_helpers.cdt_ctx._cdt_ctx]],
                                                       return_type: int, value:
                                                       Union[aerospike_helpers.expressions.resources._BaseExpr,
                                                             Any], bin:
                                                       Union[aerospike_helpers.expressions.resources._BaseExpr,
                                                             str])
```

Create an expression that selects list items identified by value and returns selected data specified by return_type.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int,
        value: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], bin:
        Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that selects list items identified by value and returns selected data specified by return_type.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [List Return Types](#) values One of the aerospike list return types.
- **value** (*TypeValue*) – Value or value expression of element to get.
- **bin** (*TypeBinName*) – List bin name or list expression.

Returns

Expression.

Example:

```
# Get the index of the element with value, 3, in list bin "a".
expr = ListGetByValue(None, aerospike.LIST_RETURN_INDEX, 3, ListBin("a")) .
    →compile()
```

```
class aerospike_helpers.expressions.list.ListGetByValueList (ctx: Union[None,
    List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int,
    value: Union[aerospike_helpers.expressions.resources._BaseExpr, List[Any]], bin:
    Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that selects list items identified by values and returns selected data specified by return_type.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int,
        value: Union[aerospike_helpers.expressions.resources._BaseExpr, List[Any]], bin:
        Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that selects list items identified by values and returns selected data specified by return_type.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [List Return Types](#) values Value specifying what should be returned from the operation. This should be one of the [List Return Types](#) values One of the aerospike list return types.
- **value** (*TypeListValue*) – List or list expression of values of elements to get.
- **bin** (*TypeBinName*) – List bin name or list expression.

Returns

Expression.

Example:

```
#Get the indexes of the the elements in list bin "a" with values [3, 6, 12].
expr = ListGetByValueList(None, aerospike.LIST_RETURN_INDEX, [3, 6, 12],_
    →ListBin("a")).compile()
```

```
class aerospike_helpers.expressions.list.ListGetByValueRange (ctx: Union[None,
    List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int,
    value_begin: Union[aerospike_helpers.expressions.resources._BaseExpr, Any],
    value_end: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], bin:
    Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that selects list items identified by value range and returns selected data specified by return_type.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int,
        value_begin: Union[aerospike_helpers.expressions.resources._BaseExpr, Any],
        value_end: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], bin:
        Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that selects list items identified by value range and returns selected data specified by return_type.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [List Return Types](#) values One of the aerospike list return types.
- **value_begin** (*TypeValue*) – Value or value expression of first element to get.
- **value_end** (*TypeValue*) – Value or value expression of ending element.
- **bin** (*TypeBinName*) – List bin name or list expression.

Returns

Expression.

Example:

```
# Get rank of values between 3 (inclusive) and 7 (exclusive) in list bin "a".
expr = ListGetByValueRange(None, aerospike.LIST_RETURN_RANK, 3, 7, ListBin("a
→")).compile()
```

```
class aerospike_helpers.expressions.list.ListGetByValueRelRankRange (ctx:
    Union[None,
    List[aerospike_helpers.cdt_ctx._cdt_ctx]],
    return_type: int,
    turn_type: int,
    value: Union[aerospike_helpers.expressions.Any],
    rank: int,
    <MagicMock id='140171717161232'>,
    count: int,
    <MagicMock id='140171717171792'>,
    bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
    str])
```

Create an expression that selects list items nearest to value and greater by relative rank with a count limit and returns selected data specified by return_type.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int,
        value: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], rank:
        Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
        id='140171717161232'>], count: Union[aerospike_helpers.expressions.resources._BaseExpr,
        int, <MagicMock id='140171717171792'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
        str])
```

Create an expression that selects list items nearest to value and greater by relative rank with a count limit

and returns selected data specified by return_type.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [List Return Types](#) values One of the aerospike list return types.
- **value** (*TypeValue*) – Value or vaule expression to get items relative to.
- **rank** (*TypeRank*) – Rank intger expression. rank relative to “value” to start getting elements.
- **count** (*TypeCount*) – Integer value or integer value expression, how many elements to get.
- **bin** (*TypeBinName*) – List bin name or list expression.

Returns

Expression.

Example:

```
# Get the next 2 values in list bin "a" larger than 3.
expr = ListGetByValueRelRankRange(None, aerospike.LIST_RETURN_VALUE, 3, 1, 2,
→ ListBin("a")).compile()
```

```
class aerospike_helpers.expressions.list.ListGetByValueRelRankRangeToEnd(ctx:
    Union[None,
          List[aerospike_helpers.cdt_ctx._cdt_ctx]],
    return_type: int,
    value: Union[aerospike_helpers.expressions.resources._BaseExpr, Any],
    rank: Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
id='140171717161232'>],
    bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
str])
```

Create an expression that selects list items nearest to value and greater by relative rank

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int,
        value: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], rank:
        Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
id='140171717161232'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
str])
```

Create an expression that selects list items nearest to value and greater by relative rank and returns selected data specified by return_type.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.

- **return_type** (`int`) – Value specifying what should be returned from the operation. This should be one of the [List Return Types](#) values One of the aerospike list return types.
- **value** (`TypeValue`) – Value or value expression to get items relative to.
- **rank** (`TypeRank`) – Rank integer expression. rank relative to “value” to start getting elements.
- **bin** (`TypeBinName`) – List bin name or list expression.

Returns Expression.

Example:

```
# Get the values of all elements in list bin "a" larger than 3.
expr = ListGetByValueRelRankRangeToEnd(None, aerospike.LIST_RETURN_VALUE, 3, -1, ListBin("a")).compile()
```

```
class aerospike_helpers.expressions.list.ListIncrement(ctx: Union[None,
    List[aerospike_helpers.cdt_ctx._cdt_ctx]], policy: Optional[Dict[str,
    Any]], index: Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
    id='140171717163152'>], value: Union[aerospike_helpers.expressions.resources._BaseExpr,
    Any], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that increments list[index] by value.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], policy: Optional[Dict[str,
    Any]], index: Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
    id='140171717163152'>], value: Union[aerospike_helpers.expressions.resources._BaseExpr,
    Any], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that increments list[index] by value.

Parameters

- **ctx** (`TypeCDT`) – Optional context path for nested CDT.
- **policy** (`TypePolicy`) – Optional dictionary of list write options [list write options](#).Optional list write policy.
- **index** (`TypeIndex`) – Index of value to increment.
- **value** (`TypeValue`) – Value or value expression.
- **bin** (`TypeBinName`) – Bin name or list expression.

Returns List expression.

Example:

```
# Check if incremented value in list bin "a" is the largest in the list.
expr = Eq(
    ListGetByRank(None, aerospike.LIST_RETURN_VALUE, ResultType.INTEGER, -1, #rank of -1 == largest element.
    ListIncrement(None, None, 1, 5, ListBin("a"))),
    ListGetByIndex(None, aerospike.LIST_RETURN_VALUE, ResultType.INTEGER,
    1,
```

(continues on next page)

(continued from previous page)

```
ListIncrement(None, None, 1, 5, ListBin("a")))
).compile()
```

```
class aerospike_helpers.expressions.list.ListInsert(ctx: Union[None,
    List[aerospike_helpers.cdt_ctx._cdt_ctx]], policy: Optional[Dict[str,
    Any]], index: Union[aerospike_helpers.expressions.resources._BaseExpr,
    int, <MagicMock id='140171717163152'>], value: Union[aerospike_helpers.expressions.resources._BaseExpr,
    Any], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that inserts value to specified index of list.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], policy: Optional[Dict[str,
    Any]], index: Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
    id='140171717163152'>], value: Union[aerospike_helpers.expressions.resources._BaseExpr,
    Any], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that inserts value to specified index of list.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **policy** (*TypePolicy*) – Optional dictionary of list write options *list write options*.
- **index** (*TypeIndex*) – Target index for insertion, integer or integer expression.
- **value** (*TypeValue*) – Value or value expression to be inserted.
- **bin** (*TypeBinName*) – Bin name or list expression.

Returns

List expression.

Example:

```
# Check if list bin "a" has length > 5 after insert.
expr = GT(
    ListSize(None, ListInsert(None, None, 0, 3, ListBin("a"))),
    5).compile()
```

```
class aerospike_helpers.expressions.list.ListInsertItems(ctx: Union[None,
    List[aerospike_helpers.cdt_ctx._cdt_ctx]], policy: Optional[Dict[str,
    Any]], index: Union[aerospike_helpers.expressions.resources._BaseExpr,
    int, <MagicMock id='140171717163152'>], values: Union[aerospike_helpers.expressions.resources._BaseExpr,
    List[Any]], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that inserts each input list item starting at specified index of list.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], policy: Optional[Dict[str, Any]], index: Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock id='140171717163152'>], values: Union[aerospike_helpers.expressions.resources._BaseExpr, List[Any]], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that inserts each input list item starting at specified index of list.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **policy** (*TypePolicy*) – Optional dictionary of list write options *list write options*.Optional list write policy.
- **index** (*TypeIndex*) – Target index where item insertion will begin, integer or integer expression.
- **values** (*TypeListValue*) – List or list expression of items to be inserted.
- **bin** (*TypeBinName*) – Bin name or list expression.

Returns List expression.

Example:

```
# Check if list bin "a" has length > 5 after inserting items.
expr = GT(
    ListSize(None, ListInsertItems(None, None, 0, [4, 7], ListBin("a"))),
    5).compile()
```

```
class aerospike_helpers.expressions.list.ListRemoveByIndex(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], index: Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock id='140171717163152'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that removes “count” list items starting at specified index.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], index: Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock id='140171717163152'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that removes “count” list items starting at specified index.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **index** (*TypeIndex*) – Index integer or integer expression of element to remove.
- **bin** (*TypeBinName*) – List bin name or list expression.

Returns list expression.

Example:

```
# Get size of list bin "a" after index 3 has been removed.
expr = ListSize(None, ListRemoveByIndex(None, 3, ListBin("a"))).compile()
```

```
class aerospike_helpers.expressions.list.ListRemoveByIndexRange (ctx:  
    Union[None,  
    List[aerospike_helpers.cdt_ctx._cdt_ctx]  
index:  
    Union[aerospike_helpers.expressions.resources._BaseExpr,  
int, <MagicMock  
id='140171717163152'>],  
count:  
    Union[aerospike_helpers.expressions.resources._BaseExpr,  
int, <MagicMock  
id='140171717171792'>],  
bin:  
    Union[aerospike_helpers.expressions.resources._BaseExpr,  
str])
```

Create an expression that removes “count” list items starting at specified index.

```
__init__ (ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], index:  
    Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock  
id='140171717163152'>], count: Union[aerospike_helpers.expressions.resources._BaseExpr,  
int, <MagicMock id='140171717171792'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,  
str])
```

Create an expression that removes “count” list items starting at specified index.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **index** (*TypeIndex*) – Starting index integer or integer expression of elements to remove.
- **count** (*TypeCount*) – Integer or integer expression, how many elements to remove.
- **bin** (*TypeBinName*) – List bin name or list expression.

Returns

list expression.

Example:

```
# Get size of list bin "a" after index 3, 4, and 5 have been removed.  
expr = ListSize(None, ListRemoveByIndexRange(None, 3, 3, ListBin("a"))).  
→compile()
```

```
class aerospike_helpers.expressions.list.ListRemoveByIndexRangeToEnd (ctx:  
    Union[None,  
    List[aerospike_helpers.cdt_ctx._cdt_ctx]  
index:  
    Union[aerospike_helpers.expressions.resources._BaseExpr,  
int, <MagicMock  
id='140171717163152'>],  
bin:  
    Union[aerospike_helpers.expressions.resources._BaseExpr,  
str])
```

Create an expression that removes list items starting at specified index to the end of list.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], index:
         Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
               id='140171717163152'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
               str])
```

Create an expression that removes list items starting at specified index to the end of list.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **index** (*TypeIndex*) – Starting index integer or integer expression of elements to remove.
- **bin** (*TypeBinName*) – List bin name or list expression.

Returns list expression.

Example:

```
# Remove all elements starting from index 3 in list bin "a".
expr = ListRemoveByIndexRangeToEnd(None, 3, ListBin("a")).compile()
```

```
class aerospike_helpers.expressions.list.ListRemoveByRank(ctx: Union[None,
         List[aerospike_helpers.cdt_ctx._cdt_ctx]], rank:
         Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
               id='140171717161232'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
               str])
```

Create an expression that removes list item identified by rank.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], rank:
         Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
               id='140171717161232'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
               str])
```

Create an expression that removes list item identified by rank.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **rank** (*TypeRank*) – Rank integer or integer expression of element to remove.
- **bin** (*TypeBinName*) – List bin name or list expression.

Returns list expression.

Example:

```
# Remove smallest value in list bin "a".
expr = ListRemoveByRank(None, 0, ListBin("a")).compile()
```

```
class aerospike_helpers.expressions.list.ListRemoveByRankRange (ctx:  
    Union[None,  
          List[aerospike_helpers.cdt_ctx._cdt_ctx].  
rank:  
    Union[aerospike_helpers.expressions.resources._BaseExpr,  
          int, <MagicMock  
          id='140171717161232'>],  
count:  
    Union[aerospike_helpers.expressions.resources._BaseExpr,  
          int, <MagicMock  
          id='140171717171792'>],  
bin:  
    Union[aerospike_helpers.expressions.resources._BaseExpr,  
          str])
```

Create an expression that removes “count” list items starting at specified rank.

```
__init__ (ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], rank:  
    Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock  
    id='140171717161232'>], count: Union[aerospike_helpers.expressions.resources._BaseExpr,  
    int, <MagicMock id='140171717171792'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,  
    str])
```

Create an expression that removes “count” list items starting at specified rank.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **rank** (*TypeRank*) – Rank integer or integer expression of element to start removing at.
- **count** (*TypeCount*) – Count integer or integer expression of elements to remove.
- **bin** (*TypeBinName*) – List bin name or list expression.

Returns list expression.

Example:

```
# Remove the 3 smallest items from list bin "a".  
expr = ListRemoveByRankRange(None, 0, 3, ListBin("a")).compile()
```

```
class aerospike_helpers.expressions.list.ListRemoveByRankRangeToEnd (ctx:  
    Union[None,  
          List[aerospike_helpers.cdt_ctx._cdt_ctx].  
rank:  
    Union[aerospike_helpers.expressions.resources._BaseExpr,  
          int, <MagicMock  
          id='140171717161232'>],  
bin:  
    Union[aerospike_helpers.expressions.resources._BaseExpr,  
          str])
```

Create an expression that removes list items starting at specified rank to the last ranked item.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], rank:
        Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
              id='140171717161232'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
              str])
```

Create an expression that removes list items starting at specified rank to the last ranked item.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **rank** (*TypeRank*) – Rank integer or integer expression of element to start removing at.
- **bin** (*TypeBinName*) – List bin name or list expression.

Returns list expression.

Example:

```
# Remove the 2 largest elements from List bin "a".
expr = ListRemoveByRankRangeToEnd(None, -2, ListBin("a")).compile()
```

```
class aerospike_helpers.expressions.list.ListRemoveByValue(ctx: Union[None,
                                                                List[aerospike_helpers.cdt_ctx._cdt_ctx]],
                                                       value:
                                                       Union[aerospike_helpers.expressions.resources._BaseExpr,
                                                             Any], bin:
                                                       Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that removes list items identified by value.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], value:
        Union[aerospike_helpers.expressions.resources._BaseExpr, Any], bin:
        Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that removes list items identified by value.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **value** (*TypeValue*) – Value or value expression to remove.
- **bin** (*TypeBinName*) – bin name or bin expression.

Returns list expression.

Example:

```
# See if list bin "a", with `3` removed, is equal to list bin "b".
expr = Eq(ListRemoveByValue(None, 3, ListBin("a")), ListBin("b")).compile()
```

```
class aerospike_helpers.expressions.list.ListRemoveByValueList(ctx:
                                                               Union[None,
                                                                     List[aerospike_helpers.cdt_ctx._cdt_ctx]],
                                                               values:
                                                               Union[aerospike_helpers.expressions.resources._BaseExpr,
                                                                     List[Any]], bin:
                                                               Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that removes list items identified by values.

__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], values: Union[aerospike_helpers.expressions.resources._BaseExpr, List[Any]], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
Create an expression that removes list items identified by values.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **values** (*TypeListValue*) – List of values or list expression.
- **bin** (*TypeBinName*) – List bin name or list expression.

Returns list expression.

Example:

```
# Remove elements with values [1, 2, 3] from list bin "a".
expr = ListRemoveByValueList(None, [1, 2, 3], ListBin("a")).compile()
```

class aerospike_helpers.expressions.list.ListRemoveByValueRange(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], begin: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], end: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
Create an expression that removes list items identified by value range (begin inclusive, end exclusive). If begin is None, the range is less than end. If end is None, the range is greater than or equal to begin.

__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], begin: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], end: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
Create an expression that removes list items identified by value range (begin inclusive, end exclusive). If begin is None, the range is less than end. If end is None, the range is greater than or equal to begin.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **begin** (*TypeValue*) – Begin value or value expression for range.
- **end** (*TypeValue*) – End value or value expression for range.
- **bin** (*TypeBinName*) – List bin name or list expression.

Returns list expression.

Example:

```
# Remove list of items with values >= 3 and < 7 from list bin "a".
expr = ListRemoveByValueRange(None, 3, 7, ListBin("a")).compile()
```

```
class aerospike_helpers.expressions.list.ListRemoveByValueRelRankRange(ctx:
    Union[None,
    List[aerospike_helpers.cdt_cxt.ctx._cdt_cxt]],
    value:
    Union[aerospike_helpers.expressions.Any],
    rank:
    Union[aerospike_helpers.expressions.int,
    <MagicMock
    id='140171717161232'>],
    count:
    Union[aerospike_helpers.expressions.int,
    <MagicMock
    id='140171717171792'>],
    bin:
    Union[aerospike_helpers.expressions.str])
)

```

Create an expression that removes list items nearest to value and greater by relative rank with a count limit.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_cxt.ctx._cdt_cxt]], value:
    Union[aerospike_helpers.expressions.resources._BaseExpr, Any], rank:
    Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
    id='140171717161232'>], count: Union[aerospike_helpers.expressions.resources._BaseExpr,
    int, <MagicMock id='140171717171792'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
    str])

```

Create an expression that removes list items nearest to value and greater by relative rank with a count limit.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **value** (*TypeValue*) – Start value or value expression.
- **rank** (*TypeRank*) – Rank integer or integer expression.
- **count** (*TypeCount*) – How many elements to remove.
- **bin** (*TypeBinName*) – List bin name or list expression.

Returns list expression.

Example:

```
# After removing the 3 elements larger than 4 by relative rank, does list_
→bin "a" include 9?.
expr = GT(
    ListGetByValue(None, aerospike.LIST_RETURN_COUNT, 9,
        ListRemoveByValueRelRankRange(None, 4, 1, 0, ListBin("a"))),
    0).compile()

```

```
class aerospike_helpers.expressions.list.ListRemoveByValueRelRankToEnd(ctx:
    Union[None,
    List[aerospike_helpers.cdt_cxt._cdt_cxt]],
    value:
    Union[aerospike_helpers.expressions.Any],
    rank:
    Union[aerospike_helpers.expressions.int],
    <MagicMock
    id='140171717161232'>],
    bin:
    Union[aerospike_helpers.expressions.str])
```

Create an expression that removes list items nearest to value and greater by relative rank.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_cxt._cdt_cxt]], value:
    Union[aerospike_helpers.expressions.resources._BaseExpr], rank:
    Union[aerospike_helpers.expressions.resources._BaseExpr], int, <MagicMock
    id='140171717161232'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
    str])
```

Create an expression that removes list items nearest to value and greater by relative rank.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **value** (*TypeValue*) – Start value or value expression.
- **rank** (*TypeRank*) – Rank integer or integer expression.
- **bin** (*TypeBinName*) – List bin name or list expression.

Returns

list expression.

Example:

```
# Remove elements larger than 4 by relative rank in list bin "a".
expr = ListRemoveByValueRelRankToEnd(None, 4, 1, ListBin("a")).compile()
```

```
class aerospike_helpers.expressions.list.ListSet(ctx: Union[None,
    List[aerospike_helpers.cdt_cxt._cdt_cxt]],
    policy: Optional[Dict[str,
    Any]], index:
    Union[aerospike_helpers.expressions.resources._BaseExpr],
    int, <MagicMock
    id='140171717163152'>], value:
    Union[aerospike_helpers.expressions.resources._BaseExpr],
    Any], bin:
    Union[aerospike_helpers.expressions.resources._BaseExpr,
    str])
```

Create an expression that sets item value at specified index in list.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_cxt._cdt_cxt]], policy: Optional[Dict[str,
    Any]], index: Union[aerospike_helpers.expressions.resources._BaseExpr], int, <MagicMock
    id='140171717163152'>], value: Union[aerospike_helpers.expressions.resources._BaseExpr],
    Any], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that sets item value at specified index in list.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **policy** (*TypePolicy*) – Optional dictionary of list write options *list write options*. Optional list write policy.
- **index** (*TypeIndex*) – index of value to set.
- **value** (*TypeValue*) – value or value expression to set index in list to.
- **bin** (*TypeBinName*) – bin name or list expression.

Returns List expression.

Example:

```
# Get smallest element in list bin "a" after setting index 1 to 10.
expr = ListGetByRank(None, aerospike.LIST_RETURN_VALUE, ResultType.INTEGER,
    ↪ 0,
    ListSet(None, None, 1, 10, ListBin("a"))).compile()
```

```
class aerospike_helpers.expressions.list.ListSize(ctx: Union[None,
    List[aerospike_helpers.cdt_ctx._cdt_ctx]], bin:
    Union[aerospike_helpers.expressions.resources._BaseExpr,
    str])
```

Create an expression that returns list size.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], bin:
    Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that returns list size.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **bin** (*TypeBinName*) – List bin name or list expression.

Returns Integer expression.

Example:

```
#Take the size of list bin "a".
expr = ListSize(None, ListBin("a")).compile()
```

```
class aerospike_helpers.expressions.list.ListSort(ctx: Union[None,
    List[aerospike_helpers.cdt_ctx._cdt_ctx]], order: int, bin:
    Union[aerospike_helpers.expressions.resources._BaseExpr,
    str])
```

Create an expression that sorts a list.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], order: int, bin:
    Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that sorts a list.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **order** (*int*) – Optional flags modifying the behavior of list_sort. This should be constructed by bitwise or'ing together values from *List Sort Flags*.
- **bin** (*TypeBinName*) – List bin name or list expression.

Returns list expression.

Example:

```
# Get value of sorted list bin "a".
expr = ListSort(None, aerospike.LIST_SORT_DEFAULT, "a").compile()
```

aerospike_helpers.expressions.map module

Map expressions contain map read and modify expressions.

Example:

```
import aerospike_helpers.expressions as exp
#Take the size of map bin "b".
expr = exp.MapSize(None, exp.MapBin("b")).compile()
```

```
class aerospike_helpers.expressions.map.MapClear(ctx: Union[None,
    List[aerospike_helpers.cdt_ctx._cdt_ctx]], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that removes all items in map.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], bin:
    Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that removes all items in map.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **bin** (*TypeBinName*) – Map bin or map expression.

Returns Map expression.

Example:

```
# Clear map bin "b".
expr = MapClear(None, MapBin("b")).compile()
```

```
class aerospike_helpers.expressions.map.MapGetByIndex(ctx: Union[None,
    List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int,
    value_type: int, index: Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
    id='140171716602192'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
    str])
```

Create an expression that selects map item identified by index and returns selected data specified by return_type.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int, value_type:
    int, index: Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
    id='140171716602192'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
    str])
```

Create an expression that selects map item identified by index and returns selected data specified by return_type.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [Map Return Types](#) values One of the aerospike map return types.
- **value_type** (*int*) – The value type that will be returned by this expression (ResultType).
- **index** (*TypeIndex*) – Integer or integer expression of index to get element at.
- **bin** (*TypeBinName*) – Map bin name or map expression.

Returns Expression.

Example:

```
# Get the value at index 0 in map bin "b". (assume this value is an integer)
expr = MapGetByIndex(None, aerospike.MAP_RETURN_VALUE, ResultType.INTEGER, 0,
    → MapBin("b")).compile()
```

```
class aerospike_helpers.expressions.map.MapGetByIndexRange(ctx: Union[None,
    List[aerospike_helpers.cdt_ctx.cdt_ctx]], return_type:
    int, index:
    Union[aerospike_helpers.expressions.resource.
    int, <MagicMock id='140171716602192'>], count:
    Union[aerospike_helpers.expressions.resource.
    int, <MagicMock id='140171716969616'>], bin:
    Union[aerospike_helpers.expressions.resource.
    str])
```

Create an expression that selects “count” map items starting at specified index.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx.cdt_ctx]], return_type: int, index:
    Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock id='140171716602192'>], count: Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock id='140171716969616'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that selects “count” map items starting at specified index and returns selected data specified by return_type.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [Map Return Types](#) values One of the aerospike map return types.
- **index** (*TypeIndex*) – Integer or integer expression of index to start getting elements at.
- **count** (*TypeCount*) – Integer or integer expression for count of elements to get.
- **bin** (*TypeBinName*) – Map bin name or map expression.

Returns Expression.

Example:

```
# Get elements at indexes 3, 4, 5, 6 in map bin "b".
expr = MapGetByIndexRange(None, aerospike.MAP_RETURN_VALUE, 3, 4, MapBin("b
→")).compile()
```

```
class aerospike_helpers.expressions.map.MapGetByIndexRangeToEnd(ctx:
    Union[None,
          List[aerospike_helpers.cdt_ctx._cdt_ctx]],
    return_type:
        int,
        index:
            Union[aerospike_helpers.expressions.resources._BaseExpr,
                  int,
                  <MagicMock
id='140171716602192'>],
    bin:
        Union[aerospike_helpers.expressions.resources._BaseExpr,
              str])
```

Create an expression that selects map items starting at specified index to the end of map.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int, in-
dex: Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
id='140171716602192'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
str])
```

Create an expression that selects map items starting at specified index to the end of map and returns selected data specified by return_type.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the *Map Return Types* values One of the aerospike map return types.
- **index** (*TypeIndex*) – Integer or integer expression of index to start getting elements at.
- **bin** (*TypeBinName*) – Map bin name or map expression.

Returns Expression.

Example:

```
# Get element at index 5 to end from map bin "b".
expr = MapGetByIndexRangeToEnd(None, aerospike.MAP_RETURN_VALUE, 5, MapBin("b
→")).compile()
```

```
class aerospike_helpers.expressions.map.MapGetByKey(ctx:
    Union[None,
          List[aerospike_helpers.cdt_ctx._cdt_ctx]],
    return_type:
        int,
        value_type:
            int,
            key:
                Union[aerospike_helpers.expressions.resources._BaseExpr,
                      Any],
                bin:
                    Union[aerospike_helpers.expressions.resources._BaseExpr,
                          str])
```

Create an expression that selects map item identified by key and returns selected data specified by return_type.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int, value_type:
        int, key: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], bin:
        Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that selects map item identified by key and returns selected data specified by return_type.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the *Map Return Types* values One of the aerospike map return types.
- **value_type** (*int*) – The value type that will be returned by this expression (ResultType).
- **key** (*TypeKey*) – Key value or value expression of element to get.
- **bin** (*TypeBinName*) – Map bin name or map expression.

Returns

Expression.

Example:

```
# Get the value at key "key0" in map bin "b". (assume the value at key0 is
# an integer)
expr = MapGetByKey(None, aerospike.MAP_RETURN_VALUE, ResultType.INTEGER,
                   "key0", MapBin("b")).compile()
```

```
class aerospike_helpers.expressions.map.MapGetByKeyList(ctx: Union[None,
                                                                List[aerospike_helpers.cdt_ctx._cdt_ctx]],
                                                       return_type: int, keys:
                                                       Union[aerospike_helpers.expressions.resources._BaseExpr,
                                                             List[Any]], bin:
                                                       Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that selects map items identified by keys and returns selected data specified by return_type.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int,
        keys: Union[aerospike_helpers.expressions.resources._BaseExpr, List[Any]], bin:
        Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that selects map items identified by keys and returns selected data specified by return_type.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the *Map Return Types* values One of the aerospike map return types.
- **keys** (*TypeKeyList*) – List of key values or list expression.
- **bin** (*TypeBinName*) – Map bin name or map expression.

Returns

Expression.

Example:

```
# Get elements at keys "key3", "key4", "key5" in map bin "b".
expr = MapGetByKeyList(None, aerospike.MAP_RETURN_VALUE, ["key3", "key4",
→"key5"], MapBin("b")).compile()
```

```
class aerospike_helpers.expressions.map.MapGetByKeyRange(ctx: Union[None,
    List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int, begin:
    Union[aerospike_helpers.expressions.resources._BaseExpr, Any],
    end: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], bin:
    Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that selects map items identified by key range.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type:
    int, begin: Union[aerospike_helpers.expressions.resources._BaseExpr, Any],
    end: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], bin:
    Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that selects map items identified by key range (begin inclusive, end exclusive). If begin is nil, the range is less than end. If end is aerospike.CDTInfinite(), the range is greater than equal to begin. Expression returns selected data specified by return_type.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the *Map Return Types* values One of the aerospike map return types.
- **begin** (*TypeKey*) – Key value or expression.
- **end** (*TypeKey*) – Key value or expression.
- **bin** (*TypeBinName*) – Map bin name or map expression.

Returns

Expression.

Example:

```
# Get elements at keys "key3", "key4", "key5", "key6" in map bin "b".
expr = MapGetByKeyRange(None, aerospike.MAP_RETURN_VALUE, "key3", "key7",
→MapBin("b")).compile()
```

```
class aerospike_helpers.expressions.map.MapGetByKeyRelIndexRange (ctx:
    Union[None,
    List[aerospike_helpers.cdt_ctx._cdt_c
    return_type:
    int,      key:
    Union[aerospike_helpers.expressions.
    Any],   index:
    Union[aerospike_helpers.expressions.
    int,      <Mag-
    icMock
    id='140171716602192'>],
    count:
    Union[aerospike_helpers.expressions.
    int,      <Mag-
    icMock
    id='140171716969616'>],
    bin:
    Union[aerospike_helpers.expressions.
    str])
```

Create an expression that selects map items nearest to key and greater by index with a count limit.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_c
key: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], index:
Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
id='140171716602192'>], count: Union[aerospike_helpers.expressions.resources._BaseExpr,
int, <MagicMock id='140171716969616'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
str])
```

Create an expression that selects map items nearest to key and greater by index with a count limit. Expression returns selected data specified by return_type.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the *Map Return Types* values One of the aerospike map return types.
- **key** (*TypeKey*) – Key value or value expression.
- **index** (*TypeIndex*) – Index integer or integer value expression.
- **count** (*TypeCount*) – Integer count or integer value expression.
- **bin** (*TypeBinName*) – Map bin name or map expression.

Returns

Expression.

Example:

```
# Get the next 2 elements with keys larger than "key3" from map bin "b".
expr = MapGetByKeyRelIndexRange(None, aerospike.MAP_RETURN_VALUE, "key3", 1, ↵
                                2, MapBin("b")).compile()
```

```
class aerospike_helpers.expressions.map.MapGetByKeyRelIndexRangeToEnd(ctx:
    Union[None,
          List[aerospike_helpers.cdt_ctx._cdt_ctx]],
    return_type: int,
    key: Union[aerospike_helpers.expressions.Any],
    index: Union[aerospike_helpers.expressions._BaseExpr, Any],
    <MagicMock id='140171716602192'>,
    bin: Union[aerospike_helpers.expressions._BaseExpr, str])
```

Create an expression that selects map items nearest to key and greater by index with a count limit.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int,
        key: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], index:
        Union[aerospike_helpers.expressions.resources._BaseExpr, int], <MagicMock
        id='140171716602192'>, bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
        str])
```

Create an expression that selects map items nearest to key and greater by index with a count limit. Expression returns selected data specified by return_type.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [Map Return Types](#) values One of the aerospike map return types.
- **key** (*TypeKey*) – Key value or value expression.
- **index** (*TypeIndex*) – Index integer or integer value expression.
- **bin** (*TypeBinName*) – Map bin name or map expression.

Returns

Expression.

Example:

```
# Get elements with keys larger than "key2" from map bin "b".
expr = MapGetByKeyRelIndexRangeToEnd(None, aerospike.MAP_RETURN_VALUE, "key2"
→", 1, MapBin("b")).compile()
```

```
class aerospike_helpers.expressions.map.MapGetByRank (ctx: Union[None,
    List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int,
    value_type: int, rank: Union[aerospike_helpers.expressions.resources._BaseExpr,
        int, <MagicMock id='140171716589904'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
        str])
```

Create an expression that selects map items identified by rank and returns selected data specified by return_type.

```
__init__ (ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int, value_type: int, rank: Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock id='140171716589904'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that selects map items identified by rank and returns selected data specified by return_type.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [Map Return Types](#) values One of the aerospike map return types.
- **value_type** (*int*) – The value type that will be returned by this expression (ResultType).
- **rank** (*TypeRank*) – Rank integer or integer expression of element to get.
- **bin** (*TypeBinName*) – Map bin name or map expression.

Returns

Expression.

Example:

```
# Get the smallest element in map bin "b".
expr = MapGetByRank(None, aerospike.MAP_RETURN_VALUE, aerospike.ResultType.
    →INTEGER, 0, MapBin("b")).compile()
```

```
class aerospike_helpers.expressions.map.MapGetByRankRange (ctx: Union[None,
    List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int, rank: Union[aerospike_helpers.expressions.resources._BaseExpr,
        int, <MagicMock id='140171716589904'>], count: Union[aerospike_helpers.expressions.resources._BaseExpr,
        int, <MagicMock id='140171716969616'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
        str])
```

Create an expression that selects “count” map items starting at specified rank.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int,
rank: Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
id='140171716589904'>], count: Union[aerospike_helpers.expressions.resources._BaseExpr,
int, <MagicMock id='140171716969616'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
str])
```

Create an expression that selects “count” map items starting at specified rank and returns selected data specified by return_type.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the *Map Return Types* values One of the aerospike map return types.
- **rank** (*TypeRank*) – Rank integer or integer expression of first element to get.
- **count** (*TypeCount*) – Count integer or integer expression for how many elements to get.
- **bin** (*TypeBinName*) – Map bin name or map expression.

Returns Expression.

Example:

```
# Get the 3 smallest elements in map bin "b".
expr = MapGetByRankRange(None, aerospike.MAP_RETURN_VALUE, 0, 3, MapBin("b
→")).compile()
```

```
class aerospike_helpers.expressions.map.MapGetByRankRangeToEnd(ctx:
Union[None,
List[aerospike_helpers.cdt_ctx._cdt_ctx]],
return_type:
int, rank:
Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
id='140171716589904'>],
bin:
Union[aerospike_helpers.expressions.resources._BaseExpr,
str])
```

Create an expression that selects map items starting at specified rank to the last ranked item.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int,
rank: Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
id='140171716589904'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
str])
```

Create an expression that selects map items starting at specified rank to the last ranked item and returns selected data specified by return_type.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the *Map Return Types* values One of the aerospike map return types.
- **rank** (*TypeRank*) – Rank integer or integer expression of first element to get.

- **bin** (*TypeBinName*) – Map bin name or map expression.

Returns Expression.

Example:

```
# Get the three largest elements in map bin "b".
expr = MapGetByRankRangeToEnd(None, aerospike.MAP_RETURN_VALUE, -3, MapBin("b
→")) .compile()
```

```
class aerospike_helpers.expressions.map.MapGetByValue (ctx: Union[None,
                                                               List[aerospike_helpers.cdt_ctx._cdt_ctx]],
                                                       return_type: int, value:
                                                       Union[aerospike_helpers.expressions.resources._Base
                                                       Any], bin:
                                                       Union[aerospike_helpers.expressions.resources._Base
                                                       str])
```

Create an expression that selects map items identified by value.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int,
        value: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], bin:
        Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that selects map items identified by value and returns selected data specified by *return_type*.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [Map Return Types](#) values One of the aerospike map return types.
- **value** (*TypeValue*) – Value or value expression of element to get.
- **bin** (*TypeBinName*) – Map bin name or map expression.

Returns Expression.

Example:

```
# Get the rank of the element with value, 3, in map bin "b".
expr = MapGetByValue(None, aerospike.MAP_RETURN_RANK, 3, MapBin("b")) .
→compile()
```

```
class aerospike_helpers.expressions.map.MapGetByValueList (ctx: Union[None,
                                                               List[aerospike_helpers.cdt_ctx._cdt_ctx]],
                                                       return_type: int, value:
                                                       Union[aerospike_helpers.expressions.resources._Base
                                                       List[Any]], bin:
                                                       Union[aerospike_helpers.expressions.resources._Base
                                                       str])
```

Create an expression that selects map items identified by values.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int,
        value: Union[aerospike_helpers.expressions.resources._BaseExpr, List[Any]], bin:
        Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that selects map items identified by values and returns selected data specified by *return_type*.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the *Map Return Types* values One of the aerospike map return types.
- **value** (*TypeListValue*) – List or list expression of values of elements to get.
- **bin** (*TypeBinName*) – Map bin name or map expression.

Returns Expression.

Example:

```
# Get the indexes of the elements in map bin "b" with values [3, 6, 12].
expr = MapGetByValueList(None, aerospike.MAP_RETURN_INDEX, [3, 6, 12],_
    →MapBin("b")) .compile()
```

```
class aerospike_helpers.expressions.map.MapGetByValueRange (ctx: Union[None,
    List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int,
    value_begin: Union[aerospike_helpers.expressions.resources._BaseExpr, Any],
    value_end: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], bin:
    Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that selects map items identified by value range.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], return_type: int,
    value_begin: Union[aerospike_helpers.expressions.resources._BaseExpr, Any],
    value_end: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], bin:
    Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that selects map items identified by value range (begin inclusive, end exclusive). If begin is None, the range is less than end. If end is None, the range is greater than equal to begin. Expression returns selected data specified by return_type.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the *Map Return Types* values One of the aerospike map return types.
- **value_begin** (*TypeValue*) – Value or value expression of first element to get.
- **value_end** (*TypeValue*) – Value or value expression of ending element.
- **bin** (*TypeBinName*) – Map bin name or map expression.

Returns Expression.

Example:

```
# Get elements with values between 3 and 7 from map bin "b".
expr = MapGetByValueRange(None, aerospike.MAP_RETURN_VALUE, 3, 7, MapBin("b
    →")) .compile()
```

```
class aerospike_helpers.expressions.map.MapGetByValueRelRankRange (ctx:
    Union[None,
    List[aerospike_helpers.cdt_ctx.cdt_
    re-
    turn_type:
    int, value:
    Union[aerospike_helpers.expression_
    Any], rank:
    Union[aerospike_helpers.expression_
    int, <Mag-
    icMock
    id='140171716589904'>],
    count:
    Union[aerospike_helpers.expression_
    int, <Mag-
    icMock
    id='140171716969616'>],
    bin:
    Union[aerospike_helpers.expression_
    str])
```

Create an expression that selects map items nearest to value and greater by relative rank with a count limit.
Expression returns selected data specified by return_type.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx.cdt_ctx]], return_type: int,
        value: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], rank:
        Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
        id='140171716589904'>], count: Union[aerospike_helpers.expressions.resources._BaseExpr,
        int, <MagicMock id='140171716969616'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
        str])
```

Create an expression that selects map items nearest to value and greater by relative rank with a count limit.
Expression returns selected data specified by return_type.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [Map Return Types](#) values One of the aerospike list return types.
- **value** (*TypeValue*) – Value or vaule expression to get items relative to.
- **rank** (*TypeRank*) – Rank intger expression. rank relative to “value” to start getting elements.
- **count** (*TypeCount*) – Integer value or integer value expression, how many elements to get.
- **bin** (*TypeBinName*) – List bin name or list expression.

Returns

Expression.

Example:

```
# Get the next 2 values in map bin "b" larger than 3.
expr = MapGetByValueRelRankRange(None, aerospike.MAP_RETURN_VALUE, 3, 1, 2, ↗
    ↗MapBin("b")) .compile()
```

```
class aerospike_helpers.expressions.map.MapGetByValueRelRankRangeToEnd(ctx:
    Union[None,
          List[aerospike_helpers.cdt_cx
re-
turn_type:
int,
value:
Union[aerospike_helpers.ex
Any],
rank:
Union[aerospike_helpers.ex
int,
<Mag-
ic-
Mock
id='140171716589904'>],
bin:
Union[aerospike_helpers.ex
str])
```

Create an expression that selects map items nearest to value and greater by relative rank.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx.cdt_ctx]], return_type: int,
        value: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], rank:
        Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
id='140171716589904'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
str])
```

Create an expression that selects map items nearest to value and greater by relative rank. Expression returns selected data specified by return_type.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **return_type** (*int*) – Value specifying what should be returned from the operation. This should be one of the [Map Return Types](#) values One of the aerospike map return types.
- **value** (*TypeValue*) – Value or vaule expression to get items relative to.
- **rank** (*TypeRank*) – Rank intger expression. rank relative to “value” to start getting elements.
- **bin** (*TypeBinName*) – Map bin name or map expression.

Returns

Expression.

Example:

```
# Get the values of all elements in map bin "b" larger than 3.
expr = MapGetByValueRelRankRangeToEnd(None, aerospike.MAP_RETURN_VALUE, 3, 1,
→ MapBin("b")).compile()
```

```
class aerospike_helpers.expressions.map.MapIncrement (ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], policy: Optional[Dict[str, Any]], key: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], value: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that increments a map value, by value, for all items identified by key. Valid only for numbers.

```
__init__ (ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], policy: Optional[Dict[str, Any]], key: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], value: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that increments a map value, by value, for all items identified by key. Valid only for numbers.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **policy** (*TypePolicy*) – Optional map write policy.
- **key** (*TypeKey*) – Key value or value expression element to increment.
- **value** (*TypeValue*) – Increment element by value expression.
- **bin** (*TypeBinName*) – Map bin or map expression.

Returns Map expression.

Example:

```
# Increment element at 'vageta' in map bin "b" by 9000.
expr = MapIncrement(None, None, 'vageta', 9000, MapBin("b")).compile()
```

```
class aerospike_helpers.expressions.map.MapPut (ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], policy: Optional[Dict[str, Any]], key: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], value: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that writes key/val to map bin.

```
__init__ (ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], policy: Optional[Dict[str, Any]], key: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], value: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that writes key/val to map bin.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **policy** (*TypePolicy*) – Optional map write policy.

- **key** (*TypeKey*) – Key value or value expression to put into map.
- **value** (*TypeValue*) – Value or value expression to put into map.
- **bin** (*TypeBinName*) – Map bin or map expression.

Returns Map expression.

Example:

```
# Put {27: 'key27'} into map bin "b".
expr = MapPut(None, None, 27, 'key27', MapBin("b")).compile()
```

```
class aerospike_helpers.expressions.map.MapPutItems(ctx: Union[None,
    List[aerospike_helpers.cdt_ctx._cdt_ctx]], policy: Optional[Dict[str,
    Any]], map: map, bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
    str])
```

Create an expression that writes each map item to map bin.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], policy: Optional[Dict[str,
    Any]], map: map, bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that writes each map item to map bin.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **policy** (*TypePolicy*) – Optional map write policy.
- **map** (*map*) – Map or map expression of items to put into target map.
- **bin** (*TypeBinName*) – Map bin or map expression.

Returns Map expression.

Example:

```
# Put {27: 'key27', 28: 'key28'} into map bin "b".
expr = MapPut(None, None, {27: 'key27', 28: 'key28'}, MapBin("b")).compile()
```

```
class aerospike_helpers.expressions.map.MapRemoveByIndex(ctx: Union[None,
    List[aerospike_helpers.cdt_ctx._cdt_ctx]], index: Union[aerospike_helpers.expressions.resources._BaseExpr,
    int, <MagicMock id='140171716602192'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
    str])
```

Create an expression that removes map item identified by index.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], index: Union[aerospike_helpers.expressions.resources._BaseExpr,
    int, <MagicMock id='140171716602192'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
    str])
```

Create an expression that removes map item identified by index.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.

- **index** (*TypeIndex*) – Index integer or integer expression of element to remove.
- **bin** (*TypeBinName*) – Bin name or map expression.

Returns Map expression.

Example:

```
# Remove element with smallest key from map bin "b".
expr = MapRemoveByIndex(None, 0, MapBin("b")).compile()
```

```
class aerospike_helpers.expressions.map.MapRemoveByIndexRange (ctx: Union[None,
    List[aerospike_helpers.cdt_ctx._cdt_ctx]], index:
    Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
    id='140171716602192'>], count:
    Union[aerospike_helpers.expressions.resources._BaseExpr,
    int, <MagicMock id='140171716969616'>], bin:
    Union[aerospike_helpers.expressions.resources._BaseExpr,
    str])
```

Create an expression that removes count map items starting at specified index.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], index:
    Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
    id='140171716602192'>], count: Union[aerospike_helpers.expressions.resources._BaseExpr,
    int, <MagicMock id='140171716969616'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
    str])
```

Create an expression that removes count map items starting at specified index.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **index** (*TypeIndex*) – Starting index integer or integer expression of elements to remove.
- **count** (*TypeCount*) – Integer or integer expression, how many elements to remove.
- **bin** (*TypeBinName*) – Map bin name or map expression.

Returns Map expression.

Example:

```
# Get size of map bin "b" after index 3, 4, and 5 have been removed.
expr = MapSize(None, MapRemoveByIndexRange(None, 3, 3, MapBin("b"))).
    compile()
```

```
class aerospike_helpers.expressions.map.MapRemoveByIndexRangeToEnd (ctx:
Union[None,
List[aerospike_helpers.cdt_ctx._cdt_ctx]],
index:
Union[aerospike_helpers.expressions.expression,
int,
<MagicMock
id='140171716602192'>],
bin:
Union[aerospike_helpers.expressions.expression,
str])
```

Create an expression that removes map items starting at specified index to the end of map.

```
__init__ (ctx: Union[None,
List[aerospike_helpers.cdt_ctx._cdt_ctx]], index:
Union[aerospike_helpers.expressions.resources._BaseExpr,
int,
<MagicMock
id='140171716602192'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
str])
```

Create an expression that removes map items starting at specified index to the end of map.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **index** (*TypeIndex*) – Starting index integer or integer expression of elements to remove.
- **bin** (*TypeBinName*) – Map bin name or map expression.

Returns

Map expression.

Example:

```
# Remove all elements starting from index 3 in map bin "b".
expr = MapRemoveByIndexRangeToEnd(None, 3, MapBin("b")).compile()
```

```
class aerospike_helpers.expressions.map.MapRemoveByKey (ctx: Union[None,
List[aerospike_helpers.cdt_ctx._cdt_ctx]],
key:
Union[aerospike_helpers.expressions.resources._BaseExpr,
Any],
bin:
Union[aerospike_helpers.expressions.resources._BaseExpr,
str])
```

Create an expression that removes a map item identified by key.

```
__init__ (ctx: Union[None,
List[aerospike_helpers.cdt_ctx._cdt_ctx]], key:
Union[aerospike_helpers.expressions.resources._BaseExpr,
Any],
Union[aerospike_helpers.expressions.resources._BaseExpr,
str])
```

Create an expression that removes a map item identified by key.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **key** (*TypeKey*) – Key value or value expression of key to element to remove.
- **bin** (*TypeBinName*) – Map bin or map expression.

Returns

Map expression.

Example:

```
# Remove element at key 1 in map bin "b".
expr = MapRemoveByKey(None, 1, MapBin("b")).compile()
```

```
class aerospike_helpers.expressions.map.MapRemoveByKeyList (ctx: Union[None,
List[aerospike_helpers.cdt_ctx._cdt_ctx]], keys:
List[Union[aerospike_helpers.expressions.resources._BaseExpr, Any]], bin:
Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that removes map items identified by keys.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], keys:
List[Union[aerospike_helpers.expressions.resources._BaseExpr, Any]], bin:
Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that removes map items identified by keys.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **key** (*List [TypeKey]*) – List of key values or a list expression of keys to elements to remove.
- **bin** (*TypeBinName*) – Map bin or map expression.

Returns

Map expression.

Example:

```
# Remove elements at keys [1, 2] in map bin "b".
expr = MapRemoveByKeyList(None, [1, 2], MapBin("b")).compile()
```

```
class aerospike_helpers.expressions.map.MapRemoveByKeyRange (ctx: Union[None,
List[aerospike_helpers.cdt_ctx._cdt_ctx]], begin:
Union[aerospike_helpers.expressions.resources._BaseExpr, Any], end:
Union[aerospike_helpers.expressions.resources._BaseExpr, Any], bin:
Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that removes map items identified by key range (begin inclusive, end exclusive). If begin is None, the range is less than end. If end is None, the range is greater than equal to begin.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], begin:
Union[aerospike_helpers.expressions.resources._BaseExpr, Any], end:
Union[aerospike_helpers.expressions.resources._BaseExpr, Any], bin:
Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that removes map items identified by key range (begin inclusive, end exclusive). If begin is None, the range is less than end. If end is None, the range is greater than equal to begin.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **begin** (*TypeValue*) – Begin value expression.
- **end** (*TypeValue*) – End value expression.
- **bin** (*TypeBinName*) – Map bin or map expression.

Returns Map expression.

Example:

```
# Remove elements at keys between 1 and 10 in map bin "b".
expr = MapRemoveByKeyRange(None, 1, 10 MapBin("b")).compile()
```

```
class aerospike_helpers.expressions.map.MapRemoveByKeyRelIndexRange (ctx:
    Union[None,
          List[aerospike_helpers.cdt_ctx._cdt_ctx]],
    key: Union[aerospike_helpers.expressions.Any],
    index: Union[aerospike_helpers.expressions.int,
                 <MagicMock
                     id='140171716602192'>],
    count: Union[aerospike_helpers.expressions.int,
                 <MagicMock
                     id='140171716969616'>],
    bin: Union[aerospike_helpers.expressions.str])
```

Create an expression that removes map items nearest to key and greater by index with a count limit.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], key:
        Union[aerospike_helpers.expressions.resources._BaseExpr, Any], index:
        Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
            id='140171716602192'>], count: Union[aerospike_helpers.expressions.resources._BaseExpr,
            int, <MagicMock id='140171716969616'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
            str])
```

Create an expression that removes map items nearest to key and greater by index with a count limit.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **key** (*TypeKey*) – Key value or expression for key to start removing from.
- **index** (*TypeIndex*) – Index integer or integer expression.
- **count** (*TypeCount*) – Integer expression for how many elements to remove.
- **bin** (*TypeBinName*) – Map bin or map expression.

Returns [Map expression.

Example:

```
# Remove 3 elements with keys greater than "key1" from map bin "b".
expr = MapRemoveByKeyRelIndexRange(None, "key1", 1, 3, MapBin("b")).compile()
```

```
class aerospike_helpers.expressions.map.MapRemoveByKeyRelIndexRangeToEnd (ctx:  
    Union[None,  
          List[aerospike_helpers.cdt_ctx._cdt_ctx]],  
    key:  
        Union[aerospike_helpers.  
              Any],  
    in-  
    dex:  
        Union[aerospike_helpers.  
              int,  
              <Mag-  
              ic-  
              Mock  
              id='140171716602192'>],  
    bin:  
        Union[aerospike_helpers.  
              str])
```

Create an expression that removes map items nearest to key and greater by index.

```
__init__ (ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], key:  
    Union[aerospike_helpers.expressions.resources._BaseExpr, Any], index:  
        Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock  
              id='140171716602192'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,  
              str])
```

Create an expression that removes map items nearest to key and greater by index.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **key** (*TypeKey*) – Key value or expression for key to start removing from.
- **index** (*TypeIndex*) – Index integer or integer expression.
- **bin** (*TypeBinName*) – Map bin or map expression.

Returns Map expression.

Example:

```
# Map bin "b" has {"key1": 1, "key2": 2, "key3": 3, "key4": 4}.  
# Remove each element where the key has greater index than "key1".  
expr = MapRemoveByKeyRelIndexRangeToEnd(None, "key1", 1, MapBin("b")).  
→compile()
```

```
class aerospike_helpers.expressions.map.MapRemoveByRank (ctx: Union[None,  
    List[aerospike_helpers.cdt_ctx._cdt_ctx]], rank:  
        Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock  
              id='140171716589904'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,  
              str])
```

Create an expression that removes map item identified by rank.

```
__init__ (ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], rank:  
    Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock  
          id='140171716589904'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,  
          str])
```

Create an expression that removes map item identified by rank.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **rank** (*TypeRank*) – Rank integer or integer expression of element to remove.
- **bin** (*TypeBinName*) – Map bin name or map expression.

Returns Map expression.

Example:

```
# Remove smallest value in map bin "b".
expr = MapRemoveByRank(None, 0, MapBin("b")).compile()
```

```
class aerospike_helpers.expressions.map.MapRemoveByRankRange(ctx: Union[None,
    List[aerospike_helpers.cdt_ctx._cdt_ctx]], rank:
    Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
    id='140171716589904'>], count:
    Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
    id='140171716969616'>], bin:
    Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that removes “count” map items starting at specified rank.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], rank:
    Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
    id='140171716589904'>], count: Union[aerospike_helpers.expressions.resources._BaseExpr,
    int, <MagicMock id='140171716969616'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
    str])
```

Create an expression that removes “count” map items starting at specified rank.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **rank** (*TypeRank*) – Rank integer or integer expression of element to start removing at.
- **count** (*TypeCount*) – Count integer or integer expression of elements to remove.
- **bin** (*TypeBinName*) – Map bin name or map expression.

Returns Map expression.

Example:

```
# Remove the 3 smallest items from map bin "b".
expr = MapRemoveByRankRange(None, 0, 3, MapBin("b")).compile()
```

```
class aerospike_helpers.expressions.map.MapRemoveByRankRangeToEnd (ctx:
    Union[None,
          List[aerospike_helpers.cdt_ctx._cdt_ctx]],
    rank:
        Union[aerospike_helpers.expressions.resources._BaseExpr,
              int, <MagicMock
id='140171716589904'>],
    bin:
        Union[aerospike_helpers.expressions.resources._BaseExpr,
              str])
```

Create an expression that removes map items starting at specified rank to the last ranked item.

```
__init__ (ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]],
          rank:
              Union[aerospike_helpers.expressions.resources._BaseExpr,
                    int, <MagicMock
id='140171716589904'>],
          bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
                    str])
```

Create an expression that removes map items starting at specified rank to the last ranked item.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **rank** (*TypeRank*) – Rank integer or integer expression of element to start removing at.
- **bin** (*TypeBinName*) – Map bin name or map expression.

Returns

Map expression.

Example:

```
# Remove the 2 largest elements from map bin "b".
expr = MapRemoveByRankRangeToEnd(None, -2, MapBin("b")).compile()
```

```
class aerospike_helpers.expressions.map.MapRemoveByValue (ctx: Union[None,
    List[aerospike_helpers.cdt_ctx._cdt_ctx]],
    value:
        Union[aerospike_helpers.expressions.resources._BaseExpr,
              Any], bin:
        Union[aerospike_helpers.expressions.resources._BaseExpr,
              str])
```

Create an expression that removes map items identified by value.

```
__init__ (ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]],
          value:
              Union[aerospike_helpers.expressions.resources._BaseExpr,
                    Any], bin:
                  Union[aerospike_helpers.expressions.resources._BaseExpr,
                        str])
```

Create an expression that removes map items identified by value.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **value** (*TypeValue*) – Value or value expression to remove.
- **bin** (*TypeBinName*) – Bin name or map expression.

Returns

Map expression.

Example:

```
# Remove {"key1": 1} from map bin "b".
expr = MapRemoveByValue(None, 1, MapBin("b")).compile()
```

```
class aerospike_helpers.expressions.map.MapRemoveByValueList(ctx: Union[None,
    List[aerospike_helpers.cdt_ctx._cdt_ctx]], values:
    Union[aerospike_helpers.expressions.resources._BaseExpr],
    List[Any]], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that removes map items identified by values.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], values:
    Union[aerospike_helpers.expressions.resources._BaseExpr],
    List[Any]], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that removes map items identified by values.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **values** (*TypeListValue*) – List of values or list expression.
- **bin** (*TypeBinName*) – Bin name or map expression.

Returns Map expression.

Example:

```
# Remove elements with values 1, 2, 3 from map bin "b".
expr = MapRemoveByValueList(None, [1, 2, 3], MapBin("b")).compile()
```

```
class aerospike_helpers.expressions.map.MapRemoveByValueRange(ctx: Union[None,
    List[aerospike_helpers.cdt_ctx._cdt_ctx]], begin:
    Union[aerospike_helpers.expressions.resources._BaseExpr],
    Any], end: Union[aerospike_helpers.expressions.resources._BaseExpr],
    Any], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that removes map items identified by value range (begin inclusive, end exclusive). If begin is nil, the range is less than end. If end is aerospike.CDTInfinite(), the range is greater than equal to begin.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], begin:
    Union[aerospike_helpers.expressions.resources._BaseExpr],
    Any], end: Union[aerospike_helpers.expressions.resources._BaseExpr],
    Any], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that removes map items identified by value range (begin inclusive, end exclusive). If begin is nil, the range is less than end. If end is aerospike.CDTInfinite(), the range is greater than equal to begin.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **begin** (*TypeValue*) – Begin value or value expression for range.
- **end** (*TypeValue*) – End value or value expression for range.
- **bin** (*TypeBinName*) – Bin name or map expression.

Returns Map expression.

Example:

```
# Remove list of items with values >= 3 and < 7 from map bin "b".
expr = MapRemoveByValueRange(None, 3, 7, MapBin("b")).compile()
```

```
class aerospike_helpers.expressions.map.MapRemoveByValueRelRankRange (ctx:
    Union[None,
          List[aerospike_helpers.cdt_ctx._cdt_ctx]],
    value:
        Union[aerospike_helpers.expressions.Any],
    rank:
        Union[aerospike_helpers.expressions.int,
              <MagicMock
id='140171716589904'>],
    count:
        Union[aerospike_helpers.expressions.int,
              <MagicMock
id='140171716969616'>],
    bin:
        Union[aerospike_helpers.expressions.str])
```

Create an expression that removes map items nearest to value and greater by relative rank with a count limit.

```
__init__(ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], value:
    Union[aerospike_helpers.expressions.resources._BaseExpr, Any], rank:
    Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock
id='140171716589904'>], count: Union[aerospike_helpers.expressions.resources._BaseExpr,
int, <MagicMock id='140171716969616'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
str])
```

Create an expression that removes map items nearest to value and greater by relative rank with a count limit.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **value** (*TypeValue*) – Value or value expression to start removing from.
- **rank** (*TypeRank*) – Integer or integer expression of rank.
- **count** (*TypeCount*) – Integer count or integer expression for how many elements to remove.
- **bin** (*TypeBinName*) – Bin name or map expression.

Returns Map expression.

Example:

```
# Remove the next 4 elements larger than 3 from map bin "b".
expr = MapRemoveByValueRelRankRangeToEnd(None, 3, 1, 4, MapBin("b")).
    compile()
```

```
class aerospike_helpers.expressions.map.MapRemoveByValueRelRankRangeToEnd (ctx:  
    Union[None,  
          List[aerospike_helpers.cdt_ctx._cdt_ctx]],  
    value:  
        Union[aerospike_helpers._Any],  
    rank:  
        Union[aerospike_helpers._Any],  
        int,  
        <MagicMock  
        id='140171716589904'>,  
    bin:  
        Union[aerospike_helpers.expressions.resources._BaseExpr,  
              str])
```

Create an expression that removes map items nearest to value and greater by relative rank.

```
__init__ (ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], value:  
    Union[aerospike_helpers.expressions.resources._BaseExpr, Any], rank:  
    Union[aerospike_helpers.expressions.resources._BaseExpr, int, <MagicMock  
          id='140171716589904'>], bin: Union[aerospike_helpers.expressions.resources._BaseExpr,  
              str])
```

Create an expression that removes map items nearest to value and greater by relative rank.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **value** (*TypeValue*) – Value or value expression to start removing from.
- **rank** (*TypeRank*) – Integer or integer expression of rank.
- **bin** (*TypeBinName*) – Bin name or map expression.

Returns

Map expression.

Example:

```
# Remove all elements with values larger than 3 from map bin "b".  
expr = MapRemoveByValueRelRankRangeToEnd(None, 3, 1, MapBin("b")).compile()
```

```
class aerospike_helpers.expressions.map.MapSize (ctx: Union[None,  
    List[aerospike_helpers.cdt_ctx._cdt_ctx]],  
    bin: Union[aerospike_helpers.expressions.resources._BaseExpr,  
              str])
```

Create an expression that returns map size.

```
__init__ (ctx: Union[None, List[aerospike_helpers.cdt_ctx._cdt_ctx]], bin:  
    Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that returns map size.

Parameters

- **ctx** (*TypeCDT*) – Optional context path for nested CDT.
- **bin** (*TypeBinName*) – Map bin name or map expression.

Returns

Integer expression.

Example:

```
#Take the size of map bin "b".
expr = MapSize(None, MapBin("b")).compile()
```

aerospike_helpers.expressions.bit module

Bitwise expressions contain bit read and modify expressions.

Example:

```
import aerospike_helpers.expressions as exp
# Let blob bin "c" == bytearray([3] * 5).
# Count set bits starting at 3rd byte in bin "c" to get count of 6.
expr = exp.BitCount(16, 8 * 3, exp.BlobBin("c")).compile()
```

```
class aerospike_helpers.expressions.bitwise.BitAdd(policy: Optional[Dict[str, Any]],
bit_offset: int, bit_size: int,
value: int, action: int, bin:
Union[aerospike_helpers.expressions.resources._BaseExpr,
str])
```

Create an expression that performs a bit_add operation.

```
__init__(policy: Optional[Dict[str, Any]], bit_offset: int, bit_size: int, value: int, action: int, bin:
Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that performs a bit_add operation. Note: integers are stored big-endian.

Parameters

- **policy** (*TypePolicy*) – An optional aerospike bit policy.
- **bit_offset** (*int*) – Bit index of where to start operation.
- **bit_size** (*int*) – Number of bits to be operated on.
- **value** (*int*) – Integer value or expression for value to add.
- **action** (*int*) – An aerospike bit overflow action.
- **bin** (*TypeBinName*) – Blob bin name or blob expression.

Returns resulting blob with the bits operated on.

Example:

```
# Let blob bin "c" == bytearray([1] * 5).
# Bit add the second byte of bin "c" to get bytearray([1, 2, 1, 1, 1])
expr = BitAdd(None, 8, 8, 1, aerospike.BIT_OVERFLOW_FAIL).compile()
```

```
class aerospike_helpers.expressions.bitwise.BitAnd(policy: Optional[Dict[str, Any]],
bit_offset: int, bit_size: int, value:
Union[bytes, bytearray], bin:
Union[aerospike_helpers.expressions.resources._BaseExpr,
str])
```

Create an expression that performs a bit_and operation.

```
__init__(policy: Optional[Dict[str, Any]], bit_offset: int, bit_size: int, value: Union[bytes, bytearray],
bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that performs a bit_and operation.

Parameters

- **policy** (*TypePolicy*) – An optional aerospike bit policy.

- **bit_offset** (*int*) – Bit index of where to start operation.
- **bit_size** (*int*) – Number of bits to be operated on.
- **value** (*TypeBitValue*) – Bytes value or blob expression containing bytes to use in operation.
- **bin** (*TypeBinName*) – Blob bin name or blob expression.

Returns Resulting blob with the bits operated on.

Example:

```
# Let blob bin "c" == bytearray([1] * 5).
# bitwise and `0` with the first byte of blob bin c so that the returned
# value is bytearray([0, 5, 5, 5, 5]).
expr = BitAnd(None, 0, 8, bytearray([0]), BlobBin("c")).compile()
```

```
class aerospike_helpers.expressions.bitwise.BitCount(bit_offset: int, bit_size: int, bin:
                                                    Union[aerospike_helpers.expressions.resources._BaseExpr,
                                                    str])
```

Create an expression that performs a bit_count operation.

```
__init__(bit_offset: int, bit_size: int, bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
                                                    str])
```

Create an expression that performs a bit_count operation.

Parameters

- **bit_offset** (*int*) – Bit index of where to start reading.
- **bit_size** (*int*) – Number of bits to count.
- **bin** (*TypeBinName*) – Blob bin name or blob expression.

Returns Blob, bit_size bits rounded up to the nearest byte size.

Example:

```
# Let blob bin "c" == bytearray([3] * 5).
# Count set bits starting at 3rd byte in bin "c" to get count of 6.
expr = BitCount(16, 8 * 3, BlobBin("c")).compile()
```

```
class aerospike_helpers.expressions.bitwise.BitGet(bit_offset: int, bit_size: int, bin:
                                                    Union[aerospike_helpers.expressions.resources._BaseExpr,
                                                    str])
```

Create an expression that performs a bit_get operation.

```
__init__(bit_offset: int, bit_size: int, bin: Union[aerospike_helpers.expressions.resources._BaseExpr,
                                                    str])
```

Create an expression that performs a bit_get operation.

Parameters

- **bit_offset** (*int*) – Bit index of where to start reading.
- **bit_size** (*int*) – Number of bits to get.
- **bin** (*TypeBinName*) – Blob bin name or blob expression.

Returns Blob, bit_size bits rounded up to the nearest byte size.

Example:

```
# Let blob bin "c" == bytearray([1, 2, 3, 4, 5].
# Get 2 from bin "c".
expr = BitGet(8, 8, BlobBin("c")).compile()
```

```
class aerospike_helpers.expressions.bitwise.BitGetInt(bit_offset: int, bit_size: int, sign: bool, bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that performs a bit_get_int operation.

```
__init__(bit_offset: int, bit_size: int, sign: bool, bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that performs a bit_get_int operation.

Parameters

- **bit_offset** (`int`) – Bit index of where to start reading.
- **bit_size** (`int`) – Number of bits to get.
- **bool** (`sign`) – True for signed, False for unsigned.
- **bin** (`TypeBinName`) – Blob bin name or blob expression.

Returns

Integer expression.

Example:

```
# Let blob bin "c" == bytearray([1, 2, 3, 4, 5].
# Get 2 as an integer from bin "c".
expr = BitGetInt(8, 8, True, BlobBin("c")).compile()
```

```
class aerospike_helpers.expressions.bitwise.BitInsert(policy: Optional[Dict[str, Any]], byte_offset: int, value: Union[bytes, bytearray], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that performs a bit_insert operation.

```
__init__(policy: Optional[Dict[str, Any]], byte_offset: int, value: Union[bytes, bytearray], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that performs a bit_insert operation.

Parameters

- **policy** (`TypePolicy`) – An optional aerospike bit policy.
- **byte_offset** (`int`) – Integer byte index of where to insert the value.
- **value** (`TypeBitValue`) – A bytes value or blob value expression to insert.
- **bin** (`TypeBinName`) – Blob bin name or blob value expression.

Returns

Resulting blob containing the inserted bytes.

Example:

```
# Let blob bin "c" == bytearray([1] * 5).
# Insert 3 so that returned value is bytearray([1, 3, 1, 1, 1, 1]).
expr = BitInsert(None, 1, bytearray([3]), BlobBin("c")).compile()
```

```
class aerospike_helpers.expressions.bitwise.BitLeftScan(bit_offset: int, bit_size: int, value: bool, bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that performs a bit_lscan operation.

```
__init__(bit_offset: int, bit_size: int, value: bool, bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that performs a bit_lscan operation.

Parameters

- **bit_offset** (`int`) – Bit index of where to start reading.
- **bit_size** (`int`) – Number of bits to read.
- **bool** (`value`) – Bit value to check for.
- **bin** (`TypeBinName`) – Blob bin name or blob expression.

Returns Index of the left most bit starting from bit_offset set to value. Returns -1 if not found.

Example:

```
# Let blob bin "c" == bytearray([3] * 5).
# Scan the first byte of bin "c" for the first bit set to 1. (should get 6)
expr = BitLeftScan(0, 8, True, BlobBin("c")).compile()
```

```
class aerospike_helpers.expressions.bitwise.BitLeftShift(policy: Optional[Dict[str, Any]], bit_offset: int, bit_size: int, shift: int, bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that performs a bit_lshift operation.

```
__init__(policy: Optional[Dict[str, Any]], bit_offset: int, bit_size: int, shift: int, bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that performs a bit_lshift operation.

Parameters

- **policy** (`TypePolicy`) – An optional aerospike bit policy.
- **bit_offset** (`int`) – Bit index of where to start operation.
- **bit_size** (`int`) – Number of bits to be operated on.
- **shift** (`int`) – Number of bits to shift by.
- **bin** (`TypeBinName`) – Blob bin name or blob expression.

Returns Resulting blob with the bits operated on.

Example:

```
# Let blob bin "c" == bytearray([1] * 5).
# Bit left shift the first byte of bin "c" to get bytearray([8, 1, 1, 1, 1]).
expr = BitLeftShift(None, 0, 8, 3, BlobBin("c")).compile()
```

```
class aerospike_helpers.expressions.bitwise.BitNot(policy: Optional[Dict[str, Any]], bit_offset: int, bit_size: int, bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that performs a bit_not operation.

```
__init__(policy: Optional[Dict[str, Any]], bit_offset: int, bit_size: int, bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that performs a bit_not operation.

Parameters

- **policy** (*TypePolicy*) – An optional aerospike bit policy.
- **bit_offset** (*int*) – Bit index of where to start operation.
- **bit_size** (*int*) – Number of bits to be operated on.
- **bin** (*TypeBinName*) – Blob bin name or blob expression.

Returns Resulting blob with the bits operated on.

Example:

```
# Let blob bin "c" == bytearray([255] * 5).
# bitwise, not, all of "c" to get bytearray([254] * 5).
expr = BitNot(None, 0, 40, BlobBin("c")).compile()
```

```
class aerospike_helpers.expressions.bitwise.BitOr(policy: Optional[Dict[str, Any]], bit_offset: int, bit_size: int, value: Union[bytes, bytearray], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that performs a bit_or operation.

```
__init__(policy: Optional[Dict[str, Any]], bit_offset: int, bit_size: int, value: Union[bytes, bytearray], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that performs a bit_or operation.

Parameters

- **policy** (*TypePolicy*) – An optional aerospike bit policy.
- **bit_offset** (*int*) – Bit index of where to start operation.
- **bit_size** (*int*) – Number of bits to be operated on.
- **value** (*TypeBitValue*) – Bytes value or blob expression containing bytes to use in operation.
- **bin** (*TypeBinName*) – Blob bin name or blob expression.

Returns Resulting blob with the bits operated on.

Example:

```
# Let blob bin "c" == bytearray([1] * 5).
# bitwise Or `8` with the first byte of blob bin c so that the returned
# value is bytearray([9, 1, 1, 1, 1]).
expr = BitOr(None, 0, 8, bytearray([8]), BlobBin("c")).compile()
```

```
class aerospike_helpers.expressions.bitwise.BitRemove(policy: Optional[Dict[str, Any]], byte_offset: int, byte_size: int, bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that performs a bit_remove operation.

```
__init__(policy: Optional[Dict[str, Any]], byte_offset: int, byte_size: int, bin:
        Union[aerospike_helpers.expressions.resources._BaseExpr, str])
Create an expression that performs a bit_remove operation.
```

Parameters

- **policy** (*TypePolicy*) – An optional aerospike bit policy.
- **byte_offset** (*int*) – Byte index of where to start removing from.
- **byte_size** (*int*) – Number of bytes to remove.
- **bin** (*TypeBinName*) – Blob bin name or blob value expression.

Returns Resulting blob containing the remaining bytes.

Example:

```
# Let blob bin "c" == bytearray([1] * 5).
# Remove 1 element so that the returned value is bytearray([1] * 4).
expr = BitRemove(None, 1, 1, BlobBin("c")).compile()
```

```
class aerospike_helpers.expressions.bitwise.BitResize(policy: Optional[Dict[str,
                                                               Any]], byte_size:
                                                               int, flags: int, bin:
                                                               Union[aerospike_helpers.expressions.resources._Base
                                                               Expr, str])
```

Create an expression that performs a bit_resize operation.

```
__init__(policy: Optional[Dict[str, Any]], byte_size: int, flags: int, bin:
        Union[aerospike_helpers.expressions.resources._BaseExpr, str])
Create an expression that performs a bit_resize operation.
```

Parameters

- **policy** (*TypePolicy*) – An optional aerospike bit policy.
- **byte_size** (*int*) – Number of bytes the resulting blob should occupy.
- **flags** (*int*) – One or a combination of bit resize flags.
- **bin** (*TypeBinName*) – Blob bin name or blob value expression.

Returns Blob value expression of resized blob bin.

Example:

```
# Blob bin "c" == bytearray([1] * 5).
# Resize blob bin "c" from the front so that the returned value is
# bytearray([0] * 5 + [1] * 5).
expr = BitResize(None, 10, aerospike.BIT_RESIZE_FROM_FRONT, BlobBin("c")).
        compile()
```

```
class aerospike_helpers.expressions.bitwise.BitRightScan(bit_offset: int, bit_size:
                                                       int, value: bool, bin:
                                                       Union[aerospike_helpers.expressions.resources._Base
                                                       Expr, str])
```

Create an expression that performs a bit_rscan operation.

```
__init__(bit_offset: int, bit_size: int, value: bool, bin:
        Union[aerospike_helpers.expressions.resources._BaseExpr, str])
Create an expression that performs a bit_rscan operation.
```

Parameters

- **bit_offset** (`int`) – Bit index of where to start reading.
- **bit_size** (`int`) – Number of bits to read.
- **bool** (`value`) – Bit value to check for.
- **bin** (`TypeBinName`) – Blob bin name or blob expression.

Returns Index of the right most bit starting from bit_offset set to value. Returns -1 if not found.

Example:

```
# Let blob bin "c" == bytearray([3] * 5).
# Scan the first byte of bin "c" for the right most bit set to 1. (should
# →get 7)
expr = BitRightScan(0, 8, True, BlobBin("c")).compile()
```

```
class aerospike_helpers.expressions.bitwise.BitRightShift(policy:          Optional[Dict[str, Any]],
                                                               bit_offset: int, bit_size: int, shift: int, bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that performs a bit_rshift operation.

```
__init__(policy: Optional[Dict[str, Any]], bit_offset: int, bit_size: int, shift: int, bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
Create an expression that performs a bit_rshift operation.
```

Parameters

- **policy** (`TypePolicy`) – An optional aerospike bit policy.
- **bit_offset** (`int`) – Bit index of where to start operation.
- **bit_size** (`int`) – Number of bits to be operated on.
- **shift** (`int`) – Number of bits to shift by.
- **bin** (`TypeBinName`) – Blob bin name or blob expression.

Returns Resulting blob with the bits operated on.

Example:

```
# Let blob bin "c" == bytearray([8] * 5).
# Bit left shift the first byte of bin "c" to get bytearray([4, 8, 8, 8, 8]).
expr = BitRightShift(None, 0, 8, 1, BlobBin("c")).compile()
```

```
class aerospike_helpers.expressions.bitwise.BitSet(policy: Optional[Dict[str, Any]],
                                                               bit_offset: int, bit_size: int, value: Union[bytes, bytearray], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that performs a bit_set operation.

```
__init__(policy: Optional[Dict[str, Any]], bit_offset: int, bit_size: int, value: Union[bytes, bytearray], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
Create an expression that performs a bit_set operation.
```

Parameters

- **policy** (`TypePolicy`) – An optional aerospike bit policy.

- **bit_offset** (`int`) – Bit index of where to start overwriting.
- **bit_size** (`int`) – Number of bits to overwrite.
- **value** (`TypeBitValue`) – Bytes value or blob expression containing bytes to write.
- **bin** (`TypeBinName`) – Blob bin name or blob expression.

Returns Resulting blob expression with the bits overwritten.

Example:

```
# Let blob bin "c" == bytearray([0] * 5).
# Set bit at offset 7 with size 1 bits to 1 to make the returned value_
→bytearray([1, 0, 0, 0, 0]).
expr = BitSet(None, 7, 1, bytearray([255]), BlobBin("c")).compile()
```

```
class aerospike_helpers.expressions.bitwise.BitSetInt(policy: Optional[Dict[str,
    Any]], bit_offset: int,
    bit_size: int, value: int, bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that performs a bit_set_int operation. Note: integers are stored big-endian.

```
__init__(policy: Optional[Dict[str, Any]], bit_offset: int, bit_size: int, value: int, bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that performs a bit_set_int operation. Note: integers are stored big-endian.

Parameters

- **policy** (`TypePolicy`) – An optional aerospike bit policy.
- **bit_offset** (`int`) – Bit index of where to start writing.
- **bit_size** (`int`) – Number of bits to overwrite.
- **value** (`int`) – Integer value or integer expression containing value to write.
- **bin** (`TypeBinName`) – Blob bin name or blob expression.

Returns Resulting blob expression with the bits overwritten.

Example:

```
# Let blob bin "c" == bytearray([0] * 5).
# Set bit at offset 7 with size 1 bytes to 1 to make the returned value_
→bytearray([1, 0, 0, 0, 0]).
expr = BitSetInt(None, 7, 1, 1, BlobBin("c")).compile()
```

```
class aerospike_helpers.expressions.bitwise.BitSubtract(policy: Optional[Dict[str,
    Any]], bit_offset: int,
    bit_size: int, value: int, action: int, bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that performs a bit_subtract operation. Note: integers are stored big-endian.

```
__init__(policy: Optional[Dict[str, Any]], bit_offset: int, bit_size: int, value: int, action: int, bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that performs a bit_subtract operation. Note: integers are stored big-endian.

Parameters

- **policy** (*TypePolicy*) – An optional aerospike bit policy.
- **bit_offset** (*int*) – Bit index of where to start operation.
- **bit_size** (*int*) – Number of bits to be operated on.
- **value** (*int*) – Integer value or expression for value to add.
- **action** (*int*) – An aerospike bit overflow action.
- **bin** (*TypeBinName*) – Blob bin name or blob expression.

Returns resulting blob with the bits operated on.

Example:

```
# Let blob bin "c" == bytearray([1] * 5).
# Bit subtract the second byte of bin "c" to get bytearray([1, 0, 1, 1, 1])
expr = BitSubtract(None, 8, 8, 1, aerospike.BIT_OVERFLOW_FAIL).compile()
```

```
class aerospike_helpers.expressions.bitwise.BitXor(policy: Optional[Dict[str, Any]],
                                                    bit_offset: int, bit_size: int, value:
                                                    Union[bytes, bytearray], bin:
                                                    Union[aerospike_helpers.expressions.resources._BaseExpr,
                                                    str])
```

Create an expression that performs a bit_xor operation.

```
__init__(policy: Optional[Dict[str, Any]], bit_offset: int, bit_size: int, value: Union[bytes, bytearray],
        bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that performs a bit_xor operation.

Parameters

- **policy** (*TypePolicy*) – An optional aerospike bit policy.
- **bit_offset** (*int*) – Bit index of where to start operation.
- **bit_size** (*int*) – Number of bits to be operated on.
- **value** (*TypeBitValue*) – Bytes value or blob expression containing bytes to use in operation.
- **bin** (*TypeBinName*) – Blob bin name or blob expression.

Returns Resulting blob with the bits operated on.

Example:

```
# Let blob bin "c" == bytearray([1] * 5).
# bitwise Xor `1` with the first byte of blob bin c so that the returned
# value is bytearray([0, 1, 1, 1, 1]).
expr = BitXor(None, 0, 8, bytearray([1]), BlobBin("c")).compile()
```

aerospike_helpers.expressions.hllmodule

Hyper Log Log expressions contain hll read and modify expressions.

Example:

```
import aerospike_helpers.expressions as exp
# Get count from HLL bin "d".
expr = exp.HLLGetCount(exp.HLLBin("d")).compile()
```

```
class aerospike_helpers.expressions.hll.HLLAdd(policy: Optional[Dict[str, Any]], list: Union[aerospike_helpers.expressions.resources._BaseExpr, List[Any]], index_bit_count: Optional[int], mh_bit_count: Optional[int], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that performs an hll_add.

```
__init__(policy: Optional[Dict[str, Any]], list: Union[aerospike_helpers.expressions.resources._BaseExpr, List[Any]], index_bit_count: Optional[int], mh_bit_count: Optional[int], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that performs an hll_add.

Parameters

- **policy** (*TypePolicy*) – An optional aerospike HLL policy.
- **list** (*TypeListValue*) – A list or list expression of elements to add to the HLL.
- **index_bit_count** (*int*) – Number of index bits. Must be between 4 and 16 inclusive.
- **mh_bit_count** (*int*) – Number of min hash bits. Must be between 4 and 51 inclusive.
- **bin** (*TypeBinName*) – A hll bin name or bin expression to apply this function to.

Returns Returns the resulting hll bin after adding elements from list.

Example:

```
# Let HLL bin "d" have the following elements, ['key1', 'key2', 'key3'],
→ index_bits 8, mh_bits 8.
# Add ['key4', 'key5', 'key6'] so that the returned value is ['key1', 'key2',
→ 'key3', 'key4', 'key5', 'key6']
expr = HLLAdd(None, ['key4', 'key5', 'key6'], 8, 8, HLLBin("d")).compile()
```

```
class aerospike_helpers.expressions.hll.HLLDescribe(bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that performs an as_operations_hll_describe.

```
__init__(bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that performs an as_operations_hll_describe.

Parameters **bin** (*TypeBinName*) – A hll bin name or bin expression to read from.

Returns List bin, a list containing the index_bit_count and minhash_bit_count.

Example:

```
# Get description of HLL bin "d".
expr = HLLDescribe(HLLBin("d")).compile()
```

```
class aerospike_helpers.expressions.hll.HLLGetCount(bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that performs an as_operations_hll_get_count.

```
__init__(bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that performs an as_operations_hll_get_count.

Parameters **bin** (*TypeBinName*) – A hll bin name or bin expression to read from.

Returns Integer bin, the estimated number of unique elements in an HLL.

Example:

```
# Get count from HLL bin "d".
expr = HLLGetCount(HLLBin("d")).compile()
```

class aerospike_helpers.expressions.hll.**HLLGetIntersectCount** (*values*:

Union[aerospike_helpers.expressions.resources._BaseExpr, Any], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str]]

Create an expression that performs an as_operations_hll_get_intersect_count.

__init__ (*values*: *Union[aerospike_helpers.expressions.resources._BaseExpr, Any]*, *bin*: *Union[aerospike_helpers.expressions.resources._BaseExpr, str]*)
Create an expression that performs an as_operations_hll_get_intersect_count.

Parameters

- **values** (*TypeValue*) – A single HLL or list of HLLs, values or expressions, to intersect with bin.
- **bin** (*TypeBinName*) – A hll bin name or bin expression to read from.

Returns Integer bin, estimated number of elements in the set intersection.

Example:

```
# Let HLLBin "d" contain keys ['key%s' % str(i) for i in range(10000)].
# Let values be a list containing one HLL object with keys ['key%s' % str(i) ↴for i in range(5000, 15000)].
# Find the count of keys in the intersection of HLL bin "d" and all HLLs in ↴values. (Should be around 5000)
expr = HLLGetIntersectCount(values, HLLBin("d")).compile()
```

class aerospike_helpers.expressions.hll.**HLLGetSimilarity** (*values*:

Union[aerospike_helpers.expressions.resources._BaseExpr, Any], bin: Union[aerospike_helpers.expressions.resources._BaseExpr, str]]

Create an expression that performs an as_operations_hll_get_similarity.

__init__ (*values*: *Union[aerospike_helpers.expressions.resources._BaseExpr, Any]*, *bin*: *Union[aerospike_helpers.expressions.resources._BaseExpr, str]*)
Create an expression that performs an as_operations_hll_get_similarity.

Parameters

- **values** (*TypeValue*) – A single HLL or list of HLLs, values or expressions, to calculate similarity with.
- **bin** (*TypeBinName*) – A hll bin name or bin expression to read from.

Returns Float bin, stimated similarity between 0.0 and 1.0.

Example:

```
# Let HLLBin "d" contain keys ['key%s' % str(i) for i in range(10000)].
# Let values be a list containing one HLL object with keys ['key%s' % str(i) ↴for i in range(5000, 15000)].
```

(continues on next page)

(continued from previous page)

```
# Find the similarity the HLL in values to HLL bin "d". (Should be around 0.
→33)
# Note that similarity is defined as intersect(A, B, ...) / union(A, B, ...).
expr = HLLGetSimilarity(values, HLLBin("d")).compile()
```

class aerospike_helpers.expressions.hll.**HLLGetUnion**(values:

```
Union[aerospike_helpers.expressions.resources._BaseExpr,
      Any],           bin:
Union[aerospike_helpers.expressions.resources._BaseExpr,
      str])
```

Create an expression that performs an hll_get_union.

__init__(values: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], bin:
Union[aerospike_helpers.expressions.resources._BaseExpr, str])

Create an expression that performs an hll_get_union.

Parameters

- **values** (*TypeValue*) – A single HLL or list of HLLs, values or expressions, to union with bin.
- **bin** (*TypeBinName*) – A hll bin name or bin expression to read from.

Returns HLL bin representing the set union.

Example:

```
# Let HLLBin "d" contain keys ['key%s' % str(i) for i in range(10000)].
# Let values be a list containing HLL objects retrieved from the aerospike_
→database.
# Find the union of HLL bin "d" and all HLLs in values.
expr = HLLGetUnion(values, HLLBin("d")).compile()
```

class aerospike_helpers.expressions.hll.**HLLGetUnionCount**(values:

```
Union[aerospike_helpers.expressions.resources._BaseExpr,
      Any],           bin:
Union[aerospike_helpers.expressions.resources._BaseExpr,
      str])
```

Create an expression that performs an as_operations_hll_get_union_count.

__init__(values: Union[aerospike_helpers.expressions.resources._BaseExpr, Any], bin:
Union[aerospike_helpers.expressions.resources._BaseExpr, str])

Create an expression that performs an as_operations_hll_get_union_count.

Parameters

- **values** (*TypeValue*) – A single HLL or list of HLLs, values or expressions, to union with bin.
- **bin** (*TypeBinName*) – A hll bin name or bin expression to read from.

Returns Integer bin, estimated number of elements in the set union.

Example:

```
# Let HLLBin "d" contain keys ['key%s' % str(i) for i in range(10000)].
# Let values be a list containing one HLL object with keys ['key%s' % str(i)_
→for i in range(5000, 15000)].
# Find the count of keys in the union of HLL bin "d" and all HLLs in values._
→(Should be around 15000)
expr = HLLGetUnionCount(values, HLLBin("d")).compile()
```

```
class aerospike_helpers.expressions.hll.HLLMayContain(list:  
    Union[aerospike_helpers.expressions.resources._Base  
        List[Any]], bin:  
    Union[aerospike_helpers.expressions.resources._Base  
        str])
```

Create an expression that checks if the HLL bin contains any keys in list.

```
__init__(list: Union[aerospike_helpers.expressions.resources._BaseExpr, List[Any]], bin:  
    Union[aerospike_helpers.expressions.resources._BaseExpr, str])
```

Create an expression that checks if the HLL bin contains any keys in list.

Parameters

- **list** (*TypeListValue*) – A list expression of keys to check if the HLL may contain them.
- **bin** (*TypeBinName*) – Integer bin, a hll bin name or bin expression to read from.

Returns 1 if bin contains any key in list, 0 otherwise.

Example:

```
# Check if HLL bin "d" contains any of the keys in `list`.  
expr = HLLMayContain(["key1", "key2", "key3"], HLLBin("d")).compile()
```

aerospike_helpers.expressions.resourcesmodule

Resources used by all expressions.

```
class aerospike_helpers.expressions.resources.ResultType
```

Flags used to indicate expression value_type.

```
BOOLEAN = 1  
INTEGER = 2  
STRING = 3  
LIST = 4  
MAP = 5  
BLOB = 6  
FLOAT = 7  
GEOJSON = 8  
HLL = 9
```

1.8.1.3 aerospike_helpers.cdt_ctx module

Note: Requires server version >= 4.6.0

Helper functions to generate complex data type context (cdt_ctx) objects for use with operations on nested CDTs (list, map, etc).

Example:

```

from __future__ import print_function
import aerospike
from aerospike import exception as ex
from aerospike_helpers import cdt_ctx
from aerospike_helpers.operations import map_operations
from aerospike_helpers.operations import list_operations
import sys

# Configure the client.
config = {"hosts": [("127.0.0.1", 3000)]}

# Create a client and connect it to the cluster.
try:
    client = aerospike.client(config).connect()
except ex.ClientError as e:
    print("Error: {} [{1}]".format(e.msg, e.code))
    sys.exit(1)

key = ("test", "demo", "foo")
nested_list = [{"name": "John", "id": 100}, {"name": "Bill", "id": 200}]
nested_list_bin_name = "nested_list"

# Write the record.
try:
    client.put(key, {nested_list_bin_name: nested_list})
except ex.RecordError as e:
    print("Error: {} [{1}]".format(e.msg, e.code))

# EXAMPLE 1: read a value from the map nested at list index 1.
try:
    ctx = [cdt_ctx.cdt_ctx_list_index(1)]

    ops = [
        map_operations.map_get_by_key(
            nested_list_bin_name, "id", aerospike.MAP_RETURN_VALUE, ctx
        )
    ]

    _, _, result = client.operate(key, ops)
    print("EXAMPLE 1, id is: ", result)
except ex.ClientError as e:
    print("Error: {} [{1}]".format(e.msg, e.code))
    sys.exit(1)

# EXAMPLE 2: write a new nested map at list index 2 and get the value at its 'name' ↩
# key.
# NOTE: The map is appended to the list, then the value is read using the ctx.
try:
    new_map = {"name": "Cindy", "id": 300}

    ctx = [cdt_ctx.cdt_ctx_list_index(2)]

    ops = [
        list_operations.list_append(nested_list_bin_name, new_map),
        map_operations.map_get_by_key(
            nested_list_bin_name, "name", aerospike.MAP_RETURN_VALUE, ctx
        ),
    ],

```

(continues on next page)

(continued from previous page)

```

]

_, _, result = client.operate(key, ops)
print("EXAMPLE 2, name is: ", result)
except ex.ClientError as e:
    print("Error: {} [{}].format(e.msg, e.code))")
    sys.exit(1)

# Cleanup and close the connection to the Aerospike cluster.
client.remove(key)
client.close()

"""
EXPECTED OUTPUT:
EXAMPLE 1, id is: {'nested_list': 200}
EXAMPLE 2, name is: {'nested_list': 'Cindy'}
"""

```

`aerospike_helpers.cdt_ctx.cdt_ctx_list_index(index)`

Creates a nested cdt_ctx object for use with list or map operations.

The cdt_ctx object is initialized to lookup an object in a list by index. If the index is negative, the lookup starts backwards from the end of the list. If it is out of bounds, a parameter error will be returned.

Parameters `index (int)` – The index to look for in the list.

Returns A cdt_ctx object, a list of these is usable with list and map operations.

`aerospike_helpers.cdt_ctx.cdt_ctx_list_index_create(index: int, order: int = <MagicMock id='140171718694032'>, pad: bool = False) → aerospike_helpers.cdt_ctx.cdt_ctx`

Creates a nested cdt_ctx object for use with list or map operations.

Create a list with the given sort order at the given index.

Parameters

- `key (object)` – The index to create the list at.
- `order (int)` – The sort order to create the list with. One of `list sort orders`. Default == `aerospike.LIST_UNORDERED`
- `pad (Bool)` – If index is out of bounds and pad is True, the list will be created at index and empty list elements inserted behind it. Pad is only compatible with unordered lists.

Returns A cdt_ctx object, a list of these is usable with list and map operations.

`aerospike_helpers.cdt_ctx.cdt_ctx_list_rank(rank)`

Creates a nested cdt_ctx object for use with list or map operations.

The cdt_ctx object is initialized to lookup an object in a list by rank. If the rank is negative, the lookup starts backwards from the largest rank value.

Parameters `rank (int)` – The rank to look for in the list.

Returns A cdt_ctx object, a list of these is usable with list and map operations.

`aerospike_helpers.cdt_ctx.cdt_ctx_list_value(value)`

Creates a nested cdt_ctx object for use with list or map operations.

The cdt_ctx object is initialized to lookup an object in a list by value.

Parameters `value` (*object*) – The value to look for in the list.

Returns A cdt_ctx object, a list of these is usable with list and map operations.

`aerospike_helpers.cdt_ctx.cdt_ctx_map_index(index)`

Creates a nested cdt_ctx object for use with list or map operations.

The cdt_ctx object is initialized to lookup an object in a map by index. If the index is negative, the lookup starts backwards from the end of the map. If it is out of bounds, a parameter error will be returned.

Parameters `index` (*int*) – The index to look for in the map.

Returns A cdt_ctx object, a list of these is usable with list and map operations.

`aerospike_helpers.cdt_ctx.cdt_ctx_map_key(key)`

Creates a nested cdt_ctx object for use with list or map operations.

The cdt_ctx object is initialized to lookup an object in a map by key.

Parameters `key` (*object*) – The key to look for in the map.

Returns A cdt_ctx object, a list of these is usable with list and map operations.

`aerospike_helpers.cdt_ctx.cdt_ctx_map_key_create(key: any, order: int = <MagicMock id='140171718272272'>) → aerospike_helpers.cdt_ctx._cdt_ctx`

Creates a nested cdt_ctx object for use with list or map operations.

Create a map with the given sort order at the given key.

Parameters

- **key** (*object*) – The key to create the map at.
- **order** (*int*) – The sort order to create the map with. One of the aerospike *map sort orders*. Default == aerospike.MAP_UNORDERED

Returns A cdt_ctx object, a list of these is usable with list and map operations.

`aerospike_helpers.cdt_ctx.cdt_ctx_map_rank(rank)`

Creates a nested cdt_ctx object for use with list or map operations.

The cdt_ctx object is initialized to lookup an object in a map by index. If the rank is negative, the lookup starts backwards from the largest rank value.

Parameters `rank` (*int*) – The rank to look for in the map.

Returns A cdt_ctx object, a list of these is usable with list and map operations.

`aerospike_helpers.cdt_ctx.cdt_ctx_map_value(value)`

Creates a nested cdt_ctx object for use with list or map operations.

The cdt_ctx object is initialized to lookup an object in a map by value.

Parameters `value` (*object*) – The value to look for in the map.

Returns A cdt_ctx object, a list of these is usable with list and map operations.

1.9 GeoJSON Class — GeoJSON

1.9.1 GeoJSON

```
class aerospike.GeoJSON
```

Starting with version 3.7.0, the Aerospike server supports storing GeoJSON data. A Geo2DSphere index can be

built on a bin which contains GeoJSON data, enabling queries for the points contained within given shapes using `geo_within_geojson_region()` and `geo_within_radius()`, and for the regions which contain a point using `geo_contains_geojson_point()` and `geo_contains_point()`.

On the client side, wrapping geospatial data in an instance of the `aerospike.GeoJSON` class enables serialization of the data into the correct type during write operation, such as `put()`. On reading a record from the server, bins with geospatial data it will be deserialized into a `GeoJSON` instance.

See also:

Geospatial Index and Query.

```
from __future__ import print_function
import aerospike
from aerospike import GeoJSON

config = { 'hosts': [ ('127.0.0.1', 3000)]}
client = aerospike.client(config).connect()
client.index_geo2dsphere_create('test', 'pads', 'loc', 'pads_loc_geo')
# Create GeoJSON point using WGS84 coordinates.
latitude = 28.608389
longitude = -80.604333
loc = GeoJSON({'type': "Point",
               'coordinates': [longitude, latitude]})
print(loc)
# Alternatively create the GeoJSON point from a string
loc = aerospike.geojson('{"type": "Point", "coordinates": [-80.604333, 28.608389]}')
# Create a user record.
bins = {'pad_id': 1,
        'loc': loc}

# Store the record.
client.put(('test', 'pads', 'launchpad1'), bins)

# Read the record.
(k, m, b) = client.get(('test', 'pads', 'launchpad1'))
print(b)
client.close()
```

class `GeoJSON`(`[geo_data]`)

Optionally initializes an object with a GeoJSON `str` or a `dict` of geospatial data.

`wrap(geo_data)`

Sets the geospatial data of the `GeoJSON` wrapper class.

Parameters `geo_data` (`dict`) – a `dict` representing the geospatial data.

`unwrap() → dict` of geospatial data

Gets the geospatial data contained in the `GeoJSON` class.

Returns a `dict` representing the geospatial data.

`loads(raw_geo)`

Sets the geospatial data of the `GeoJSON` wrapper class from a GeoJSON string.

Parameters `raw_geo` (`str`) – a GeoJSON string representation.

`dumps() → a GeoJSON string`

Gets the geospatial data contained in the `GeoJSON` class as a GeoJSON string.

Returns a GeoJSON `str` representing the geospatial data.

New in version 1.0.53.

1.10 Data_Mapping — Python Data Mappings

How Python types map to server types

Note: By default, the `aerospike.Client` maps the supported types `int`, `str`, `float`, `bytarray`, `list`, `dict` to matching aerospike server `types` (`int`, `string`, `double`, `blob`, `list`, `map`). When an unsupported type is encountered, the module uses `cPickle` to serialize and deserialize the data, storing it into a blob of type ‘Python’ (`AS_BYTES PYTHON`).

The functions `set_serializer()` and `set_deserializer()` allow for user-defined functions to handle serialization, instead. The user provided function will be run instead of `cPickle`. The serialized data is stored as type (`AS_BYTES_BLOB`). This type allows the storage of binary data readable by Aerospike Clients in other languages. The `serialization` config param of `aerospike.client()` registers an instance-level pair of functions that handle serialization.

Unless a user specified serializer has been provided, all other types will be stored as Python specific bytes. Python specific bytes may not be readable by Aerospike Clients for other languages.

The following table shows which Python types map directly to Aerospike server types.

Python Type	Server type
<code>int</code>	<code>integer</code>
<code>long</code>	<code>integer</code>
<code>str</code>	<code>string</code>
<code>unicode</code>	<code>string</code>
<code>float</code>	<code>double</code>
<code>dict</code>	<code>map</code>
<code>list</code>	<code>list</code>
<code>bytarray</code>	<code>blob</code>
<code>aerospike.GeoJSON</code>	<code>GeoJSON</code>

It is possible to nest these datatypes. For example a list may contain a dictionary, or a dictionary may contain a list as a value.

Note: Unless a user specified serializer has been provided, all other types will be stored as Python specific bytes. Python specific bytes may not be readable by Aerospike Clients for other languages.

CHAPTER 2

Indices and tables

- genindex
- modindex
- search

Python Module Index

a

aerospike (*64-bit Linux and OS X*), 3
aerospike.exception (*64-bit Linux and OS X*),
 138
aerospike.predexp (*64-bit Linux and OS X*), 127
aerospike.predicates (*64-bit Linux and OS X*),
 121
aerospike_helpers, 143
aerospike_helpers.cdt_ctx, 256
aerospike_helpers.expressions.base, 189
aerospike_helpers.expressions.bitwise,
 244
aerospike_helpers.expressions.hll, 252
aerospike_helpers.expressions.list, 198
aerospike_helpers.expressions.map, 219
aerospike_helpers.expressions.resources,
 256
aerospike_helpers.operations.bitwise_operations,
 173
aerospike_helpers.operations.hll_operations,
 181
aerospike_helpers.operations.list_operations,
 144
aerospike_helpers.operations.map_operations,
 158
aerospike_helpers.operations.operations,
 143

Symbols

<code>__init__()</code> (<i>aerospike_helpers.expressions.base.And method</i>), 189	<code>__init__()</code> (<i>aerospike_helpers.expressions.base.KeyStr method</i>), 194
<code>__init__()</code> (<i>aerospike_helpers.expressions.base.BinExists method</i>), 189	<code>__init__()</code> (<i>aerospike_helpers.expressions.base.LE method</i>), 194
<code>__init__()</code> (<i>aerospike_helpers.expressions.base.BinType method</i>), 189	<code>__init__()</code> (<i>aerospike_helpers.expressions.base.LT method</i>), 195
<code>__init__()</code> (<i>aerospike_helpers.expressions.base.BlobBin method</i>), 190	<code>__init__()</code> (<i>aerospike_helpers.expressions.base.LastUpdateTime method</i>), 195
<code>__init__()</code> (<i>aerospike_helpers.expressions.base.CmpGeo method</i>), 190	<code>__init__()</code> (<i>aerospike_helpers.expressions.base.ListBin method</i>), 195
<code>__init__()</code> (<i>aerospike_helpers.expressions.base.CmpRegex method</i>), 190	<code>__init__()</code> (<i>aerospike_helpers.expressions.base.MapBin method</i>), 196
<code>__init__()</code> (<i>aerospike_helpers.expressions.base.DeviceSize method</i>), 191	<code>__init__()</code> (<i>aerospike_helpers.expressions.base.NE method</i>), 196
<code>__init__()</code> (<i>aerospike_helpers.expressions.base.DigestMod method</i>), 191	<code>__init__()</code> (<i>aerospike_helpers.expressions.base.Not method</i>), 196
<code>__init__()</code> (<i>aerospike_helpers.expressions.base.Eq method</i>), 191	<code>__init__()</code> (<i>aerospike_helpers.expressions.base.Or method</i>), 196
<code>__init__()</code> (<i>aerospike_helpers.expressions.base.FloatBin method</i>), 191	<code>__init__()</code> (<i>aerospike_helpers.expressions.base.SetName method</i>), 197
<code>__init__()</code> (<i>aerospike_helpers.expressions.base.GE method</i>), 192	<code>__init__()</code> (<i>aerospike_helpers.expressions.base.SinceUpdateTime method</i>), 197
<code>__init__()</code> (<i>aerospike_helpers.expressions.base.GT method</i>), 192	<code>__init__()</code> (<i>aerospike_helpers.expressions.base.StrBin method</i>), 197
<code>__init__()</code> (<i>aerospike_helpers.expressions.base.GeoBin method</i>), 192	<code>__init__()</code> (<i>aerospike_helpers.expressions.base.TTL method</i>), 197
<code>__init__()</code> (<i>aerospike_helpers.expressions.base.HLLBin method</i>), 193	<code>__init__()</code> (<i>aerospike_helpers.expressions.base.VoidTime method</i>), 198
<code>__init__()</code> (<i>aerospike_helpers.expressions.base.IntBin method</i>), 193	<code>__init__()</code> (<i>aerospike_helpers.expressions.bitwise.BitAdd method</i>), 244
<code>__init__()</code> (<i>aerospike_helpers.expressions.base.IsTombstone method</i>), 193	<code>__init__()</code> (<i>aerospike_helpers.expressions.bitwise.BitAnd method</i>), 244
<code>__init__()</code> (<i>aerospike_helpers.expressions.base.KeyBlob method</i>), 193	<code>__init__()</code> (<i>aerospike_helpers.expressions.bitwise.BitCount method</i>), 245
<code>__init__()</code> (<i>aerospike_helpers.expressions.base.KeyExists method</i>), 194	<code>__init__()</code> (<i>aerospike_helpers.expressions.bitwise.BitGet method</i>), 245
<code>__init__()</code> (<i>aerospike_helpers.expressions.base.KeyInt method</i>), 194	<code>__init__()</code> (<i>aerospike_helpers.expressions.bitwise.BitGetInt method</i>), 246
	<code>__init__()</code> (<i>aerospike_helpers.expressions.bitwise.BitInsert method</i>), 246

`__init__()` (*aerospike_helpers.expressions.bitwise.BitLeftScan*) (*aerospike_helpers.expressions.list.ListGetByRankRange*
method), 247
`__init__()` (*aerospike_helpers.expressions.bitwise.BitLeftShift*) (*aerospike_helpers.expressions.list.ListGetByRankRangeToB*
method), 247
`__init__()` (*aerospike_helpers.expressions.bitwise.BitNot*) (*aerospike_helpers.expressions.list.ListGetByValue*
method), 248
`__init__()` (*aerospike_helpers.expressions.bitwise.BitOr*) (*aerospike_helpers.expressions.list.ListGetByValueList*
method), 248
`__init__()` (*aerospike_helpers.expressions.bitwise.BitRemove*) (*aerospike_helpers.expressions.list.ListGetByValueRange*
method), 248
`__init__()` (*aerospike_helpers.expressions.bitwise.BitResize*) (*aerospike_helpers.expressions.list.ListGetByValueRelRank*
method), 249
`__init__()` (*aerospike_helpers.expressions.bitwise.BitRightScan*) (*aerospike_helpers.expressions.list.ListGetByValueRelRank*
method), 249
`__init__()` (*aerospike_helpers.expressions.bitwise.BitRightShift*) (*aerospike_helpers.expressions.list.ListIncrement*
method), 250
`__init__()` (*aerospike_helpers.expressions.bitwise.BitSet*) (*aerospike_helpers.expressions.list.ListInsert*
method), 250
`__init__()` (*aerospike_helpers.expressions.bitwise.BitSetInt*) (*aerospike_helpers.expressions.list.ListInsertItems*
method), 251
`__init__()` (*aerospike_helpers.expressions.bitwise.BitSubtract*) (*aerospike_helpers.expressions.list.ListRemoveByIndex*
method), 251
`__init__()` (*aerospike_helpers.expressions.bitwise.BitXor*) (*aerospike_helpers.expressions.list.ListRemoveByIndexRang*
method), 252
`__init__()` (*aerospike_helpers.expressions.hll.HLLAdd*) (*aerospike_helpers.expressions.list.ListRemoveByIndexRang*
method), 253
`__init__()` (*aerospike_helpers.expressions.hll.HLLDescribe*) (*aerospike_helpers.expressions.list.ListRemoveByRank*
method), 253
`__init__()` (*aerospike_helpers.expressions.hll.HLLGetCount*) (*aerospike_helpers.expressions.list.ListRemoveByRankRang*
method), 253
`__init__()` (*aerospike_helpers.expressions.hll.HLLGetIntersectionCount*) (*aerospike_helpers.expressions.list.ListRemoveByRankRang*
method), 254
`__init__()` (*aerospike_helpers.expressions.hll.HLLGetSimilarity*) (*aerospike_helpers.expressions.list.ListRemoveByValue*
method), 254
`__init__()` (*aerospike_helpers.expressions.hll.HLLGetUnion*) (*aerospike_helpers.expressions.list.ListRemoveByValueList*
method), 255
`__init__()` (*aerospike_helpers.expressions.hll.HLLGetUnionCount*) (*aerospike_helpers.expressions.list.ListRemoveByValueRang*
method), 255
`__init__()` (*aerospike_helpers.expressions.hll.HLLMayContain*) (*aerospike_helpers.expressions.list.ListRemoveByValueRelR*
method), 256
`__init__()` (*aerospike_helpers.expressions.list.ListAppend*) (*aerospike_helpers.expressions.list.ListRemoveByValueRelR*
method), 198
`__init__()` (*aerospike_helpers.expressions.list.ListAppendItem*) (*aerospike_helpers.expressions.list.ListSet*
method), 199
`__init__()` (*aerospike_helpers.expressions.list.ListClear*) (*aerospike_helpers.expressions.list.ListSize*
method), 199
`__init__()` (*aerospike_helpers.expressions.list.ListGetByIndex*) (*aerospike_helpers.expressions.list.ListSort*
method), 200
`__init__()` (*aerospike_helpers.expressions.list.ListGetByIndexRange*) (*aerospike_helpers.expressions.map.MapClear*
method), 201
`__init__()` (*aerospike_helpers.expressions.list.ListGetByIndexRangeIfEnd*) (*aerospike_helpers.expressions.map.MapGetByIndex*
method), 201
`__init__()` (*aerospike_helpers.expressions.list.ListGetByRank*) (*aerospike_helpers.expressions.map.MapGetByIndexRange*
method), 202

`__init__()` (*aerospike_helpers.expressions.map.MapGetByIndexRangeToEnd*) (*aerospike_helpers.expressions.map.MapRemoveByRankRange*)
method), 221
`__init__()` (*aerospike_helpers.expressions.map.MapGetByKey*) (*aerospike_helpers.expressions.map.MapRemoveByValue*)
method), 221
`__init__()` (*aerospike_helpers.expressions.map.MapGetByKeyList*) (*aerospike_helpers.expressions.map.MapRemoveByValueList*)
method), 222
`__init__()` (*aerospike_helpers.expressions.map.MapGetByKeyRange*) (*aerospike_helpers.expressions.map.MapRemoveByValueRange*)
method), 223
`__init__()` (*aerospike_helpers.expressions.map.MapGetByKeyRelIndexRange*) (*aerospike_helpers.expressions.map.MapRemoveByValueRange*)
method), 224
`__init__()` (*aerospike_helpers.expressions.map.MapGetByKeyRelIndexRangeTillEnd*) (*aerospike_helpers.expressions.map.MapRemoveByValueRange*)
method), 225
`__init__()` (*aerospike_helpers.expressions.map.MapGetByRank*) (*aerospike_helpers.expressions.map.MapSize*)
method), 226
`__init__()` (*aerospike_helpers.expressions.map.MapGetByRankRange*) (*in module aerospike*), 35
method), 226
`__init__()` (*aerospike_helpers.expressions.map.MapGetByRankRangeToEnd*)
method), 227
`add_ops()` (*aerospike.Query* method), 116
`__init__()` (*aerospike_helpers.expressions.map.MapGetByValue*)
`add_ops()` (*aerospike.Scan* method), 103
method), 228
`Admin Operations`, 85
`__init__()` (*aerospike_helpers.expressions.map.MapGetByValueList*)
`admin_change_password()` (*aerospike.Client* method), 87
method), 228
`__init__()` (*aerospike_helpers.expressions.map.MapGetByValueRange*)
`admin_create_role()` (*aerospike.Client* method), 85
method), 229
`__init__()` (*aerospike_helpers.expressions.map.MapGetByValueRelRankRange*)
`admin_create_range()` (*aerospike.Client* method), 87
method), 230
`__init__()` (*aerospike_helpers.expressions.map.MapGetByValueRelRankRangeToEnd*)
`admin_drop_role()` (*aerospike.Client* method), 86
method), 231
`admin_drop_user()` (*aerospike.Client* method), 87
`__init__()` (*aerospike_helpers.expressions.map.MapIncrement*)
`admin_grant_privileges()` (*aerospike.Client* method), 86
method), 232
`__init__()` (*aerospike_helpers.expressions.map.MapPut*)
`admin_grant_roles()` (*aerospike.Client* method), 87
method), 232
`__init__()` (*aerospike_helpers.expressions.map.MapPutItems*)
`admin_query_role()` (*aerospike.Client* method), 86
method), 233
`admin_query_roles()` (*aerospike.Client* method),
`__init__()` (*aerospike_helpers.expressions.map.MapRemoveByIndex*)
method), 233
`admin_query_user()` (*aerospike.Client* method), 88
`__init__()` (*aerospike_helpers.expressions.map.MapRemoveByIndexRange*)
`admin_query_users()` (*aerospike.Client* method), 88
`__init__()` (*aerospike_helpers.expressions.map.MapRemoveByIndexRangeToEnd*)
`admin_revoke_privileges()` (*aerospike.Client* method), 86
method), 235
`__init__()` (*aerospike_helpers.expressions.map.MapRemoveByKey*)
`admin_revoke_roles()` (*aerospike.Client* method), 87
method), 235
`__init__()` (*aerospike_helpers.expressions.map.MapRemoveByKeyList*)
`admin_set_password()` (*aerospike.Client* method), 87
method), 236
`__init__()` (*aerospike_helpers.expressions.map.MapRemoveByKeyRange*)
aerospike (module), 3
method), 236
`__init__()` (*aerospike_helpers.expressions.map.MapRemoveByKeyRelIndexRange*)
aerospike (module), 138
method), 237
`aerospike.LIST_SORT_DEFAULT` (*in module aerospike*),
`__init__()` (*aerospike_helpers.expressions.map.MapRemoveByKeyRelIndexRangeToEnd*)
aerospike.LIST_SORT_DROP_DUPLICATES (*in module aerospike*), 138
method), 238
`__init__()` (*aerospike_helpers.expressions.map.MapRemoveByRank*)
aerospike.predexp (module), 127
method), 238
`__init__()` (*aerospike_helpers.expressions.map.MapRemoveByRankRange*)
aerospike.predicates (module), 121
method), 239
`aerospike_helpers (module)`, 143

aerospike_helpers.cdt_ctx (*module*), 256
aerospike_helpers.expressions.base (*module*), 189
aerospike_helpers.expressions.bitwise (*module*), 244
aerospike_helpers.expressions.hll (*module*), 252
aerospike_helpers.expressions.list (*module*), 198
aerospike_helpers.expressions.map (*module*), 219
aerospike_helpers.expressions.resources (*module*), 256
aerospike_helpers.operations.bitwise_operations (*module*), 173
aerospike_helpers.operations.hll_operations (*module*), 181
aerospike_helpers.operations.list_operations (*module*), 144
aerospike_helpers.operations.map_operations (*module*), 158
aerospike_helpers.operations.operations (*module*), 143
AerospikeError, 138
AlwaysForbidden, 139
And (*class in aerospike_helpers.expressions.base*), 189
append () (*aerospike.Client method*), 50
append () (*in module aerospike_helpers.operations.operations*), 143
apply () (*aerospike.Client method*), 74
apply () (*aerospike.Query method*), 114
apply () (*aerospike.Scan method*), 103
AS_BYTES_BLOB (*in module aerospike*), 34
AS_BYTES_CSHARP (*in module aerospike*), 34
AS_BYTES_DOUBLE (*in module aerospike*), 34
AS_BYTES_ERLANG (*in module aerospike*), 34
AS_BYTES_GEOJSON (*in module aerospike*), 35
AS_BYTES_HLL (*in module aerospike*), 34
AS_BYTES_INTEGER (*in module aerospike*), 34
AS_BYTES_JAVA (*in module aerospike*), 34
AS_BYTES_LIST (*in module aerospike*), 35
AS_BYTES_MAP (*in module aerospike*), 35
AS_BYTES_PHP (*in module aerospike*), 34
AS_BYTES_PYTHON (*in module aerospike*), 34
AS_BYTES_RUBY (*in module aerospike*), 34
AS_BYTES_STRING (*in module aerospike*), 34
AS_BYTES_TYPE_MAX (*in module aerospike*), 35
AS_BYTES_UNDEF (*in module aerospike*), 34
AUTH_EXTERNAL (*in module aerospike*), 29
AUTH_EXTERNAL_INSECURE (*in module aerospike*), 29
AUTH_INTERNAL (*in module aerospike*), 29

B

Batch Operations, 45
between () (*in module aerospike.predicates*), 121
bin (*aerospike.exception.RecordError attribute*), 139
BinExists (*class in aerospike_helpers.expressions.base*), 189
BinIncompatibleType, 140
BinNameError, 140
BinType (*class in aerospike_helpers.expressions.base*), 189
bit_add () (*in module aerospike_helpers.operations.bitwise_operations*), 175
bit_and () (*in module aerospike_helpers.operations.bitwise_operations*), 176
bit_count () (*in module aerospike_helpers.operations.bitwise_operations*), 176
bit_get () (*in module aerospike_helpers.operations.bitwise_operations*), 176
bit_get_int () (*in module aerospike_helpers.operations.bitwise_operations*), 177
bit_insert () (*in module aerospike_helpers.operations.bitwise_operations*), 177
bit_lscan () (*in module aerospike_helpers.operations.bitwise_operations*), 177
bit_lshift () (*in module aerospike_helpers.operations.bitwise_operations*), 178
bit_not () (*in module aerospike_helpers.operations.bitwise_operations*), 178
bit_or () (*in module aerospike_helpers.operations.bitwise_operations*), 178
BIT_OVERFLOW_FAIL (*in module aerospike*), 33
BIT_OVERFLOW_SATURATE (*in module aerospike*), 33
BIT_OVERFLOW_WRAP (*in module aerospike*), 33
bit_remove () (*in module aerospike_helpers.operations.bitwise_operations*), 179
bit_resize () (*in module aerospike_helpers.operations.bitwise_operations*), 179
BIT_RESIZE_DEFAULT (*in module aerospike*), 33
BIT_RESIZE_FROM_FRONT (*in module aerospike*), 33
BIT_RESIZE_GROW_ONLY (*in module aerospike*), 33
BIT_RESIZE_SHRINK_ONLY (*in module aerospike*), 33

bit_rscan()	(in module <code>aerospike_helpers.operations.bitwise_operations</code>),	<code>BitXor</code> (<i>class in aerospike_helpers.expressions.bitwise</i>), 252
179		BLOB (<i>aerospike_helpers.expressions.resources.ResultType attribute</i>), 256
bit_rshift()	(in module <code>aerospike_helpers.operations.bitwise_operations</code>)	<code>BlobBin</code> (<i>class in aerospike_helpers.expressions.base</i>), 190
180		
bit_set()	(in module <code>aerospike_helpers.operations.bitwise_operations</code>),	<code>BOOLEAN</code> (<i>aerospike_helpers.expressions.resources.ResultType attribute</i>), 256
180		
bit_subtract()	(in module <code>aerospike_helpers.operations.bitwise_operations</code>)	C
180		
BIT_WRITE_CREATE_ONLY	(in module <code>aerospike</code>), 33	<code>calc_digest()</code> (<i>in module aerospike</i>), 10
BIT_WRITE_DEFAULT	(in module <code>aerospike</code>), 33	<code>cdt_ctx_list_index()</code> (<i>in module aerospike_helpers.cdt_ctx</i>), 258
BIT_WRITE_NO_FAIL	(in module <code>aerospike</code>), 33	<code>cdt_ctx_list_index_create()</code> (<i>in module aerospike_helpers.cdt_ctx</i>), 258
BIT_WRITE_PARTIAL	(in module <code>aerospike</code>), 33	<code>cdt_ctx_list_rank()</code> (<i>in module aerospike_helpers.cdt_ctx</i>), 258
BIT_WRITE_UPDATE_ONLY	(in module <code>aerospike</code>), 33	<code>cdt_ctx_list_value()</code> (<i>in module aerospike_helpers.cdt_ctx</i>), 258
bit_xor()	(in module <code>aerospike_helpers.operations.bitwise_operations</code>),	<code>cdt_ctx_map_index()</code> (<i>in module aerospike_helpers.cdt_ctx</i>), 259
181		<code>cdt_ctx_map_key()</code> (<i>in module aerospike_helpers.cdt_ctx</i>), 259
BitAdd	(<i>class in aerospike_helpers.expressions.bitwise</i>), 244	<code>cdt_ctx_map_key_create()</code> (<i>in module aerospike_helpers.cdt_ctx</i>), 259
BitAnd	(<i>class in aerospike_helpers.expressions.bitwise</i>), 244	<code>cdt_ctx_map_rank()</code> (<i>in module aerospike_helpers.cdt_ctx</i>), 259
BitCount	(<i>class in aerospike_helpers.expressions.bitwise</i>), 245	<code>cdt_ctx_map_value()</code> (<i>in module aerospike_helpers.cdt_ctx</i>), 259
BitGet	(<i>class in aerospike_helpers.expressions.bitwise</i>), 245	
BitGetInt	(<i>class in aerospike_helpers.expressions.bitwise</i>), 246	<code>CDTInfinite()</code> (<i>in module aerospike</i>), 9
BitInsert	(<i>class in aerospike_helpers.expressions.bitwise</i>), 246	<code>CDTWildcard()</code> (<i>in module aerospike</i>), 9
BitLeftScan	(<i>class in aerospike_helpers.expressions.bitwise</i>), 246	<code>Client</code> (<i>class in aerospike</i>), 37, 39, 45, 49, 51, 52, 57, 68, 72, 73, 78, 82, 85
BitLeftShift	(<i>class in aerospike_helpers.expressions.bitwise</i>), 247	<code>client()</code> (<i>in module aerospike</i>), 3
BitNot	(<i>class in aerospike_helpers.expressions.bitwise</i>), 247	<code>ClientError</code> , 138
BitOr	(<i>class in aerospike_helpers.expressions.bitwise</i>), 248	<code>close()</code> (<i>aerospike.Client method</i>), 38
BitRemove	(<i>class in aerospike_helpers.expressions.bitwise</i>), 248	<code>ClusterChangeError</code> , 140
BitResize	(<i>class in aerospike_helpers.expressions.bitwise</i>), 249	<code>ClusterError</code> , 140
BitRightScan	(<i>class in aerospike_helpers.expressions.bitwise</i>), 249	<code>CmpGeo</code> (<i>class in aerospike_helpers.expressions.base</i>), 190
BitRightShift	(<i>class in aerospike_helpers.expressions.bitwise</i>), 250	<code>CmpRegex</code> (<i>class in aerospike_helpers.expressions.base</i>), 190
BitSet	(<i>class in aerospike_helpers.expressions.bitwise</i>), 250	<code>code</code> (<i>aerospike.exception.AerospikeError attribute</i>), 138
BitSetInt	(<i>class in aerospike_helpers.expressions.bitwise</i>), 251	<code>connect()</code> (<i>aerospike.Client method</i>), 37
BitSubtract	(<i>class in aerospike_helpers.expressions.bitwise</i>), 251	<code>contains()</code> (<i>in module aerospike.predicates</i>), 125
		D
		<code>delete()</code> (<i>in module aerospike_helpers.operations.operations</i>), 143
		<code>DeviceOverload</code> , 139
		<code>DeviceSize</code> (<i>class in aerospike_helpers.expressions.base</i>), 191

DigestMod	(class aerospike_helpers.expressions.base), 191	in	geojson_var() (<i>in module aerospike.predexp</i>), 131
dumps ()	(<i>aerospike.GeoJSON method</i>), 260		geojson_within() (<i>in module aerospike.predexp</i>), 137
E			get() (<i>aerospike.Client method</i>), 42
ElementExistsError	, 139		get_key_digest() (<i>aerospike.Client method</i>), 44
ElementNotFoundError	, 139		get_many() (<i>aerospike.Client method</i>), 45
Eq	(<i>class in aerospike_helpers.expressions.base</i>), 191		get_nodes() (<i>aerospike.Client method</i>), 78
equals ()	(<i>in module aerospike.predicates</i>), 121		GT (<i>class in aerospike_helpers.expressions.base</i>), 192
execute_background ()	(<i>aerospike.Query method</i>), 117		
execute_background ()	(<i>aerospike.Scan method</i>), 107		
exists ()	(<i>aerospike.Client method</i>), 41		
exists_many ()	(<i>aerospike.Client method</i>), 47		
ExpiredPassword	, 140		
F			
file	(<i>aerospike.exception.AerospikeError attribute</i>), 138		HLL (<i>aerospike_helpers.expressions.resources.ResultType attribute</i>), 256
FilteredOut	, 139		hll_add() (<i>in module aerospike_helpers.operations.hll_operations</i>), 183
FLOAT	(<i>aerospike_helpers.expressions.resources.ResultType attribute</i>), 256		hll_describe() (<i>in module aerospike_helpers.operations.hll_operations</i>), 184
FloatBin	(<i>class in aerospike_helpers.expressions.base</i>), 191		hll_fold() (<i>in module aerospike_helpers.operations.hll_operations</i>), 184
ForbiddenError	, 139		hll_get_count() (<i>in module aerospike_helpers.operations.hll_operations</i>), 184
ForbiddenPassword	, 140		hll_get_intersect_count() (<i>in module aerospike_helpers.operations.hll_operations</i>), 184
foreach ()	(<i>aerospike.Query method</i>), 113		hll_get_similarity() (<i>in module aerospike_helpers.operations.hll_operations</i>), 184
foreach ()	(<i>aerospike.Scan method</i>), 106		hll_get_union() (<i>in module aerospike_helpers.operations.hll_operations</i>), 184
func	(<i>aerospike.exception.UDFError attribute</i>), 141		hll_get_union_count() (<i>in module aerospike_helpers.operations.hll_operations</i>), 185
G			hll_init() (<i>in module aerospike_helpers.operations.hll_operations</i>), 185
GE	(<i>class in aerospike_helpers.expressions.base</i>), 192		hll_refresh_count() (<i>in module aerospike_helpers.operations.hll_operations</i>), 185
geo_contains_geojson_point ()	(<i>in module aerospike.predicates</i>), 123		hll_set_union() (<i>in module aerospike_helpers.operations.hll_operations</i>), 185
geo_contains_point ()	(<i>in module aerospike.predicates</i>), 124		HLL_WRITE_ALLOW_FOLD (<i>in module aerospike</i>), 34
geo_within_geojson_region ()	(<i>in module aerospike.predicates</i>), 122		HLL_WRITE_CREATE_ONLY (<i>in module aerospike</i>), 34
geo_within_radius ()	(<i>in module aerospike.predicates</i>), 123		HLL_WRITE_DEFAULT (<i>in module aerospike</i>), 34
GeoBin	(<i>class in aerospike_helpers.expressions.base</i>), 192		HLL_WRITE_NO_FAIL (<i>in module aerospike</i>), 34
geodata ()	(<i>in module aerospike</i>), 13		HLL_WRITE_UPDATE_ONLY (<i>in module aerospike</i>), 34
GEOJSON	(<i>aerospike_helpers.expressions.resources.ResultType attribute</i>), 256		HLLAdd (<i>class in aerospike_helpers.expressions.hll</i>), 252
GeoJSON	(<i>class in aerospike</i>), 259		HLLBin (<i>class in aerospike_helpers.expressions.base</i>), 193
geojson ()	(<i>in module aerospike</i>), 13		
GeoJSON	.GeoJSON (<i>class in aerospike</i>), 260		
geojson_bin ()	(<i>in module aerospike.predexp</i>), 128		
geojson_contains ()	(<i>in module aerospike.predexp</i>), 137		
geojson_value ()	(<i>in module aerospike.predexp</i>), 129		

HLLDescribe (class *aerospike_helpers.expressions.hll*), 253
HLLGetCount (class *aerospike_helpers.expressions.hll*), 253
HLLGetIntersectCount (class *aerospike_helpers.expressions.hll*), 254
HLLGetSimilarity (class *aerospike_helpers.expressions.hll*), 254
HLLGetUnion (class *aerospike_helpers.expressions.hll*), 255
HLLGetUnionCount (class *aerospike_helpers.expressions.hll*), 255
HLLMayContain (class *aerospike_helpers.expressions.hll*), 255

|

IllegalState, 141
in_doubt (*aerospike.exception.AerospikeError* attribute), 138
increment () (*aerospike.Client method*), 51
increment () (in module *aerospike_helpers.operations.operations*), 143
Index Operations, 82
INDEX_GEO2DSPHERE (in module *aerospike*), 35
index_geodspHERE_create () (*aerospike.Client method*), 84
index_integer_create () (*aerospike.Client method*), 82
index_list_create () (*aerospike.Client method*), 83
index_map_keys_create () (*aerospike.Client method*), 83
index_map_values_create () (*aerospike.Client method*), 83
index_name (*aerospike.exception.IndexError* attribute), 140
INDEX_NUMERIC (in module *aerospike*), 35
index_remove () (*aerospike.Client method*), 85
INDEX_STRING (in module *aerospike*), 35
index_string_create () (*aerospike.Client method*), 82
INDEX_TYPE_LIST (in module *aerospike*), 35
INDEX_TYPE_MAPKEYS (in module *aerospike*), 35
INDEX_TYPE_MAPVALUES (in module *aerospike*), 35
IndexError, 140
IndexNotFoundError, 140
IndexNameMaxCount, 140
IndexNameMaxLen, 140
IndexNotFound, 140
IndexNotReadable, 140
IndexOOM, 140
Info Operations, 78
info () (*aerospike.Client method*), 78

in info_all () (*aerospike.Client method*), 79
info_node () (*aerospike.Client method*), 80
in IntBin (class in *aerospike_helpers.expressions.base*), 193
in INTEGER (*aerospike_helpers.expressions.resources.ResultType* attribute), 256
in integer_bin () (in module *aerospike.predexp*), 128
integer_equal () (in module *aerospike.predexp*), 135
in integer_greater () (in module *aerospike.predexp*), 135
in integer_greatereq () (in module *aerospike.predexp*), 135
integer_less () (in module *aerospike.predexp*), 135
integer_lesseq () (in module *aerospike.predexp*), 136
integer_unequal () (in module *aerospike.predexp*), 136
integer_value () (in module *aerospike.predexp*), 129
integer_var () (in module *aerospike.predexp*), 130
InvalidCommand, 141
InvalidCredential, 141
InvalidField, 141
InvalidHostError, 138
InvalidPassword, 141
InvalidPrivilege, 141
InvalidRequest, 139
InvalidRole, 141
InvalidUser, 141
is_connected () (*aerospike.Client method*), 38
IsTombstone (class in *aerospike_helpers.expressions.base*), 193

J

job_info () (*aerospike.Client method*), 77
JOB_QUERY (in module *aerospike*), 30
JOB_SCAN (in module *aerospike*), 30
JOB_STATUS_COMPLETED (in module *aerospike*), 30
JOB_STATUS_INPROGRESS (in module *aerospike*), 30
JOB_STATUS_UNDEF (in module *aerospike*), 30

K

key (*aerospike.exception.RecordError* attribute), 139
KeyBlob (class in *aerospike_helpers.expressions.base*), 193
KeyExists (class in *aerospike_helpers.expressions.base*), 194
KeyInt (class in *aerospike_helpers.expressions.base*), 194
KeyStr (class in *aerospike_helpers.expressions.base*), 194

L	
LastUpdateTime	(class in <i>aerospike_helpers.expressions.base</i>), 195
LE	(class in <i>aerospike_helpers.expressions.base</i>), 194
line	(<i>aerospike.exception.AerospikeError</i> attribute), 138
LIST	(<i>aerospike_helpers.expressions.resources.ResultType</i> attribute), 256
List Operations	, 52
list_append()	(<i>aerospike.Client</i> method), 52
list_append()	(in module <i>aerospike_helpers.operations.list_operations</i>), 144
list_append_items()	(in module <i>aerospike_helpers.operations.list_operations</i>), 145
list_bin()	(in module <i>aerospike.predexp</i>), 128
list_clear()	(<i>aerospike.Client</i> method), 55
list_clear()	(in module <i>aerospike_helpers.operations.list_operations</i>), 145
list_extend()	(<i>aerospike.Client</i> method), 53
list_get()	(<i>aerospike.Client</i> method), 55
list_get()	(in module <i>aerospike_helpers.operations.list_operations</i>), 145
list_get_by_index()	(in module <i>aerospike_helpers.operations.list_operations</i>), 145
list_get_by_index_range()	(in module <i>aerospike_helpers.operations.list_operations</i>), 146
list_get_by_rank()	(in module <i>aerospike_helpers.operations.list_operations</i>), 146
list_get_by_rank_range()	(in module <i>aerospike_helpers.operations.list_operations</i>), 147
list_get_by_value()	(in module <i>aerospike_helpers.operations.list_operations</i>), 147
list_get_by_value_list()	(in module <i>aerospike_helpers.operations.list_operations</i>), 147
list_get_by_value_range()	(in module <i>aerospike_helpers.operations.list_operations</i>), 148
list_get_by_value_rank_range_relative()	(in module <i>aerospike_helpers.operations.list_operations</i>), 148
list_get_range()	(<i>aerospike.Client</i> method), 56
list_get_range()	(in module <i>aerospike_helpers.operations.list_operations</i>), 149
list_increment()	(in module <i>aerospike_helpers.operations.list_operations</i>), 150
list_insert()	(<i>aerospike.Client</i> method), 53
list_insert()	(in module <i>aerospike_helpers.operations.list_operations</i>), 150
list_insert_items()	(<i>aerospike.Client</i> method), 53
list_insert_items()	(in module <i>aerospike_helpers.operations.list_operations</i>), 150
list_iterate_and()	(in module <i>aerospike.predexp</i>), 131
list_iterate_or()	(in module <i>aerospike.predexp</i>), 131
LIST_ORDERED	(in module <i>aerospike</i>), 31
list_pop()	(<i>aerospike.Client</i> method), 54
list_pop()	(in module <i>aerospike_helpers.operations.list_operations</i>), 151
list_pop_range()	(<i>aerospike.Client</i> method), 54
list_pop_range()	(in module <i>aerospike_helpers.operations.list_operations</i>), 151
list_remove()	(<i>aerospike.Client</i> method), 54
list_remove()	(in module <i>aerospike_helpers.operations.list_operations</i>), 151
list_remove_by_index()	(in module <i>aerospike_helpers.operations.list_operations</i>), 152
list_remove_by_index_range()	(in module <i>aerospike_helpers.operations.list_operations</i>), 152
list_remove_by_rank()	(in module <i>aerospike_helpers.operations.list_operations</i>), 153
list_remove_by_rank_range()	(in module <i>aerospike_helpers.operations.list_operations</i>), 153
list_remove_by_value()	(in module <i>aerospike_helpers.operations.list_operations</i>), 153
list_remove_by_value_list()	(in module <i>aerospike_helpers.operations.list_operations</i>), 154
list_remove_by_value_range()	(in module <i>aerospike_helpers.operations.list_operations</i>), 154
list_remove_by_value_rank_range_relative()	(in module <i>aerospike_helpers.operations.list_operations</i>), 155
list_remove_range()	(<i>aerospike.Client</i> method),

		ListGetByRankRange	(class	in
			<i>aerospike_helpers.expressions.list)</i> , 202	
		ListGetByRankRangeToEnd	(class	in
			<i>aerospike_helpers.expressions.list)</i> , 203	
		ListGetByValue	(class	in
			<i>aerospike_helpers.expressions.list)</i> , 204	
		ListGetByValueList	(class	in
			<i>aerospike_helpers.expressions.list)</i> , 205	
		ListGetByValueRange	(class	in
			<i>aerospike_helpers.expressions.list)</i> , 205	
		ListGetByValueRelRankRange	(class	in
			<i>aerospike_helpers.expressions.list)</i> , 206	
		ListGetByValueRelRankRangeToEnd	(class	in
			<i>aerospike_helpers.expressions.list)</i> , 207	
		ListIncrement	(class	in
			<i>aerospike_helpers.expressions.list)</i> , 208	
		ListInsert	(class	in
			<i>aerospike_helpers.expressions.list)</i> , 209	
		ListInsertItems	(class	in
			<i>aerospike_helpers.expressions.list)</i> , 209	
		ListRemoveByIndex	(class	in
			<i>aerospike_helpers.expressions.list)</i> , 210	
		ListRemoveByIndexRange	(class	in
			<i>aerospike_helpers.expressions.list)</i> , 210	
		ListRemoveByIndexRangeToEnd	(class	in
			<i>aerospike_helpers.expressions.list)</i> , 211	
		ListRemoveByRank	(class	in
			<i>aerospike_helpers.expressions.list)</i> , 212	
		ListRemoveByRankRange	(class	in
			<i>aerospike_helpers.expressions.list)</i> , 212	
		ListRemoveByRankRangeToEnd	(class	in
			<i>aerospike_helpers.expressions.list)</i> , 213	
		ListRemoveByValue	(class	in
			<i>aerospike_helpers.expressions.list)</i> , 214	
		ListRemoveByValueList	(class	in
			<i>aerospike_helpers.expressions.list)</i> , 214	
		ListRemoveByValueRange	(class	in
			<i>aerospike_helpers.expressions.list)</i> , 215	
	in	ListRemoveByValueRelRankRange	(class	in
			<i>aerospike_helpers.expressions.list)</i> , 215	
	in	ListRemoveByValueRelRankToEnd	(class	in
			<i>aerospike_helpers.expressions.list)</i> , 216	
		ListSet	(class	in
			<i>aerospike_helpers.expressions.list)</i> ,	
		217		
	in	ListSize	(class	in
			<i>aerospike_helpers.expressions.list)</i> ,	
		218		
	in	ListSort	(class	in
			<i>aerospike_helpers.expressions.list)</i> ,	
		218		
	in	loads()	(<i>aerospike.GeoJSON method</i>)	260
		LOG_LEVEL_DEBUG	(<i>in module aerospike</i>)	35
	in	LOG_LEVEL_ERROR	(<i>in module aerospike</i>)	35
		LOG_LEVEL_INFO	(<i>in module aerospike</i>)	35
	in	LOG_LEVEL_OFF	(<i>in module aerospike</i>)	36
		LOG_LEVEL_TRACE	(<i>in module aerospike</i>)	35

LOG_LEVEL_WARN (*in module aerospike*), 35
LT (*class in aerospike_helpers.expressions.base*), 195
LuaNotFound, 141

M

MAP (*aerospike_helpers.expressions.resources.ResultType attribute*), 256
Map Operations, 57
map_bin () (*in module aerospike.predexp*), 129
map_clear () (*aerospike.Client method*), 60
map_clear () (*in module aerospike_helpers.operations.map_operations*), 158
MAP_CREATE_ONLY (*in module aerospike*), 32
map_decrement () (*aerospike.Client method*), 60
map_decrement () (*in module aerospike_helpers.operations.map_operations*), 158
map_get_by_index () (*aerospike.Client method*), 66
map_get_by_index () (*in module aerospike_helpers.operations.map_operations*), 158
map_get_by_index_range () (*aerospike.Client method*), 67
map_get_by_index_range () (*in module aerospike_helpers.operations.map_operations*), 159
map_get_by_key () (*aerospike.Client method*), 64
map_get_by_key () (*in module aerospike_helpers.operations.map_operations*), 159
map_get_by_key_index_range_relative () (*in module aerospike_helpers.operations.map_operations*), 159
map_get_by_key_list () (*aerospike.Client method*), 65
map_get_by_key_list () (*in module aerospike_helpers.operations.map_operations*), 160
map_get_by_key_range () (*aerospike.Client method*), 65
map_get_by_key_range () (*in module aerospike_helpers.operations.map_operations*), 161
map_get_by_rank () (*aerospike.Client method*), 67
map_get_by_rank () (*in module aerospike_helpers.operations.map_operations*), 161
map_get_by_rank_range () (*aerospike.Client method*), 67
map_get_by_rank_range () (*in module aerospike_helpers.operations.map_operations*), 162
map_get_by_value () (*aerospike.Client method*), 65
map_get_by_value () (*in module aerospike_helpers.operations.map_operations*), 162
map_get_by_value_list () (*aerospike.Client method*), 66
map_get_by_value_list () (*in module aerospike_helpers.operations.map_operations*), 162
map_get_by_value_range () (*aerospike.Client method*), 66
map_get_by_value_range () (*in module aerospike_helpers.operations.map_operations*), 163
map_get_by_value_rank_range_relative () (*in module aerospike_helpers.operations.map_operations*), 163
map_increment () (*aerospike.Client method*), 60
map_increment () (*in module aerospike_helpers.operations.map_operations*), 164
MAP_KEY_ORDERED (*in module aerospike*), 32
MAP_KEY_VALUE_ORDERED (*in module aerospike*), 32
map_put () (*aerospike.Client method*), 59
map_put () (*in module aerospike_helpers.operations.map_operations*), 165
map_put_items () (*aerospike.Client method*), 59
map_put_items () (*in module aerospike_helpers.operations.map_operations*), 165
map_remove_by_index () (*aerospike.Client method*), 63
map_remove_by_index () (*in module aerospike_helpers.operations.map_operations*), 165
map_remove_by_index_range () (*aerospike.Client method*), 63
map_remove_by_index_range () (*in module aerospike_helpers.operations.map_operations*), 166
map_remove_by_key () (*aerospike.Client method*), 61
map_remove_by_key () (*in module aerospike_helpers.operations.map_operations*), 166
map_remove_by_key_index_range_relative () (*in module aerospike_helpers.operations.map_operations*), 167
map_remove_by_key_list () (*aerospike.Client method*), 61
map_remove_by_key_list () (*in module aerospike_helpers.operations.map_operations*), 168
map_remove_by_key_range () (*aerospike.Client*

<i>method), 61</i>	<i>MAP_WRITE_FLAGS_CREATE_ONLY (in module aerospike), 31</i>
<code>map_remove_by_key_range() (in module aerospike_helpers.operations.map_operations), 168</code>	<i>MAP_WRITE_FLAGS_DEFAULT (in module aerospike), 31</i>
<code>map_remove_by_rank () (aerospike.Client method), 64</code>	<i>MAP_WRITE_FLAGS_NO_FAIL (in module aerospike), 32</i>
<code>map_remove_by_rank () (in module aerospike_helpers.operations.map_operations), 169</code>	<i>MAP_WRITE_FLAGS_PARTIAL (in module aerospike), 32</i>
<code>map_remove_by_rank_range () (aerospike.Client method), 64</code>	<i>MAP_WRITE_FLAGS_UPDATE_ONLY (in module aerospike), 31</i>
<code>map_remove_by_rank_range () (in module aerospike_helpers.operations.map_operations), 169</code>	<i>MapBin (class in aerospike_helpers.expressions.base), 195</i>
<code>map_remove_by_value () (aerospike.Client method), 62</code>	<i>MapClear (class in aerospike_helpers.expressions.map), 219</i>
<code>map_remove_by_value () (in module aerospike_helpers.operations.map_operations), 169</code>	<i>MapGetByIndex (class in aerospike_helpers.expressions.map), 219</i>
<code>map_remove_by_value_list () (aerospike.Client method), 62</code>	<i>MapGetByIndexRange (class in aerospike_helpers.expressions.map), 220</i>
<code>map_remove_by_value_list () (in module aerospike_helpers.operations.map_operations), 170</code>	<i>MapGetByIndexRangeToEnd (class in aerospike_helpers.expressions.map), 221</i>
<code>map_remove_by_value_range () (aerospike.Client method), 62</code>	<i>MapGetByKey (class in aerospike_helpers.expressions.map), 221</i>
<code>map_remove_by_value_range () (in module aerospike_helpers.operations.map_operations), 170</code>	<i>MapGetByKeyList (class in aerospike_helpers.expressions.map), 222</i>
<code>map_remove_by_value_rank_range_relative () (in module aerospike_helpers.operations.map_operations), 171</code>	<i>MapGetByKeyRange (class in aerospike_helpers.expressions.map), 223</i>
<code>MAP_RETURN_COUNT (in module aerospike), 32</code>	<i>MapGetByKeyRelIndexRange (class in aerospike_helpers.expressions.map), 223</i>
<code>MAP_RETURN_INDEX (in module aerospike), 32</code>	<i>MapGetByKeyRelIndexRangeToEnd (class in aerospike_helpers.expressions.map), 224</i>
<code>MAP_RETURN_KEY (in module aerospike), 33</code>	<i>MapGetByKeyRank (class in aerospike_helpers.expressions.map), 225</i>
<code>MAP_RETURN_KEY_VALUE (in module aerospike), 33</code>	<i>MapGetByRankRange (class in aerospike_helpers.expressions.map), 226</i>
<code>MAP_RETURN_NONE (in module aerospike), 32</code>	<i>MapGetByRankRangeToEnd (class in aerospike_helpers.expressions.map), 227</i>
<code>MAP_RETURN_RANK (in module aerospike), 32</code>	<i>MapGetByValue (class in aerospike_helpers.expressions.map), 228</i>
<code>MAP_RETURN_REVERSE_INDEX (in module aerospike), 32</code>	<i>MapGetByValueList (class in aerospike_helpers.expressions.map), 228</i>
<code>MAP_RETURN_REVERSE_RANK (in module aerospike), 32</code>	<i>MapGetByValueRange (class in aerospike_helpers.expressions.map), 229</i>
<code>MAP_RETURN_VALUE (in module aerospike), 33</code>	<i>MapGetByValueRelRankRange (class in aerospike_helpers.expressions.map), 229</i>
<code>map_set_policy () (aerospike.Client method), 59</code>	<i>MapGetByValueRelRankRangeToEnd (class in aerospike_helpers.expressions.map), 230</i>
<code>map_set_policy () (in module aerospike_helpers.operations.map_operations), 172</code>	<i>MapIncrement (class in aerospike_helpers.expressions.map), 231</i>
<code>map_size () (aerospike.Client method), 60</code>	<i>mapkey_iterate_and () (in module aerospike.predexp), 132</i>
<code>map_size () (in module aerospike_helpers.operations.map_operations), 172</code>	<i>mapkey_iterate_or () (in module aerospike.predexp), 132</i>
<code>MAP_UNORDERED (in module aerospike), 32</code>	<i>MapPut (class in aerospike_helpers.expressions.map), 232</i>
<code>MAP_UPDATE (in module aerospike), 32</code>	
<code>MAP_UPDATE_ONLY (in module aerospike), 32</code>	

MapPutItems (class *aerospike_helpers.expressions.map*), 233
MapRemoveByIndex (class *aerospike_helpers.expressions.map*), 233
MapRemoveByIndexRange (class *aerospike_helpers.expressions.map*), 234
MapRemoveByIndexRangeToEnd (class *aerospike_helpers.expressions.map*), 234
MapRemoveByKey (class *aerospike_helpers.expressions.map*), 235
MapRemoveByKeyList (class *aerospike_helpers.expressions.map*), 236
MapRemoveByKeyRange (class *aerospike_helpers.expressions.map*), 236
MapRemoveByKeyRelIndexRange (class *aerospike_helpers.expressions.map*), 237
MapRemoveByKeyRelIndexRangeToEnd (class *aerospike_helpers.expressions.map*), 237
MapRemoveByRank (class *aerospike_helpers.expressions.map*), 238
MapRemoveByRankRange (class *aerospike_helpers.expressions.map*), 239
MapRemoveByRankRangeToEnd (class *aerospike_helpers.expressions.map*), 239
MapRemoveByValue (class *aerospike_helpers.expressions.map*), 240
MapRemoveByValueList (class *aerospike_helpers.expressions.map*), 241
MapRemoveByValueRange (class *aerospike_helpers.expressions.map*), 241
MapRemoveByValueRelRankRange (class *aerospike_helpers.expressions.map*), 242
MapRemoveByValueRelRankRangeToEnd (class *aerospike_helpers.expressions.map*), 242
MapSize (class in *aerospike_helpers.expressions.map*), 243
mapval_iterate_and () (in module *aerospike.predexp*), 133
mapval_iterate_or () (in module *aerospike.predexp*), 133
module (*aerospike.exception.UDFError* attribute), 141
msg (*aerospike.exception.AerospikeError* attribute), 138
Multi-Ops, 68

N

NamespaceNotFound, 139
NE (class in *aerospike_helpers.expressions.base*), 196
Not (class in *aerospike_helpers.expressions.base*), 196
NotAuthenticated, 141
null (in module *aerospike*), 35
null () (in module *aerospike*), 9
Numeric Operations, 51

in O
OP_LIST_APPEND (in module *aerospike*), 15
in OP_LIST_APPEND_ITEMS (in module *aerospike*), 15
OP_LIST_CLEAR (in module *aerospike*), 16
in OP_LIST_GET (in module *aerospike*), 17
in OP_LIST_GET_BY_INDEX (in module *aerospike*), 17
in OP_LIST_GET_BY_INDEX_RANGE (in module *aerospike*), 18
in OP_LIST_GET_BY_RANK (in module *aerospike*), 18
OP_LIST_GET_BY_RANK_RANGE (in module *aerospike*), 18
in OP_LIST_GET_BY_VALUE (in module *aerospike*), 18
in OP_LIST_GET_BY_VALUE_LIST (in module *aerospike*), 19
in OP_LIST_GET_BY_VALUE_RANGE (in module *aerospike*), 19
OP_LIST_GET_RANGE (in module *aerospike*), 17
OP_LIST_INCREMENT (in module *aerospike*), 15
in OP_LIST_INSERT (in module *aerospike*), 15
OP_LIST_INSERT_ITEMS (in module *aerospike*), 15
in OP_LIST_POP (in module *aerospike*), 16
OP_LIST_POP_RANGE (in module *aerospike*), 16
in OP_LIST_REMOVE (in module *aerospike*), 16
OP_LIST_REMOVE_BY_INDEX (in module *aerospike*), 19
OP_LIST_REMOVE_BY_INDEX_RANGE (in module *aerospike*), 19
OP_LIST_REMOVE_BY_RANK (in module *aerospike*), 20
OP_LIST_REMOVE_BY_RANK_RANGE (in module *aerospike*), 20
OP_LIST_REMOVE_BY_VALUE (in module *aerospike*), 20
OP_LIST_REMOVE_BY_VALUE_LIST (in module *aerospike*), 20
OP_LIST_REMOVE_BY_VALUE_RANGE (in module *aerospike*), 21
OP_LIST_REMOVE_RANGE (in module *aerospike*), 16
OP_LIST_SET (in module *aerospike*), 17
OP_LIST_SET_ORDER (in module *aerospike*), 21
OP_LIST_SIZE (in module *aerospike*), 17
OP_LIST_SORT (in module *aerospike*), 21
OP_LIST_TRIM (in module *aerospike*), 17
OP_MAP_CLEAR (in module *aerospike*), 23
OP_MAP_DECREMENT (in module *aerospike*), 22
OP_MAP_GET_BY_INDEX (in module *aerospike*), 26
OP_MAP_GET_BY_INDEX_RANGE (in module *aerospike*), 26
OP_MAP_GET_BY_KEY (in module *aerospike*), 25
OP_MAP_GET_BY_KEY_RANGE (in module *aerospike*), 25
OP_MAP_GET_BY_RANK (in module *aerospike*), 26
OP_MAP_GET_BY_RANK_RANGE (in module *aerospike*), 26

OP_MAP_GET_BY_VALUE (*in module aerospike*), 25
 OP_MAP_GET_BY_VALUE_RANGE (*in module aerospike*), 25
 OP_MAP_INCREMENT (*in module aerospike*), 22
 OP_MAP_PUT (*in module aerospike*), 22
 OP_MAP_PUT_ITEM (*in module aerospike*), 22
 OP_MAP_REMOVE_BY_INDEX (*in module aerospike*), 24
 OP_MAP_REMOVE_BY_INDEX_RANGE (*in module aerospike*), 24
 OP_MAP_REMOVE_BY_KEY (*in module aerospike*), 23
 OP_MAP_REMOVE_BY_KEY_LIST (*in module aerospike*), 23
 OP_MAP_REMOVE_BY_KEY_RANGE (*in module aerospike*), 23
 OP_MAP_REMOVE_BY_RANK (*in module aerospike*), 24
 OP_MAP_REMOVE_BY_RANK_RANGE (*in module aerospike*), 25
 OP_MAP_REMOVE_BY_VALUE (*in module aerospike*), 23
 OP_MAP_REMOVE_BY_VALUE_LIST (*in module aerospike*), 24
 OP_MAP_REMOVE_BY_VALUE_RANGE (*in module aerospike*), 24
 OP_MAP_SET_POLICY (*in module aerospike*), 21
 OP_MAP_SIZE (*in module aerospike*), 22
 operate () (*aerospike.Client method*), 68
 operate_ordered () (*aerospike.Client method*), 71
 OPERATOR_APPEND (*in module aerospike*), 14
 OPERATOR_INCR (*in module aerospike*), 14
 OPERATOR_PREPEND (*in module aerospike*), 14
 OPERATOR_READ (*in module aerospike*), 14
 OPERATOR_TOUCH (*in module aerospike*), 14
 OPERATOR_WRITE (*in module aerospike*), 14
 OpNotApplicable, 139
 Or (*class in aerospike_helpers.expressions.base*), 196

POLICY_COMMIT_LEVEL_ALL (*in module aerospike*), 27
 POLICY_COMMIT_LEVEL_MASTER (*in module aerospike*), 27
 POLICY_EXISTS_CREATE (*in module aerospike*), 27
 POLICY_EXISTS_CREATE_OR_REPLACE (*in module aerospike*), 27
 POLICY_EXISTS_IGNORE (*in module aerospike*), 27
 POLICY_EXISTS_REPLACE (*in module aerospike*), 27
 POLICY_EXISTS_UPDATE (*in module aerospike*), 28
 POLICY_GEN_EQ (*in module aerospike*), 28
 POLICY_GEN_GT (*in module aerospike*), 28
 POLICY_GEN_IGNORE (*in module aerospike*), 28
 POLICY_KEY_DIGEST (*in module aerospike*), 28
 POLICY_KEY_SEND (*in module aerospike*), 28

POLICY_READ_MODE_AP_ALL (*in module aerospike*), 27
 POLICY_READ_MODE_AP_ONE (*in module aerospike*), 27
 POLICY_READ_MODE_SC_ALLOW_REPLICA (*in module aerospike*), 27
 POLICY_READ_MODE_SC_ALLOW_UNAVAILABLE (*in module aerospike*), 27
 POLICY_READ_MODE_SC_LINEARIZE (*in module aerospike*), 27
 POLICY_READ_MODE_SC_SESSION (*in module aerospike*), 27
 POLICY_REPLICA_ANY (*in module aerospike*), 28
 POLICY_REPLICA_MASTER (*in module aerospike*), 28
 POLICY_REPLICA_PREFER_RACK (*in module aerospike*), 28
 POLICY_REPLICA_SEQUENCE (*in module aerospike*), 28
 POLICY_RETRY_NONE (*in module aerospike*), 28
 POLICY_RETRY_ONCE (*in module aerospike*), 28
 predexp () (*aerospike.Query method*), 117
 predexp_and () (*in module aerospike.predexp*), 127
 predexp_not () (*in module aerospike.predexp*), 127
 predexp_or () (*in module aerospike.predexp*), 127
 prepend () (*aerospike.Client method*), 50
 prepend () (*in module aerospike_helpers.operations.operations*), 143
 PRIV_DATA_ADMIN (*in module aerospike*), 36
 PRIV_READ (*in module aerospike*), 36
 PRIV_READ_WRITE (*in module aerospike*), 36
 PRIV_READ_WRITE_UDF (*in module aerospike*), 36
 PRIV_SYS_ADMIN (*in module aerospike*), 36
 PRIV_USER_ADMIN (*in module aerospike*), 36
 PRIV_WRITE (*in module aerospike*), 36
 put () (*aerospike.Client method*), 39

Q

Query (*class in aerospike*), 111
 query () (*aerospike.Client method*), 72
 query_apply () (*aerospike.Client method*), 76
 QueryError, 140
 QueryQueueFull, 140
 QueryTimeout, 140

R

range () (*in module aerospike.predicates*), 126
 read () (*in module aerospike_helpers.operations.operations*), 144
 rec_device_size () (*in module aerospike.predexp*), 134
 rec_digest_modulo () (*in module aerospike.predexp*), 133

rec_last_update () (*in module aerospike.predexp*), 134
rec_void_time() (*in module aerospike.predexp*), 134
Record Operations, 38
RecordBusy, 140
RecordError, 139
RecordExistsError, 139
RecordGenerationError, 139
RecordKeyMismatch, 139
RecordNotFound, 139
RecordTooBig, 140
REGEX_EXTENDED (*in module aerospike*), 36
REGEX_ICASE (*in module aerospike*), 36
REGEX_NEWLINE (*in module aerospike*), 36
REGEX_NONE (*in module aerospike*), 36
REGEX_NOSUB (*in module aerospike*), 36
remove () (*aerospike.Client method*), 44
remove_bin () (*aerospike.Client method*), 45
results () (*aerospike.Query method*), 111
results () (*aerospike.Scan method*), 104
ResultType (*class in aerospike_helpers.expressions.resources*), 256
RoleExistsError, 141
RoleViolation, 141

S

Scan (*class in aerospike*), 103
Scan and Query, 72
scan () (*aerospike.Client method*), 72
scan_apply () (*aerospike.Client method*), 76
scan_info () (*aerospike.Client method*), 77
SCAN_PRIORITY (*in module aerospike*), 29
SCAN_STATUS_ABORTED (*in module aerospike*), 29
SCAN_STATUS_COMPLETED (*in module aerospike*), 29
SCAN_STATUS_INPROGRESS (*in module aerospike*), 29
SCAN_STATUS_UNDEF (*in module aerospike*), 29
SecurityNotEnabled, 141
SecurityNotSupported, 141
SecuritySchemeNotSupported, 141
select () (*aerospike.Client method*), 43
select () (*aerospike.Query method*), 111
select () (*aerospike.Scan method*), 103
select_many () (*aerospike.Client method*), 48
SERIALIZER_NONE (*in module aerospike*), 30
SERIALIZER_PYTHON (*in module aerospike*), 30
SERIALIZER_USER (*in module aerospike*), 30
ServerError, 139
ServerFull, 139
set_deserializer () (*in module aerospike*), 11
set_log_handler () (*in module aerospike*), 13
set_log_level () (*in module aerospike*), 13
set_serializer () (*in module aerospike*), 10
set_xdr_filter () (*aerospike.Client method*), 80
SetName (*class in aerospike_helpers.expressions.base*), 197
shm_key () (*aerospike.Client method*), 81
SinceUpdateTime (*class in aerospike_helpers.expressions.base*), 197
StrBin (*class in aerospike_helpers.expressions.base*), 197
STRING (*aerospike_helpers.expressions.resources.ResultType attribute*), 256
String Operations, 49
string_bin () (*in module aerospike.predexp*), 128
string_equal () (*in module aerospike.predexp*), 136
string_regex () (*in module aerospike.predexp*), 137
string_unequal () (*in module aerospike.predexp*), 136
string_value () (*in module aerospike.predexp*), 130
string_var () (*in module aerospike.predexp*), 130

T

touch () (*aerospike.Client method*), 43
touch () (*in module aerospike_helpers.operations.operations*), 144
truncate () (*aerospike.Client method*), 81
TTL (*class in aerospike_helpers.expressions.base*), 197
TTL_DONT_UPDATE (*in module aerospike*), 29
TTL_NAMESPACE_DEFAULT (*in module aerospike*), 29
TTL_NEVER_EXPIRE (*in module aerospike*), 29

U

udf_get () (*aerospike.Client method*), 74
udf_list () (*aerospike.Client method*), 73
udf_put () (*aerospike.Client method*), 73
udf_remove () (*aerospike.Client method*), 73
UDF_TYPE LUA (*in module aerospike*), 35
UDFError, 141
UDFNotFound, 141
unset_serializers () (*in module aerospike*), 11
UnsupportedFeature, 139
unwrap () (*aerospike.GeoJSON method*), 260
User Defined Functions, 73
UserExistsError, 141

V

VoidTime (*class in aerospike_helpers.expressions.base*), 198

W

where () (*aerospike.Query method*), 111
wrap () (*aerospike.GeoJSON method*), 260

```
write()           (in           module  
    aerospike_helpers.operations.operations),  
144
```